INCH-POUND


MIL-DTL-3628/226
18 December 2002

DETAIL SPECIFICATION SHEET

BADGE, IDENTIFICATION, GUARD, DEPARTMENT OF THE ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-3628.



BASE



RANKS



DEVICE

DASH NO.
-1 Guard
-2 Supervisory Guard

MATERIAL: Red Brass

FINISH:

-1: Hard Enameled or Epoxied, Nickel Plated, Mirror-like Polished, and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 16.
-2: Hard Enameled or Epoxied, Gold Plated, Mirror-like Polished, and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 6.

DIMENSIONS:

BASE:
WIDTH: 2 inches (REF)
HEIGHT: 3-1/8 inches (REF)
THICKNESS (at thickest point): 0.120 ± 0.010 inch

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:15Z
Check the source to verify that this is the current version before use.

DEVICE:
DIAMETER: 3/4 inch (REF)
THICKNESS (at thickest point): 0.075 ± 0.005 inch

ASSEMBLED THICKNESS: 0.145 ± 0.010 inch

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die. TIOH Drawing Number B-5-158A shall be used as additional reference.

2. A full forcer shall be used to bring up the details of the base design.

3. The badge shall be dapped to a radius of 5 inches ± 1/4 inch along the horizontal plane.

4. Engraving on the base shall be as detailed below:

TOP SCROLL, -1 & -2: "DEPARTMENT OF THE ARMY" already engraved in government furnished die.

SECOND SCROLL, -1 & -2: Engraved as required for the base locality, i.e., "FORT BELVOIR." Letters shall be approximately 3/16 inch in height and block style.

THIRD SCROLL, -1 & -2: "GUARD" already engraved in government furnished die.

BOTTOM SCROLL (Letters or numbers on the bottom scroll shall be approximately 1/4 inch in height and block style.):
-1: Engraved consecutively as specified in the procurement document for badge number, i.e., "165," "166."
-2: Engraved as required for ranks of "CHIEF," "CAPT," "LT," and "SGT."

5. Enamel/epoxy colors shall conform to TIOH Hard Enamel Chip Colors indicated below for both -1 and -2:

BASE:	
Engraving in all four scrolls	Ultramarine Blue #18
DEVICE (also see TIOH Drawing B-5-158A):	
Flag stripes	Alternating Scarlet #1 & White #28
Background of stars in flag	Ultramarine Blue #18
Stars above Liberty Bell	Ultramarine Blue #18
Background around flag & Liberty Bell	White #28
Motto band	Ultramarine Blue #18

6. The attaching device shall be a coil type pin with heavy-duty catch. The pin stem shall be 2 inches ± 1/64 inch long. The pin and catch shall be hard soldered or fused on the vertical center line between the top and bottom scrolls. The joint and catch shall be positioned on the same level plane to each other.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:15Z
Check the source to verify that this is the current version before use.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-0103/005)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:15Z
Check the source to verify that this is the current version before use.