NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/227B
15 July 2021
SUPERSEDING
MIL-DTL-3628/227A
13 September 2016

DETAIL SPECIFICATION SHEET

BADGE, IDENTIFICATION, COMBAT RESCUE OFFICER, AIR FORCE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-3628.



MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230) or Nickel Silver 65/35 (UNS Alloy No.C-752)

FINISH: Nickel Plated, Mirror-like Polished and shall match The Institute of Heraldry Metal Finish Chip Number 16

DIMENSIONS:
HEIGHT (overall): 1-1/2 inches (REF)
WIDTH (overall): 1-17/32 inches (REF)
THICKNESS (at thickest point): 0.105 inch ± 0.010 inch

ATTACHING DEVICE:
1: Attaching device shall be prong and clutch type.

2: Two prongs shall be located on the horizontal center line of the badge equidistant from each end and 1-1/8 inches ± 1/64 inch apart.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:15Z
Check the source to verify that this is the current version before use.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The badge shall be dapped 1/16 inch in the horizontal direction.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2021-587)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:15Z
Check the source to verify that this is the current version before use.