NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/228E
4 October 2021
SUPERSEDING
MIL-DTL-3628/228D
14 February 2020

DETAIL SPECIFICATION SHEET

BADGE, IDENTIFICATION, HONOR GUARD, U.S. AIR FORCE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-3628.



APPRENTICE



BASIC



SENIOR



MASTER

AMSC N/A

FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:15Z
Check the source to verify that this is the current version before use.

DASH NO.

-1: Apprentice-Regular	-9: Apprentice-Regular Epoxy
-2: Apprentice- Miniature	-10: Apprentice-Miniature Epoxy
-3: Basic-Regular	-11: Basic-Regular Epoxy
-4: Basic-Miniature	-12: Basic-Miniature Epoxy
-5: Senior-Regular	-13: Senior-Regular Epoxy
-6: Senior-Miniature	-14: Senior-Miniature Epoxy
-7: Master-Regular	-15: Master-Regular Epoxy
-8: Master-Miniature	-16: Master-Miniature Epoxy

MATERIAL: (-1 thru -16) Red Brass 85/15 (UNS Alloy No.C-230)

FINISH: (-1 thru -8) Nickel Plated, Mirror-like Polished Highlights, and shall match TIOH Metal Finish Chip Number 16.

(-9 thru -16) Epoxied, Nickel Plated, Mirror-like Polished Highlights, and shall match TIOH Metal Finish Chip Number 16.

DIMENSIONS:

HEIGHT:

-1, -3, -9 and -11: 2 inches (REF)
-2, -4, -10 and -12: 1-1/2 inches (REF)
-5 and -13: 2-3/8 inches (REF)
-6 and -14: 1-13/16 inches (REF)
-7 and -15: 2-1/2 inches (REF)
-8 and -16: 1-7/8 inches (REF)

WIDTH:

-1 and -9: 1-11/16 inches (REF)
-2 and -10: 1-3/16 inches (REF)
-3, -5, -7, -11, -13 and -15: 2 inches (REF)
-4, -6, -8, -12, -14 and -16: 1-1/2 inches (REF)

THICKNESS (At thickest point):

-1, -3, -5, -7, -9, -11, -13 and -15: 0.124 inch $\pm$ 0.010 inch
-2, -4, -6, -8, -10, -12, -14 and -16: 0.118 inch $\pm$ 0.010 inch

ATTACHING DEVICE:

1. Attaching device shall be prong and wing type clutch.

2. Each badge shall get 3 prongs.

3. For -1, -2, -9, 10, the top 2 prongs shall be placed on a horizontal line from top corner to top corner and 1/8th inch from the edge. The bottom prong shall be placed on the vertical center line 1/8th inch from the bottom.

4. For -3, -5, -7, -11, 13, -15, each prong shall be placed on a 1-3/4 inch circle, 120 degrees apart with one prong located on the horizontal center line 1/8 inch from the bottom.

5. For -4, -6, -8, -12, -14, -16, each prong shall be placed on a 1-1/4 inch circle, 120 degrees apart with one prong located on the horizontal center line 1/8 inch from the bottom.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:15Z
Check the source to verify that this is the current version before use.

EPOXY: When authorized, stoned epoxy shall be applied to the badge as an alternative finish and shall match TIOH Enamel Color Chip Numbers listed below:

COLOR and NUMBER	LOCATION
Red #4	Plume
Blue #18	Background
White #28	Helmet, Outer Scroll
Brown #32	Rifles
Yellow #37	Leaves

NOTE:
The term (REF) refers to the measurements taken from the Government furnished hub or die.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2021-756)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:15Z
Check the source to verify that this is the current version before use.