NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/232E
22 August 2022
SUPERSEDING
MIL-DTL-3628/232D
4 October 2021

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, AVIATION, AIR WING, U.S. COAST GUARD AUXILIARY

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.

pierced

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230) or Nickel Silver 65/35 (UNS Alloy No. C752)

FINISH:
WINGS AND ANCHOR: Nickel Plated (Red Brass only), Mirror-like Polished, and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 16.
DISK WITH SHIELD: Epoxy resin, 24K Gold Plated, Mirror-like Polished, and shall match TIOH Metal Finish Chip Number 6.

DIMENSIONS:
HEIGHT (Overall):
-1: 11/16 inch (REF)
-2: 3/8 inch (REF)
WIDTH (Overall):
-1: 2-3/16 inch (REF)
-2: 1-3/8 inch (REF)
THICKNESS (At thickest point):
-1: 0.091 ± 0.010 inch
-2: 0.083 ± 0.010 inch

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:16Z
Check the source to verify that this is the current version before use.

ATTACHING DEVICE:

1. Attaching device shall be prong and wing type clutch.

2. Two prongs shall be located on the reverse on the horizontal center line, for -1: the prongs shall be located equidistant from each end and 1-15/16 inches ± 1/64 inch apart, -2: the prongs shall be located equidistant from each end and 15/16 inches ± 1/64 inch apart.

EPOXY: epoxied areas shall be as shown. Epoxy resin (stoning epoxy) may be at the option of the manufacturer. When hard enamel is used, the material requirement shall be gilding metal 95/5 (UNS Alloy No. C-230). When epoxy is used, the material requirement shall be either red brass or gilding material. Colors shall conform to TIOH Hard Enamel Color Chip Numbers listed below:

TIOH HARD ENAMEL COLOR CHIPS	
COLOR	**CHIP NUMBER**
Blue	#20

Surrounding center gold disk with shield filled with TIOH epoxy color chip number 20.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Piercing shall be as indicated for the regular size badge only.

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - IH
Navy - CG1

Preparing activity:
Navy - CG1

Review activity:
DLA - CT

(Project No. 8455-2022-177)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:16Z
Check the source to verify that this is the current version before use.