INCH-POUND

MIL-DTL-3628/236
19 April 2006

DETAIL SPECIFICATION SHEET

BADGE, Qualification, Special Operations Diver
& Special Operations Diving Supervisor, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-3628.

SPECIAL OPERATIONS DIVER BADGE

SPECIAL OPERATIONS DIVING SUPERVISOR BADGE

DASH NO.
- 1: Special Operations Diver, Regular Size
- 2: Special Operations Diving Supervisor, Regular Size
- 3: Special Operations Diver, Miniature Size
- 4: Special Operations Diving Supervisor, Miniature Size
- 5: Special Operations Diver, Regular Size, Subdued
- 6: Special Operations Diving Supervisor, Regular Size, Subdued

MATERIAL: Red Brass

FINISH:
-1, thru -4: Nickel plated, Silver Plated, Oxidized, Relieved, Matte Finish and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 14.
-5, -6: Dull, Flat Black Enamel Finish

DIMENSIONS:
HEIGHT (Overall):
- 1: 1-1/8 inch (REF)
- 2: 1-1/8 inch (REF)
- 3: 11/16 INCH (REF)
- 4: 11/16 INCH (REF)
- 5: 1-1/8 inch (REF)
- 6: 1-1/8 inch (REF)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:17Z
Check the source to verify that this is the current version before use.

WIDTH (Overall):
- 1: 1-1/8 inch (REF)
- 2: 1-1/8 inch (REF)
- 3: 11/16 INCH (REF)
- 4: 11/16 INCH (REF)
- 5: 1-1/8 inch (REF)
- 6: 1-1/8 inch (REF)

THICKNESS (at thickest point):
- 1: .0.105 ± 0.010
- 2: 0.110 ± 0.010
- 3: 0.093 ± 0.010
- 4: 0.095 ± 0.010
- 5: 0.105 ± 0.010
- 6: 0.110 ± 0.010

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Dash No. - 1 thru – 6: Attaching device shall be prong and clutch. Two prongs shall be located on the reverse on the vertical center line.

3. Dash No. – 1, - 2, - 5, - 6: The prongs shall be located equidistant from each end on the vertical center line 7/8 inches ± 1/64 inch apart.
Dash No. - 3 and - 4: The prongs shall be located equidistant from each end on the vertical center line 1/2 inch ± 1/64 inch apart.

4. The dull flat black enamel for Dash No. - 5 and - 6 shall match FED-STD-595, Chip No. 37038.

5. Army items for Dash No. – 1 through - 4 may be nickel or rhodium plated with mirror-like polished finish which shall match The Institute of Heraldry metal Finish Chip Number 16 for commercial sale only. For nickel or rhodium plated items, the silver plating requirement shall not apply.

Custodians:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-2006-026)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:17Z
Check the source to verify that this is the current version before use.