NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/236B
5 October 2020
SUPERSEDING
MIL-DTL-3628/236A
30 November 2015

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, SPECIAL OPERATIONS DIVER AND SPECIAL OPERATION DIVING SUPERVISOR, U.S. ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-3628.

SPECIAL OPERATIONS DIVER BADGE

SPECIAL OPERATIONS DIVING SUPERVISOR BADGE

DASH NO.
- 1: Special Operations Diver, Regular Size
- 2: Special Operations Diving Supervisor, Regular Size
- 3: Special Operations Diver, Miniature Size
- 4: Special Operations Diving Supervisor, Miniature Size
- 5: Special Operations Diver, Regular Size, Subdued
- 6: Special Operations Diving Supervisor, Regular Size, Subdued

MATERIAL: Red Brass 85/15 (UNS Alloy No. C- 230)

FINISH:
-1, thru -4: Nickel plated, Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 16.

-5, -6: Dull, Flat Black Enamel Finish and shall match TIOH Metal Finish Chip Number 21.

DIMENSIONS:
HEIGHT (Overall):
- 1: 1-1/8 inch (REF)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:17Z
Check the source to verify that this is the current version before use.

- 2: 1-1/8 inch (REF)
- 3: 11/16 INCH (REF)
- 4: 11/16 INCH (REF)
- 5: 1-1/8 inch (REF)
- 6: 1-1/8 inch (REF)

WIDTH (Overall):
- 1: 1-1/8 inch (REF)
- 2: 1-1/8 inch (REF)
- 3: 11/16 INCH (REF)
- 4: 11/16 INCH (REF)
- 5: 1-1/8 inch (REF)
- 6: 1-1/8 inch (REF)

THICKNESS (At thickest point):
- 1: .0.105 $\pm$ 0.010
- 2: 0.110 $\pm$ 0.010
- 3: 0.093 $\pm$ 0.010
- 4: 0.095 $\pm$ 0.010
- 5: 0.105 $\pm$ 0.010
- 6: 0.110 $\pm$ 0.010

ATTACHING DEVICE:

1. - 1 thru – 6: Attaching device shall be prong and wing type clutch.

2. Two prongs shall be located on the reverse on the vertical center line. For – 1, - 2, - 5, and - 6, the prongs shall be located equidistant from each end on the vertical center line 7/8 inches $\pm$ 1/64 inch apart. For- 3 and - 4: The prongs shall be located equidistant from each end on the vertical center line 1/2 inch $\pm$ 1/64 inch apart.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. -1 through - 4: Silver Plated Oxidized Buffed Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14, May be used for commercial sale.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2020-591)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:17Z
Check the source to verify that this is the current version before use.