INCH-POUND
MIL-DTL-3628/237A
28 NOVEMBER 2006
SUPERSEDING
MIL-DTL-3628/237
21 FEBRUARY 2006

DETAIL SPECIFICATION SHEET
BADGE, QUALIFICATION, COMBAT ACTION, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-3628.



1ST AWARD

2D AWARD

DASH NO.

-1: 1st Award Regular Size
-2: 2nd Award Regular Size
-3: 1st Award Miniature Size
-4: 2nd Award Miniature Size
-5: 1st Award Dress Miniature
-6: 2nd Award Dress Miniature
-7: 1st Award Regular Size Subdued
-8: 2nd Award Regular Size Subdued

MATERIAL: Red Brass

FINISH:

-1 thru -6: Nickel plated, Silver Plated, Oxidized, Relieved, Matte Finish and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 14.
-7, -8: Dull, Flat Black Enamel Finish

DIMENSIONS:

HEIGHT (Overall):

-1, -7: 1 inch (REF)
-2, -8: 1-1/8 inch (REF)
-3: 5/8 inch (REF)
-4: 11/16 inch (REF)
-5: 7/16 inch (REF)
-6: 15/32 inch REF)

WIDTH (Overall):

-1, -2, -7, -8: 2 inches (REF)
-3, -4: 1-3/16 inch (REF)
-5, -6: 13/16 inch (REF)

THICKNESS (at thickest point):

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:18Z
Check the source to verify that this is the current version before use.

-1, -2, -7, -8: 0.100 ± 0.010
-3, -4: 0.082 ± 0.005
-5, -6: 0.065 ± 0.005

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Dashes No. -1 thru -6 may be nickel or rhodium plated with a mirror-like polished finish for commercial sale and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 16. The silver plating requirement shall not apply with this finish..

3. A forcer shall be used to bring up the design of the bayonet.

4. Attaching device shall be prong and wing type clutch. Two prongs shall be located on the reverse on the horizontal center line, equidistant from each end and the following distance apart.

Dash No -1,-2, -7, -8: 1-1/4 inches ± 1/64 inch apart.
Dash No -3, -4: 1 inch ± 1/64 inch apart.
Dash No -5, -6: 3/4 inch ± 1/64 inch apart.

5. The dull flat black enamel for Dash No. -7, -8 shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 21.

6. Piercing shall be as indicated.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-2006-014)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:18Z
Check the source to verify that this is the current version before use.