INCH-POUND

MIL-DTL-3628/238B
15 May 2008
SUPERSEDING
MIL-DTL-3628/238A
13 NOVEMBER 2006

DETAIL SPECIFICATION SHEET

BADGE, OCCUPATIONAL, SPACE, AIR FORCE/ARMY

This specification is approved for use by all Departments
and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.



BASIC **SENIOR** **MASTER**

DASH NO:

-1 Basic, Regular Size (AF, A)	-4 Senior, Regular Size (AF, A)	-7 Master, Regular Size (AF, A)
-2 Basic, Miniature Size (AF,A)	-5 Senior, Miniature Size (AF, A)	-8 Master, Miniature Size (AF, A)
-3 Basic, Dress Mini Size (A)	-6 Senior, Dress Mini Size (A)	-9 Master, Dress Mini Size (A)

MATERIAL: Red Brass

FINISH: Nickel Plated Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 16.

DIMENSIONS:

HEIGHT (overall):

-1: 7/8 inch (REF)	-4: 1-1/4 inches (REF)	-7: 1-1/4 inches (REF)
-2: 5/8 inch (REF)	-5: 13/16 inch (REF)	-8: 13/16 inch (REF)
-3: 7/16 inch (REF)	-6: 5/8 inch (REF)	-9: 5/8 inch (REF)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:18Z
Check the source to verify that this is the current version before use.

WIDTH (overall):
-1, -4, -7: 3 inches (REF)
-2, -5, -8: 2 inches (REF)
-3, -6, -9: 1-1/2 inches (REF)

THICKNESS (at thickest point):
-1, -4, -7: 0.160 ± 0.010 inch
-2, -5, -8: 0.125 ± 0.010 inch
-3, -6, -9: 0.095 ± 0.010 inch

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Attaching device shall be prong and clutch type. Two prongs shall be located on the reverse on the horizontal center line. The prongs shall be located equidistant from each end 2 inches ± 1/64 inch apart on regular size, 1- 5/16 inches ± 1/64 inch apart on miniature size and 1 inch ± 1/64 inch apart on dress mini.

3. Piercing shall be as indicated for both Regular and Miniature size badges and the Dress Minis need not be pierced.

4. Army badges -2,-5,-8 may be manufactured with a dull, flat black enamel finish and shall match FED-STD-595, Chip Number 37038 or TIOH Metal Finish Chip #21 Dull Flat Black.

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army - IH
Air Force - 11

Preparing activity:
Army - IH
(Project No. 8455-2008-137)

Review activities:
Air Force - 99
DLA – CT

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:18Z
Check the source to verify that this is the current version before use.