NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/238E
23 February 2023
SUPERSEDING
MIL-DTL-3628/238D
15 April 2019

DETAIL SPECIFICATION SHEET

BADGE, OCCUPATIONAL, SPACE, AIR FORCE/SPACE FORCE/ARMY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.



BASIC **SENIOR** **MASTER**

DASH NO:

-1 Basic, Regular Size (AF, A)	-4 Senior, Regular Size (AF, A)	-7 Master, Regular Size (AF, A)
-2 Basic, Miniature Size (AF,A)	-5 Senior, Miniature Size (AF, A)	-8 Master, Miniature Size (AF, A)
-3 Basic, Dress Mini Size (A)	-6 Senior, Dress Mini Size (A)	-9 Master, Dress Mini Size (A)

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: Nickel Plated Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 16.

DIMENSIONS:

HEIGHT (Overall):

-1: 7/8 inch (REF)	-4: 1-1/4 inches (REF)	-7: 1-1/4 inches (REF)
-2: 5/8 inch (REF)	-5: 13/16 inch (REF)	-8: 13/16 inch (REF)
-3: 7/16 inch (REF)	-6: 5/8 inch (REF)	-9: 5/8 inch (REF)

WIDTH (Overall):

-1, -4, -7: 3 inches (REF)
-2, -5, -8: 2 inches (REF)
-3, -6, -9: 1-1/2 inches (REF)

THICKNESS (At thickest point):

-1, -4, -7: 0.160 ± 0.010 inch
-2, -5, -8: 0.125 ± 0.010 inch
-3, -6, -9: 0.095 ± 0.010 inch

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:18Z
Check the source to verify that this is the current version before use.

ATTACHING DEVICE:

1: Attaching device shall be prong and clutch type.

2: Two prongs shall be located on the reverse on the horizontal center line. The prongs shall be located equidistant from each end 2 inches ± 1/64 inch apart on regular size, 1- 5/16 inches ± 1/64 inch apart on miniature size and 1 inch ± 1/64 inch apart on dress mini.

PIERCING: Shall be as indicated for both Regular and Miniature size badges. The dress miniature shall not be pierced.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Army badges ONLY -1,-4,-7 may be manufactured with a dull, flat black enamel finish and shall TIOH Metal Finish Chip #21 Dull Flat Black.

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2023-088)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:18Z
Check the source to verify that this is the current version before use.