INCH-POUND

MIL-DTL-3628/239
25 July 2006

DETAIL SPECIFICATION SHEET


BADGE, IDENTIFICATION, AIR STAFF, AIR FORCE

This specification is approved for use by all Departments
and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628.



ASSEMBELED



BASE



DEVICE

DASH NO:
-1 Basic, Regular Size
-2 Basic, Miniature Size

MATERIAL: Gilding Metal

FINISH:

Base - Hard Enameled/Epoxied, Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

Device:
Wreath and Star - Hard Enameled/Epoxied, Nickel Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.
Eagle and Shield - Hard Enameled/Epoxied, Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Sample Number 6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:19Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

HEIGHT (overall):

-1: Device: 2 inches
Base: 1-1/4 inches (REF)

-2: Device: 1-1/2 inches (REF)
Base: 15/16 inch

WIDTH (overall):

-1: Device: 2 inches
Base: 1-5/16 inches (REF)

-2: Device: 1-1/2 inches (REF)
Base: 1 inch

THICKNESS (at thickest point):

-1: Overall: 0.180 inches (REF)
Device: 0.100 inches (REF)
Base: 0.080 inches ± 0.010 for all.

-2: Overall: 0.145
Device: 0.083
Base: 0.062 ± 0.010 for all.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Attaching device shall be prong and flat ball clutch type.
-1: Two prongs shall be on a horizontal line 9/16 of an inch from the top of the device, 1-5/16 inches apart and one prong shall be on the vertical center line, 5/16 of an inch from the bottom of the device.
-2: Two prongs shall be on a horizontal line 7/16 of an inch from the top of the device, 1 inches apart and one prong shall be on the vertical center line, 3/16 of an inch from the bottom of the device.

3. The device shall be secured to the base by two or more rivets. The rivets may be an integral part of the device or fabricated from any type brass or soldered to the reverse of the device.

4. Piercing shall be as indicated for both regular and miniature size badges.

5. Enameled/Epoxied areas shall be as indicated. The colors shall conform to The Institute of Heraldry (TIOH) Hard Enamel Chip Numbers listed below:

COLOR	CHIP #
RED	1 (Inner circle of star)
ULTRAMARINE BLUE	18 (Base and areas around star)
WHITE	28 (Star tips and lower part of shield)
BRITTANY BLUE	34 (Upper part of shield)

Custodian: Preparing activity:

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:19Z
Check the source to verify that this is the current version before use.

Army - IH
Air Force - 11

Army - IH
(Project No. 8455-2006/063)

Review activities:
Air Force - 99
DLA – CT

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:19Z
Check the source to verify that this is the current version before use.