INCH-POUND

MIL-DTL-3628/239B
20 June 2016
SUPERSEDING
MIL-DTL-3628/239A
5 October 2006

DETAIL SPECIFICATION SHEET


BADGE, IDENTIFICATION, AIR STAFF, U.S. AIR FORCE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628.



ASSEMBELED



BASE



DEVICE

DASH NO:
-1: Basic, Regular Size
-2: Basic, Miniature Size

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH:
Base: Epoxied resin, 24K Gold Plated, Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 6.
Device:
Wreath and Star – Epoxied resin, Silver Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 13.
Eagle and Shield – Epoxied resin, 24K Gold Plated, Matte Finish Polished Highlights and shall match TIOH Metal Finish Sample Number 8.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:18Z
Check the source to verify that this is the current version before use.

DIMENSIONS:
HEIGHT (overall):
-1: Device: 2 inches
Base: 1-1/4 inches (REF)
-2: Device: 1-1/2 inches (REF)
Base: 15/16 inch
WIDTH (overall):
-1: Device: 2 inches
Base: 1-5/16 inches (REF)
-2: Device: 1-1/2 inches (REF)
Base: 1 inch
THICKNESS (at thickest point):
-1: Overall: 0.180 inches (REF)
Device: 0.100 inches (REF)
Base: 0.080 inches ± 0.010 for all.
-2: Overall: 0.145
Device: 0.083
Base: 0.062 ± 0.010 for all.

ATTACHING DEVICE:
1. Attaching device shall be prong and flat ball clutch type.

2. For -1: Two prongs shall be on a horizontal line 9/16 of an inch from the top of the device, 1-5/16 inches apart and one prong shall be on the vertical center line, 5/16 of an inch from the bottom of the device. For -2: Two prongs shall be on a horizontal line 7/16 of an inch from the top of the device, 1 inches apart and one prong shall be on the vertical center line, 3/16 of an inch from the bottom of the device.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The device for –1 shall have a screw point attached to the reverse side which shall be made from any type brass. The back screw plate shall be made from any type 1/4 inch hard brass. The screw post shall be approximately 5/32 inch high and shall be hard soldered or fused to the device in a location to correctly position the device to the base as indicated. The base shall have an 1/8 inch hole in its center. The two pieces shall be secured by a Type A back plate without the prongs as shown on TIOH Drawing 4-4-89. For -2 the manufacturer shall secure the device to the base by two or more rivets. The rivets may be an integral part of the device or fabricated from any type brass or soldered to the reverse of the device. The manufacturer may use this method for -1 also.

3. Piercing shall be as indicated for both regular and miniature size badges.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:18Z
Check the source to verify that this is the current version before use.

EPOXY: Epoxy resin shall be applied to the Badge Identification as indicated above, and shall match TIOH Hard Enamel Color Chip Numbers listed below.

TIOH HARD ENAMEL COLOR CHIPS	
COLOR	**CHIP NUMBER**
Red	#1
Ultramarine Blue	#18
White	#28
Brittany Blue	#34

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2016-496)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:18Z
Check the source to verify that this is the current version before use.