NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/239D
13 July 2026
SUPERSEDING
MIL-DTL-3628/239C
29 April 2021

DETAIL SPECIFICATION SHEET


BADGE, IDENTIFICATION, AIR STAFF, U.S. AIR FORCE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628.



ASSEMBELED



BASE



DEVICE

DASH NO:
-1: Basic, Regular Size
-2: Basic, Miniature Size

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH:
Base: Epoxied resin, 24K Gold Plated, Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 6.
Device:
Wreath and Star – Epoxied resin, Silver Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 13.
Eagle and Shield – Epoxied resin, 24K Gold Plated, Matte Finish Polished Highlights and shall match TIOH Metal Finish Sample Number 8.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:18Z
Check the source to verify that this is the current version before use.

DIMENSIONS:
HEIGHT (overall):
-1: Device: 2 inches
Base: 1-1/4 inches (REF)
-2: Device: 1-1/2 inches (REF)
Base: 15/16 inch
WIDTH (overall):
-1: Device: 2 inches
Base: 1-5/16 inches (REF)
-2: Device: 1-1/2 inches (REF)
Base: 1 inch
THICKNESS (at thickest point):
-1: Overall: 0.180 inch ± 0.010 (REF)
Device: 0.100 inch ± 0.010 (REF)
Base: 0.080 inch ± 0.005 for all.
-2: Overall: 0.145 inch ± 0.005
Device: 0.083 inch ± 0.005
Base: 0.062 ± 0.005 for all.

ATTACHING DEVICE:
1. Attaching device should be prong and flat ball clutch type.

2. For -1: Two prongs shall be on a horizontal line 9/16 of an inch from the top of the device, 1-5/16 inches apart and one prong shall be on the vertical center line, 5/16 of an inch from the bottom of the device. For -2: Two prongs shall be on a horizontal line 7/16 of an inch from the top of the device, 1 inch apart and one prong shall be on the vertical center line, 3/16 of an inch from the bottom of the device.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The device for –1 shall have a screw point attached to the reverse side which shall be made from any type of brass. The back screw plate shall be made from any type 1/4 inch hard brass. The screw post shall be approximately 5/32 inch high and shall be hard soldered or fused to the device in a location to correctly position the device to the base as indicated. The base shall have a 1/8 inch hole in its center. The two pieces shall be secured by a Type A back plate without the prongs as shown on TIOH Drawing 4-4-89. For -2 the manufacturer shall secure the device to the base by two or more rivets. The rivets may be an integral part of the device or fabricated from any type of brass or soldered to the reverse of the device. The manufacturer may use this method for -1 also.

3. Piercing shall be as indicated for both regular and miniature size badges.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:18Z
Check the source to verify that this is the current version before use.

EPOXY: Epoxy resin shall be applied to the Badge Identification as indicated above and shall match TIOH Hard Epoxy Color Chip Numbers listed below.

TIOH HARD EPOXY COLOR CHIPS	
COLOR	**CHIP NUMBER**
Red	#1
Ultramarine, Blue	#18
White	#28
Brittany Blue	#34

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2026-436)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:18Z
Check the source to verify that this is the current version before use.