INCH-POUND

MIL-DTL-3628/240A
18 May 2016
SUPERSEDING
MIL-DTL-3628/240
20 April 2006

DETAIL SPECIFICATION SHEET

BADGE, BERET, SPECIAL TACTICS OFFICER, U.S. AIR FORCE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628.

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: Nickel Plated, Mirror-like Polished and shall match The Institute of Heraldry Metal Finish Chip Number 16.

DIMENSIONS:
HEIGHT (overall):
1-1/2 inch (REF)
WIDTH (overall):
1-1/2 inches (REF)
THICKNESS (at thickest point):
0.080 ± 0.005 inch

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:19Z
Check the source to verify that this is the current version before use.

ATTACHING DEVICE:

1. Attaching device shall be prong and clutch type.

2. Two prongs shall be located on the reverse on the horizontal center line. The prongs shall be located equidistant from each end 1 inch ± 1/64 inch apart.

NOTE:

The term (REF) refers to the measurements taken from the Government furnished hub or die.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2016-455)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T20:19Z
Check the source to verify that this is the current version before use.