MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

POTTING COMPOUNDS

TO ALL HOLDERS OF DOD-STD-35-116(MI):

1. THE FOLLOWING PAGES OF DOD-STD-35-116(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED.

| NEW PAGE | DATE | SUPERSEDED PAGE | DATE |
|---|---|---|---|
| v | 18 SEPTEMBER 1992 | v | 7 JULY 1978 |
| 3 | 18 SEPTEMBER 1992 | 3 | 7 JULY 1978 |
| 4 | 18 SEPTEMBER 1992 | 4 | 7 JULY 1978 |
| 5 | 18 SEPTEMBER 1992 | 5 | 7 JULY 1978 |
| 6 | 18 SEPTEMBER 1992 | 6 | 7 JULY 1978 |
| 11 | 18 SEPTEMBER 1992 | 11 | 7 JULY 1978 |
| 12 | 18 SEPTEMBER 1992 | 12 | 7 JULY 1978 |
| 45 | 7 JULY 1978 | (Reprinted without change) | |
| 46 | 18 SEPTEMBER 1992 | 46 | 7 JULY 1978 |
| 47 | 18 SEPTEMBER 1992 | 47 | 7 JULY 1978 |
| 48 | 18 SEPTEMBER 1992 | 48 | 7 JULY 1978 |
| 67 | 7 JULY 1978 | (Reprinted without change) | |
| 68 | 18 SEPTEMBER 1992 | 68 | 7 JULY 1978 |
| 69 | 18 SEPTEMBER 1992 | 69 | 7 JULY 1978 |
| 70 | 18 SEPTEMBER 1992 | 70 | 7 JULY 1978 |
| 91 | 18 SEPTEMBER 1992 | 91 | 7 JULY 1978 |
| 92 | 18 SEPTEMBER 1992 | 92 | 7 JULY 1978 |
| 93 | 18 SEPTEMBER 1992 | 93 | 7 JULY 1978 |
| 94 | 18 SEPTEMBER 1992 | 94 | 7 JULY 1978 |
| 109 | 7 JULY 1978 | (Reprinted without change) | |
| 110 | 18 SEPTEMBER 1992 | 110 | 7 JULY 1978 |
| 111 | 18 SEPTEMBER 1992 | 111 | 7 JULY 1978 |
| 112 | 18 SEPTEMBER 1992 | 112 | 7 JULY 1978 |

AMSC N/A AREA EGDS
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

| NEW PAGE | DATE | SUPERSEDED PAGE | DATE |
|---|---|---|---|
| 121 | 18 SEPTEMBER 1992 | 121 | 7 JULY 1978 |
| 122 | 18 SEPTEMBER 1992 | 122 | 7 JULY 1978 |
| 123 | 18 SEPTEMBER 1992 | 123 | 7 JULY 1978 |
| 124 | 18 SEPTEMBER 1992 | 124 | 7 JULY 1978 |
| 155 | 18 SEPTEMBER 1992 | 155 | 7 JULY 1978 |
| 156 | 18 SEPTEMBER 1992 | 156 | 7 JULY 1978 |
| 157 | 18 SEPTEMBER 1992 | 157 | 7 JULY 1978 |
| 158 | 18 SEPTEMBER 1992 | 158 | 7 JULY 1978 |

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of DOD-STD-35-116(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army-MI

Review activities:
Army-AT, AV, CR, ER
ME, MR, SC

User activity
Army - AR

Preparing activity:
Army - MI

(Project EGDS-A453)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

CONTENTS

| | | | Page |
|---|---|---|---|
| Paragraph | 1. | SCOPE | 1 |
| | 1.1 | General | 1 |
| | 1.2 | Purpose | 1 |
| | 1.3 | Utilization | 1 |
| | 1.4 | Military Specification Exception Title Index | 1 |
| | 2. | APPLICABLE DOCUMENTS | 5 |
| | 2.1 | Government documents | 5 |
| | 2.2 | Non-Government publications | 5 |
| | 3. | DEFINITIONS | 7 |
| | 4. | GENERAL REQUIREMENTS | 9 |
| | 4.1 | Introduction | 9 |
| | 4.2 | Specification Requirement Sheet (SRS) | 9 |
| | 4.3 | Units of measure | 9 |
| | 5 | DETAILED REQUIREMENTS | 11 |
| | 5.1 | Introduction | 11 |
| | 5.2 | MSE Formats | 11 |
| | 5.3 | Referenced documents | 11 |
| | 5.4 | Deleted | 11 |
| | 5.5 | Tabulation | 12 |
| | 5.6 | Keyword Code Index (KCI) and Standard Paragraphs | 15 |
| | 5.6.1 | Interrelationship of Codes | 15 |
| | 5.6.2 | Automatic MSE Data | 15 |
| | 5.6.3 | DOD-STD-35 Tables | 15 |

TABLES

| | | | |
|---|---|---|---|
| Table | I. | Title Index | 2 |
| | II. | Deleted | 12 |
| | III. | Tabulation Candidates | 13 |

APPENDICES

| | | | |
|---|---|---|---|
| Appendix | A. | Characteristic Code Index | 163 |
| | | Index | 171 |



Source: https://assist.dla.mil -- Downloaded: 202640-23T21:03Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX

| MSE TITLE | TITLE CODE | BASE DOCUMENT NUMBER | BASE DOCUMENT COVERAGE |
|---|---|---|---|
| POTTING COMPOUND, EPOXY | 615001 | MIL-C-22608 | HIGH TEMP |
| | | MIL-P-46067 | EMBEDDING |
| | | MIL-I-46865 | COLLOIDAL SILICA FILLED |
| | | MIL-C-82644 | ENCAPSULATING |
| POTTING COMPOUND, POLYSULFIDE | 615002 | MIL-C-22608 | HIGH TEMP |
| POTTING COMPOUND, POLYURETHANE | 615003 | MIL-M-24041 | MOLDING CHEM CURED |
| | | MIL-P-43081 | LOW MOLECULAR WEIGHT |
| | | MIL-C-47002 | COATING, SINGLE COMPONENT |
| | | MIL-M-81999 | AIRCRAFT STRUC |





Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX (CONT)

| MSE TITLE | TITLE CODE | BASE DOCUMENT NUMBER | BASE DOCUMENT COVERAGE |
|---|---|---|---|
| POTTING COMPOUND, SILICONE | 615004 | MIL-S-23586 | ENCAPSULATING COMPOUND |
| | | MIL-I-46838 | RTV |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

| | |
|---|---|
| MIL-M-81999 | Molding Compound, Reversion Resistant, Non Carcinogen Curing Polyurethane, Aircraft Structure |

STANDARDS

FEDERAL

| | |
|---|---|
| FED-STD-141 | Paint, Varnish, Lacquer and Related Materials, Methods of Inspection, Sampling and Testing |

MILITARY

| | |
|---|---|
| MIL-STD-130 | Identification Marking of U.S. Military Property |
| MIL-STD-1523 | Age Controls of Age-Sensitive Elastomeric Materiel (For Aerospace Applications) |
| MIL-STD-1285 | Marking of Electrical and Electronic Parts |

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation.

| | |
|---|---|
| ASTM D 149 | Dielectric Breakdown Voltage and Dielectric Strength of Solid Electrical Insulating Materials at Commercial Power Frequencies |


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

| | |
|---|---|
| ASTM C 177 | Thermal Conductivity of Materials by Means of the Guarded Hot Plate, Method of Test for |
| ASTM D 257 | DC Resistance of Conductance of Insulating Materials |
| ASTM D 395 | Compression Set of Rubber |
| ASTM D 412 | Rubber, Determination of Tension Characteristics |
| ASTM D 570 | Water Absorption of Plastics |
| ASTM D 618 | Conditioning Plastics and Electrical Insulating Materials for Testing |
| ASTM D 696 | Coefficient of Linear Thermal Expansion of Plastics |
| ASTM D 732 | Shear Strength of Plastics |
| ASTM D 746 | Brittleness Temperature of Plastics and Elastomers by Impact |
| ASTM D 1149 | Accelerated Ozone Cracking of Vulcanized Rubber |
| ASTM D 1621 | Compressive Properties of Rigid Cellular Plastics |
| ASTM D 2471 | Gel Time and Peak Exothermic Temperature of Reacting Thermosetting Resins |
| ASTM D 2734 | Void Content of Reinforced Plastics |
| ASTM E 380 | Metric Practic Guide |

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103.)


Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the currentversion before use.

## 5. DETAILED REQUIREMENTS

5.1 Introduction. This section provides instructions for completion of the SRS and references for instructions on specific requirements contained in DOD-STD-35.

5.2 MSE formats. AEDPS has the capability to prepare a six-section or a single-section document. The six-section document appears similar to a six-section military specification. The single-section document appears similar to a military specification sheet. Specification requirements described in DOD-STD-35 are applicable to either of the formats selected. It is mandatory that one of the two following codes and an "X" be entered on the SRS to create the desired MSE format:

a. 0700 for a six-section format

b. 0800 for a single-section format

5.3 Referenced documents. Section 2 of the MSE may contain a list of all referenced documents within Sections 3, 4, and 5 of the MSE. Instructions for referencing documents to appear in Section 2 of the forthcoming MSE are contained in DOD-STD-35.

5.4 Deleted



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

5.5 Tabulation. Instructions for tabulation are provided in DOD-STD-35. Table III provides codes for column headings which may be used for Potting Compounds characteristics. When different units of measure within one system (U.S. or SI) are available for specifying a characteristic, only one of the units may be tabulated; e.g. either ounces or pounds.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

CHAR
CODE STANDARD PARAGRAPH

1914 CHEMICAL COMPOSITION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE CHEMICAL COMPOSITION TABLE.

CHEMICAL COMPOSITION TABLE

| INGREDIENT | QUANTITY | UNITS |
|---|---|---|
| 6715 | 6716 | 6717 |
| 6718 | 6719 | 6720 |
| 6721 | 6722 | 6723 |
| 6724 | 6725 | 6726 |
| 6727 | 6728 | 6729 |
| 6730 | 6731 | 6732 |
| 6733 | 6734 | 6735 |
| 6736 | 6737 | 6738 |
| 6739 | 6740 | 6741 |
| 6742 | 6743 | 6744 |
| 6745 | 6746 | 6747 |
| 6748 | 6749 | 6750 |
| 6751 | 6752 | 6753 |
| 6754 | 6755 | 6756 |

1902 CHEMICAL COMPOSITION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1902.

1904 CHEMICAL COMPOSITION. SUPPLIERS CERTIFICATE OF COMPLIANCE WITH THE CHEMICAL COMPOSITION REQUIREMENT(S) MAY BE ACCEPTED IN LIEU OF A SPECIFIC TEST.

1906 CHEMICAL COMPOSITION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1906.

1908 TEST METHOD 1908 SHALL APPLY.



Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

| CHARACTERISTIC NAME | CHAR CODE |
|---|---|
| COEFFICIENT OF LINEAR EXPANSION | |
| REQUIREMENTS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 1964 |
| AS FOLLOWS: (SELECT ONE) | 1966 |
| U.S. | |
| MINIMUM (INCH PER INCH PER DEGREE CELSIUS X 10 TO THE -6) | 1968 |
| MAXIMUM (INCH PER INCH PER DEGREE CELSIUS X 10 TO THE -6) | 1971 |
| SI | |
| MINIMUM (MILLIMETER PER MILLIMETER PER DEGREE CELSIUS X 10 TO THE -6) | 1970 |
| MAXIMUM (MILLIMETER PER MILLIMETER PER DEGREE CELSIUS X 10 TO THE -6) | 1973 |
| TEST METHODS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 1974 |
| PER ASTM D 696 | 1976 |
| NUMBER OF SPECIMENS TO BE TESTED (QUANTITY) | 1982 |



Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the currentversion before use.

| CHAR CODE | STANDARD PARAGRAPH |
|---|---|
| 1964 | COEFFICIENT OF LINEAR EXPANSION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1964. |
| 1966 | COEFFICIENT OF LINEAR EXPANSION. THE AVERAGE COEFFICIENT SHALL BE AS FOLLOWS: |
| 1968 | NOT LESS THAN 1968 INCH PER INCH DEGREE CELSIUS TIMES 10 TO THE NEGATIVE 6 POWER. |
| 1971 | NOT GREATER THAN 1971 INCH PER INCH PER DEGREE CELSIUS TIMES 10 TO THE NEGATIVE 6 POWER. |
| 1970 | NOT LESS THAN 1970 MILLIMETER PER MILLIMETER PER DEGREE CELSIUS TIMES 10 TO THE NEGATIVE 6 POWER. |
| 1973 | NOT GREATER THAN 1973 MILLIMETER PER MILLIMETER PER DEGREE CELSIUS TIME 10 TO THE NEGATIVE 6 POWER. |
| 1974 | COEFFICIENT OF LINEAR EXPANSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1974. |
| 1976 | COEFFICIENT OF LINEAR EXPANSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM D 696. |
| 1982 | THERE SHALL BE 1982 SPECIMENS TESTED. |



Source: https://assist.dla.mil -- Downloaded: 20260-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

| CHARACTERISTIC NAME | CHAR CODE |
|---|---|
| COEFFICIENT OF LINEAR EXPANSION (CONT) | |
| PER ASTM D 696 (CONT) | |
| SPECIMEN WIDTH (SELECT ONE) | |
| (INCHES) | 1984 |
| (MILLIMETERS) | 1986 |
| SPECIMEN THICKNESS (SELECT ONE) | |
| (INCHES) | 1988 |
| (MILLIMETERS) | 1989 |
| SPECIMEN LENGTH (SELECT ONE) | |
| (INCHES) | 1991 |
| (MILLIMETERS) | 1992 |
| NUMBER OF TEST CYCLES (QUANTITY) | 1994 |
| TEST TEMPERATURE (DEGREES CELSIUS) | 1996 |
| TOLERANCE PLUS OR MINUS (DEGREES CELSIUS) | 1998 |
| COMPRESSION SET | |
| REQUIREMENTS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 1922 |
| MAXIMUM COMPRESSION SET (PERCENT) | 1924 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

| CHAR CODE | STANDARD PARAGRAPH |
|---|---|
| 2060 | THE TEST SPECIMEN SHALL BE 2060 INCH(S) IN LENGTH. |
| 2062 | THE TEST SPECIMEN SHALL BE 2062 MILLIMETER(S) IN LENGTH. |
| 2050 | THE TEST SPECIMEN SHALL BE 2050 INCH(S) IN DIAMETER. |
| 2052 | THE TEST SPECIMEN SHALL BE 2052 MILLIMETER(S) IN DIAMETER. |
| 2061 | THE TEST TEMPERATURE SHALL BE 2061 DEGREES CELSIUS. |
| 2063 | THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2063 DEGREES CELSIUS. |
| 2065 | THE TEST RELATIVE HUMIDITY SHALL BE 2065 PERCENT. |
| 2067 | THE TEST RELATIVE HUMIDITY TOLERANCE SHALL BE PLUS OR MINUS 2067 PERCENT. |
| 2152 | DIELECTRIC STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2152. |
| 2154 | DIELECTRIC STRENGTH. THE REQUIREMENT(S) SHALL BE AS FOLLOWS: |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

| CHARACTERISTIC NAME | CHAR CODE |
|---|---|
| DIELECTRIC STRENGTH (CONT) | |
| AS FOLLOWS: (CONT) | |
| MINIMUM DIELECTRIC STRENGTH (SELECT ONE) | |
| (VOLTS PER 0.001 INCH) | 2156 |
| (VOLTS PER MILLIMETER) | 2158 |
| MINIMUM BREAKDOWN VOLTAGE (VOLTS) | 2160 |
| TEST METHODS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 2102 |
| PER ASTM D 149 | 2104 |
| NUMBER OF SPECIMENS TO BE TESTED (QUANTITY) | 2106 |
| SPECIMEN WIDTH (SELECT ONE) | |
| (INCHES) | 2112 |
| (MILLIMETERS) | 2114 |
| SPECIMEN THICKNESS (SELECT ONE) | |
| (INCHES) | 2116 |
| (MILLIMETERS) | 2118 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

| CHAR CODE | STANDARD PARAGRAPH |
|---|---|
| 2156 | THE DIELECTRIC STRENGTH SHALL BE NOT LESS THAN 2156 VOLT(S) PER 0.001 INCH. |
| 2158 | THE DIELECTRIC STRENGTH SHALL BE NOT LESS THAN 2158 VOLT(S) PER MILLIMETER. |
| 2160 | THE BREAKDOWN VOLTAGE SHALL BE NOT LESS THAN 2160 VOLT(S). |
| 2102 | DIELECTRIC STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2102. |
| 2104 | DIELECTRIC STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM D 149. |
| 2106 | THERE SHALL BE 2106 SPECIMEN(S) TESTED. |
| 2112 | THE TEST SPECIMEN SHALL BE 2112 INCH(S) IN WIDTH. |
| 2114 | THE TEST SPECIMEN SHALL BE 2114 MILLIMETER(S) IN WIDTH. |
| 2116 | THE TEST SPECIMEN SHALL BE 2116 INCH(S) IN THICKNESS. |
| 2118 | THE TEST SPECIMEN SHALL BE 2118 MILLIMETER(S) IN THICKNESS. |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

| CHARACTERISTIC NAME | CHAR CODE |
|---|---|
| DIELECTRIC STRENGTH (CONT) | |
| PER ASTM D 149 (CONT) | |
| SPECIMEN LENGTH (SELECT ONE) | |
| (INCHES) | 2108 |
| (MILLIMETERS) | 2110 |
| SPECIMEN DIAMETER (SELECT ONE) | |
| (INCHES) | 2120 |
| (MILLIMETERS) | 2122 |
| NUMBER OF SPECIMENS TO BE TESTED (QUANTITY) | 2123 |
| SHORT TIME TEST TO BREAKDOWN. | 2134 |
| MAXIMUM VOLTAGE APPLICATION RATE (VOLTS PER SECOND) | 2136 |
| TEST VOLTAGE (SELECT ONE) | |
| (VOLTS, DC) | 2128 |
| (VOLTS, AC) | 2130 |
| FREQUENCY (HERTZ) | 2132 |
| TEST MEDIUM (SELECT ONE) | |
| OIL. | 2124 |
| AIR. | 2126 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

| CHAR CODE | STANDARD PARAGRAPH |
|---|---|
| 2462 | THERE SHALL BE 2462 SPECIMEN(S) TESTED. |
| 2450 | THE TEST SPECIMEN SHALL BE 2450 INCH(S) IN WIDTH. |
| 2452 | THE TEST SPECIMEN SHALL BE 2452 MILLIMETER(S) IN WIDTH. |
| 2454 | THE TEST SPECIMEN SHALL BE 2454 INCH(S) IN THICKNESS. |
| 2456 | THE TEST SPECIMEN SHALL BE 2456 MILLIMETER(S) IN THICKNESS. |
| 2446 | THE TEST SPECIMEN SHALL BE 2446 INCH(S) IN LENGTH. |
| 2448 | THE TEST SPECIMEN SHALL BE 2448 MILLIMETER(S) IN LENGTH. |
| 2449 | THE TEST SPECIMEN SHALL BE 2449 INCH(S) IN DIAMETER. |
| 2451 | THE TEST SPECIMEN SHALL BE 2451 MILLIMETER(S) IN DIAMETER. |
| 2444 | THE INDENTATION DURATION SHALL BE 2444 SECOND(S). |
| 2445 | THE TEST TEMPERATURE SHALL BE 2445 DEGREE(S) CELSIUS. |
| 2447 | THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2447 DEGREE(S) CELSIUS. |



Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

| CHARACTERISTIC NAME | CHAR CODE |
|---|---|
| HUMIDITY | |
| REQUIREMENTS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 4798 |
| AS FOLLOWS: | 3381 |
| MAXIMUM WEIGHT LOSS (PERCENT) | 3380 |
| MAXIMUM MOISTURE ABSORPTION (PERCENT) | 3382 |
| TEST METHODS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 4788 |
| PER ASTM D 570 | 3384 |
| SPECIMEN WIDTH (SELECT ONE) | |
| (INCHES) | 3386 |
| (MILLIMETERS) | 3388 |
| SPECIMEN THICKNESS (SELECT ONE) | |
| (INCHES) | 3400 |
| (MILLIMETERS) | 3402 |
| SPECIMEN LENGTH (SELECT ONE) | |
| (INCHES) | 3403 |
| (MILLIMETERS) | 3405 |





Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

| CHAR CODE | STANDARD PARAGRAPH |
|---|---|
| 4798 | HUMIDITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4798. |
| 3381 | HUMIDITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS: |
| 3380 | THE WEIGHT LOSS SHALL BE NOT GREATER THAN 3380 PERCENT. |
| 3382 | THE MOISTURE ABSORPTION SHALL BE NOT GREATER THAN 3382 PERCENT. |
| 4788 | HUMIDITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4788. |
| 3384 | HUMIDITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM D 570. |
| 3386 | THE TEST SPECIMEN SHALL BE 3386 INCH(S) IN WIDTH. |
| 3388 | THE TEST SPECIMEN SHALL BE 3388 MILLIMETER(S) IN WIDTH. |
| 3400 | TEST SPECIMEN SHALL BE 3400 INCH(S) IN THICKNESS. |
| 3402 | THE TEST SPECIMEN SHALL BE 3402 MILLIMETER(S) IN THICKNESS. |
| 3403 | THE TEST SPECIMEN SHALL BE 3403 INCH(S) IN LENGTH. |
| 3405 | THE TEST SPECIMEN SHALL BE 3405 MILLIMETER(S) IN LENGTH. |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

| CHARACTERISTIC NAME | CHAR CODE |
|---|---|
| HUMIDITY (CONT) | |
| PER ASTM D 570 (CONT) | |
| SPECIMEN DIAMETER (SELECT ONE) | |
| (INCHES) | 3404 |
| (MILLIMETERS) | 3406 |
| FIRST SPECIMEN TEST MEDIA (NAME) | 3408 |
| FIRST MEDIA TEMPERATURE (DEGREES CELSIUS) | 3410 |
| FIRST DURATION (SELECT ONE) | |
| (HOURS) | 3412 |
| (DAYS) | 3414 |
| (WEEKS) | 3416 |
| FIRST TOLERANCE, PLUS OR MINUS (HOURS) | 3418 |
| FIRST RELATIVE HUMIDITY (PERCENT) | 3420 |
| SECOND TEST MEDIA (NAME) | 3426 |
| SECOND TEST MEDIA TEMPERATURE (DEGREES CELSIUS) | 3427 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

| CHAR CODE | STANDARD PARAGRAPH |
|---|---|
| 3700 | THE DURATION FROM IMMERSION TO TEST SHALL BE NOT GREATER THAN 3700 HOUR(S). |
| 3701 | MEDIA-4 SHALL BE 3701. |
| 3703 | MEDIA-4 SHALL BE IN ACCORDANCE WITH 3703. |
| 3705 | TYPE 3705 SHALL APPLY TO MEDIA-4. |
| 3707 | DURATION OF IMMERSION IN MEDIA-4 SHALL BE 3707 HOUR(S). |
| 3709 | MEDIA-4 TEMPERATURE SHALL BE 3709 DEGREES CELSIUS. |
| 3711 | MEDIA-4 TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 3711 DEGREES CELSIUS. |
| 3715 | THE COOLING DURATION AT STANDARD CONDITIONS SHALL BE 3715 MINUTE(S). |
| 3717 | THE COOLING DURATION AT STANDARD CONDITIONS SHALL BE 3717 HOUR(S). |
| 3719 | THE DURATION FROM IMMERSION TO TEST SHALL BE NOT GREATER THAN 3719 HOUR(S). |
| 1380 | INSULATION RESISTANCE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1380. |



Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

| CHARACTERISTIC NAME | CHAR CODE |
|---|---|
| INSULATION RESISTANCE (CONT) | |
| REQUIREMENTS (CONT) | |
| AS FOLLOWS: | 6359 |
| NO EVIDENCE OF PHYSICAL DAMAGE. | 1407 |
| MINIMUM INSULATION RESISTANCE (MEGOHMS) | 1386 |
| TEST METHODS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 1371 |
| PER ASTM D 257 | 2581 |
| NUMBER OF SPECIMENS TESTED (QUANTITY) | 2583 |
| SPECIMEN WIDTH (SELECT ONE) | |
| (INCHES) | 2580 |
| (MILLIMETERS) | 2582 |
| SPECIMEN THICKNESS (SELECT ONE) | |
| (INCHES) | 2584 |
| (MILLIMETERS) | 2586 |



Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

| CHAR CODE | STANDARD PARAGRAPH |
|---|---|
| 6359 | INSULATION RESISTANCE. THE REQUIREMENT(S) SHALL BE AS FOLLOWS: |
| 1407 | THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE. |
| 1386 | INSULATION RESISTANCE AFTER TEST SHALL BE NOT LESS THAN 1386 MEGOHMS. |
| 1371 | INSULATION RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1371. |
| 2581 | INSULATION RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM D 257. |
| 2583 | THERE SHALL BE 2583 SPECIMEN(S) TESTED. |
| 2580 | THE TEST SPECIMEN SHALL BE 2580 INCH(S) IN WIDTH. |
| 2582 | THE TEST SPECIMEN SHALL BE 2582 MILLIMETER(S) IN WIDTH. |
| 2584 | THE TEST SPECIMEN SHALL BE 2584 INCH(S) IN THICKNESS. |
| 2586 | THE TEST SPECIMEN SHALL BE 2586 MILLIMETER(S) IN THICKNESS. |



Source: https://assist.dla.mil -- Downloaded: 202610-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

| CHARACTERISTIC NAME | CHAR CODE |
|---|---|
| INSULATION RESISTANCE (CONT) | |
| PER ASTM D 257 (CONT) | |
| SPECIMEN LENGTH (SELECT ONE) | |
| (INCHES) | 2588 |
| (MILLIMETERS) | 2590 |
| SPECIMEN DIAMETER (SELECT ONE) | |
| (INCHES) | 2592 |
| (MILLIMETERS) | 2594 |
| K FACTOR | |
| REQUIREMENTS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 3732 |
| K FACTOR (NUMBER) | 3734 |
| TEST METHODS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 3738 |
| PER ASTM C 177 | 3740 |





Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

| CHAR CODE | STANDARD PARAGRAPH |
|---|---|
| 2716 | OZONE RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2716. |
| 2717 | OZONE RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM D 1149. |
| 2736 | THE OZONE CONCENTRATION SHALL BE NOT LESS THAN 2736 PARTS PER 100 MILLION BY VOLUME. |
| 2738 | THE OZONE CONCENTRATION TEMPERATURE SHALL BE 2738 DEGREES CELSIUS. |
| 2740 | THE OZONE CONCENTRATION TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2740 DEGREES CELSIUS. |
| 2744 | THE EXPOSURE DURATION SHALL BE 2744 MINUTE(S). |
| 2742 | THE EXPOSURE DURATION SHALL BE 2742 HOUR(S). |
| 2743 | PEEL STRENGTH. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2743. |
| 2745 | PEEL STRENGTH. THE REQUIREMENT(S) SHALL BE AS FOLLOWS: |
| 2747 | THE PEEL STRENGTH SHALL BE NOT LESS THAN 2747 POUND(S) PER INCH OF WIDTH. |
| 2749 | THE PEEL STRENGTH SHALL BE NOT LESS THAN 2749 NEWTON(S) PER MILLIMETER OF WIDTH. |



Supersedes page 121 of 7 July 1978

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

| CHARACTERISTIC NAME | CHAR CODE |
|---|---|
| PEEL STRENGTH (CONT) | |
| TEST METHODS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 2762 |
| PER DOCUMENT (DOC DES) | 2764 |
| TEST SPECIMEN TEMPERATURE (DEGREES CELSIUS) | 2766 |
| TOLERANCE, PLUS OR MINUS (DEGREES CELSIUS) | 2768 |
| POROSITY | |
| REQUIREMENTS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 2772 |
| OPEN CELL POROSITY (PERCENT) | 2774 |
| TOLERANCE (PERCENT) | 2776 |
| TEST METHODS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 2782 |
| PER ASTM D 2734 | 2784 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

| CHAR CODE | STANDARD PARAGRAPH |
|---|---|
| 2762 | PEEL STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2762. |
| 2764 | PEEL STRENGTH. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2764. |
| 2766 | THE TEST SPECIMEN TEMPERATURE SHALL BE 2766 DEGREES CELSIUS. |
| 2768 | THE TEST SPECIMEN TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 2768 DEGREES CELSIUS. |
| 2772 | POROSITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2772. |
| 2774 | POROSITY. THE OPEN CELL POROSITY SHALL BE 2774 PERCENT. |
| 2776 | THE TOLERANCE SHALL BE PLUS OR MINUS 2776 PERCENT. |
| 2782 | POROSITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2782. |
| 2784 | POROSITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM D 2734. |



Supersedes page 123 of 7 JULY 1978

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

| CHARACTERISTIC NAME | CHAR CODE |
|---|---|
| POT LIFE | |
| REQUIREMENTS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 2788 |
| MINIMUM POT LIFE (HOURS) | 2790 |
| TEMPERATURE (DEGREES CELSIUS) | 2792 |
| FREE OF CRACKS AND BUBBLES. | 2794 |
| PROPER MIXING INSTRUCTIONS BY MANUFACTURER. | 2796 |
| TEST METHODS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 2801 |
| PER ASTM D 2471 | 2803 |
| SAMPLE SIZE (SELECT ONE) | |
| (MILLILITERS) | 2805 |
| (OUNCES) | 2807 |
| SHEAR STRENGTH | |
| REQUIREMENTS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 2811 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

| CHAR CODE | STANDARD PARAGRAPH |
|---|---|
| 3050 | THE TEST TEMPERATURE SHALL BE 3050 DEGREES CELSIUS. |
| 3052 | THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 3052 DEGREES CELSIUS. |
| 3054 | THE TEST RELATIVE HUMIDITY SHALL BE 3054 PERCENT. |
| 3056 | THE TEST RELATIVE HUMIDITY TOLERANCE SHALL BE PLUS OR MINUS 3056 PERCENT. |
| 3176 | VOLUME RESISTIVITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3176. |
| 3178 | VOLUME RESISTIVITY. THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE. |
| 3180 | THE VOLUME RESISTIVITY AT THE INITIAL MEASUREMENT SHALL BE NOT LESS THAN 3180 OHM(S) PER INCH. |
| 3182 | THE VOLUME RESISTIVITY AT THE INITIAL MEASUREMENT SHALL BE NOT LESS THAN 3182 OHM(S) PER MILLIMETER. |
| 3184 | THE VOLUME RESISTIVITY AFTER CONDITIONING SHALL BE NOT LESS THAN 3184 OHM(S) PER INCH. |
| 3186 | THE VOLUME RESISTIVITY AFTER CONDITIONING SHALL BE 3186 OHM(S) PER MILLIMETER. |



Supersedes page 155 of 7 JULY 1978

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

| CHARACTERISTIC NAME | CHAR CODE |
|---|---|
| VOLUME RESISTIVITY (CONT) | |
| TEST METHODS (SELECT ONE) | |
| PER BASE DOCUMENT EXCEPT ____ | 3132 |
| PER ASTM D 257 | 3153 |
| NUMBER OF SPECIMENS TO BE TESTED (QUANTITY) | 3154 |
| SPECIMEN WIDTH (SELECT ONE) | |
| (INCHES) | 3160 |
| (MILLIMETERS) | 3162 |
| SPECIMEN THICKNESS (SELECT ONE) | |
| (INCHES) | 3164 |
| (MILLIMETERS) | 3166 |
| SPECIMEN LENGTH (SELECT ONE) | |
| (INCHES) | 3156 |
| (MILLIMETERS) | 3158 |
| SPECIMEN DIAMETER (SELECT ONE) | |
| (INCHES) | 3168 |
| (MILLIMETERS) | 3170 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.

| CHAR CODE | STANDARD PARAGRAPH |
|---|---|
| 3132 | VOLUME RESISTIVITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3132. |
| 3153 | VOLUME RESISTIVITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTM D 257. |
| 3154 | THERE SHALL BE 3154 SPECIMEN(S) TESTED. |
| 3160 | THE TEST SPECIMEN SHALL BE 3160 INCH(S) IN WIDTH. |
| 3162 | THE TEST SPECIMEN SHALL BE 3162 MILLIMETER(S) IN WIDTH. |
| 3164 | THE TEST SPECIMEN SHALL BE 3164 INCH(S) IN THICKNESS. |
| 3166 | THE TEST SPECIMEN SHALL BE 3166 MILLIMETER(S) IN THICKNESS. |
| 3156 | THE TEST SPECIMEN SHALL BE 3156 INCH(S) IN LENGTH. |
| 3158 | THE TEST SPECIMEN SHALL BE 3158 MILLIMETER(S) IN LENGTH. |
| 3168 | THE TEST SPECIMEN SHALL BE 3168 INCH(S) IN DIAMETER. |
| 3170 | THE TEST SPECIMEN SHALL BE 3170 MILLIMETER(S) IN DIAMETER. |





Source: https://assist.dla.mil -- Downloaded: 20260-23T21:03Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

| CHARACTERISTIC NAME | CHAR CODE |
|---|---|
| VOLUME RESISTIVITY (CONT) | |
| PER ASTM D 257 (CONT) | |
| TEST TEMPERATURE | 3171 |
| TOLERANCE, PLUS OR MINUS (DEGREES CELSIUS) | 3172 |
| CONDITIONING PERIOD (SELECT ONE) | |
| (HOURS) | 3173 |
| (DAYS) | 3175 |
| STORAGE CONDITIONS | |
| (YEARS) | 1529 |
| CERTIFY MAXIMUM CURE DATE TO DELIVERY (QUARTERS) | 4942 |
| CERTIFY MINIMUM SHELF LIFE AFTER DELIVERY (QUARTERS) | 4943 |
| CERTIFY MAXIMUM MANUFACTURE DATE TO DELIVERY (QUARTERS) | 4944 |
| AGE LIMITATION PER MIL-STD-1523. | 5209 |





Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:03Z
Check the source to verify that this is the current version before use.