MILITARY SPECIFICATION

GROMMETS, POLYCARBONATE (FOR SEPARATE LOADED PROJECTILE)

This Specification is approved for use within US Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements, quality assurance provisions, and packaging for grommets for use in protecting the rotating band of separate loaded projectiles.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified (see 6.2), the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament,Munitions and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

MIL-STD-1169	-	Packaging, Packing and Marking for Shipment of Inert Ammunition Components
MIL-STD-1235	-	Single-and Multi-level Continuous Sampling Procedures and Tables for Inspection by Attributes

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS (See 6.4)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER (ARDC)

9251527	-	Grommet for M483, M483A1, M692, M825, M718, M731, M687, M485A1, M741 and M795 (155MM) Projectiles
9251987	-	Grommet for M107, M110, M116, M804, M118 and M121 (155MM) Projectiles
9255509	-	Grommet for M437 (175MM) Projectile
9270722	-	Grommet for M404 (8 inch) Projectile
9270723	-	Grommet for M509A1 (8 inch) Projectile
9321436	-	Grommet for M549 (155MM) Projectile
9349630	-	Grommet for M650 (8 inch) Projectile

(Copies of specifications, standards, drawings and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer).

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:13Z
Check the source to verify that this is the current version before use.

or MS standards), the text of this specification, shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Grommet. Material, parts and assemblies shall comply with all requirements specified on the applicable drawing and with all requirements specified in the applicable specifications.

3.2 Impact. The grommet shall not have visual cracks when subjected to the impact of a 100 pound striker dropped from a height of 3 feet, when tested as specified in 4.5.1.

3.3 First article inspection. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3).

3.4 Workmanship. The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following:

3.4.1 Metal parts. All parts shall be dry and free of chips, burrs, sharp edges, dirt, grease, and other foreign material. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agent.

3.4.2 Grommet. All grommets shall be made in a thorough, workmanlike manner. The grommet shall be free from cracks, burrs, sharp edges, holes, sink marks, splay (silver streaking), flash, surface blemishes, dirt, grease and other foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements and for the provisions of MIL-A-48078 as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all reqirements of sections 3 and 5. The inspection set forth in this

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:13Z
Check the source to verify that this is the current version before use.

specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in the sample quantities as indicated.

PART DESCRIPTION	DRAWINGS	QUANTITY
Fastener, Grommet	9255510	20
Grommet Assembly	9251527	20*
	9251987	
	9255509	
	9270722	
	9270723	
	9321436	
	9349630	

* From each mold cavity.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:13Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-G-48090A (AR)

PARAGRAPH	TITLE Fastener, Grommet Grommet Assembly		SHEET 1 OF 1		DRAWING NUMBER See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Fastener, Grommet (Dwg. 9255510)				
	Examination for defects	20	-	3.1	4.4.2.1
	Grommet Assembly See Applicable Drawing: 9251527 9251987 9255509 9270722 9270723 9321436 9349630				
	Examination for defects	20*	-	3.1	See applicable Quality Conformance Inspection paragraph 4.5.1
	Impact Test	10*	-	3.1	

NOTES:

*From each mold cavity (including fastener)

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:13Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of grommets shall contain:

a. Polycarbonate from not more than one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-1235 or MIL-STD-105 as applicable. Inspection Level shall be II.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:13Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-48090A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 9255510
4.4.2.1	Fastener, Grommet		NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Thickness		.40%	3.1	Gage
102	Distance from hook end to bail end		.40%	3.1	Gage
103	Distance between hooks		.40%	3.1	Gage
104	Total length of bail		.40%	3.1	Gage
105	Length of hooks		.40%	3.1	Gage
Minor					
201	Profile of fastener		.65%	3.1	Gage
202	Evidence of poor workmanship		.65%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22 19:13Z
Check the source to verify that this is the current version before use.

1 Aug 83 which may not be used.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.2	Grommet for M483, M692, M718, M731, M687 M741, XM795, XM825, M485A2 and M718E1, (155MM) Projectiles	1	1	9251527
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101	Diameter of top (nose facing) ridge		.40%	3.1	Gage
102	Diameter of bottom ridge		.40%	3.1	Gage
103	Wall thickness		.40%	3.1	Gage
104	Outside diameter		.40%	3.1	Gage
105	Diameter of inside ridge		.40%	3.1	Gage
106	Width of gap		.40%	3.1	Gage
107	Diameter of hole for fastener (2 places)		.40%	3.1	Gage
108	Thickness of inside ridge		.40%	3.1	Gage
109	Distance between bottom and top ridge inside		.40%	3.1	Gage
110	Distance between bottom ridge and inside ridge		.40%	3.1	Gage
111	Grommet fails to close properly		.40%	3.1	Visual/Manual
Minor					
201	Thickness of outside ridge (2 places)		.65%	3.1	Gage
202	Position of closure lip (2 places)		.65%	3.1	Gage
203	Width of closure lip (2 places)		.65%	3.1	Gage
204	Marking missing, misleading or unidentifiable		.65%	3.1	Visual
205	Color		.65%	3.1	Visual
206	Evidence of poor workmanship		.65%	3.4	Visual

NOTES:

Conditioning: The grommet shall be conditioned at ambient temperature for a minimum of [illegible] hours before any dimensional inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 20260-22T19:13Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.3	Grommet for M107, M110, M116, M118 and M121 (155MM) Projectles	1	1	9251987
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101	Diameter of outside ridge (2 places)		.40%	3.1	Gage
102	Inside diameter		.40%	3.1	Gage
103	Outside diameter		.40%	3.1	Gage
104	Width of gap		.40%	3.1	Gage
105	Diameter of hole for fastener (2 places)		.40%	3.1	Gage
106	Distance between bottom and top ridge inside		.40%	3.1	Gage
107	Grommet fails to close properly		.40%	3.1	Visual/manual
Minor					
201	Thickness of outside ridge (2 places)		.65%	3.1	Gage
202	Position of closure lip (2 places)		.65%	3.1	Gage
203	Width of closure lip (2 places)		.65%	3.1	Gage
204	Marking missing, misleading or unidentifiable		.65%	3.1	Visual
205	Color		.65%	3.1	Visual
206	Evidence of poor workmanship		.65%	3.4	Visual

NOTES:

Conditioning: The grommet shall be conditioned at ambient temperature for a minimum of 24 hrs before any dimensional inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:13Z
Check the source to verify that this is the currenversion before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Grommet for M437 (175MM) Projectile	1 OF 1	9255509
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101	Diameter of top (nose facing) ridge		.40%	3.1	Gage
102	Diameter of bottom ridge		.40%	3.1	Gage
103	Diameter of first ridge from top		.40%	3.1	Gage
104	Diameter of second ridge from top		.40%	3.1	Gage
105	Inside diameter		.40%	3.1	Gage
106	Outside diameter		.40%	3.1	Gage
107	Width of gap		.40%	3.1	Gage
108	Diameter of hole for fastener (2 places		.40%	3.1	Gage
109	Thickness of inside ridges (2 places)		.40%	3.1	Gage
110	Distance between bottom and top ridge inside		.40%	3.1	Gage
111	Distance between top ridge and first ridge		.40%	3.1	Gage
112	Distance between top ridge and second ridge		.40%	3.1	Gage
113	Grommet fails to close properly		.40%	3.1	Visual/manual
Minor					
201	Thickness of outside ridge (2 places)		.65%	3.1	Gage
202	Position of closure lip (2 places)		.65%	3.1	Gage
203	Width of closure lip (2 places)		.65%	3.1	Gage
204	Marking missing, misleading or unidentifiable		.65%	3.1	Visual
205	Color		.65%	3.1	Visual
206	Evidence of poor workmanship		.65%	3.4	Visual

NOTES:

Conditioning: The grommet shall be conditioned at ambient temperature for a minimum of 24 hrs before any dimensional inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2020-10-22 19:13Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Grommet for M106 or M404 (8 Inch) Projectile	1 OF 1	9270722
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101	Diameter of top (nose facing) ridge		.40%	3.1	Gage
102	Diameter of bottom ridge		.40%	3.1	Gage
103	Inside diameter		.40%	3.1	Gage
104	Outside diameter		.40%	3.1	Gage
105	Diameter of inside ridge		.40%	3.1	Gage
106	Diameter of hole for fastener (2 places		.40%	3.1	Gage
107	Width of gap		.40%	3.1	Gage
108	Thickness of inside ridge		.40%	3.1	Gage
109	Distance between bottom and top ridge inside		.40%	3.1	Gage
110	Distance between bottom ridge and inside ridge		.40%	3.1	Gage
111	Grommet fails to close properly		.40%	3.1	Visual/manual
Minor					
201	Thickness of outside ridge (2 places)		.65%	3.1	Gage
202	Position of closure lip (2 places)		.65%	3.1	Gage
203	Width of closure lip (2 places)		.65%	3.1	Gage
204	Marking missing, misleading or unidentifiable		.65%	3.1	Visual
205	Color		.65%	3.1	Visual
206	Evidence of poor workmanship		.65%	3.4	Visual

NOTES:

Conditioning: The grommet shall be conditioned at ambient temperature for a minimum of 24 hrs before any dimensional inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET	OF	DRAWING NUMBER
4.4.2.6	Grommet for M509A1 (8 Inch) Projectile		1	1	9270723
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101	Diameter of top (nose facing) ridge		.40%	3.1	Gage
102	Diameter of bottom ridge		.40%	3.1	Gage
103	Inside diameter		.40%	3.1	Gage
104	Outside diameter		.40%	3.1	Gage
105	Diameter of inside ridge (2 places)		.40%	3.1	Gage
106	Diameter of hole for fastener (2 places		.40%	3.1	Gage
107	Width of gap		.40%	3.1	Gage
108	Thickness of inside ridge		.40%	3.1	Gage
109	Distance between bottom and top ridge inside		.40%	3.1	Gage
110	Distance between bottom ridge and inside ridge		.40%	3.1	Gage
111	Distance between inside ridges		.40%	3.1	Gage
112	Grommet fails to close properly		.40%	3.1	Visual/manual
Minor					
201	Thickness of outside ridge (2 places)		.65%	3.1	Gage
202	Position of closure lip (2 places)		.65%	3.1	Gage
203	Width of closure lip (2 places)		.65%	3.1	Gage
204	Marking missing, misleading or unidentifiable		.65%	3.1	Visual
205	Color		.65%	3.1	Visual
206	Evidence of poor workmanship		.65%	3.4	Visual

NOTES:

Conditioning: The grommet shall be conditioned at ambient temperature for a minimum of 24 hrs before any dimensional inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.7	Grommet for M549 (155MM) Projectile	1	1	9321436
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101	Diameter of top (nose facing) ridge		.40%	3.1	Gage
102	Diameter of bottom ridge		.40%	3.1	Gage
103	Inside diameter		.40%	3.1	Gage
104	Outside diameter		.40%	3.1	Gage
105	Diameter of inside ridge (2 places)		.40%	3.1	Gage
106	Diameter of hole for fastener (2 places		.40%	3.1	Gage
107	Width of gap		.40%	3.1	Gage
108	Thickness of inside ridge		.40%	3.1	Gage
109	Distance between top ridge and inside ridge		.40%	3.1	Gage
110	Distance between inside ridges		.40%	3.1	Gage
111	Distance between bottom ridge and inside ridge		.40%	3.1	Gage
112	Grommet fails to close properly		.40%	3.1	Visual/manual
Minor					
201	Thickness of outside ridge (2 places)		.65%	3.1	Gage
202	Position of closure lip (2 places)		.65%	3.1	Gage
203	Width of closure lip (2 places)		.65%	3.1	Gage
204	Marking missing, misleading or unidentifiable		.65%	3.1	Visual
205	Color		.65%	3.1	Visual
206	Evidence of poor workmanship		.65%	3.4	Visual

NOTES:

Conditioning: The grommet shall be conditioned at ambient temperature for a minimum of 24 hrs before any dimensional inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:132
Check the source to verify that this is the currentversion before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Grommet for M650 (8 Inch) Projectile	1 OF 2	9349630
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101	Diameter of top (nose facing) ridge		.40%	3.1	Gage
102	Diameter of bottom ridge		.40%	3.1	Gage
103	Diameter of first ridge from top		.40%	3.1	Gage
104	Diameter of second ridge from top		.40%	3.1	Gage
105	Diameter of third ridge from top		.40%	3.1	Gage
106	Inside diameter		.40%	3.1	Gage
107	Outside diameter		.40%	3.1	Gage
108	Width of gap		.40%	3.1	Gage
109	Diameter of hole for fastener (2 places)		.40%	3.1	Gage
110	Thickness of inside ridge (3 places)		.40%	3.1	Gage
111	Distance between bottom and top ridge inside		.40%	3.1	Gage
112	Distance between bottom ridge and first ridge		.40%	3.1	Gage
113	Distance between bottom ridge and second ridge		.40%	3.1	Gage
114	Distance between bottom ridge and third ridge		.40%	3.1	Gage
115	Grommet fails to close properly		.40%	3.1	Visual/manual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.8	Grommet for M650 (8 Inch) Projectile				9349630
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Thickness of outside ridge (2 places)		.65%	3.1	Gage
202	Position of closure lip (2 places)		.65%	3.1	Gage
203	Width of closure lip (2 places)		.65%	3.1	Gage
204	Marking missing, misleading or unidentifiable		.65%	3.1	Visual
205	Color		.65%	3.1	Visual
206	Evidence of poor workmanship		.65%	3.4	Visual

NOTES:

Conditioning: The grommet shall be conditioned at ambient temperature for a minimum of 24 hrs before any dimensional inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article Table, Quality Conformance Inspection Tables, and herein.

4.4.3.1 Impact. Major defect. A random sample of 1 grommet per cavity per shift shall be selected for this test. If any projectile rotating band or obturator is damaged, or if the grommet cracks, the lot shall be rejected. Grommets shall be disposed of after completion of this test.

4.4.4 Inspection equipment. For inspection equipment required to perform the examinations and tests prescribed herein the contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.4.4.1 Automatic inspection equipment. All automatic test and inspection equipment when utilized by the contractor shall be subjected to periodic verification and calibration check during production. The procedures shall include as a minimum: frequency, method of verification, and the method of retrieval of item produced between verification/calibration. These procedures shall be included in the operation/calibration procedures as required by the above paragraph.

4.4.5 Dimensional control of molded plastic parts. In place of normal sampling and inspections associated with the Classification of Defects, and after a curing time of 24 hrs, a sample of three (3) parts (as molded) from each cavity shall be fully inspected dimensionally to qualify a new or reworked cavity for use in production. The molded parts shall carry the individual cavity identification. As a control of each cavity during production, the above quantity of parts from each cavity shall be inspected for the defects listed in the applicable quality conformance inspection paragraphs after continuous production of each 500 parts or at the end of each shift, whichever occurs first. Of the three (3) samples, one (1) sample shall be the last part produced. Reduced sampling of one (1) grommet per cavity may be implemented after ten (10) consecutive days of production have been found acceptable. If a failure occurs, sampling will revert to the original three (3) grommets per cavity and the sequence of reduced sampling of one grommet per cavity can be initiated after ten (10) consecutive days of production again have been found acceptable. If any defective parts are found during qualification of the cavity, the cavity producing the defective part will not be used in production. If any defective parts are found when inspection is performed for the control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for inspection for each separate type of defect according to the applicable quality

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

conformance inspection paragraph. All cavities removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above.

4.5 Methods of inspection.

4.5.1 Impact. The grommets shall be assembled to a projectile of the class on which the grommet will be used or a simulated projectile having a body and rotating band of materials and dimensions prescribed for the service projectile. The grommet and projectile assembly shall be placed in a fixture and a 100 pound (min.) striker shall be dropped from a height of 3 feet (min.) to impact the grommet. No blow shall strike the closure. After the blow, the grommet and projectile assembly shall be rotated on the longitudinal axis through approximately 90 degrees and another blow applied until a total of 2 blows have been applied. The above procedure shall be repeated on each assembly. The grommet and the rotating band shall be visually inspected for compliance with applicable requirements.

5. PACKAGING

5.1 Packing.

5.1.1 Level B. Unless otherwise specified by the procuring activity, all packing and marking shall be in accordance with MIL-STD-1169. The grommets shall be packed in the molded (relaxed) position.

6. NOTES

6.1 Intended use. The grommets covered by this specification are intended for use in protecting the rotating band and obturator of separate loaded projectiles during shipment and storage.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to US Army Armament Research, Development and Engineering Center (ARDEC) ATTN: AMSMC-QAR-I, Dover, NJ 07801-5001.

6.4 Data requirements. When this specification is used in an acquisition and data are required to be delivered, the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (CDRL), incorporated into the contract. When the provisions of DOD FAR Supplement Part 27, Sub-Part 27.410-6 (DD Form 1423) are

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:13Z
Check the source to verify that this is the current version before use.

invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specificaion are cited in the following paragraphs.

Paragraph	Data Requirement Title	Applicable DID
4.4.4	Inspection Equipment Descriptive Documentation	DI-R-1714

6.5 Drawings. Drawings listed in Section 2 of this specification under the headings US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal ARRADCOM drawings. Technical data originally prepared by these activities or ARRADCOM is now under the cognizance of ARDEC.

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

6.7 Subject term (key word) listing.

Grommets, Polycarbonate Projectile
Military Specification
Packaging, Ammunition

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 8140-A627)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARDEC
ATTN: AMSMC-QA
PICATINNY ARSENAL, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:13Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-G-48090A	GROMMETS, POLYCARBONATE (FOR SEPARATE LOADED PROJECTILE)

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:13Z
Check the source to verify that this is the current version before use.