7 July 1976
SUPERSEDING
(See Section 6)

MILITARY SPECIFICATION

HEADSET H-251( )/U

This specification is approved for use by the Electronics Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of dynamic double earphone headset; designated as Headset H-251( )/U. (See 6.1)

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

NN-P-71	Pallet, Materials-handling, Wood
QQ-S-781	Strapping, Steel, Flat and Seals
PPP-B-585	Box, Wood, Wirebound
PPP-B-601	Boxes, Wood, Cleated-Plywood
PPP-B-621	Boxes, Wood, Nailed and Lock-cover
PPP-B-636	Boxes, Fiber
PPP-B-640	Box, Fiberboard, Corrugated, Triple Wall
PPP-C-843	Cushioning Material, Cellulosic
PPP-F-320	Fiberboard, Corrugated and Solid Sheet Stock
PPP-P-291	Paperboard, Wrapping, Cushioning

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:48Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-S-760	Strapping, Nonmetallic (and Connectors)
PPP-T-45	Tape, Gummed, Paper, Reinforced and Plain for Sealing and Securing
PPP-T-97	Tape, Pressure-Sensitive Adhesive, Filament Reinforced

MILITARY

MIL-P-116	Preservation-Packaging, Methods of
MIL-P-11268	Parts, Materials, and Processes Used in Electronics Equipment
MIL-M-13231	Marking of Electronic Items
MIL-F-14072	Finishes for Ground Electronic Equipment

STANDARDS

FED-STD-356	Commercial Packaging of Supplies and Equipment
MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-147	Palletized and Containerized Unit Loads 40"x48" Pallets
MIL-STD-202	Test Methods for Electronic and Electrical Component Parts
MIL-STD-252	Wired Equipment, Classification of Visual and Mechanical Defects
MIL-STD-454	Standard General Requirements for Electronic Equipment
MIL-STD-810	Environmental Test Methods

DRAWINGS

ELECTRONICS COMMAND

DL-SM-B-461688	Headset H-251( )/U
SC-GL-58877	Gages for Connector U-182( )/U

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:48Z
Check the source to verify that this is the current version before use.

NAVY

SK-N-864 Simulated Gun Blast Producing Equipments

(Copies of documents required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.2 Other Publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue on date of invitation for bids or request for proposal shall apply.

AMERICAN NATIONAL STANDARDS INSTITUTE, INC.

S3.7-1973 - Coupler Calibration of Earphones
S1.10-1966 - Calibration of Microphones
S1.12-1967 - Specifications for Laboratory Standard Microphones

(Application for copies should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, N.Y. 10018)

3. REQUIREMENTS

3.1 First Article. When specified in the contract or purchase order, the contractor shall furnish sample units for first article inspection and approval (See 4.3).

3.2 Construction. The headset shall be constructed in accordance with the requirement of this specification and Drawing and Data List DL-SM-B-461688 (including the requirements for parts, materials and processes thereon) (See 4.4).

3.3 Parts, Materials and Processes; General. In addition to the requirements of this specification, the requirements of MIL-P-11268, including the selection requirements therein, shall apply. (See 4.4).

3.4 Finish. The equipment shall be finished in accordance with Specification MIL-F-14072 and the equipment drawings (See 4.4).

3.5 Marking. Marking shall conform to Specification MIL-M-13231 (See 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:48Z
Check the source to verify that this is the current version before use.

3.6 Performance Characteristics.

3.6.1 Headset H-251( )/U. (See 4.7.2.1)

3.6.1.1 Pull and Jerk. The headset shall withstand ten pounds of tension and one and a half pounds of jerk between the headband and connector without damage.

3.6.1.2 Impedance. The headset input impedance, measured at the connector, shall be 500 ohms ± 10 percent.

3.6.1.3 Insulation Resistance. The insulation resistance between pins A or B of the connector and any external metallic part shall be not less than one megohm.

3.6.1.4 Operation. The headset shall receive intelligible voice signals without buzzing, rattling or other spurious sounds.

3.6.2 Earphone. (See 4.7.2.2)

3.6.2.1 Response. The acoustic output of the earphone shall be between 104 and 110 db above a reference level of 0.0002 dynes per square centimeter when 1 milliwatts rms power, at frequencies from 20 to 3500 Hz, is applied to the earphone terminals.

3.6.2.2 Distortion. The acoustic output of the earphone shall have no more than 5 percent total harmonic distortion at any frequency in the range of 20 to 3500 Hz.

3.6.2.3 Overload. The earphone shall show no more than 3 db change from its original response curve after being subjected to the test specified in 4.7.2.2.3.

3.6.2.4 Impedance. The input impedance of the earphone at 1000 Hz shall be 1000 ohms ± 10 percent.

3.7 Environmental. The equipment shall meet the following environmental conditions.

3.7.1 Temperature.

3.7.1.1 Low. During and after testing as specified in 4.8.1.1, the equipment shall meet the requirements of 3.6.1.2, 3.6.1.3, 3.6.1.4 and 3.6.2.1 with no more than a 3 db change in response.

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:48Z
Check the source to verify that this is the currentversion before use.

3.7.1.2 High. During and after testing as specified in 4.8.1.2, the equipment shall meet the requirements of 3.6.1.2, 3.6.1.3, 3.6.1.4 and 3.6.2.1 with no more than a 3 db change in response.

3.7.2 Humidity. The equipment shall exhibit no physical damage such as corrosion, rust, blistering, swelling or deterioration of parts and materials, and shall meet the requirements of 3.6.1.2, 3.6.1.3, 3.6.1.4 and 3.6.2.1 during the operating times specified in 4.8.2 with no more than a 3 db change in response.

3.7.3 Altitude (Elevation). The equipment shall meet the requirements of 3.6.2.1 with no more than a 5 db change in frequency response at altitudes up to 10,000 feet above sea level after storage at 50,000 feet above sea level. (See 4.8.3)

3.7.4 Immersion. The equipment shall meet the requirements of 3.6.1.2, 3.6.1.3, 3.6.1.4 and 3.6.2.1 following immersion in three feet of water for 2 hours. (See 4.8.4)

3.7.5 Blast. The equipment shall meet the requirements of 3.6.2.1 with no more than a 3 db change in frequency response following thirty rounds of blast at a peak pressure of 9.5 pounds per square inch (psi). (See 4.8.5)

3.7.6 Vibration. The equipment shall meet the requirements of 3.6.2.1 following the tests of 4.8.6.

3.7.7 Shock, Drop. The equipment shall meet the requirements of 3.6.1.3, 3.6.1.4 and 3.6.2.1 with no more than 3 db change in frequency response following the tests of 4.8.7.

3.7.8 Bounce, Loose Cargo. The equipment shall meet the requirements of 3.6.1.3 and 3.6.1.4 following the test of 4.8.8.

3.7.9 Fungus. After the fungus test of 4.8.9, the headset shall be visually examined using a 10-power magnifier. The headset shall show no more than six minute unrelated spots, each no greater than 0.015 square inch in area, of sparse microbial growth as evidenced by growth colonization (which includes branching and sporulation) on or within the equipment. Isolated instances of partial tubular germination shall not be included in this evaluation. (See 6.4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:48Z
Check the source to verify that this is the current version before use.

3.7.10 Dust. After testing as specified in 4.8.10, the equipment shall meet the requirements of 3.6.2.1 with no more than 3 db degradation.

3.7.11 Salt Fog. After the salt fog test of 4.8.11, the headset, when examined visually with the aid of a 10-power magnifier, shall show no evidence of degradation, such as flaking, pitting, blistering or loosening of finish or metal surface; or exfoliation (see 6.4) of metal. Electrical operation is not required.

3.8 Reflectance. The reflectance of incident light of any external surface, as measured at 60 degrees from a line normal to the surface, shall be less than 10 percent. (See 4.9)

3.9 Interchangeability. Like units, assemblies, subassemblies and replaceable parts shall conform to Requirement 7 of MIL-STD-454. (See 4.12)

3.10 Workmanship. The equipment shall be manufactured and assembled in accordance with Requirement 9 of MIL-STD-454 and the applicable portions of MIL-P-11268. (See 4.6)

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Classification of Inspections. The inspection requirements specified herein are classified as follows:

a. First Article inspection. (See 4.3). Does not include preparation for delivery.

b. Inspections covered by subsidiary documents (See 4.4).

c. Quality conformance inspections.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:48Z
Check the source to verify that this is the current version before use.

4.2 Classification of Inspections. (con't)

(1) Quality conformance inspection of equipment before preparation for delivery (See 4.5).

(2) Quality conformance inspection of preparation for delivery (See 4.10).

4.3 First Article. Unless otherwise specified in the contract or purchase order, the First Article inspection shall be performed by the contractor.

4.3.1 First Article Units. The contractor shall furnish seventeen (17) First Article units of the complete Headset H-251( )/U.

4.3.2 First Article Inspection. The First Article inspection shall consist of the inspections specified in subsidiary documents covering the items listed in 4.4, and the inspections specified for Group A, Group B and Group C (See Table I, II and III respectively). The inspection shall be performed in the following order: 4.4, Group A and Group B for all units; and Group C as specified in Table III. After completion of Group C environmental tests, conforming units shall be reinspected and shall pass all Group A inspection.

4.3.3 First Article Data. The First Article test plan and test report shall be furnished as required in the contract or purchase order.

4.3.4 Failures. One or more failures shall be cause for refusal to grant first article approval.

4.4 Inspections covered by subsidiary documents. The following shall be inspected under the applicable subsidiary documents as part of the inspection required by this specification, and the inspection requirement specified in the contract or purchase order.

Item	Where required
Construction	3.2
Parts, materials and processes general	3.3
Finish	3.4
Marking	3.5

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:48Z
Check the source to verify that this is the current version before use.

4.5 Quality conformance inspection of equipment before preparation for delivery. The contractor shall perform the inspection specified in 4.4, 4.5.1 through 4.5.4. This does not relieve the contractor of his responsibility for performing any additional inspection which is necessary to control the quality of the product and to assure compliance with all specification requirements.

4.5.1 Group A Inspection. Each unit on contract or purchase order shall be inspected for conformance to the inspections specified in Table I. Discrete lots shall be formed from units that pass this inspection. Factors of lot composition not defined herein or in the contract or purchase order, shall be in accordance with MIL-STD-105. Each lot shall be subject to sampling inspection, utilizing the procedures of MIL-STD-105, using the general inspection levels and AQLs indicated in Table I.

4.5.1.1 Order of inspection within Group A. Group A inspection shall be performed in an order satisfactory to the Government except that the operational inspection shall be last.

Table I. Group A inspection

Inspection	Req Para	Insp Para	AQL Major	AQL Minor
Visual & mechanical	3.10	4.6	1%	4%
Impedance	3.6.1.2	4.7.2.1.2	1%	*
Ins Resistance	3.6.1.3	4.7.2.1.3	1%	*
Operation	3.6.1.4	4.7.2.1.4	1%	*

* All electrical and operational defects are considered major.

4.5.2 Group B Inspection. Group B inspection shall normally be performed on inspection lots that have passed Group A inspection and on samples selected from units that have been subjected to and met the Group A inspection. This inspection shall conform to Table II and to the special inspection levels of Table I of MIL-STD-105.

4.5.2.1 Group B Sampling Plans. The Group B sampling plans for the AQLs listed in Table II shall be Inspection Level S-4.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:48Z
Check the source to verify that this is the current version before use.

4.5.2.2 Order of Inspection Within Group B. Group B inspection shall be performed in an order satisfactory to the government.

Table II Group B inspection

Inspection	Req Para	Insp Para	AQL
Headset			
Pull and jerk	3.6.1.1	4.7.2.1.1	4.0%
Reflectance	3.8	4.9	(for the group)
Earphone			
Response	3.6.2.1	4.7.2.2.1	4.0%
Distortion	3.6.2.2	4.7.2.2.2	(for the
Impedance	3.6.2.4	4.7.2.2.4	group)
Interchangeability	3.9	4.12	6.5%

4.5.3 Group C Inspection. Group C inspection shall be performed on units that have passed Group A and Group B inspection. This inspection shall consist of the inspections specified in Table III. Samples shall be selected in accordance with 4.5.3.1.

4.5.3.1 Sampling for Group C Inspection. For Subgroup 1, four (4) samples of the headset shall be selected at random from each 500 units or fraction thereof produced. Two samples shall be subjected to the Overload test and two samples to the Immersion test. For Subgroup II, seven samples of the headset shall be selected at random from each 1500 units or fraction thereof produced and subjected to the tests specified, one test per sample. For Subgroup III, six samples of the headset shall be selected at random from each 3000 units or fraction thereof produced and subjected to the following: one sample to the Blast test, one sample to the Dust test, two samples to the Fungus test, and two samples to the Salt Fog test. The first samples of each subgroup test shall be selected from the first production lot.

4.5.3.2 Group C Failures. Actions required relative to Group C failures shall be specified in the contract or purchase order.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:48Z
Check the source to verify that this is the current version before use.

4.5.4 Reinspection of Conforming Group C Sample Units. Unless otherwise specified, sample units which have been subject to and passed Group C inspection may be accepted on contract provided all damage is repaired and the sample units are resubjected to and pass Group A and Group B inspection.

Table III Group C inspection

Inspection	Req Para	Insp Para
Subgroup 1		
Overload	3.6.2.3	4.7.2.2.3
Immersion	3.7.4	4.8.4
Subgroup II		
Temperature	3.7.1	4.8.1
Humidity	3.7.2	4.8.2
Altitude	3.7.3	4.8.3
Vibration	3.7.6	4.8.6
Shock, drop	3.7.7	4.8.7
Bounce	3.7.8	4.8.8
Subgroup III		
Blast	3.7.5	4.8.5
Fungus	3.7.9	4.8.9
Dust	3.7.10	4.8.10
Salt fog	3.7.11	4.8.11

4.6 Visual and Mechanical. The equipment shall be examined for compliance with 3.10 and for the defects listed in MIL-STD-252.

4.7 Performance Requirements.

4.7.1 Special Test Equipment.

a. Standard Microphone. Shall be a Laboratory-type microphone in accordance with ANSI S1.12,calibrated by the reciprocity method in accordance with ANSI S1.10.

b. Earphone Coupler. Type I in accordance with ANSI S3.7.

4.7.2 Methods of Inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:48Z
Check the source to verify that this is the current version before use.

4.7.2.1 Headset H-251( )/U.

4.7.2.1.1 Pull and Jerk. Attach the headband of the headset to a fixed object and suspend a ten pound weight from the connector. After ten minutes, remove the weight and visually examine the headset for damage to connections, staycord and molded parts. Test for operation and compliance with 3.6.1.1. With the headband secured to a fixed point, as above, attach a 1.5 pound weight to the connector and allow the weight to fall freely from a point close to the headband. Repeat twelve times. Examine the headset for damage, perform the operation test and determine compliance with 3.6.1.1.

4.7.2.1.2 Impedance. Apply a 1.0 volt, 1000 Hz, Sinusoidal signal through a decade resistance box (initially set to 500 ohms) in series with pins A and B of the connector. Vary the decade resistance until the voltage across the connector pins, as read on a VTVM, is equal to the voltage across the decade resistance. The decade resistance reading shall meet the requirement of 3.6.1.2.

4.7.2.1.3 Insulation Resistance. The assembly shall be tested in accordance with Method 302, test condition A, of MIL-STD-202 to meet the requirements of 3.6.1.3.

4.7.2.1.4 Operation. Connect the headset under test to an oscillator/amplifier. Adjust the amplifier to a comfortable listening level. Vary the oscillator frequency through the range of 20 to 3500 Hz and determine compliance with 3.6.1.4.

4.7.2.2 Earphone.

4.7.2.2.1 Response. Constant-available-power frequency response measurements shall be made at 20,30,50,70,100,200,300,700,1000, 1500,2000,2500,3000 and 3500 Hz. Response measurements shall be made in accordance with ANSI S3.7 in a Type-1 Earphone Coupler except that the coupling weight shall be one kilogram. Determine compliance with 3.6.2.1.

4.7.2.2.2 Distortion. Component harmonic distortion shall be measured at the frequencies cited in 4.7.2.2.1, in accordance with the procedures of ANSI S3.7, to meet the requirements of 3.6.2.2.

4.7.2.2.3 Overload. Operate the earphone at a 300 milliwatt level, 1000 Hz, for a period of 8 hours. Repeat the Response tests at the 1 milliwatt level for compliance with 3.6.2.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:48Z
Check the source to verify that this is the current version before use.

4.7.2.2.4 Impedance. Using the procedures described in ANSI S3.7, measure the impedance at 1000 Hz for compliance with 3.6.2.4.

4.8 Environmental Conditions.

4.8.1 Temperature.

4.8.1.1 Low. The equipment shall be tested in accordance with Method 502, Procedure I of MIL-STD-810. The storage temperature shall be minus 65°F, maintained for four hours, and the operating temperature shall be minus 40°F. Prior to, during and following the test, the equipment shall meet the full specification performance of 3.6.1.2 and 3.6.1.3. Prior to and following the test, the equipment shall meet the requirement of 3.6.1.4 and the earphone shall meet the requirements of 3.6.2.1 with no more than 3 db change in response.

4.8.1.2 High. The equipment shall be tested in accordance with Method 501, Procedure I of MIL-STD-810. The storage temperature shall be 155°F, maintained for two hours and the operating temperature shall be 150°F. Prior to, during and following the test, the equipment shall meet the full specification performance of 3.6.1.2 and 3.6.1.3. Prior to and following the test, the equipment shall meet the requirement of 3.6.1.4 and the earphone shall meet the requirements of 3.6.2.1 with no more than 3 db change in response.

4.8.2 Humidity. The equipment shall be tested in accordance with Method 507, Procedure II of MIL-STD-810, with measurements made during the last five hour period of each cycle. Prior to, during and following the test, the equipment shall meet the full specification performance of 3.6.1.2 and 3.6.1.3. Prior to and following the test, the equipment shall meet the requirement of 3.6.1.4 and the earphone shall meet the requirements of 3.6.2.1 with no more than 3 db change in response.

4.8.3 Altitude. The equipment shall be tested in accordance with Method 500, Procedure I of MIL-STD-810. Prior to, during and following the test the earphone shall meet the requirements of 3.6.2.1 with no more than 5 db change in response.

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:48Z
Check the source to verify that this is the currentversion before use.

4.8.4 Immersion. The headset shall be tested in accordance with Method 512, Procedure I, of MIL-STD-810. Prior to and following the test, the equipment shall meet the full specification performance of 3.6.1.2, 3.6.1.3, 3.6.1.4 and 3.6.2.1.

4.8.5 Blast. Mount the earphone element under test on the carriage of the Simulated Gun Blast Producing Equipment in accordance with U.S. Navy Drawing SK-N-864 with the front edge of the element in the test plane and with its axis coincident with that of the explosion chamber. Subject the earphone to 30 rounds of blast at a peak pressure of 9.5 psi. Prior to and following the test, the element shall meet the requirements of 3.6.2.1 with no more than 3 db change in response.

4.8.6 Vibration. The earphone shall be tested in accordance with Method 201 of MIL-STD-202. Mounting of the earphone in the test jig shall simulate the mounting in the headset. Prior to and following the test, the element shall meet the full specification requirement of 3.6.2.1.

4.8.7 Shock, Drop. The headset shall be dropped twelve times from a height of six feet onto a concrete floor faced with 1/8 inch thick asphalt tile. Prior to and following the test, the equipment shall meet the requirements of 3.6.1.3, 3.6.1.4 and 3.6.2.1 with no more than 3 db change in response. Mechanical damage shall be superficial only. This test shall be performed at a temperature of -40°F (-40°C).

4.8.8 Bounce, Loose Cargo. The equipment shall be tested in accordance with Method 514, Procedure XI, Part 2 of MIL-STD-810 except that the equipment shall lay at random on the test table and no reorientation shall occur at the half hour periods. Prior to and following the test, the equipment shall meet the requirements of 3.6.1.3 and 3.6.1.4

4.8.9 Fungus. The headset shall be subjected to the fungus test specified in Method 508, Procedure I, of MIL-STD-810. There shall be abundant growth colonization (See 6.4) on 50 percent or more of the area of the control item after 14 and 28 days. No cleaning of the headset is permitted for 72 hours prior to the Fungus test. Handling, prior to and during the test, shall be accomplished without contaminating the headset. Inability of the headset to meet the requirements of 3.7.9 shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:48Z
Check the source to verify that this is the current version before use.

4.8.10 Dust Test. The equipment shall be tested in accordance with Method 510, Procedure I, of MIL-STD-810 to meet the requirement of 3.7.10.

4.8.11 Salt Fog. The headset shall be subjected to the salt fog test specified in Method 509, Procedure I, of MIL-STD-810. No corrosion products shall be deposited on the test item by the facility. Inability of the headset to meet the requirements of 3.7.11 shall constitute failure of this test.

4.9 Reflectance. Using a Gardner Laboratory, Bethesda, Maryland, Portable 60 degree Glossmeter, or equal, make ten measurements at different points on the plastic surface. Average the ten readings to determine compliance with 3.8.

4.10 Quality conformance inspection of preparation for delivery. Preparation for delivery shall be inspected in accordance with MIL-P-116 to determine conformance to the requirements of Section 5.

4.11 Rough handling test (preparation for delivery). When rough handling test in accordance with MIL-P-116 is required by the contract, the functional tests of 4.7.2.1.4 shall be conducted to determine freedom from operational malfunction caused by rough handling.

4.12 Inspection for Dimensional Interchangeability. The insertable assembly dimensions shall be measured or gaged with applicable gages to the dimensions listed on mechanical gage drawings SC-GL-58877 for U-182( )/U connector to determine conformance to the physical interchangeability requirement of 3.9. When a listed dimension is not within specified or design limits, it shall be considered a major defect.

5. PACKAGING

5.1 Preservation. Preservation shall be level A,B or Commercial as specified (See 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning. Headset H-251( )/U shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. Headset H-251( )/U shall be dried in accordance with the applicable procedure of MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:48Z
Check the source to verify that this is the current version before use.

5.1.1.3 Preservation Application. Preservatives shall not be used.

5.1.1.4 Unit Packing. Each headset H-251( )/U shall be individually unit packed method III as follows: wrap each headset in paperboard conforming to PPP-P-291, type III. Secure the wrap with tape conforming PPP-T-45, type III, grade A. Cushion each set by wrapping in cellulosic cushioning material conforming to PPP-C-843, type II, sufficiently to prevent damage. Place the cushioned headset within a snug-fitting fiberboard box conforming to PPP-B-636, W5c. Close the box in accordance with the appendix of the box specification.

5.1.2 Level B.

5.1.2.1 Cleaning, drying, preservation application and unit packing. Each headset H-251( )/U shall be cleaned, dried, preserved and unit packed as specified in 5.1.1.

5.1.3 Commercial. Preservation shall be in accordance with Fed. Std. No. 356.

5.2 Packing. Packing shall be level A,B or Commercial as specified (see 6.2). Shipping containers for level A and B shall be capable of stacking and supporting superimposed loads during shipment and storage without damaging the container(s) or its contents.

5.2.1 Level A. A quantity of Headset H-251( )/U, unit packed as specified in 5.1.1, shall be packed within a snug-fitting fiberboard box conforming to PPP-B-636, type CF, class weather-resistant. Box closure shall be as specified in the appendix of the box specification. A quantity of the containers shall be packed within a close-fitting box conforming to PPP-B-601, overseas type; PPP-B-621, style 4, class 2; or PPP-B-585, style 2 or 3, class 3. When the gross weight exceeds 200 pounds, or the container length and width is 48 x 24 inches or more and the weight exceeds 100 pounds, 3 x 4 inch skids, laid flat, shall be applied in accordance with the requirements of the container specification, or if not specified in the specification, in a manner which will adequately support the item and facilitate the use of material handling equipment. Closure and strapping shall be in accordance with the applicable container specification or appendix thereto except that metal strapping shall conform to QQ-S-781, type 1, finish A.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:48Z
Check the source to verify that this is the current version before use.

5.2.1.1 Unitization. Palletization shall be required when: containers specified in 5.2.1 do not require skids; quantities per destination comprise a pallet load; and container size permits use of one of the pallet patterns of MIL-STD-147. A quantity of containers, packed as specified in 5.2.1, except that container strapping may be omitted, shall be placed on a pallet, load type 1, conforming to MIL-STD-147. The pallet shall be softwood conforming to NN-P-71, type IV, size 2. The load shall be "bonded" to the pallet by strapping conforming to QQ-S-781, type 1, finish A or shrink film.

5.2.2 Level B. A quantity of Headset H-251( )/U, unit packed as specified in 5.1.2, shall be packed within a close-fitting fiberboard box conforming to PPP-B-636, type CF, class weather-resistant. Box closure shall be as specified in the appendix of the box specification. A quantity of the containers shall be packed within a close-fitting fiberboard box conforming to PPP-B-640, class 2, style E, or PPP-B-636, type CF, class weather-resistant, variety DW. The gross weight of boxes conforming to PPP-B-640, shall not exceed 250 pounds. When the gross weight exceeds 200 pounds, or the container length and width is 48 x 24 inches or more and the weight exceeds 100 pounds, containers will be pallet-mounted on pallets conforming to NN-P-71, type IV. Closure shall be in accordance with the appendix of the applicable box specification. Reinforcing shall be by pressure-sensitive filament tape banding or nonmetallic strapping conforming to PPP-T-97 and PPP-S-760, respectively; selection of the material and application shall be in accordance with the appendix of the applicable box specification.

5.2.2.1 Unitization. Palletization shall be required when: containers specified in 5.2.2 do not require pallet mounting; quantities per destination comprise a pallet load; and container size permits use of one of the pallet patterns of MIL-STD-147. A quantity of containers, packed as specified in 5.2.2, shall be placed on a pallet, load type 1, conforming to MIL-STD-147. The pallet shall be softwood conforming to NN-P-71, type IV, size 2. A fiberboard cap shall be employed over the load having two sides extending down the stacked load at least 12 inches to accomodate marking requirements. The cap shall be fabricated of fiberboard conforming to PPP-F-320, class weather-resistant, W5s or V3c. The load shall be "bonded" to the pallet by strapping conforming to QQ-S-781, type 1, finish A or shrink film.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:48Z
Check the source to verify that this is the current version before use.

5.2.3 Commercial Packing. Commercial packing shall be in accordance with Fed. Std. No. 356.

5.3 Marking.

5.3.1 Military Marking. In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.

5.3.2 Commercial Marking. In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with Fed. Std. No. 356.

6. NOTES

6.1 Intended use. Headset H-251( )/U is a double earphone headset with a six foot retractile cord terminated in a 5 pin audio connector (U-182( )/U) and having an input impedance of 500 ohms. It is used with military man-pack radios (AN/PRC-25, etc.) and fits under the Infantrymen's Helmet.

6.2 Ordering Data. Procurement documents should specify the following:

a. Title, number and date of this specification and any amendment thereto.

b. Level A, level B or commercial preservation and packing (See Section 5).

c. When the rough handling test is required.

d. The number of First Article samples required (See 4.3.1).

6.3 Nomenclature. The parentheses in the nomenclature will be deleted or replaced by a letter identifying the particular design; for example: H-251W/U. The contractor should apply for nomenclature in accordance with the applicable clause in the contract.

6.4 Definitions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:48Z
Check the source to verify that this is the current version before use.

6.4.1 Branching. Branching is a connected arrangement of filaments (hyphae) formed by shoots or secondary stems growing from the main stem of filament (hypha).

6.4.2 Exfoliation. Exfoliation is corrosion along the grain bounderies of the metal resulting in the peeling of separating, or both, of successive layers of the metal. The appearance resembles loose book pages or onion skin peeling.

6.4.3 Growth Colonization. Growth colonization is a mass of individual plants, generally of one species, living together; or a group of hyphae which is formed from one spore or cell and may be one individual plant. Colonization which completely covers the surface of the nutrient material constitutes abundant growth.

6.4.4 Microbial Growth. Microbial growth is the growth of very minute organisms. Such organisms, when present in large numbers, may provide a colony visible to the naked eye.

6.4.5 Sporulation. Sporulation is the formation of minute unicellular reproductive or dormat bodies called spores.

6.4.6 Tubular Germination. Tubular germination is partial growth by the production of hyphae, which are tubular shaped fungal filaments. Tubular germination constitutes restricted individual spore growth not proceeding to colonization.

6.5 Verification Inspection. Verification by the Government will be limited to the amount deemed necessary to determine compliance with the contract and will be limited in severity to the definitive quality assurance provisions established in this specification and the contract. The amount of verification inspection by the Government will be adjusted to make maximum utilization of the contractor's quality control system and the quality history of the product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:48Z
Check the source to verify that this is the current version before use.

6.6 Supersession. This specification supersedes that part of MIL-H-55692(EL) relating to Headset H-251( )/U.

6.7 Environmental. Environmental pollution prevention measures are contained in the packaging material specifications referenced herein. Refer to material specifications or procuring activity for recommended disposability methods.

Custodian:

Army - EL

Preparing Activity

Army - EL

Project No. 5965-A130

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:48Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:48Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDING OFFICER
U.S. ARMY ELECTRONICS COMMAND
ATTN: AMSEL-TD-S
FORT MONMOUTH, N.J. 07703

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:48Z
Check the source to verify that this is the current version before use.