MILITARY SPECIFICATION

TEST VEHICLE WITH CARTRIDGE CASE M169 FOR M549 FUZE LOADING, ASSEMBLING AND PACKAGING

This specification is approved for use by the U.S. Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the loading, assembling and packaging for one type of test vehicle designated as Test Vehicle with Cartridge Case, M169 for M549 Fuze.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitations, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification for.
MIL-P-60942	-	Primer, Percussion for 40MM.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.

FSC 1390

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings and publications. The following other Government documents form a part of this specification to the extent specified herein:

DRAWING (SEE 6.8)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

PRODUCT AND PACKING DRAWINGS

9349984	-	Packing and Marking for Box, Fiberboard For Test Vehicle with Cartridge Case M169 for M549 Fuze.
9349986	-	Packing and Marking for Box, Wood for Test Vehicle with Cartridge Case M169 for M549 Fuze.
9349828	-	Test Vehicle with Cartridge Case M169 for M549 Fuze.
9349971	-	Cartridge 40MM: Test Vehicle for M549 Fuze.

INSPECTION EQUIPMENT DRAWINGS

9202253	-	Chamber Gage.
9202254	-	Limit.
9202255	-	Alignment.
9202528	-	Flush Pin.
9202529	-	Flush Pin.

CODE OF FEDERAL REGULATIONS

TITLE 49	-	Transporation, Parts 100-199.

(The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402. Orders should specify, "49 CFR 100-199 (latest revision)").

(Copies of specifications, standards, handbooks, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the test of this specification shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Test vehicle. The test vehicle shall comply with all requirements specified on Drawing (Dwg.) 9349828, all associated drawings, and with all requirements in applicable specifications.

3.3 Primer. The primers shall be dried at 110°F for 24 hours prior to assembly to case cartridge.

3.4 Mean velocity. The mean velocity shall be 790 ± 10.0 feet-per-second (f.p.s.).

3.5 Workmanship. All parts and assemblies shall be fabricated loaded and assembled in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, grease, rust, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous; however, a few light scratches not exposing base material may be permitted. All required marking and stamping shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following type of inspection shall be conducted on this item.:

a. Quality Assurance Inspection (See 4.4).

4.3 First article inspection. Not applicable to this specification.

4.4 Quality conformance inspection.

4.4.1.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each inspection lot shall contain:

a. Cartridge cases from one interfix lot number from one manufacturer.

b. Metal parts from one interfix lot number from one manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

c. Primers from one lot number from one manufacturer.

d. Propellant from not more than one lot from one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63996(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8886327
4.4.2.1	Cartridge Case Assembly, Prior to Loading				NEXT HIGHER ASSEMBLY 9349828
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101.	Closing cup missing		100%	3.2	Visual
102.	Propellant weight		-	3.2	4.4.3.2
103.	Propellant weight (alternate method)		-	3.2	4.4.3.3

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8886327
4.4.2.2	Cartridge Case Assembly, Prior to Inserting Base Plug and Primer.				NEXT HIGHER ASSEMBLY 9349828
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:					
1.	Spilled powder from cartridge case		100%	3.2	Visual
2.	Propellant charge weight obviously incorrect (See 6.7)		100%	3.2	Visual
MAJOR:					
101.	Propellant charge weight obviously incorrect (See 6.7)		100%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8886327
4.4.2.3	Cartridge Case Assembly				NEXT HIGHER ASSEMBLY 9349828
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:					
1.	Primer above flush with base plug		100%	3.2	Gage
MAJOR:					
101.	Security of crimp of base plug	4.4.3.4	4.4.3.4	3.2	4.5.2
102.	Base plug above flush		0.40%	3.2	9202528
103.	Depth of base plug, max.		0.40%	3.2	9202528
104.	Depth to primer from base plug, max.		0.40%	3.2	9202529
105.	Primer damaged		0.40%	3.2	Visual
106.	Excessive sealing compound on exterior surface of primer		0.40%	3.2	Visual
MINOR					
201.	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63996(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9349828
4.4.2.4	Test Vehicle, Prior to Assembling Inert Body Assembly				NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:	None defined				
MINOR:					
201.	O-ring (packing) missing in groove		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

8

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63996(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9349828
4.4.2.5	Test Vehicle				NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101.	Chamber gage failure		100%	3.2	9202253, 9202254, 9202255
102.	Pull test	20	2.50%	3.2	4.5.1
103.	Air pressure	200	1.50%	3.2	4.5.4
104.	Depth of charge surface		0.40%	3.2	Gage
105.	Diameter of rotating bands		0.40%	3.2	Gage
106.	O-ring exposed		0.40%	3.2	Visual
MINOR:					
201.	Total length		0.65%	3.2	Gage
202.	Marking missing or unidentifiable		0.65%	3.2	Visual
203.	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63996(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9349984
4.4.2.6	Unsealed Fiber Box				NEXT HIGHER ASSEMBLY 9349986
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101.	Test vehicle inverted		0.40%	3.2	Visual
102.	Incorrect number of test vehicles		0.40%	3.2	Visual
103.	Fillers missing		0.40%	3.2	Visual
MINOR:	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63996(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9349984
4.4.2.7	Sealed Fiber Box				NEXT HIGHER ASSEMBLY 9349986
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101.	Container damaged		0.40%	3.2	Visual
MINOR:					
201.	Contents loose		0.65%	3.2	Manual
202.	Label missing or unidentifiable		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-T-63996(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9349986
4.4.2.8	Sealed Wooden Packing Box				NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL:	None defined				
MAJOR:					
101.	Box damaged		0.40%	3.2	Visual
MINOR:					
201.	Contents loose		0.65%	3.2	Manual
202.	Car seal missing or improperly positioned		0.65%	3.2	Visual
203.	Marking misleading or unidentifiable		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Check test for deterioration of primers. If the total time between original acceptance of any lot and the assembly of that lot into the test vehicle exceeds two years, or if the primers have been subjected to adverse conditions; however brief, at any time since previous tests, the primer lot shall be subjected to and must satisfactorily pass the check test for deterioration specified in MIL-P-60942 immediately before the primer lot is assembled into the test vehicle. This test shall be performed by the contractor on primers selected by the Government inspector at the facility assembling the primers into the test vehicle (see 6.6).

4.4.3.2 Propellant weight of case, cartridge. The propellant weight shall be determined and then check weighed 100 percent. The check weighing shall be accomplished independently of the original weighing or determination, using a different balance from that used to make the original weighing and if performed manually, shall be performed by another operator. Any charge which fails to comply with the requirement specified on the applicable drawing shall be classified defective and removed from the lot.

4.4.3.3 Propellant weight of case cartridge alternate method. At the start of production 380 consecutive samples per station per machine shall be selected and weighed 100 percent. All samples shall comply with the applicable drawing requirement. If all samples comply with the applicable drawing requirement, five (5) samples per station every 2 hours production shall be selected and the average weight of the five (5) samples must meet the assessed mean propellant weight within $\pm$ 30 mgs. If the average weight fails the applicable drawing requirement, correction will be made and 380 consecutive samples weighed from that station. If all samples meet the applicable requirement, the sampling every 2 hours will be resumed.

4.4.3.4 Security of crimp of base plug. Five (5) cartridge case assemblies shall be randomly selected every four (4) hours production and subjected to this test. If any base plug moves more than .005 above flush with rear of case, the four (4) hours production represented by the sample shall be rejected. This test applies to each piece of equipment performing this operation.

4.4.3.5 Specific gravity of inert material. Two (2) sample cup assemblies shall be selected from each four (4) hours production and subjected to this test. If any sample fails to comply with the specified gravity requirement on the applicable drawing, the four (4) hours production represented by the sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

4.4.3.6 Mean velocity. Fifty (50) test vehicles shall be selected from each lot and subjected to this test.

4.4.3.6.1 Rejection. The lot shall be rejected if:

a. Mean velocity fails to meet the applicable requirement (see 3.4).

b. Three (3) or more base plugs are more than .005 above flush with rear of cartridge case (see 4.5.6).

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph Reference/Inspection Method Column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval, inspection equipment designs in accordance with terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test methods and procedures.

4.5.1 Pull test. The test vehicle shall be placed in an approved fixture and the force specified on the applicable drawing shall be applied. Observation shall be made for the requirement specified on the drawing. Cartridge case assemblies may be reused after undergoing a Government approved rework. Body assemblies may be reused. Test vehicle shall be pulled for total separation.

4.5.2 Security of crimp of base plug. The cartridge case assembly shall be assembled to a projectile and fired. Measurement for base plug more than .005 above flush from the rear of the cartridge case shall be measured from the highest point on the base plug to a point on the cartridge case directly beside it, radially.

4.5.3 Specific gravity of inert material. The specific gravity of the inert material shall be determined as follows:

Weigh the empty body assembly in grams and record as We. Fill the empty assembly with water at 75 degrees ± 2 degrees F., weigh in grams and record the weight as Ww. Determine the volume by subtracting We from Ww. Load the assembly with inert material, weigh in grams and record the weight as Wl. Determine the inert material weight by subtracting We from Wl. Calculate the specific gravity as follows:

$$\text{Specific gravity} = \frac{Wl - We}{Ww - We}$$

4.5.4 Air pressure. The test vehicle shall be placed in an approved test fixture and a measured quantity of air shall be applied to produce the required air pressure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

4.5.5 Mean velocity. The test vehicle shall be assembled as a cartridge (Dwg. 9349971) and fired from a mann barrel launcher placed on an approved mount. Distance to impact 200 meters minimum. Impact media, a backstop suitable to provide safety to range personnel and the public. The velocity shall be measured at 30 feet from the muzzle of the launcher and check measured at the same base line. The monitoring devices and time recorders shall be a dual system set-up for recording two (2) separate readings and shall be within 3 feet per second. If the two (2) readings differ more than 3 feet per second (individual shots), the results shall be discarded and another round fired in its place. When proving ground reports results for mean velocity, the number of "no test" rounds shall also be reported.

Observation shall be made and results calculated and recorded for mean velocity. The mean velocity of the lot being tested shall be corrected by the correction factor determined for the particular test launcher being used on the day of the test firing. When velocity values are suspected to be outliers, they shall be tested using the statistical procedure approved by the Government proving ground and the mean velocity adjusted accordingly. However, no more than four values consisting of no more than two on the high side and no more than two on the low side, shall be considered for exclusion.

4.5.6 Movement of base plug. The movement of the base plug shall be measured from the highest point on the base plug to a point on cartridge case directly beside it radially.

5. PACKAGING

5.1 Preservation and packaging.

5.1.1 Level B. Preservation and packaging shall be in accordance with Dwg. 9349984.

5.2 Packing.

5.2.1 Level B. The test vehicle shall be packed in accordance with Dwg. 9349986.

5.3 Shipping. When shipments of more than one lot are made as a carload, each lot must be kept separate, and the division between lots clearly indicated, to prevent mixing in transit.

5.4 Marking. Marking shall be in accordance with Dwgs. 9349984, 9349986 and Code of Federal Regulations, Title 49, Parts 100-199.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

5.5 Unitization. Unitization shall be prescribed by the procuring agency as specified in the contract or order.

6. NOTES

6.1 Intended use. This specification covers one type of test vehicle for use in acceptance testing of M549 Fuzes.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078(AR). Submit equipment designs as required to Commander, ARRADCOM, ATTN: DRDAR-QAF-I, Dover, NJ 07801. Request letter of submittal state contractor, contract number, specification number, item nomenclature and classification of defects or test paragraph.

6.4 Submission of results of contractor-conducted examinations and tests. Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to Commander, ARRADCOM, ATTN: DRDAR-QAF-S.

6.5 Submission of test data. In addition to the normal distribution of records, when the test vehicles are procured by ARRADCOM, one (1) copy of all ballistic data and ammunition data cards shall be forwarded to: Commander, ARRADCOM, ATTN: DRDAR-QAF-S, Dover, NJ 07801.

6.6 Cost of check test. The Contracting Officer will arrange for the contractor to be reimbursed for the expense incurred in the performance of the check test for deterioration of the primer assemblies. The tests shall be conducted at Government expense without cost to contractor who loaded the primer assemblies or to the contractor assembling the assemblies into the cartridge, and shall not constitute a basis for rejection against either contractor except where deterioration has occurred as a direct result of carelessness in handling, storage, etc, permitted while the primer assembly lot was under the jurisdiction of either contractor.

6.7 If any cartridge case, prior to insertion of the base plug and primer, is suspected of containing an underweight or or overweight propellant charge, based on visual inspection, it will be removed from the lot and weighed on suitable scales. Any cartridge case found with less than 75% or more than 125% of the assessed propellant load will be classified as a critical defect and removed from the lot. Any cartridge case found to have a propellant weight out of drawing tolerance but within ± 25% of the assessed propellant load will be classified as a major defect and removed from the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

6.8 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by this activities is now under the cognizance of ARRADCOM.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-A347)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament R&D Command
Attn: DRDAR-QAA
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-T-63996(AR) Test Vehicle with Ctg Case M169 for M549 Fuze

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:08Z
Check the source to verify that this is the current version before use.