MIL-C-52323A(ME)
3 February 1975
SUPERSEDING
MIL-C-52323(MO)
9 December 1963

MILITARY SPECIFICATION

CARRIAGE ASSEMBLY; CABLEWAY, MEDIUM

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the carriage assembly which is used with the medium cableway.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

MM-L-736	- Lumber; Hardwood.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.

Military

MIL-P-116	- Preservation-Packaging, Methods of.
MIL-T-704	- Treatment and Painting of Materiel.
MIL-G-10924	- Grease, Automotive and Artillery.
MIL-G-23827	- Grease, Aircraft and Instrument, Gear and Actuator Screw.

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.

FSC 5420

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

DRAWINGS

ME

TA13208E5012 - Carriage Assembly; Medium Cableway.

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN WELDING SOCIETY, INC. (AWS)

D1.1 - Structural Welding Code.

(Application for copies should be addressed to the American Welding Society, Inc., 2501 N.W. Seventh Street, Miami, FL 33125.)

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section IX, Welding Qualifications

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street NW, Washington, DC 20036.)

3. REQUIREMENTS

3.1 Description. The carriage assembly shall be as shown on Top Assembly TA13208E5012 and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the supplier shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly, and operation of the carriage assembly. Any data (e.g. shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the supplier or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 First article (preproduction model). The supplier shall furnish one carriage assembly for examination and testing within the time frame specified (see 6.2) to prove prior to starting production that his production methods will produce carriage assemblies that comply with the requirements of this specification. Examination and tests shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.3).

3.3 Material. Material shall be as specified herein and as shown on the applicable drawings.

3.3.1 Hardwood. Hardwood shall be in accordance with MM-L-736, Type II, and shall be beech, birch, rock elm, hickory, locust, hard maple, oak, or pecan structural plank. The lumber shall be dried to a moisture content of not more than 19 percent and shall be dressed on four sides (S4S) to the dimensions shown on the drawings. The wood blocks shall be free of loose knots, splits, checks, and wormholes.

3.4 Lubrication. When delivered, the sheave bearings shall be lubricated with grease conforming to MIL-G-10924 or MIL-G-23827. Each carriage assembly shall be tagged in a conspicuous place to indicate the temperature range and grade of grease used.

3.5 Treatment and painting. The carriage assembly, except for pins, bolts, nuts, and bearings, shall be treated and painted in accordance with

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

MIL-T-704, Type A. Pins, sheaves, nuts, and bolts shall be coated as specified in 5.1.1.

3.6 Identification marking. The carriage assembly shall be identified as shown on the drawings. Metal stamping shall be legible after painting.

3.7 Stenciling. The nomenclature, National Stock Number,(NSN) weight, and cube shall be stenciled on each carriage assembly. The letters "NET WT" shall precede the numerals in the weight and the letters "CU" shall precede the cubic displacement. Markings shall be Gothic-Type capitals and Arabic numerals 3/4-inch high. Stenciling shall conform to MIL-T-704.

3.8 Workmanship.

3.8.1 Metal fabrication. Metal used in fabrication shall be free from kinks and sharp bends. The straightening of material shall be done by methods that will not cause injury to the material. Corners shall be square and true. Flame-cutting, using tips suitable for the thickness of the steel may be employed instead of shearing and sawing. All bends shall be made with controlled means to insure uniformity of size and shape. precaution shall be taken to avoid overheating. Heated steel shall be allowed to cool slowly. External surfaces shall be free of burrs, sharp edges, and corners, except when sharp edges or corners are required or where they are not detrimental to safety.

3.8.2 Boltholes and pinholes. Boltholes and pinholes shall be drilled or reamed throught steel templates. Holes shall be drilled undersize prior to welding and machining and reamed to full size after all welding and machining of the carriage assembly have been completed, or shall be drilled full size after all welding and machining have been completed.

3.8.3 Welders and welding.

3.8.3.1 Welders. Before assigning any welder to manual welding work covered by this specification, the supplier shall provide the contracting officer with certification that the welder has passed qualification tests as prescribed by either of the following listed codes for the type of welding operations to be performed and that such qualification is effective as defined by the particular code:

AWS D1.1, Structural Welding Code, Section 5, Qualification.
ASME Boiler and Pressure Vessel Code, Section IX, Welding Qualifications.

Suppliers who only make horizontal welds need not qualify welders for "all position welding." Subject to approval by the Government, the supplier's standard welder qualification may be substituted in lieu of the above codes

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

provided that the supplier's procedure is equivalent to the above codes. The supplier shall be responsible for determining that automatic welding equipment operators are capable of producing quality welds in accordance with AWS and ASME codes.

3.8.3.2 Welding. The surfaces of parts to be welded shall be free from scale, paint, grease, and other foreign matter. Welding shall be done by the shielded metal-arc or gas metal-arc (MIG) process and shall conform to the provisions of the AWS D1.1. All welded parts shall be free from cracks and other imperfections that may reduce the effectiveness of the part. Work shall be positioned for flat welding when practicable. Before welding over previously deposited weld metal, all traces of slag shall be removed, and the deposit and adjoining base metal shall be wire brushed clean.

3.8.3.3 Welding jigs. Components shall be assembled in steel jigs or frames and welded while held in position. The jigs or frames shall be of a design that will limit the distortion to an amount that can be removed without changing the physical characteristics of the metal of the parts being welded.

3.8.4 Interchangeability. All like components shall be interchangeable with respect to installation, performance, and quality.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The supplier is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.1.2 Parts and components. Parts and components detailed on the drawings shall be inspected in accordance with the Supplementary Quality Assurance Provisions (SQAP) shown on the drawings. The drawings specify the characteristics requiring SQAP inspection, the sampling plan, and the basis for acceptance and rejection (see 6.4 and 6.5).

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:14Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. Inspections shall be classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).
(c) Inspection of preparation for delivery (see 4.6).

4.3 Preproduction inspection.

4.3.1 Examination. The preproduction carriage assembly shall be examined for the defects specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling for examination. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined as specified in 4.5.1. AQL shall be 2.5 percent defective for major defects and 4.0 percent defective for minor defects.

4.5 Inspection procedure.

4.5.1 Examination. The carriage assembly shall be examined as specified herein, for the following defects:

Major

101. Dimensions not as specified.
102. Materials not as specified.
103. Components missing or not as specified.
104. Weld defects, such as base-metal cracks adjacent to or behind welds, cracks in weld metal, undercutting of base metal, lack of fusion with parent metal or between parts, porosity, lack of penetration, slag inclusions, or spatter.
105. Sheaves out of round, axis of the axle hole or bearing not concentric with the rim of the sheave, warped or bent sheave.
106. Components containing projections or burrs.
107. Sheaves not lubricated or lubricant not as specified.
108. Sheaves not free to rotate.
109. Wood blocks containing checks, splits, loose knots, or wormholes.
110. Workmanship not as specified.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:14Z
Check the source to verify that this is the current version before use.

Minor

201. Identification or special marking incorrect, illegible, or missing.
202. Stenciling not as specified.
203. Treatment and painting not as specified.

4.6 Inspection of preparation for delivery.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

111. Hook weldment not removed as specified for Level A.
112. Unprotected surfaces not coated with preservative as specified for Level A.
113. Boxes not as specified for Level A or B.
114. Components not blocked or braced within the box as specified for Level A or B.
115. Marking missing, illegible, incorrect or incomplete.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be Level A or C as specified (see 6.2).

5.1.1 Level A. The hook weldment shall be removed to provide minimum cube. Pins, nuts, bolts, and sheaves shall be coated with Type P-1 preservative. The preservative shall conform to the applicable specification listed in and shall be applied in accordance with MIL-P-116.

5.1.2 Level C. Each carriage assembly shall be preserved and packaged in a manner to provide protection against corrosion and damage from the supplier to the initial destination.

5.2 Packing. Packing shall be Level A, B, or C as specified (see 6.2).

5.2.1 Level A. Each carriage assembly, preserved and packaged as specified in 5.1, shall be packed in a close-fitting box conforming to PPP-B-601, Overseas Type, Grade B, style optional; or PPP-B-621, Class 2, style optional.

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:14Z
Check the source to verify that this is the currentversion before use.

The contents shall be blocked and braced within the box in a manner to prevent free movement or damage. Box closure shall be in accordance with the appendix to the applicable box specification.

5.2.2 Level B. Each carriage assembly shall be packed as specified in 5.2.1 for Level A except the boxes shall be Domestic Type or Class as applicable.

5.2.3 Level C. The carriage assemblies shall be packed to assure carrier acceptance and safe delivery to destination at lowest ratings in containers complying with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.3 Marking. Marking for shipment and storage shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The carriage assembly is intended to be used for transporting equipment on the medium cableway.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Time frame required for submission of preproduction model (see 3.2).
(c) Level of preservation and packaging and level of packing required (see 5.1 and 5.2).

6.3 Preproduction model. Any changes or deviations of production carriage assemblies from the approved preproduction model during production will be subject to the approval of the contracting officer. Approval of the preproduction model will not relieve the supplier of his obligation to furnish carriage assemblies conforming to this specification.

6.4 Supplementary Quality Assurance Provisions (SQAP). The contracting officer should require the supplier to maintain records of all SQAP inspections. A suggested paragraph is as follows:

"The supplier shall maintain complete records of all examinations and tests performed to verify the requirements of classified SQAP characteristics. The records shall include, as a minimum, lot size, sample size, drawing requirement, actual measurement, number and type of deficiencies found, quantity approved, quantity rejected, corrective action taken when applicable."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

6.5 Definitions.

6.5.1 Supplementary Quality Assurance Provisions (SQAP). A SQAP is a contractual requirement that supplements Section 4 of the specification. SQAP indicates the minimum requirements which must be inspected on the product drawings to verify the design objectives of the product and assure interchangeability of repair parts.

Custodian:

Army - ME

Preparing activity:

Army - ME

Project No. 5420-A181

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:14Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-C-52323A(ME) Carriage Assembly; Cableway, Medium

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Mobility Equipment Research and
Development Center
ATTN: STSFB-DS
Fort Belvoir, Virginia 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.