MIL-C-60906A(MU)
11 August 1972
Superseding
MIL-C-60906(MU)
25 March 1968

MILITARY SPECIFICATION

CABLE, ASSEMBLY, SPECIAL PURPOSE, ELECTRICAL; T4179A

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of cable assembly used to test the M454 Projectile.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-S-19500/240 - Semiconductor Device, Diode, Silicon Rectifier Type S IN647
MIL-S-60902 - Soldering Electrical Connections for Nuclear Weapons Systems, Procedures for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-750 - Test Methods for Semiconductor Devices
MIL-STD-810 - Environmental Test Methods
MIL-STD-1168 - Lot Numbering of Ammunition
MS2437-1 - Complete Drum Assembly
MS2437-61 - Locking Ring
MS2437-81 - Gasket
RC32GF682K - Resistor

FSC-1190

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.

DRAWINGS

ORDNANCE CORPS

8794342 - Seal, Metallic, Assembly, Details and Instructions for Application
8800546 - Bag, Packing, Ammunition, for Cable Assembly
8806652 - Marking and Sealing for Cylindrical Containers
8857456 - Connector, Plug, Electrical
8860900 - Drum, Metal, Shipping (Interior)
8864768 - Cap, Dust
8864995 - Drum, Metal, Shipping for Cable Assembly, Special Purpose, Electrical: T4179
8865586 - Connector, Plug, Electrical, Special
9212669 - Sealing, Compound
9221392 - Cable Assembly Special Purpose Electrical: T4179A
9221393 - Strain Relief
9221410 - Molding Compound
9223341 - Jacket, Neoprene
9223342 - Primer for Neoprene
9223343 - Primer for Metal
ET9221392 - Equipment Tabulation

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The cable assembly shall comply with all requirements specified on the drawing (dwg) 9221392, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.2.1 Mating assembly. The assemblies shall be capable of being completely mated and unmated with their proper receptacles, without the use of tools. This capability shall be verified as specified in 4.4.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Serialization. The contractor shall assign serial numbers as required by drawings. The contractor may select any number which complies with the drawing requirement. These numbers shall not be duplicated.

3.5 Circuit resistance. The circuit resistance shall be tested as specified in 4.4.2 and comply with the requirements in Table I. The current through the cable shall be limited to 100 milliamperes(ma) maximum(max).

Table I

Cable Circuit Resistance

From Pin	To Pin	Ohms
2	A	6800 ± 10 percent
3	C	0.1 max
11	6	0.1 max
6	B	0.1 max
9	13	0.1 max

3.6 Diode. Test diode in circuit between pin 13 and pin E in accordance with 4.4.3. The forward voltage drop, VF, of each diode shall not exceed 1.0 volt when subjected to a forward current of 400 ± 40 milliamperes direct current. The reverse leakage current, IR, shall not exceed 0.25 microamperes direct current when subjected to a peak reverse voltage, VR, of 400 ± 40 volts.

3.7 Insulation resistance. The insulation resistance between each terminal and the connector shells and all other terminals listed in Table II shall be greater than 20 megohms at ambient and 10 megohms when tested at high and low temperature as specified in 4.4.4. Cable connector shells shall be at ground potential (test fixture ground).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.

Table II

Cable Insulation Resistance

Positive potential applied to pin	All other pins and connector shells minus potential except pins
A	2
B	6, 11
C	3
9	13 and E
F	
D	
1	
4	
5	
7	
8	
10	
12	
14	

3.8 Environmental testing. The cable assembly shall comply with MIL-STD-810, visual inspection and failure criteria, section 3. The cable assembly shall also comply with 3.5, 3.6 and 3.7 before and after each environmental test. Testing shall be as specified in 4.4.5. Tests shall be conducted in order specified.

3.8.1 Low temperature. The cable assembly shall withstand exposure to a storage temperature of -40 ± 5 degrees Fahrenheit (°F) for a duration of 48 hours, min and shall comply with 3.7 while at this temperature after bending 90 ± 10 degrees when tested as specified in 4.4.5.1.

3.8.2 High temperature. The cable assembly shall withstand exposure to a temperature of 160 ± 5°F and shall comply with 3.7 while at 160 ± 5°F when tested as specified in 4.4.5.2.

3.8.3 Transportation vibration. The cable assembly packed for shipment shall withstand vibration when tested as specified in 4.4.5.3.

3.9 Pull test. Each cable termination shall withstand a pull 15 ± 1 pounds without evidence of physical damage such as loose insulation, cracking, breaking or stretching of molding or insulation, when tested as specified in paragraph 4.4.6. Cable assemblies shall comply with 3.5, 3.6 and 3.7 following this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.

3.10 Torque test. The cable termination (see dwg. 9921392) shall withstand a torque of 30 ± 5 inch pounds without evidence of physical damage such as loose insulation, cracking, breaking or stretching of molding or insulation when tested as specified in 4.4.7. Cable assemblies shall comply with 3.5, 3.6 and 3.7 following this test.

3.11 Workmanship.

3.11.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.11.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.11.3 Burrs. Parts shall be free from burrs.

3.11.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.11.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection. (see 6.4)

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall shall submit 3 complete assemblies (see dwg. 9221392) and 3 sets of parts for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table III. Tests need not be conducted in order specified in Table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.

Table III

First Article Inspections and Tests

Examination or Test	Destructive	Non-Destructive	Assembly	Parts
1. Classification of characteristics (see 4.3.2.1)		X	X	X
2. Mating assembly (see 3.2.1)		X	X	
3. Circuit resistance (see 3.5)		X	X	
4. Diode (see 3.6)		X	X	
5. Insulation resistance (see 3.7)		X	X	
6. Low temperature (see 3.8.1)		X	X	
7. High temperature (see 3.8.2)		X	X	
8. Vibration (see 3.8.3)	X		X	
9. Pull test (see 3.9)		X	X	
10. Torque test (see 3.10)		X	X	

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table IV and Table V), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.

Table IV

Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-72	all	140-141	124	256-259	177	541-549	230
73	72	142	125	260-262	178	550-559	231
74	73	143-144	126	263-265	179	560-569	232
75	74	145	127	266-268	180	570-579	233
76	75	146-147	128	269-271	181	580-590	234
77	76	148-149	129	272-275	182	591-601	235
78	77	150	130	276-278	183	602-613	236
79	78	151-152	131	279-282	184	614-625	237
80	79	153-154	132	283-285	185	626-637	238
81-82	80	155-156	133	286-289	186	638-649	239
83	81	157	134	290-293	187	650-662	240
84	82	158-159	135	294-296	188	663-676	241
85	83	160-161	136	297-300	189	677-690	242
86	84	162-163	137	301-304	190	691-704	243
87	85	164-165	138	305-308	191	705-719	244
88-89	86	166-167	139	309-312	192	720-735	245
90	87	168	140	313-316	193	736-751	246
91	88	169-170	141	317-320	194	752-768	247
92	89	171-172	142	321-324	195	769-785	248
93	90	173-174	143	325-329	196	786-804	249
94-95	91	175-176	144	330-333	197	805-823	250
96	92	177-178	145	334-338	198	824-842	251
97	93	179-180	146	339-342	199	843-863	252
98	94	181-182	147	343-347	200	864-884	253
99-100	95	183-184	148	348-352	201	885-907	254
101	96	185-187	149	353-356	202	908-930	255
102	97	188-189	150	357-361	203	931-955	256
103	98	190-191	151	362-366	204	956-981	257
104-105	99	192-193	152	367-372	205	982-1008	258
106	100	194-195	153	373-377	206	1009-1036	259
107	101	196-197	154	378-382	207	1037-1066	260
108-109	102	198-200	155	383-388	208	1067-1098	261
110	103	201-202	156	389-393	209	1099-1131	262
111	104	203-204	157	394-399	210	1132-1166	263
112-113	105	205-207	158	400-405	211	1167-1204	264
114	106	208-209	159	406-411	212	1205-1243	265
115	107	210-212	160	412-417	213	1244-1285	266
116-117	108	213-214	161	418-424	214	1286-1330	267
118	109	215-217	162	425-430	215	1331-1378	268
119	110	218-219	163	431-437	216	1379-1429	269
120-121	111	220-222	164	438-443	217	1430-1483	270
122	112	223-224	165	444-450	218	1484-1542	271
123-124	113	225-227	166	451-457	219	1543-1605	272
125	114	228-230	167	458-465	220	1606-1673	273
126-127	115	231-232	168	466-472	221	1674-1747	274
128	116	233-235	169	473-480	222	1748-1827	275
129-130	117	236-238	170	481-488	223	1828-1914	276
131	118	239-241	171	489-496	224	1915-2010	277
132-133	119	242-243	172	497-504	225	2011-2115	278
134	120	244-246	173	505-513	226	2116-2232	279
135-136	121	247-249	174	514-521	227	2233-2361	280
137	122	250-252	175	522-530	228	over 2361	298
138-139	123	253-255	176	531-540	229		

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.

Table V
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Primer for metal (see dwg 9223343); primer for neoprene (see dwg 9223342); molding compound (see dwg 9221410); sealing compound (see dwg 9212669); jacket neoprene (see dwg 9223341); semiconductor device 1N647 (see MIL-S-19500/240); resistor (see RC32GF682K); connector, plug, electrical (see dwg 8857456); cap, dust (see dwg 8864768); connector plug, electrical (see dwg 8865586); covering details of dwg 9221392.

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Objective evidence (see 6.2) available for part in accordance with applicable drawing or standard	Visual
Minor:		
201.	Serialization (see 3.4)	Visual
202.	Workmanship (see 3.11)	Visual-Manual

4.3.2.1.2 Strain relief (see dwg 9221393 covering a detail of dwg 9221392).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.

Major:		
101.	Outside diameter of body, min	Gage
102.	Wall thickness at small diameter, min	Gage
103.	Small inside diameter, max	Gage
104.	Three small holes present	Visual
105.	Total length, max	Gage
106.	Diameter of thread clearance, max	Gage
107.	Pitch diameter of thread, max	Gage
108.	Minor diameter of thread, max	Gage
109.	Depth to bottom of thread clearance, min	Gage
110.	Depth of large inside diameter, max	Gage
111.	Length to outside taper, min	Gage
112.	Material (see 3.1)	Visual
113.	Objective evidence (see 6.2) available for protective finish in accordance with dwg 9221393	Visual
Minor:		
201.	Serialization (see 3.4)	Visual
202.	Workmanship (see 3.11)	Visual-Manual

4.3.2.1.3 Cable assembly, special purpose electrical T4179A (see dwg 9221392) before potting and molding of connectors and assembly of strain relief to forward connector.

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Cable correctly wired	Visual
102.	Insulation tubing present on resistor and semiconductor device	Visual
103.	Heat shrinkable tubing present on resistor and semiconductor device	Visual
104.	Soldering in accordance with MIL-S-60902(MU)	Visual
105.	Rear connector clamp screws tight	Manual
Minor:		
201.	Workmanship (see 3.11)	Visual-Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.

4.3.2.1.4 Cable assembly, special purpose electrical T4179A (see dwg 9221392) before molding of connectors.

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Proper strain relief assembly	Visual-Manual
Minor:	None defined.	

4.3.2.1.5 Cable assembly special purpose electrical T4179A (see dwg 9221392).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Proper molding	Visual-Manual
102.	Total length, min	**Measure
103.	Dust cap present	Visual
104.	Proper potting	Visual
**Measure with suitable scale		
Minor:		
201.	Serialization (see 3.4)	Visual
202.	Marking	Visual
203.	Workmanship (see 3.11)	Visual-Manual

4.3.2.1.6 Bag, packing, ammo, for cable assembly (see dwg 8800546 covering a detail of dwg 8864995)(see section 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Material (see 3.1)	Visual
102.	Length of envelope before packing, min	**Measure
103.	Width of envelope before packing, min	**Measure
**Measure with suitable scale		

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.

104.	Width of bag before packing, min	**Measure
105.	Length of bag before packing, min	**Measure
106.	Objective evidence (see 6.2) available for pressure sensitive tape and ink in accordance with applicable specification	Visual
107.	Properly packed	Visual-Manual
108.	Heat seal	Visual-Manual

**Measure with suitable scale

Minor:

201.	Marking	Visual
202.	Workmanship (see 3.11)	Visual-Manual

4.3.2.1.7 Drum, metal shipping (interior)(see dwg 8860900 covering a detail of dwg 8864995)(see section 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Objective evidence (see 6.2) available for complete drum assembly in accordance with MS2437-1	Visual
102.	Objective evidence (see 6.2) available for locking ring in accordance with MS2437-61	Visual
103.	Objective evidence (see 6.2) available for gasket in accordance with MS2437-81	Visual
Minor:		
201.	Workmanship (see 3.11)	Visual-Manual

4.3.2.1.8 Drum, metal, shipping for cable assembly, special purpose, electrical: T4179 (see dwg 8864995)(see section 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.

Major:		
101.	Contents tight in drum	Manual
102.	Drum sealed in accordance with dwg 8806652	Visual-Manual
103.	Objective evidence (see 6.2) available for metallic seal in accordance with dwg 8794342	Visual
104.	Seal present and properly assembled (see dwg 8794342)	Visual
Minor:		
201.	Marking	Visual
202.	Workmanship (see 3.11)	Visual-Manual

4.3.3 Testing. All tests shall be performed. Tests need not be performed in the order specified.

	Test	Test Classification
a.	Mating assembly	Major
b.	Circuit resistance	Major
c.	Diode	Major
d.	Insulation resistance	Major
e.	Pull test	Major
f.	Torque test	Major

None of these tests are considered destructive and samples so tested may be returned to the lot.

4.3.3.1 Mating assembly (see 3.2.1), circuit resistance (see 3.5), diode (see 3.6) and insulation resistance (see 3.7). Each cable assembly shall be tested in accordance with 4.4.1, 4.4.2, 4.4.3 and 4.4.4 as applicable. If any item fails to comply with 3.2.1, 3.5, 3.6 and 3.7 the item shall be rejected and removed from the lot.

4.3.3.2 Pull test (see 3.9; torque test (see 3.10). A sample shall be selected at random in accordance with Table VI. The sample shall be tested in accordance with 4.4.6 and 4.4.7. If any item fails to comply with 3.9 and 3.10, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.

Table VI

Sample sizes for non-destructive testing

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

4.3.4 Acceptance inspection equipment.

4.3.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL). ELs for assemblies are listed on the Equipment Tabulation, ET-9221392. When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Mating assembly (see 3.2.1). Each connector shall be assembled to its mating receptacle mounted rigidly on a fixture and comply with 3.2.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.

4.4.2 Circuit resistance (see 3.5). The resistance between pins listed in 3.5 shall be measured with an approved electrical resistance tester.

4.4.3 Diode (see 3.6). Test diode circuit in accordance with MIL-STD-750, Methods 4016.2 and 4011.3, as applicable.

4.4.4 Insulation resistance (see 3.7). The insulation resistance between each terminal and each terminal and connector shell specified in 3.6 shall be measured with either a megohmmeter or an approved test device, which applies a potential of 500 ± 50 volts direct current, interlocked at 5 milliamperes for 15 seconds minimum or until the megohmmeter or testing device stabilizes.

4.4.5 Environmental testing (see 3.8).

4.4.5.1 Low temperature (see 3.8.1). The cable assembly shall be tested in accordance with MIL-STD-810, Method 502.

4.4.5.2 High temperature (see 3.8.2). The cable assembly shall be tested in accordance with MIL-STD-810, Method 501, Procedure I.

4.4.5.3 Transportation vibration (see 3.8.3). The cable assembly shall be tested in accordance with MIL-STD-810, Method 514, Table 514-I, Procedure X, Curve AB, Fig. 514-6. The equipment shall not be operated during the test.

4.4.6 Pull (see 3.9). One end of the cable assembly shall be rigidly connected to a mating receptacle or a suitable fixture which transmits the pull through the metal portion of the connector. A 15 ± 1 pound pull shall be applied and released by pulling the cable through its longitudinal axis six consecutive times. This procedure shall be repeated using the other end of the cable assembly. After completion of the test, the cable assembly shall comply with the requirements in 3.9. The cable clamp shall cause no damage to the cable when the pull is applied.

4.4.7 Torque test (see 3.10). The connector (see dwg 8857456) end of the cable assembly shall be connected to a mating receptacle mounted on a suitable fixture. A torque of 30 ± 5 inch pounds shall be applied in a clockwise and then in a counterclockwise direction for a total of 3 times at a distance of 1/2 ± 1/8 inch to the rear of the metal portion of the connector base. The torque applying device shall not damage the rubber molding on the cable termination. After completion of the test the cable assembly shall comply with 3.10.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. The cable assembly shall be packaged in accordance with dwg 8864995 using the specified moisture barrier.

5.1.2 Level C. The cable assembly shall be packaged in accordance with dwg 8864995 except that the moisture barrier may be omitted.

5.2 Packing.

5.2.1 Level A and C. The cable assembly shall be packed in accordance with dwg 8864995.

5.3 Marking. Marking shall be as specified in accordance with dwg 8864995.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 or specification when specified on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SMUPA-QA-I.

6.4 Instructions for first article inspection (see 4.2.1). Parts may be used in subassemblies if the examination or tests (see 4.2.2, Table III) are verified by a representative designated by the Government. Subassemblies may be used in final assemblies if the examination or tests (see 4.2.2, Table III) are verified by a representative designated by the Government.

6.5 Identification of changes. The changes were so extensive in updating format and incorporating amendment changes the asterisk in the margin identifying changes has been omitted.

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1190-A060

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION: Cable, Assembly, Special Purpose, Electrical: T4179A
MIL-C-60906A(MU)

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-NR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:05Z
Check the source to verify that this is the current version before use.