MIL-C-81535A(AS)
3 February 1969
Superseding
MIL-C-81535(AS)
26 May 1967

MILITARY SPECIFICATION

CUTTER, CARTRIDGE ACTUATED, MARK 18 MOD 0

This specification has been approved by the Naval Air Systems Command, Department of the Navy.

1. SCOPE

1.1 This document governs the manufacture, assembly and preparation for delivery of the MARK 18 MOD 0 cartridge actuated cutter and the methods of inspection and tests upon which product acceptance will be based.

2. APPLICABLE DOCUMENTS

2.1 The following specifications, standards, drawings, and publications, of the issue in effect on date of invitation for bids, form a part of this document to the extent specified herein.

SPECIFICATIONS

Military

MIL-D-21625	Design and Evaluation of Cartridges for Cartridge Actuated Devices
MIL-P-20444	Primer, M42
MIL-P-116	Preservation, Methods of

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:39Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage

DRAWINGS AND ASSOCIATED LISTS

Naval Air Systems Command (Code Ident No. 30003)

DL 2518207	Cutter, Cartridge Actuated, MARK 18 MOD 0 (Formerly Code Ident No. 10001)
2518204	Cartridge, Delay, Assembly (Formerly Code Ident No. 10001)
2518212	Igniter Mix No. 212 (Formerly Code Ident No. 10001)
2518213	Mix, Time Delay, No. 213 (Formerly Code Ident No. 10001)
2518211	Explosive Charge No. 211 (Formerly Code Ident No. 10001)
2518376	Container, Inner, Assembly (Formerly Code Ident No. 10001)
2518375	Cutter, Cartridge Actuated, MARK 18 MOD 0, Packaging Assembly (Formerly Code Ident No. 10001)

Ordnance Corps of the Army (Code Ident No. 19203)

Army Dwg. 8799925	Primer, Percussion, M42, Assembly

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:39Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

BUSANDA Instruction 4030.17	Preservation, Packaging, Packing and Marking; Navy Policy for
Bureau of Naval Weapons	
WR-43	Preparation of Quality Assurance Provisions

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR 71-78	Transportation, Interstate Commerce Commission, Explosives and Other Dangerous Articles

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D. C. 20402. Orders for the above publication should request the latest edition and supplements thereto.)

3. REQUIREMENTS

3.1 General.

3.1.1 The MARK 18 MOD 0 cartridge actuated cutter covered by this specification shall be manufactured in accordance with DL 2518207 and all documents listed thereon.

3.2 Materials. All materials used in the manufacture of the cutters shall conform strictly with the specifications referred to on the respective Naval Air Systems Command drawings unless specific approval in writing covering a departure therefrom has been obtained

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:39Z
Check the source to verify that this is the current version before use.

from the Navy design activity prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.2.1 Preproduction sample. Unless otherwise specified by the procuring activity, a preproduction sample of 70 MARK 18 MOD 0 cartridge actuated cutters shall be manufactured using the same methods and procedures proposed for the production lot. The sample shall be tested as specified in 4.3.2 and is for the purpose of determining that the contractor, prior to starting production, is capable of producing items which comply with the technical requirements of the contract.

3.3 Primary components. For the purposes of this specification, the M42 primer, the igniter composition, the delay composition and the output charge are defined as primary components. See 4.3.3.

3.4 Primer. The M42 primers shall have been manufactured within the preceding 12 months, loaded with primer mixture styphnate composition No. 5086 and shall be in accordance with Drawing 8799925 and MIL-P-20444. See 4.7.1.

3.4.1 X-ray. All primers shall be X-rayed and screened for defects as outlined in 4.7.1.1.

3.5 Igniter composition and loading. The igniter composition shall be compounded and loaded in accordance with Drawings 2518212 and 2518204, respectively.

3.6 Delay composition and loading. The delay composition shall be compounded and loaded in accordance with Drawings 2518213 and 2518204, respectively.

3.7 Output charge.

3.7.1 Composition and loading. The output charge shall be compounded and loaded in accordance with Drawings 2518211 and 2518204, respectively.

3.7.2 Quantity. All output charges shall be as specified on Drawing 2518204. Charges shall be determined by weight rather than by volume measurements.

3.8 Inspection.

3.8.1 Cartridge subassembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:39Z
Check the source to verify that this is the current version before use.

3.8.1.1 Visual inspection. The complete cartridge subassembly shall be free of the visible defects noted in 4.7.2.1.

3.8.2 Assembled cutters.

3.8.2.1 Visual inspection. The completely assembled cutters shall be free of the visible defects noted in 4.7.2.2.

3.8.2.2 X-ray. All cutters shall pass the X-ray examination of 4.7.2.3.

3.9 Ballistic requirements. Cutters from each production lot, selected in accordance with 4.7.3.1, shall meet the requirements listed below when subjected to the tests prescribed in 4.7.3.2 and 4.7.3.3.

3.9.1 Delay time. The lower and upper limits of delay times shall be L = 4.90 seconds and U = 7.00 seconds, respectively, when fired over the temperature range of -65° to +160°F.

3.9.2 Output. Each unit shall furnish sufficient power to completely sever a 750-pound test nylon reefing line cord under no tension.

3.9.3 Misfire. There shall be no misfires. See 4.7.3.4.3.

3.10 Workmanship. Cutters shall be constructed and finished in a manner to assure compliance with all requirements of this specification. Particular attention should be directed to dimensions, finishes and coatings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:39Z
Check the source to verify that this is the current version before use.

4.2 Sampling. Unless otherwise specified, and when applicable, the sampling plans and procedures used in the determination of the acceptability of products submitted by a supplier shall be in accordance with the provisions of MIL-STD-105.

4.3 Lots.

4.3.1 Inspection lots. Inspection lot definition, formation, and size shall be in accordance with MIL-STD-105.

4.3.2 Preproduction sample. Before entering into quantity production, an acceptable preproduction sample of 70 cutters shall be prepared. Of these cutters, 60 shall be expended in the tests listed below and 10 shall be retained for investigative purposes. A preproduction sample acceptable for environmental and functional testing shall be defined as a sample which has met the requirements of paragraphs 3.3 through 3.8 of this specification. The contractor shall deliver the cutters to the activity designated by the contracting agency for test. Preproduction sample acceptance shall consist of the following tests as prescribed in MIL-D-21625: vibration (12), 15 "g" shock (12), temperature and humidity cycling, 14 days (12). The number in parentheses denotes the number of cartridges allocated for test. These cutters shall be conditioned for a minimum of 12 hours at +70° ± 5°F and fired with a 750-pound test nylon line under no tension threaded through the opening of the cutter. In addition, 24 cutters shall be temperature conditioned for a minimum of 12 hours (12 at -65° ± 5°F and 12 at +160° ± 5°F) and fired as provided in 4.7.3.2 and 4.7.3.3. No cutter shall produce results outside the limits set forth in paragraphs 3.9.1 and 3.9.2 and no cutter shall fail to fire. If any cutter fails to meet the requirements stated herein, the preproduction sample shall be rejected. Any quantity production prior to notification by the contracting agency of preproduction sample acceptability shall be at the contractor's risk. The preproduction cutters will not be applied as a part of the quantity specified for delivery by the contract.

4.3.3 Production lot. Unless otherwise specified in the contract, the minimum and maximum production lot size shall be 281 and 1200 cutters, respectively. Cutters required for all test purposes are selected from the production lot and will not be applied as a part of the quantity specified for delivery by the contract. Only primary components from a single lot shall be used in a production lot of cutters. One primary component production

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:39Z
Check the source to verify that this is the current version before use.

lot may be used in more than one cutter production lot. Cutters selected for the ballistic test shall be delivered to the activity designated by the contracting agency.

4.4 Gages. The contractor shall provide himself with gages as necessary to insure that the material to which this specification applies will meet the dimensional requirements on the applicable drawings.

4.5 Classification of characteristics. The characteristics verified by the tests and examinations herein are classified as Critical, Major or Minor in accordance with WR-43. Tests and examinations that verify critical characteristics are identified by the symbol (C) and major characteristics by the symbol (M). The number following the classification symbol indicates the serial number of test or examination. Tests and examinations which are not annotated with a classification code are classified minor.

4.6 Quality conformance inspection. Quality conformance inspection shall consist of verification of the characteristics classified on the drawings of DL 2518207 and verification of the following requirements and tests:

Item	Nature of Requirement Verification	Applicable Paragraphs	Classification
Primary Component	Single lot	3.3, 4.3.3	(M101)
Primer	Age, loading and acceptance	3.4, 4.7.1	(M102)
Primer	X-ray	3.4.1, 4.7.1.1	(M103)
Igniter Composition	Compounding and loading	3.5	(M104)
Delay Composition	Compounding and loading	3.6	(M105)
Output Charge	Compounding and loading	3.7.1	(M106)
Output Charge	Quantity	3.7.2	(M107)
Cartridge	Visual inspection	3.8.1.1, 4.7.2.1	(M108)
Cutter	Visual inspection	3.8.2.1, 4.7.2.2	(M109)
Cutter	X-ray	3.8.2.2, 4.7.2.3	(M110)
Cutter	Ballistic requirements	3.9, 4.7.3	(M111)
Cutter	Packaging, packing and container markings	4.6.1	(M112)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:39Z
Check the source to verify that this is the current version before use.

4.6.1 Packaging, packing and marking. The packaging and packing of cartridges and the container markings shall be in accordance with Section 5. Quality conformance inspection shall be conducted in accordance with the inspection criteria on the applicable drawings referenced in Section 5.

4.7 Tests.

4.7.1 Primer verification. Verify that the primers to be used were manufactured within the preceding 12 months and were furnished from lots certified by the supplier to have been loaded in accordance with 3.4 and accepted in accordance with the provisions of MIL-P-20444.

4.7.1.1 Primer X-ray. Primers should be mounted in suitable grooved racks. For the most revealing exposure, the primers are laid on their side with the anvil cutouts vertical. Pressure-sensitive tape may be used as an aid in positioning the primers. Reject any that are questionable from any standpoint, especially for: charge missing, cracked, or porous; cracked, deformed, or misplaced anvil; or other visible deformation or improper assembly of inert parts.

4.7.2 Visual inspection.

4.7.2.1 Cartridge subassembly. Examine each cartridge subassembly and reject for: missing, perforated, or deformed closure disc; insufficient crimp or cracked or split cartridge body lip in the crimped area at closure or primer end; primer cracked or deformed; or excessive sealant on dome of primer or closure disc.

4.7.2.2 Assembled cutter. Examine each assembled cutter and reject for: missing pull-ring or sleeve on the firing pin sear; protruding spring retainer; failure to crimp cartridge retaining areas; missing safety pin and tag; or improper crimp to retain spring retainer or anvil.

4.7.2.3 X-ray. All cutters shall be examined by X-ray and any observable imperfections in assembly shall be cause for cutter rejection. Special attention shall be given to verifying that: the cartridge assembly is properly crimped in place; all components are present; and that components are properly positioned, oriented and aligned.

4.7.3 Ballistic tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:39Z
Check the source to verify that this is the current version before use.

4.7.3.1 Sampling. Two samples of cutters will be required for the following ballistic tests. Each of the two samples shall be selected from the production lot in accordance with MIL-STD-105, Inspection Level I. In addition to the two samples of cutters required for the ballistic tests, ten additional cutters shall be furnished for investigative purposes.

4.7.3.2 Low temperature. One of the cutter samples, selected in accordance with 4.7.3.1, shall be conditioned for a minimum of 12 hours at -65° ± 5°F and fired with a 750-pound test nylon line under no tension threaded through the opening of the cutter.

4.7.3.3 High temperature. One of the cutter samples, selected in accordance with 4.7.3.1, shall be conditioned for a minimum of 12 hours at +160° ± 5°F and test fired as in 4.7.3.2.

4.7.3.4 Criteria of acceptability.

4.7.3.4.1 Delay time. With respect to delay time, the acceptance number shall be zero and the rejection number shall be one, using the limits specified in 3.9.1.

4.7.3.4.2 Output. The failure of any cutter to sever the 750-pound test nylon line, under the condition specified in 3.9.2, shall cause rejection of the lot represented.

4.7.3.4.3 Misfire. The failure of any cartridge to fire shall cause rejection of the lot represented, unless such failure is plainly attributable to faulty test equipment or procedure.

4.8 Retest. There shall be no retests.

4.8.1 Test failure. If test failure is attributable to an assignable cause, excluding the test cartridges, original test results should be discarded and the complete test reconducted.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. For definitions of packaging levels, see 6.4.

5.1.1 Level A. Level A packaging shall be used for packaging of all production lots for service use. Four cutters shall be packaged in an inner container in accordance with Drawing 2518376.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:39Z
Check the source to verify that this is the current version before use.

5.1.2 Level B. Not applicable.

5.1.3 Level C. When directed by the procuring activity, those cutters which are intended for expenditure in preproduction sample testing and for production lot acceptance tests shall be packaged in accordance with Method III of MIL-P-116 and with the Code of Federal Regulations 49 CFR 71-78.

5.2 Packing. For definitions of packing levels, see 6.4.

5.2.1 Level A. Level A packing shall be used for packing of all production lots for service use. Six inner containers as described in 5.1.1 shall be packed in accordance with Drawing 2518375.

5.2.2 Level B. Not applicable.

5.2.3 Level C. When directed by the procuring activity, cutters which are intended for expenditure in preproduction sample testing and for production lot acceptance tests, and are packaged in accordance with 5.1.3, shall be packed to afford protection against damage during direct shipment from the supply source to the first receiving activity for immediate use. Shipping containers shall be in accordance with the Code of Federal Regulations 49 CFR 71-78.

5.3 Markings.

5.3.1 Special markings. Marking of exterior containers shall be in accordance with the Code of Federal Regulations 49 CFR 71-78.

5.3.2 Normal markings. Unless otherwise specified in the contract or order, the marking information on unit packages and shipping containers shall be as specified on Drawings 2518376 and 2518375. The specified marking information shall be applied to the containers in accordance with the applicable provisions of MIL-STD-129.

6. NOTES

6.1 Intended use. The primary application for the MARK 18 MOD 0 cartridge actuated cutter is for dereefing the recovery parachute of a KDA type of target drone.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:39Z
Check the source to verify that this is the current version before use.

6.2 Ordering information. Procurement documents should specify the following:

a. title, number and date of this specification;

b. whether preproduction inspection is required, and if so, specify the test activity;

c. production lot size and test activity (see 4.3.3);

d. items of data required for each preproduction and production lot (see 6.3).

6.3 Data. For the information of contractors and contracting officers, any of the data specified in (a) subparagraphs below, (b) applicable documents listed in Section 2 of this specification or (c) referenced lower-tier documents need not be prepared for the Government and shall not be furnished to the Government unless specified in the contract or order. The data to be furnished shall be listed on DD Form 1423 (Contractor Data Requirements List) which shall be attached to and made a part of the contract or order. NAVWEPS Form 4200/15 (Drawings, Lists, and Specifications Required) shall be attached where applicable.

6.3.1 Test report. Results of ballistic tests shall be forwarded to the Naval Air Systems Command and the procuring activity.

6.3.2 Data cards. The contract or order should state the format, quantity and destination of data cards.

6.4 Definitions. The definitions of Levels A and C packaging and packing given below were extracted from BUSANDA Instruction 4030.17.

6.4.1 Level A packaging. The degree of preservation and packaging which will afford adequate protection against corrosion, deterioration and physical damage during handling, shipment, indeterminate storage and world-wide redistribution.

6.4.1.1 Level C packaging. The degree of preservation and packaging which will afford adequate protection against corrosion, deterioration and physical damage during shipment from supply source to the first receiving activity for immediate use. This level may conform to supplier's commercial practice when such meets the requirements of this level.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:39Z
Check the source to verify that this is the current version before use.

6.4.2 Level A packing. The degree of packing which will afford adequate protection during shipment, handling, indeterminate storage and world-wide redistribution.

6.4.2.1 Level C packing. The degree of packing which will afford protection against damage during direct domestic shipment from the supply source to the first receiving activity for immediate use. This level in general will conform to applicable carrier rules and regulations and may be the supplier's commercial practice when such meets the requirements of this level.

6.5 Explosives safety precautions.

6.5.1 Applicability. The loading, assembly and handling of the explosives, subassemblies and the finished items covered by this specification involve hazardous operations and therefore require suitable explosive safety precautions. At plants of the Naval Air Systems Command, Department of the Navy, and other Government plants where the Government is responsible for safety, the precautions listed below are mandatory. These same minimum provisions are recommended for observance by a contractor or manufacturer that explosively loads the item covered in this specification in order to fulfill his own safety responsibility. Other warnings and precautions, pertaining to the operational effectiveness or safety of the specified item during its use (for example, during its handling, launching or firing), are included in the detailed technical requirements of the specification. Use of this specification shall not be construed to replace other safety regulations of governmental agencies or to relieve the contractor or manufacturer of responsibility for the safety of his operations.

6.5.2 Personnel and equipment. Proper care must be exercised at all times to protect personnel from accidents, fires or explosions and to limit damage to equipment and loading areas. In connection with the above, the precautionary measures in the following paragraphs should be observed. (See also paragraph 6.5.4, Static and electrical and other applicable parts of these safety precautions.)

6.5.2.1 Explosives operations shall be kept under strict supervision. Periodic inspections shall be employed to assure compliance with established safety regulations.

6.5.2.2 Safe equipment and methods should be utilized for handling and transporting explosives and loaded parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:39Z
Check the source to verify that this is the current version before use.

6.5.2.3 Where required, remote control-barricaded-handling equipment shall be used for explosives operations such as mixing, pouring, weighing, charging, sifting, drying, pressing, casting, crimping, etc.

6.5.2.4 Employ properly proportioned and properly located protective barricades, screens or shields at all required points.

6.5.2.5 Maintain equipment such as presses, dies, crimpers, blenders, mixers, sifters, conveyors, and the like in safe operating condition.

6.5.2.6 Enforce, where necessary, the wearing of suitable safety footwear, gloves, goggles, respirators, and impregnated garments to protect personnel against burns, poisoning and associated industrial hazards.

6.5.2.7 During static tests, propulsion units such as rocket motors shall be restrained against full thrust to prevent flight if ignited, for example, during test of igniter circuit. Also, means shall be provided to harmlessly vent flames and exhaust gases.

6.5.3 Operating procedures. All loading operations shall be conducted in full accordance with a formalized operating procedure which shall include the following:

6.5.3.1 Keep only minimum, limited quantities of explosives and completed or partially loaded parts present at each stage of operation.

6.5.3.2 Allow no fires, exposed electrical or other sparking equipment, and little or no flammable material to be present in loading, handling and storage spaces. Enforce proper "Match" and "No Smoking" rules where necessary.

6.5.3.3 Appropriate safety instructions for specific operations shall be posted and personnel instructed as to the hazards present and precautions involved.

6.5.3.4 The number of working personnel and transients permitted in each work space shall be established and posted in such areas. The numbers shall be the minimum number required to accomplish necessary operations.

6.5.3.5 All loading operations should be conducted in a neat and orderly manner.

6.5.3.6 Enforce good housekeeping and maintain effective policing, inspection and supervisory methods throughout the loading area and surroundings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:39Z
Check the source to verify that this is the current version before use.

6.5.3.7 Employ effective cleaning methods periodically to minimize the accumulation of explosives or explosive dust and other contamination upon, and assure its removal from, floors, walls, ceiling, ledges, tables, benches, piping, and equipment or the items loaded. Clean up any spilled material immediately.

6.5.3.8 The exposure of explosive materials and related parts should be so controlled as to minimize the absorption of moisture from the atmosphere or other sources during loading and handling operations.

6.5.3.9 Personnel handling detonators, primers, delay elements, lead-ins, boosters, and related parts which affect functioning should, insofar as practicable, avoid using bare fingers or improper equipment in order to prevent damage, corrosion, or deterioration from perspiration or other contaminating deposits.

6.5.3.10 Keep explosives and explosive parts in approved covered receptacles with covers in place when material is not being taken out or put into the receptacles. Where necessary, receptacles should be conductive to ground electrostatic charges. (See paragraph 6.5.4.)

6.5.4 Static and electrical.

6.5.4.1 Protect operations from electrostatic charges by effectively grounding all machinery, equipment, and fixtures; and, where necessary, employ suitable grounded conductive coverings for floors, work benches and tables, and workers' conductive shoes. Workers' clothing of a type to minimize the accumulation of static charges shall be employed. Fabrics, such as silk and nylon, which generate static electricity shall be avoided. Additional grounding devices, such as grounded bracelets for workers, should be employed where operations are conducted with items which are unusually sensitive to initiation by static electricity. Such items include initiating explosives, tracer mixtures, and low energy type of electric primers, detonators and squibs. The latter types of items shall have the free ends of lead wires bared and twisted together and be packed in relatively small groups wrapped in bare non-insulated aluminum foil or other uncoated metal foil. During assembly and processing operations, such sensitive electric items should be short circuited by clips or other devices until installed with safety shunt in the final device. Additional precautions for these items should include mechanical shielding to contain or deflect fragments and blast; also electrical shielding from induced electric

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:39Z
Check the source to verify that this is the current version before use.

currents originated by sources such as lightning, static, electromagnetic radiations, etc. Where necessary for safety, humidity of work rooms should be appropriately increased, as required to lessen electrostatic effects, but without inducing excessive moisture absorption by any of the components of the item being processed.

6.5.4.2 Protect all explosive operations from the effects of electric current originating in equipment (such as soldering irons or guns, heaters, switches, wiring, motors, lights, test instruments, etc.) by suitable insulation, grounding, separation or shielding. Such electric sources may initiate explosives by heat, sparks, arcs, or by completing an electric circuit through an electric primer, detonator or squib. For example, circuits may be inadvertently completed from a defective electric soldering iron through a grounded contact. All electric types of primers, detonators or squibs provided with wire leads shall have the free ends of the wires bared and twisted together to short circuit each unit, except when in process of assembly into a finished item. Removable short circuiting clips or other devices should be employed during manufacturing operations involving items such as electric primers, detonators or squibs.

6.5.4.3 Where necessary, protect personnel and operations from electromagnetic energy. In certain work with very sensitive explosives or items, a shielded environment free from significant electromagnetic energy should be provided.

6.5.5 Operating facility and storage regulations.

6.5.5.1 All explosives including partially loaded items should be stored in suitable storage magazines located in accordance with the minimum distances prescribed in the American Table of Distances (ATD). While the explosive or loaded items are in process, stored in loading rooms, or in ready or service magazines, they should be located in accordance with Intraplant Distances set forth in the ATD. For Navy managed or contractor managed-Navy owned-explosives loading plants, the Armed Services Explosives Safety Board standards approved by the Department of Defense, the Secretary of the Navy and the Naval Air Systems Command covering quantity-distance regulations for explosives apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:39Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION
MIL-C-81535A(AS) CUTTER, CARTRIDGE ACTUATED, MARK 18 MOD 0

ORGANIZATION *(Of submitter)*	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 APR 63 1426

C-8870

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:39Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
Naval Air Systems Command
Washington, D.C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

NAVAL AIR SYSTEMS COMMAND (AIR-52021)
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:39Z
Check the source to verify that this is the current version before use.