METRIC

MIL-B-62062B(AT)
28 April 1989
SUPERSEDING
MIL-B-62062A(AT)
28 December 1973

MILITARY SPECIFICATION

BLOWER, GENERATOR COOLING: 28 VOLT DC

This specification is approved for use within the US Army Tank-Automotive Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of 28 volt (V) direct current (dc) blower designed for use in combination with a 300 ampere (A) generator on military tracked vehicles.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to : US Army Tank-Automotive Command, ATTN: AMSTA-GDS, Warren, MI 48397-5000, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document, or by letter.

AMSC N/A FSC 2920

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:13Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

FF-B-171	- Bearings, Ball, Annular (General Purpose).
TT-C-490	- Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings

MILITARY

MIL-P-514	- Plates Identification, Instruction and Marking Blank.
MIL-C-5541	- Chemical Conversion Coatings on Aluminum and Aluminum Alloys.
MIL-A-8625	- Anodic Coatings, for Aluminum and Aluminum Alloys.
MIL-F-13927	- Fungus Resistance Test; Automotive Components.
MIL-G-23827	- Grease, Aircraft and Instrument, Gear and Actuator Screw.
MIL-C-46168	- Coating, Aliphatic Polyurethane, Chemical Agent Resistant.
MIL-P-53022	- Primer, Epoxy Coating, Corrosion Inhibiting, Lead and Chromate Free.
MIL-P-53030	- Primer Coatings, Epoxy, Water Reducible, Lead and Chromate Free.
MIL-C-53039	- Coating, Aliphatic Polyurethane, Single Component, Chemical Agent Resistant.
MIL-C-81562	- Coatings, Cadmium, Tin-Cadmium and Zinc - (Mechanically Deposited)

STANDARDS

FEDERAL

FED-STD-H28/2	- Screw Thread Standards for Federal Services.

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspections by Attributes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:13Z
Check the source to verify that this is the current version before use.

MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-202	- Test Methods for Electronic and Electrical Component Parts.
MIL-STD-461	- Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference
MIL-STD-462	- Electromagnetic Interference Characteristics Measurement of.
MIL-STD-889	- Dissimilar Metals.
MIL-STD-45662	- Calibration System Requirements.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Government drawings. The following Government drawings form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

ARMY

10889713	-Generator, Engine Accessory.
10889998	-Generator, Engine Accessory.
10898759	-Blower, Electrical Rotating Equipment.
10898795	-Generator, Engine Accessory.

(Copies of specifications, standards, drawings required by the contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

AIR MOVEMENT AND CONTROL ASSOCIATION (AMCA)

AMCA standard 210-85 - Laboratory Methods of Testing Fans for Rating Purposes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:13Z
Check the source to verify that this is the current version before use.

(Applications for copies should be addressed to the Air Movement and Control Association, Inc., 30 West University Drive, Arlington Heights, IL 60004.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM B117	- Salt Spray (Fog) Testing, Method
ASTM B633	- Electrodeposited Coatings of Zinc on Iron and Steel, Standard Specification for

(Application for copies should be addressed to American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First Article. Unless otherwise specified (see 6.2), the contractor shall furnish blowers which shall be subjected to first article inspection (see 4.4). First article inspection samples, properly marked with identifying information shall be representative of the units to be furnished to the Government. All subsequent blowers delivered to the Government shall conform to these samples in all of their pertinent physical and performance attributes.

3.2 Materials. Materials shall be as specified herein, and in referenced specification, standards and drawings (see 4.7.1).

3.2.1 Recycled, virgin and reclaimed materials. There are no requirements for the exclusive use of virgin materials. The use of recycled or reclaimed (recovered) materials is acceptable provided that all other requirements of this specification are met (see 6.3.1).

3.2.2 Dissimilar metals. Dissimilar metals as defined by MIL-STD-889 shall not be used in contact with each other. Where such contact is unavoidable, the metal shall be protected against electrolytic corrosion. When protection is used, it shall be of such type that a low impedance path is offered to radio frequency currents (see 4.7.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:13Z
Check the source to verify that this is the current version before use.

3.2.3 Metal treatments.

3.2.3.1 Ferrous surfaces. Ferrous metal surfaces shall be cleaned in accordance with the applicable method specified in TT-C-490. The cleaned surfaces shall be treated in accordance with type I or type III of TT-C-490 (see 4.7.1 and 4.7.2).

3.2.3.2 Aluminum alloy surfaces. Aluminum surfaces shall be cleaned and treated in accordance with MIL-C-5541 or anodized in accordance with MIL-A-8625 (see 4.7.1 and 4.7.2).

3.2.3.3 Zinc plated surfaces. Zinc plated surfaces shall conform to Type II, class Fe/Zn 13 of ASTM B633 or type II, class 3 of MIL-C-81562 (see 4.7.1 and 4.7.2).

3.3 Design and construction. Unless otherwise specified (see 6.2), the blower shall be fabricated in accordance with Drawing 10898759 and as specified herein (see 4.7.1 and 4.7.2).

3.3.1 Interchangeability. Blowers shall have external dimensions that fall within the envelope outline of Drawing 10898759. Electrical connectors, shafts and mounting dimensions and their locations shall conform to the detail requirements of the drawing. Military standard parts shall be used whenever possible (see 4.7.1 and 4.7.2).

3.3.2 Threaded surfaces. All screw threads shall conform to FED-STD-H28/2. The thread form, class and the number of threads-per-inch shall be as specified on the referenced standards or drawings (see 4.7.1 and 4.7.2).

3.3.3 Bearings. Bearings included in blower assemblies shall meet the requirements of FF-B-171 together with any additional requirements specified on applicable standards or drawings. The bearings shall be lubricated with grease conforming to MIL-G-23827, however, maintenance lubrication shall not be required during the service life of the blower (see 4.7.1 and 4.7.2).

3.4 Performance.

3.4.1 Airflow. When operating at 25 ± 3 degrees Celsius (°C) with an input voltage of 27 V dc and an input current of not more than 14.5 A, the blower shall deliver not less than 4.2 cubic meters per minute (m3/min) at 15.2 centimeters (cm) of water back pressure (see 4.7.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:13Z
Check the source to verify that this is the current version before use.

3.4.2 Electromagnetic compatibility. The blower shall meet the requirements of MIL-STD-461A, notice 4, methods REO2 and CEO7 (see 4.7.4).

3.4.3 Dielectric strength. The blower shall withstand a voltage of 500 V root-mean-square (rms) at 60 cycles per second (cps) for 1 minute. There shall be no puncture of solid insulation, not continuing sparkover, no breakdown of dielectric material and no damage to the insulation sufficient to cause failure of the motor (see 4.7.5).

3.4.4 Environmental.

3.4.4.1 High temperature. When tested as specified in 4.7.6.1, the blower shall evidence no thrown solder, thrown impregnating compound, damaged insulation, raised armature windings, or raised commutator bars or other damage.

3.4.4.2 Low temperature. When tested as specified in 4.7.6.2, the blower shall evidence no thrown solder, thrown impregnating compound, damaged insulation, raised armature windings, or raised commutator bars or other damage.

3.4.4.3 Vibration. When tested in accordance with 4.7.6.3, the blower shall show no loosening of parts, objectionable operating characteristics, noise, wear, physical distortion or failure of components. After being subjected to vibration, the blower shall meet the requirements of 3.4.1.

3.4.4.4 Shock. When tested in accordance with 4.7.6.4, the blower shall show no change in physical, electrical, or material characteristics. After being subjected to shock, the blower shall meet the requirements of 3.4.1.

3.4.4.5 Sand and dust. After testing as specified in 4.7.6.5, the blower shall meet the requirements of 3.4.1.

3.4.4.6 Corrosion resistance. After testing as specified in 4.7.6.6, the blower shall evidence no damage affecting its operation and shall meet requirements of 3.4.1.

3.4.4.7 Fungus resistance. After having been subjected to the test specified in 4.7.6.7, the blower shall evidence no microbial growth that would adversely affect its performance and shall subsequently meet the requirements of 3.4.1.

3.4.5 Endurance. When tested in accordance with 4.7.7, the blower shall operate satisfactorily at 27 V and deliver not less than 4.2 m3/min of air at 15.2 cm of water back pressure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:13Z
Check the source to verify that this is the current version before use.

3.5 Painting. All exterior surfaces of the blower shall be painted except the electrical connections and the mating surfaces at the blower end. Prior to painting, surfaces of the blower shall be treated in accordance with 3.2.3.1 or 3.2.3.2 and then primed per MIL-P-53030 or MIL-P-53022. The dry film thickness of the primer coat shall be 1.0 to 1.5 mils. After priming, the exterior surfaces shall be topcoated with a coating conforming to MIL-C-46168 or MIL-C-53039. The dry film thickness of the topcoat shall be not less than 1.8 mils.

3.6 Identification and marking.

3.6.1 Marking. Blowers shall be marked in accordance with MIL-STD-130.

3.6.2 Nameplate. Each blower shall have a nameplate affixed to the blower exterior as specified on the drawing (see 3.3) or, if not specified, in a conspicuous place. The nameplate shall conform to the non-dimensional requirements of MIL-P-514. All nameplates shall include the following information as a minimum (see 4.7.2):

Blower, 28 volts DC.
Military part number.
Federal stock number.
Manufacturer's identification.
Manufacturer's serial number.
US

3.7 Workmanship. The workmanship shall be such as to assure a product free of rust, burrs, and scratches. All electrical connections shall be mechanically secured before being soldered or brazed to preclude the possibility of becoming loose due to vibration or shock. All solder cleaning agents and flux shall be noncorrosive. All traces of flux shall be chemically neutralized and removed after soldering (see 4.7.2).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order (see 6.2), the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the preformance of the inspection requirements specified herein, unless otherwise disapproved by the Government. The Government reserves the right to perform or witness any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:13Z
Check the source to verify that this is the current version before use.

specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptence comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual , nor does it commit the Government to acceptance of defective material.

4.1.2 Inspection equipment. Unless otherwise specified in the contract (see 6.2), the contractor is responsible for the provision and maintenance of all inspection equipment necessary to assure that supplies and services conform to contract requirements. Inspection equipment must be capable of repetitive measurements to an accuracy of 10% of the measurement tolerance. Calibration of inspection equipment shall be in accordance with MIL-STD-45662.

4.2 Classification of inspection:

a. First article inspection (see 4.4).
   1. Preproduction inspection (see 4.4.1).
   2. Initial production inspection (see 4.4.2).
b. Quality conformance inspections (see 4.5).
   1. Examinations (see 4.5.2).
   2. Tests (see 4.5.3).
c. Control tests (see 4.6).

4.3 Inspection conditions. Unless otherwise specified (see 6.2), all inspections shall be conducted under the following conditions:

a. Air temperature 23 ± 10°C
b. Barometric pressure 725 ± 50 mm Hg
   - 75
c. Relative humidity 50 ± 30 percent

4.4 First article inspection. First article inspections shall be performed on preproduction or initial production samples as specified herein. Approval of the first article sample by the Government shall not relieve the contractor of the obligation to supply blowers that are fully representative of those inspected as a first article sample. Any changes or deviation of the production units from the first article sample shall be subject to the approval of the contracting officer.

4.4.1 Preproduction inspection. When specified (see 6.2), the preproduction sample shall consist of four blowers. Preproduction inspection shall consist of inspection as specified in table I in the order specified in table II.

4.4.2 Initial production inspection. Unless otherwise specified (see 6.2), the Government shall select four blowers produced under the production contract for initial production inspection. Initial production units shall be inspected as specified in table I in the order specified in table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:13Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of inspections.

Title	Requirement	Inspection	First article Inspection Sample units 1	2	3	4	Quality conformance Examination	Tests	Control
Materials and construction	3.2, 3.2.2 thru 3.3.3	4.7.1	X	X	X	X			
Defects (see table III)	3.2.3 thru 3.3.3, 3.5, 3.6 and 3.7	4.7.2	X	X	X	X	X		
Airflow	3.4.1	4.7.3	X					X	X
Electromagnetic compatibility	3.4.2	4.7.4		X					
Dielectric strength	3.4.3	4.7.5	X		X	X			X
High temperature	3.4.4.1	4.7.6.1	X		X				
Low temperature	3.4.4.2	4.7.6.2	X			X			
Vibration	3.4.4.3	4.7.6.3	X			X			X
Shock	3.4.4.4	4.7.6.4	X			X			X
Sand and dust	3.4.4.5	4.7.6.5				X			
Corrosion resistance	3.4.4.6	4.7.6.6				X			
Fungus resistance	3.4.4.7	4.7.6.7			X				
Endurance	3.4.5	4.7.7	X						

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:13Z
Check the source to verify that this is the current version before use.

TABLE II. Order of preproduction testing.

Sample	Inspection	Title
1	4.7.5 4.7.6.1 4.7.6.2 4.7.6.3 4.7.6.4 4.7.7 4.7.3	Dielectric strength High temperature Low temperature Vibration Shock Endurance Airflow
2	4.7.4	Electromagnetic compatibility
3	4.7.5 4.7.6.1 4.7.6.7	Dielectrical strength High temperature Fungus resistance
4	4.7.5 4.7.6.2 4.7.6.3 4.7.6.6 4.7.6.4 4.7.6.5	Dielectric strength Low temperature Vibration Corrosion resistance Shock Sand and Dust

TABLE III. Order of initial production testing.

Inspection	Title
4.7.5	Dielectrical strength
4.7.6.1	High temperature
4.7.6.2	Low temperature
4.7.6.3	Vibration
4.7.6.4	Shock
4.7.7	Endurance
4.7.3	Airflow

4.4.3 First article inspection failure. Deficiencies found during, or as a result of, first article inspection shall be cause for rejection of the first article sample until evidence has been provided by the contractor that corrective action has been taken to eliminate the deficiency. Any deficiency found during, or as a result of, first article inspection, shall be evidence that all items already produced prior to completion of the first article

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:13Z
Check the source to verify that this is the current version before use.

inspection are similarly deficient unless contrary evidence satisfactory to the contracting officer is furnished by the contractor. Such deficiencies on all items shall be corrected by the contractor. The Government will not accept products until first article inspection is completed to the satisfaction of the Government.

4.5 Quality conformance inspections.

4.5.1 Sampling.

4.5.1.1 Lot formation. An inspection lot shall consist of all the blowers of one type and part number, from an identifiable production period, from one manufacturer, submitted at one time for acceptance.

4.5.1.2 Sampling for examination. Samples for quality conformance examination shall be selected in accordance with general inspection level II of MIL-STD-105.

4.5.1.3 Sampling for test. Samples for acceptance tests shall be selected in accordance with level S-3 of MIL-STD-105.

4.5.2 Examination.

4.5.2.1 Acceptable quality level (AQL). Each sample selected in accordance with 4.5.1.2 shall be examined to determine conformance to the following AQL's:

Classification	AQL
Major	1.0
Minor	2.5

4.5.2.2 Classification of defects. For examination purposes, defects shall be classified as listed in table IV.

TABLE IV. Classification of defects.

Category	Defects	Method of examination
Critical	None	
Major	AQL 1.0 % Defective	
101	Nonconformance in design and construction (see 3.3 thru 3.3.3).	Visual
102	Incorrect dimensions affecting interchangeability (see 3.3 and 3.3.1)	Visual and SIE 1/

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:13Z
Check the source to verify that this is the current version before use.

TABLE IV. Classification of defects - Continued.

Category	Defect	Method of examination
103	Defective leads and connectors (see 3.3.1)	Visual
104	Motor position alignment incorrect after shrunk fit assembly (see 3.3).	Visual SIE
105	Faulty workmanship affecting performance (see 3.7).	Visual
Minor	AQL 2.5 % Defective	
201	Incorrect dimensions not affecting interchangeability (see 3.3 and 3.3.1)	SIE
202	Improper finish (see 3.2.3).	Visual
203	Improper marking (see 3.6).	Visual
204	Faulty workmanship affecting appearence (see 3.2.3 and 3.6).	Visual

1/ SIE = Standard Inspection Equipment.

4.5.3 Test. Each blower selected in accordance with 4.5.1.3 shall be subjected to the quality conformance tests specified in table I.

4.5.3.1 Failure. Failure of any blower to pass the specified quality conformance test shall be cause for the Government to refuse acceptance of the production quantity represented, until action taken by the contractor to correct defects and prevent recurrence has been approved by the Government.

4.6 Control tests. Control tests shall be conducted on one blower from each lot of 400 units consecutively produced, except that not more than 2 blower tests shall be conducted in a 2 month period. Samples shall be taken from a production lot which has passed the quality conformance examination specified in 4.5.2.2. Control testing shall be performed as specified in table I in the following order: 4.7.5, 4.7.6.3, 4.7.6.4 and 4.7.3.

4.6.1 Failure. Failure of any blower to pass any of the specified tests shall be cause for the Government to refuse acceptance of the production quantity represented, until action taken by the contractor to correct defects and prevent recurrence has been approved by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:13Z
Check the source to verify that this is the current version before use.

4.7 Methods of inspection.

4.7.1 Materials and construction. Conformance to 3.2 through 3.2.3 and 3.3.1 through 3.3.3 shall be determined by inspection of contractor records providing proof or certification that design, construction, processing, and materials conform to requirements. Applicable records shall include drawings, specifications, design data, receiving inspection records, processing and quality control standards, vendor catalogs and certifications, industry standards, test reports, and rating data.

4.7.2 Defects. Conformance to 3.2.3 through 3.3.3 shall be determined by examination for the defects listed in table IV, and 3.5 through 3.7. Examination shall be visual or by measurement with standard inspection equipment.

4.7.3 Airflow. To determine conformance to 3.4.1, the blower shall be subjected to the applicable airflow test procedures of AMCA-standard 210-85.

4.7.4 Electromagnetic compatibility. To determine conformance to 3.4.2, the blower shall be tested in accordance with MIL-STD-462, notice 3.

4.7.5 Dielectric strength. To determine conformance to 3.4.3, the potential shall be applied to the armature and field terminals with the ground brush raised off the commutator and with the field ground disconnected. Capacitors incorporated in the motor circuit shall be disconnected during the test. Disassembly shall be required for ungrounding and examination. After the examination, the blower shall be reassembled and subjected to testing as specified in 4.7.3.

4.7.6 Environmental.

4.7.6.1 High temperature. To determine conformance to 3.4.4.1, the blower shall be stored in a test chamber at 71 ± 3°C for a period of 24 hours. The blower shall then be operated for a period of four hours at the 71 ± 3°C temperature. During operation the voltage input to the blower shall be between 27 and 29 V with the input to the blower at not more than 14.5 A.

4.7.6.2 Low temperature. To determine conformance to 3.4.4.2, the blower shall be stored in a test chamber at -18 ± 3°C for a period of 24 hours. The blower shall then be operated for a period of four hours at the -18 ± 3°C temperature. During operation the voltage input to the blower shall be between 27 and 29 V with the input to the blower at not more than 14.5 A.

4.7.6.3 Vibration. To determine conformance to 3.4.4.3, the blower shall be tested with method 201 of MIL-STD-202. The following details and exceptions shall apply:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:13Z
Check the source to verify that this is the current version before use.

a. The blower shall be rigidly mounted along any of the principal axes.
b. Vibration shall be for a total of 72 hours; 24 hours in the direction of each of the three major axes. During the latter 1/2 hour of each two hour period of vibration the blower shall be operated continuously at full load speed. Full load speed shall be obtained by adjustment of the line voltage to the 28.5 V.

4.7.6.4 Shock. To determine conformance to 3.4.4.4, the blower shall be tested in accordance with test condition K, method 213 of MIL-STD-202 with a 30 gravity units (g) peak value and using a sawtooth waveform for a duration of 11 milliseconds (ms). After having been subjected to the test specified in 4.7.3, the blower shall be disassembled and examined to determine conformance to 3.4.4.1 through 3.4.4.4.

4.7.6.5 Sand and dust. To determine conformance to 3.4.4.5, the blower shall be subjected to the test specified in method 110 of MIL-STD-202 except that chamber air speed shall be 762± 152 meters per minute (m/min).

4.7.6.6 Corrosion resistance. To determine conformance to 3.4.4.6, the blower shall be tested in accordance with the salt spray test specified in ASTM B117, except that the length of the test shall be 200 hours. After the corrosion test the blower shall be operated for one hour at 27 V before being subjected to the test specified in 4.7.3.

4.7.6.7 Fungus resistance. To determine conformance to 3.4.4.7, the blower shall be tested in accordance with class 2, method B of MIL-F-13927 except that the test period shall be a continuous 90 days. The blower shall be removed from the test cabinet without disassembly and without disturbing any fungus growths that have developed. Upon completion of the examination and replacement of access port covers, the blower shall be operated for one hour at 27 V before being subjected to the test specified in 4.7.3.

4.7.7 Endurance. To determine conformance to 3.4.5, the blower shall be subjected to continuous operation through the following test sequence:

1. 700 hours at 25 ± 3°C ambient temperature, 27 V input motor axis horizontal.
2. 150 hours at 25 ± 3°C ambient temperature, 27 V input motor axis 45 degrees, commutator down.
3. 150 hours at 25 ± 3°C ambient temperature, 27 V input motor axis 45 degrees, commutator up.

5. PACKAGING

5.1 Preservation, packaging, packing, and marking. Preservation, packaging, packing, and marking for the desired level shall be in accordance with the applicable packaging requirements specified by the contracting authority (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:13Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a of general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. Blowers covered by this specification are intended for use in combination with basic generator Drawing 10898795 and varying duct configurations on the M88 vehicle (see Drawing 10889998) and the M60A1 tank (see Drawing 10889713).

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. If first article inspection is not required (see 3.1).
c. Title, number, and date of drawing, if other than as specified (see 3.3).
d. If responsibility for inspection shall be other than as specified (see 4.1).
e. If responsibility for inspection equipment shall be other than as specified (see 4.1.2).

f. If inspection conditions are other than specified (see 4.3).
g. If preproduction inspection is required (see 4.4.1).
h. If preproduction inspection sample size shall be other than as specified (see 4.4.1).
i. If initial production inspection is not required (see 4.4.2).
j. If initial production inspection sample size shall be other than as specified (see 4.4.2).
k. Selections of applicable level and packaging requirements (see 5.1).

6.3 Definitions.

6.3.1 Recovered materials. "Recovered materials" means materials that have been collected or recovered from solid waste (see 6.3.2).

6.3.2 Solid waste. "Solid waste" means (a) any garbage, refuse, or sludge from a waste treatment plant, water supply treatment plant, or air pollution control facility; and (b) other discarded material, including solid, liquid, semisolid, or contained gaseous material resulting from industrial, commercial, mining, and agricultural operations, and from community activities. It does not include solid or dissolved material in domestic sewage, or solid or dissolved material in irrigation return flows or industrial discharges which are point sources subject to permits under section 402 of the Clean Water Act, (33 U.S.C. 1342 et seq.) or source, special nuclear, or byproduct material as defined by the Atomic Energy Act of 1954 (42 U.S.C. 2011 et seq.) (Source: Federal Acquisition Regulations, section 23.402).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:13Z
Check the source to verify that this is the current version before use.

6.4 Subject term (key word) listing.

Airflow
Corrosion resistance
Dielectric strength
Electromagnetic compatibility
Fungus resistance
Interchangeability

6.5 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army - AT

Review activity
DLA - CS

Preparing activity:
Army - AT

(Project 2920-A010)

☆U.S. GOVERNMENT PRINTING OFFICE: 1989 - 604-033/13185

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:13Z
Check the source to verify that this is the current version before use.