MILITARY SPECIFICATION
DESTRUCTOR, WARHEAD, SINGLE POINT, M14
METAL PARTS

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria, for the metal parts, for one type of destructor entitled Destructor, Warhead, Single Point, M14 Metal Parts which is used on the Nike Hercules warhead section.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

QQ-M-151	- Metals, General Specification for Inspection Of.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-1167	- Ammunition Data Card.
MIL-STD-1168	- Lot Numbering of Ammunition.
MIL-STD-1169	- Packaging, Packing and Marking of Inert Ammunition Components.

DRAWINGS

ORDNANCE CORPS

8795853 - Connector.
8795879 - Body.
8795885 - Cup.
8795887 - Ring, Retaining.
8795888 - Holder.
8795914 - Nut.
8796069 - Cup Relay.
8797371 - Sleeve.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

8799093 - Mounting Plate and Cover Assembly.
8799099 - Plate Mounting.
8799100 - Cable, Receptacle, Split Shell.
8799122 - Spacer Sub-Assembly, Arming Well.
8801181 - Connector.
8810179 - Wrench Assembly.
8810180 - Wrench.
EL-8815675 - Equipment Lists.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The destructor metal parts shall comply with all requirements specified on the drawings listed below, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

8801181 - Connector.
8795914 - Nut.
8795879 - Body.
8795885 - Cup.
8795887 - Ring, Retaining.
8795888 - Holder.
8810179 - Wrench Assembly.
8797371 - Sleeve.
8799093 - Mounting Plate and Cover Assembly.
8799122 - Spacer Sub-Assembly, Arming Well.
8796069 - Cup, Relay.

3.4 Mounting plate and cover assembly.

3.4.1 Continuity and resistance. The circuit shall be electrically continuous and shall have a resistance value of 0.015 ohms, when tested as specified in 4.4.2.

3.4.2 Dielectric strength. There shall be no evidence of dielectric failure as indicated by arcing between electrically isolated pins, or inability to attain and maintain an ac potential of 500 ± 50 volts root mean square (vrms) at 60 ± 5 Hertz (Hz), when tested as specified in 4.4.3.

3.4.3 Insulation resistance. The insulation resistance shall not be less than 20 megohms when tested as specified in 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

3.5 Rockwell hardness. The wrench assemblies shall be tested as specified in 4.4.2

3.6 Workmanship.

3.6.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.6.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.6.3 Burrs. Parts shall be free from burrs.

3.6.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.6.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 3 complete assemblies and sub-assemblies (see dwgs listed in 3.2) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table I. Tests need not be conducted in order specified in Table I.

Table I
First article inspection and tests

Inspection or Test	Dest	Non Dest
1. Classification of characteristics (see 4.3.2.1)		X
2. Continuity and resistance (see 3.4.1)		X
3. Dielectric strength (see 3.4.2)		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.	Insulation resistance (see 3.4.3)	X
5.	Rockwell hardness (see 3.5)	X

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table II and Table III), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-72	all	140-141	124	256-259	177	541-549	230
73	72	142	125	260-262	178	550-559	231
74	73	143-144	126	263-265	179	560-569	232
75	74	145	127	266-268	180	570-579	233
76	75	146-147	128	269-271	181	580-590	234
77	76	148-149	129	272-275	182	591-601	235
78	77	150	130	276-278	183	602-613	236
79	78	151-152	131	279-282	184	614-625	237
80	79	153-154	132	283-285	185	626-637	238
81-82	80	155-156	133	286-289	186	638-649	239
83	81	157	134	290-293	187	650-662	240
84	82	158-159	135	294-296	188	663-676	241
85	83	160-161	136	297-300	189	677-690	242
86	84	162-163	137	301-304	190	691-704	243
87	85	164-165	138	305-308	191	705-719	244
88-89	86	166-167	139	309-312	192	720-735	245
90	87	168	140	313-316	193	736-751	246
91	88	169-170	141	317-320	194	752-768	247
92	89	171-172	142	321-324	195	769-785	248
93	90	173-174	143	325-329	196	786-804	249
94-95	91	175-176	144	330-333	197	805-823	250
96	92	177-178	145	334-338	198	824-842	251
97	93	179-180	146	339-342	199	843-863	252
98	94	181-182	147	343-347	200	864-884	253
99-100	95	183-184	148	348-352	201	885-907	254
101	96	185-187	149	353-356	202	908-930	255
102	97	188-189	150	357-361	203	931-955	256
103	98	190-191	151	362-366	204	956-981	257
104-105	99	192-193	152	367-372	205	982-1008	258
106	100	194-195	153	373-377	206	1009-1036	259
107	101	196-197	154	378-382	207	1037-1066	260
108-109	102	198-200	155	383-388	208	1067-1098	261
110	103	201-202	156	389-393	209	1099-1131	262
111	104	203-204	157	394-399	210	1132-1166	263
112-113	105	205-207	158	400-405	211	1167-1204	264
114	106	208-209	159	406-411	212	1205-1243	265
115	107	210-212	160	412-417	213	1244-1285	266
116-117	108	213-214	161	418-424	214	1286-1330	267
118	109	215-217	162	425-430	215	1331-1378	268
119	110	218-219	163	431-437	216	1379-1429	269
120-121	111	220-222	164	438-443	217	1430-1483	270
122	112	223-224	165	444-450	218	1484-1542	271
123-124	113	225-227	166	451-457	219	1543-1605	272
125	114	228-230	167	458-465	220	1606-1673	273
126-127	115	231-232	168	466-472	221	1674-1747	274
128	116	233-235	169	473-480	222	1748-1827	275
129-130	117	236-238	170	481-488	223	1828-1914	276
131	118	239-241	171	489-496	224	1915-2010	277
132-133	119	242-243	172	497-504	225	2011-2115	278
134	120	244-246	173	505-513	226	2116-2232	279
135-136	121	247-249	174	514-521	227	2233-2361	280
137	122	250-252	175	522-530	228	over 2361	298
138-139	123	253-255	176	531-540	229		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Table III
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Plate, mounting (see dwg 8799099 covering a detail of dwg 8799093).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Diameter of connector mounting holes, maximum (max)	Gage
	102. Pitch diameter of receptacle plate mounting holes, max	Gage
	103. Minor diameter of receptacle plate mounting holes, max	Gage
	104. Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.2 Connector (see dwg 8795853 covering a detail of dwg 8799093).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Total length, minimum (min)	Gage
	102. Length to shoulder max	Gage
	103. Diameter of small end min	Gage

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:41Z
Check the source to verify that this is the current version before use.

104. Thickness through bottom of large cavity.....Gage
105. Objective evidence relative to material missing or improper (see 3.1).....Visual

Minor:
201. Evidence or poor workmanship (see 3.6).....Visual

4.3.2.1.3 Cover, safing arming well prior to plating (see dwg 8799100 covering a detail of dwg 8799093).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Diameter of connector hole,max	Gage
	102. Stamping mislocated, incorrect or unidentifiable	Visual
	103. Crack or fracture	Visual
	104. Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.4 Mounting plate and cover assembly, prior to securing cover (see dwg 8799093).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Plug contacts damaged	Visual
	102. Receptacle contacts damaged	Visual
	103. Any component or operation missing	Visual
	104. Leads damaged, or of incorrect color	Visual
	105. Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.6)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.3.2.1.5 Mounting plate and cover assembly (see 8799093).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Inside diameter of small connector cavity, min.	Gage
102.	Diameter of undercut below connector threads, min.	Gage
103.	Length of connector thread undercut, max.	Gage
104.	Location of mounting holes (functional).	Gage
105.	Minor diameter of connector thread, max.	Gage
106.	Length of mounting plate, max.	Gage
107.	Width of mounting plate, max.	Gage
108.	Pitch diameter of connector thread.	Gage
109.	Receptacle thread damaged.	Visual/Gage
110.	Bare spot in protective coating in excess of 1/4 square inch or the equivalent made up of smaller spots.	Visual
111.	Plug loose.	Manual
112.	Receptacle loose.	Manual
113.	Connector protrudes below mounting plate surface.	Visual
114.	Conector disc missing.	Visual
115.	Chamfer missing from bottom of large connector cavity.	Visual
116.	Mounting holes of plate and cover not aligned.	Visual
117.	Connector holes in cover not aligned with connectors.	Visual
118.	Any component missing.	Visual
119.	Objective evidence relative to material missing or improper (see 3.1).	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6).	Visual

4.3.2.1.6 Connector (see dwg 8810181).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Major:

101.	Pitch diameter of thread	Gage
102.	Major diameter of thread min	Gage
103.	Length to end of thread,min	Gage
104.	Length of thread pilot,max	Gage
105.	Inside diameter,min	Gage
106.	Total length	Gage
107.	Length to shoulder,min	Gage
108.	Length across wrench flats	Gage
109.	Protective finish missing	Visual
110.	Objective evidence relative to material missing or improper (see 3.1)	Visual

Minor:

201.	Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.7 Sleeve (see dwg 8797371).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:

101.	Length, min	Gage
102.	Inside diameter, min	Gage
103.	Diameter of flange, min	Gage
104.	Wall thickness	Gage
105.	Crack or fracture	Visual
106.	Objective evidence relating to material missing or improper (see 3.1)	Visual

Minor:

201.	Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.8 Nut (see dwg 8795914).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:

101.	Pitch diameter of thread	Gage
102.	Major diameter of thread,min	Gage
103.	Length to end of thread, min	Gage
104.	Length of thread pilot, max	Gage
105.	Total length	Gage
106.	Length across wrench flats	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

	107. Length to shoulder	Gage
	108. Inside diameter, min	Gage
	109. Protective finish missing	Visual
	110. Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.9 Cup relay (see dwg 8796069).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Inside diameter, min	Gage
	102. Outside diameter, max	Gage
	103. Thickness of bottom	Gage
	104. Total length, max	Gage
	105. Any operation missing	Visual
	106. Crack or fracture	Visual
	107. Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.10 Cup (see dwg 8795885).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Inside diameter, min	Gage
	102. Outside diameter of flange	Gage
	103. Length	Gage
	104. Outside diameter, max	Gage
	105. Thickness of bottom	Gage
	106. Cup cracked or cut	Visual
	107. Any operation missing	Visual
	108. Protective coating missing	Visual
	109. Objective evidence relative to material missing or improper (see 3.1)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Minor:
201. Evidence of poor workmanship (see 3.6).....Visual

4.3.2.1.11 Holder (see dwg 8795888).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Diameter of flange	Gage
102.	Outside diameter	Gage
103.	Pitch diameter of threads	Gage
104.	Minor diameter of threads,max	Gage
105.	Length from flange face to shoulder below threads	Gage
106.	Thickness of flange	Gage
107.	Inside diameter	Gage
108.	Total length	Gage
109.	Width of undercut,max	Gage
110.	Any operation missing	Visual
111.	Stamping mislocated, incorrect or unidentifiable	Visual
112.	Protective coating missing	Visual
113.	Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.12 Ring, retaining (see dwg 8795887).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Major diameter of thread	Gage
102.	Pitch diameter of thread	Gage
103.	Inside diameter	Gage
104.	Total length	Gage
105.	Width of wrench slots, min	Gage
106.	Location of wrench slots (functional)	Gage
107.	Concentricity of inside diameter with threads	Gage
108.	Depth of wrench slots, min	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

109.	Length of thread pilot,max.....	Gage
110.	Diameter of thread pilot,max.....	Gage
111.	Any operation missing.....	Visual
112.	Protective coating missing.....	Visual
113.	Objective evidence relative to material missing or improper (see 3.1).....	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6).....	Visual

4.3.2.1.13 Body (see dwg 8795879).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Pitch diameter of external thread.....	Gage
102.	Major diameter of external thread, min.....	Gage
103.	Pitch diameter of internal thread.....	Gage
104.	Minor diameter of internal thread, max.....	Gage
105.	Length of internal thread,min.....	Gage
106.	Depth of internal thread cavity.....	Gage
107.	Diameter of center cavity.....	Gage
108.	Depth of center cavity.....	Gage
109.	Thickness.....	Gage
110.	Diameter of hole below internal threads.....	Gage
111.	Length of external thread.....	Gage
112.	Depth and width of slot, min (functional).....	Gage
113.	Depth of slot, max.....	Gage
114.	Length to angled surface.....	Gage
115.	Diameter of internal thread counterbore.....	Gage
116.	Location of holes below internal threads.....	Gage
117.	Depth of internal thread counterbore, max.....	Gage
118.	Concentricity of hole below internal threads with center cavity including location with angled surface.....	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

119. Drill spot in bottom of center cavity.....Visual
120. Stamping mislocated, incorrect or unidentifiable.....Visual
121. Protective coating missing.....Visual
122. Objective evidence relative to material missing or improper (see 3.1).....Visual

Minor:
201. Evidence of poor workmanship (see 3.6).....Visual

4.3.2.1.14 Wrench assembly (see dwgs 8810179 and 8810180).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Outside diameter below flange	Gage
102.	Inside diameter	Gage
103.	Diameter of flange, min	Gage
104.	Location and width of lug, min (functional)	Gage
105.	Total length, min	Gage
106.	Thickness of flange	Gage
107.	Length of lugs, min	Gage
108.	Length across handles,max	Gage
109.	Handle above flush in wrench	Visual
110.	Handle visibly bent or tilted	Visual
111.	Weld inadequate (separation, looseness, porosity, etc)	Visual/Manual
112.	Stamping mislocated, incorrect or unidentifiable	Visual
113.	Protective coat missing	Visual
114.	Any operation missing	Visual
115.	Objective evidence relative to material missing or improper (see 3.1)	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.15 Spacer, sub-assembly, arming well (see dwg 8799122).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Major:

101.	Length	Gage
102.	Width	Gage
103.	Location and min diameter of holes 0.2040 (functional)	Gage
104.	Location and min diameter of holes 0.095 (functional)	Gage
105.	Location of pins (functional)	Gage
106.	Location and min diameter of holes 0.250 (functional)	Gage
107.	Location and min diameter of holes 0.1065 (functional)	Gage
108.	Width of center hole	Gage
109.	Length of center hole	Gage
110.	Width of top and bottom relief areas	Gage
111.	Length of bottom relief area	Gage
112.	Profile of top relief areas in corner	Gage
113.	Bare spot in protective coating in excess of 1/4 square inch, or the equivalent made up of smaller bare spots	Gage
114.	Objective evidence relative to material missing or improper (see 3.1)	Visual

Minor:

201.	Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.16 Preparation for delivery (see 5).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Preservation, packing and packaging not in accordance with MIL-STD-1169	Visual
102.	Marking not in accordance with MIL-STD-1169	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test Classification
a. Continuity and resistance	Major
b. Dielectric strength	Major
c. Insualtion resistance	Major
d. Rockwell hardness (wrench assembly)	Major

None of these tests are considered destructive and samples so tested may be returned to the lot.

4.3.3.1 Continuity and resistance, dielectric strength and insulation resistance. Each mounting plate and cover assembly in the lot shall be tested in accordance with 4.4.3, 4.4.4 and 4.4.5. If any item fails to comply with 3.4.1, 3.4.2 and 3.4.3, the item shall be rejected and removed from the lot.

4.3.3.2 Rockwell hardness. Sample wrench assemblies shall be selected at random from the lot in accordance with Table IV. The sample shall be tested in accordance with 4.4.2. For lots of 300 or less, if any item fails to comply with the drawing requirements, the lot shall be rejected.

Table IV

Lot Size	Sample Size
2-8	1
9-15	2
16-25	3
26-40	5
41-65	8
66-110	13
111-180	22
181-300	36
301 and over	MIL-STD-105 (AQL 0.25%)

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (see EL-8815675). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Rockwell hardness. The sample wrench assemblies shall be subjected to the Rockwell hardness test specified in QQ-M-151.

4.4.2 Continuity and resistance. Circuit continuity and resistance of the mounting plate and cover assembly shall be determined by applying a dc potential of 500 ± 25 vrms to the contacts and measuring the resistance with a zero calibrated ohmmeter, or other suitable means.

4.4.3 Dielectric strength. Each contact in the mounting plate and cover assembly shall be subjected to the required ac potential between electrically isolated contacts, and between each contact and the case for a minimum time duration of 15 seconds. The current shall be limited to 5 milliamperes maximum to protect human life.

4.4.4 Insulation resistance. Each contact in the mounting plate and cover assembly shall be subjected to a dc potential of 500 ± 25 vrms until a steady reading is obtained, using an insulation resistance tester from which a direct reading of resistance in megohms can be obtained.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The metal parts shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169.

5.1.2 Level C. The metal parts shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169.

5.2 Packing.

5.2.1 Levels A and C. The metal parts shall be packed in accordance with the applicable instructions contained in MIL-STD-1169.

5.3 Marking. Marking shall be in accordance with MIL-STD-1169.

5.4 Data cards. Data cards shall be prepared in accordance with MIL-STD-1167.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:41Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.

b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 and 5.4 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T.

6.4 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-1485 dated 15 July 1958.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. NUOR-A044

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:41Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

COMMANDER
Picatinny Arsenal
ATTN: SARPA-QA-N-Q
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.