MILITARY SPECIFICATION

STAND, NUCLEAR PROJECTILE
H4280

This specification is approved for use by the US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense

1. SCOPE

1.1 Scope. This specification covers requirements, quality assurance provisions and the preparation for delivery criteria for H4280 Assembly Stands for M753 8-Inch Nuclear Projectiles (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-I-6866	Inspection: Penetrant Method of
MIL-W-8611	Welding, Metal Arc and Gas Steels, and Corrosion and Heat Resistant Alloys; Process For
MIL-A-48078	Ammunition, Standard Quality Assurance Provisions, General Specification For

Beneficial comments (recommendations, additions, deletions), and any pertinent data which may be of use in improving this document, should be addressed to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAN-Q, Dover, New Jersey 07801, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426), appearing at the end of this document, or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein.

DRAWINGS (see 6.6)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9328283	Stand Assembly
9328287	Preparation of Steel and Rubber Surfaces
9328289	Lower Clamp Bonding Assembly
9328290	Shaft
9328291	Pedestal (Weldment)
9328292	Pedestal Assembly
9328293	Plate, Base
9328294	Plate, Index
9328298	Bushing
9328302	Plate, Bearing
9328304	Lower Clamp Assembly
9328310	Upper Clamp Assembly
9328312	Collar, Locking
9329695	Hinge Plate Bonding Assembly
9340513	Clamp Pad Bonding Assembly
9340515	Bracket
9340517	Bolt, Swing
9340518	Pin Swing Bolt
9340519	Pin, Hinge
9340553	Strap, Grounding
9340556	Swing Bolt Assembly
9340652	Ring, Grounding
9340654	Jack, Banana
9340655	Grounding Ring Assembly
9340714	Stand, Nuclear Projectile: H4280
9340769	Bumper
9342973	Packing & Marking for Stand, Nuclear Projectile: H4280
9344102	Plate, Identification

(Copies of specifications, standards, handbooks, drawings and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials and parts. The contractor shall provide objective evidence (see 6.4) that materials and components comply with specifications listed on the applicable drawing.

3.2 Assembly. The H4280 Stand shall comply with all applicable requirements specified on drawing (dwg.) 9340714, with all applicable subassembly dwgs., with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the dwgs. and herein.

3.3 Welding. Welding shall exhibit characteristics of fusion, penetration and soundness of weld deposit representative of good weld practice as defined in MIL-W-8611. A representative sample of the contractors welding capability shall be witnessed and approved by the Government prior to performing any welding operations. Inspection shall be performed in accordance with the applicable requirements of 4.5.1.

3.4 Fit and Function. The H4280 Stand shall support and permit the normal installation, holding, handling and removal of a blank steel cylinder simulating an M753 8-Inch Projectile Subassembly in accordance with the requirements and procedures of dwgs. 9328283 and 9340714. Testing shall be performed in accordance with 4.5.2.

3.5 First article inspection. This specification contains technical provisions for first article inspection (see 4.3.1). Requirements for submission of first article samples shall be as specified in the contract.

3.6 Workmanship. Requirements for workmanship shall be as indicated on applicable dwgs., in applicable specifications and as specified herein.

3.6.1 Cleaning and surface preparation. All parts, surfaces and assemblies shall be free of dirt, grease, rust, corrosion, welding flux, scale, unacceptable weld spatter (see 4.5.1e), metal filings or shavings or any other foreign matter prior to assembly or application of any primers or finish. Cleaning methods shall not be injurious to any of the parts or assemblies, nor shall the parts or assemblies be contaminated by the cleaning agents.

3.6.2 Finish. Paint and finishes shall comply with all applicable dwg. requirements. Prior to the application of any finish, parts and assemblies shall be dry and thoroughly clean and free of dirt, dust or any other foreign material as specified in 3.6.1. Unless otherwise specified on dwgs., primary coats shall be thoroughly dry before application of any finished coat. Finish coats shall cover all required surfaces and be continuous with the possible exception of a few light scratches not exposing base metal. Paint shall not appear on any part or area where explicitly excluded by dwg. requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

3.6.3 Plastic and metal characteristics. All parts and assemblies shall be free of warpage, porosity, inclusions, cracks, burrs or sharp edges as applicable. Threads shall be full and undamaged for the entire minimum length or depth as required by applicable dwgs.

3.6.4 Marking. Marking shall be as specified on dwgs. and shall be neat and sharply defined.

3.6.5 Assembly details. Assemblies shall be complete in accordance with dwg. requirements with particular attention to the following details, as applicable.

(a) All hardware i.e., lock washers, screws, etc., shall be present and of the correct type.

(b) All fastening devices i.e., nuts, bolts and screws shall be tight and secure.

(c) Cushioned items shall be properly prepared and securely bonded with no adhesive runover.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

1. First Article Inspection (see 4.3).

2. Quality Conformance Inspection (see 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Item Idenfication	Drawing No.	Quantity
Stand, Nuclear Projectile: H4280 (including blank steel cylinder per dwg. 9328283 to perform fit and function tests).	9340714	1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

SEQUENCE SHEET JOB NO.: 8267

NOTE: Publications requiring separate covers start with cover portion.
Publications requiring self cover start with "folio 1".

TRUE FOLIO	PRINTED FOLIO	TRUE FOLIO	PRINTED FOLIO
1	TP - H4280	2	2
3	3	4	4
5	7	6	6
7	thru	8	thru
9	9	10	10
11	39	12	40
13	DD 1426	14	BUSINESS REPLY
15		16	
17		18	
19		20	
21		22	
23		24	
25		26	
27		28	
29		30	
31		32	
33		34	
35		36	
37		38	
39		40	
41		42	
43		44	
45		46	
47		48	
49		50	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

4.3.2 Inspections to be performed. The first article quantity submitted in accordance with 4.3.1 shall be subjected to any or all of the requirements of the applicable dwgs. and to the inspections and tests specified in the First Article Table herein. All fabricated parts and assemblies shall have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All procured parts and materials shall be obtained from the same source as will be used in regular production. Inspections or tests required in the table on parts and subassemblies (Classification of Defects) before assembly shall be subject to verification by a representative of the Government designated by the Contracting Officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET		DRAWING NUMBER
4.3.2.1	Stand, Nuclear Projectile: H4280		1 OF 1		9340714
					NEXT HIGHER ASSEMBLY N.A.
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Stand, Nuclear Projectile: H4280	1	-	-	4.4.2.1 thru 4.4.2.26

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

4.3.3 Inspection equipment. The inspections and tests specified in 4.3.2 shall be accomplished with the gages and test equipment specified in 4.4.4.

4.3.4 Rejection. See MIL-A-48078.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with lot formation provisions of MIL-A-48078.

4.4.2 Examinations. See MIL-A-48078 and the Quality Conformance Inspection Tables herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
4.4.2.1	Component Verification		1 1		See Below
					NEXT HIGHER ASSEMBLY: N.A.
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Objective evidence will be required for the following items in accordance with applicable dwgs. and specifications (see note 1).		-	3.1	Visual (6.4.2)

Item	Dwg. or Spec.	Ref. on Dwg.
Grounding Strap	9340553	9340714
Jack, Banana	9340654	9340655
Bumper	9341769	9328283
Adhesive	MIL-A-81236 (Type I)	9328289 (see note 2)

NOTES:
1. Objective evidence shall also be required for all MS and MIL-SPEC hardware.
2. Adhesive must be within specified shelf-life.

Source: https://assist.dla.mil - Downloaded: 2016-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.2	Stand, Assembly				9328283
					NEXT HIGHER ASSEMBLY
					9340714
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Pedestal Assembly missing or not properly assembled to Base Plate		100%	3.2	Visual
102.	Cap Screw (MS16997-97), missing or incorrectly torqued (6 places)		100%	3.2	Visual/Gage
103.	Safety Stop loose or missing		100%	3.2	Visual/Manual
104.	Cap Screw (MS16997-58), missing or incorrectly torqued (2 places)		100%	3.2	Visual/Gage
105.	Cap Screw (MS16997-63), missing or incorrectly torqued (4 places)		100%	3.2	Visual/Gage
106.	Any component or subassembly incorrectly assembled		100%	3.2	Visual
107.	Setscrew, Hex Skt (MS51963-68), missing or incorrectly torqued (2 places)		100%	3.2	Visual/Gage
108.	Setscrew, Hex Skt (MS51963-242) missing, or incorrectly torqued		100%	3.2	Visual/Gage
109.	Locking Collar incorrectly adjusted (Note 5)		100%	3.2	Visual/Manual
110.	Spring Pin (MS16562-25) loose or missing		100%	3.2	Visual/Manual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9328283
4.4.2.2 (cont)	Stand, Assembly				NEXT HIGHER ASSEMBLY 9340714
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
111.	Bumper improperly installed, loose or missing		100%	3.2	Visual/Manual
112.	Retaining ring (MS16626-1156) missing		100%	3.2	Visual
113.	Identification plate missing or loose		100%	3.2	Visual/Manual
114.	Identification plate data incorrect, missing or illegible		100%	3.2	Visual
115.	Evidence of poor workmanship		100%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Lower Clamp Bonding Assembly	1 OF 1	9328289
			NEXT HIGHER ASSEMBLY 9328304

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Width of clamp (6.10 max.) incorrect		100%	3.2	Gage
102.	Radius (max.) incorrect		100%	3.2	Gage
103.	Objective evidence for preparation of steel and rubber bonding surfaces per dwg. 9328287 prior to bonding		100%	3.2	Visual (6.4.1)
104.	Grooves and threads not free of accumulated adhesive prior to application of rubber cushion		100%	3.2	Visual
105.	Cushion incorrectly or insecurely bonded		100%	3.2	Visual/Manual
106.	Bonding assembly incorrectly cured		100%	3.2	Record
107.	Adhesive not within shelf lifetime limit		100%	3.2	Visual
108.	Evidence of poor workmanship		100%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Shaft	1 OF 2	9328290
			NEXT HIGHER ASSEMBLY 9328304

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Pitch diameter of 1.750-12UN-2A thread incorrect		100%	3.2	Gage
102.	Major diameter of 1.750-12UN-2A thread incorrect		100%	3.2	Gage
103.	Location thru holes incorrect (6 holes)		100%	3.2	Gage
104.	Diameter thru holes incorrect (6 holes)		100%	3.2	Gage
105.	Diameter of counterbore incorrect (6 places)		100%	3.2	Gage
106.	Depth of counterbore incorrect (6 places)		100%	3.2	Gage
107.	Location of counterbore incorrect (6 places)		100%	3.2	Gage
108.	Location of keyway incorrect		100%	3.2	Gage
109.	Depth of keyway incorrect		100%	3.2	Gage
110.	Width of keyway incorrect		100%	3.2	Gage
111.	Length of stub shaft incorrect		100%	3.2	Gage
112.	Dia stub shaft incorrect		100%	3.2	Gage
113.	Width of flange incorrect		100%	3.2	Gage
114.	Perpendicularity of flange with respect to Datum A incorrect		100%	3.2	Gage
115.	Distance from flange to end of keyway incorrect		100%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9328290
4.4.2.4 (cont)	Shaft				NEXT HIGHER ASSEMBLY 9328304
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
116.	Location of groove incorrect		100%	3.2	Gage
117.	Inside diameter groove (1.473-.010) incorrect		100%	3.2	Gage
118.	Hardness incorrect		100%	3.2	Gage
119.	Protective finish incorrect or missing		100%	3.2	Visual
120.	Evidence of poor workmanship		100%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Pedestal (Weldment)	1 OF 2	9328291
			NEXT HIGHER ASSEMBLY 9328292

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Diameter bolt hole circle incorrect		100%	3.2	Gage
102.	Location of equally spaced holes incorrect (6 places)		100%	3.2	Gage
103.	Diameter of equi-spaced holes incorrect (6 places)		100%	3.2	Gage
104.	Perpendicularity of square steel tubing with respect to circular base incorrect		100%	3.2	Gage
105.	Gusset location incorrect (3 places)		100%	3.2	Gage
106.	Location of 4 hole group incorrect (Datum A)		100%	3.2	Gage
107.	Thread of 4 hole group incorrect (Datum A)		100%	3.2	Gage
108.	Location of bushing incorrect		100%	3.2	Gage
109.	Inside diameter of bushing incorrect		100%	3.2	Gage
110.	Location of threaded holes (.190-24UNC-2B) incorrect (Datum A) (2 places)		100%	3.2	Gage
111.	Pitch dia. of threaded holes (.190-24UNC-2B) incorrect (Datum A) (2 places)		100%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5 (cont)	Pedestal (Weldment)	2 OF 2	9328291
			NEXT HIGHER ASSEMBLY 9328292

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major (cont)					
112.	Location of threaded holes (.190-24UNC-2B) incorrect (Datum D) (2 places)		100%	3.2	Gage
113.	Pitch dia. of threaded holes (.190-24UNC-2B) incorrect (Datum D) (2 places)		100%	3.2	Gage
114.	Location of threaded holes (.250-20 UNC-2B) incorrect (Datum D) (2 places)		100%	3.2	Gage
115.	Pitch dia. of threaded holes (.250-20 UNC-2B) incorrect (Datum D) (2 places)		100%	3.2	Gage
116.	Any weld missing, improper or defective		100%	3.3	4.5.1
117.	Location of tube cap hole incorrect		100%	3.2	Visual
118.	Pitch dia. of thread (.312-18UNC-2B) in tube cap hole incorrect		100%	3.2	Gage
119.	Material		-	3.1	Visual (6.4.3)
120.	Evidence poor workmanship		100%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2020-10-29T00:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Pedestal Assembly				9328292
					NEXT HIGHER ASSEMBLY 9328283
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Bushing (9328298) incorrectly installed		100%	3.2	Visual
102.	Bearing Plate incorrectly installed (2 places)		100%	3.2	Visual
103.	Machine Screw (MS35190-271) incorrectly torqued (4 places)		100%	3.2	Visual/Gage
104.	Evidence of poor workmanship		100%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.7	Plate, Base		9328293
			NEXT HIGHER ASSEMBLY 9328283

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Location of corner holes incorrect (4 places)		100%	3.2	Gage
102.	Inside diameter of corner holes incorrect (4 places)		100%	3.2	Gage
103.	Location of bolt circle incorrect		100%	3.2	Gage
104.	Location of threaded holes on bolt circle incorrect (6 places)		100%	3.2	Gage
105.	Pitch diameter of .375-16 UNC-2B thread incorrect (6 places)		100%	3.2	Gage
106.	Protective finish incorrect or missing		100%	3.2	Visual
107.	Evidence of poor workmanship		100%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Plate, Index	1 OF 1	9328294
			NEXT HIGHER ASSEMBLY 9328283

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	2.002 + .002 inside diameter incorrect		100%	3.2	Gage
102.	Location of keyway incorrect		100%	3.2	Gage
103.	Keyway size incorrect		100%	3.2	Gage
104.	Location of slots incorrect (8 places)		100%	3.2	Gage
105.	Outside diameter plate incorrect		100%	3.2	Gage
106.	Hardness incorrect		100%	3.2	Gage
107.	Protective finish incorrect or missing		100%	3.2	Visual
108.	Evidence of poor workmanship		100%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Bushing				9328298
					NEXT HIGHER ASSEMBLY 9328292
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Outside diameter incorrect		100%	3.2	Gage
102.	Inside diameter incorrect		100%	3.2	Gage
103.	Material		-	3.1	Visual (6.4.3)
104.	Surface finish incorrect		100%	3.2	Gage
105.	Evidence of poor workmanship		100%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Plate, Bearing		9238302
			NEXT HIGHER ASSEMBLY 9328292

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Diameter of thru holes incorrect (2 holes)		100%	3.2	Gage
102.	Location of thru holes incorrect (2 holes)		100%	3.2	Gage
103.	Inside diameter incorrect		100%	3.2	Gage
104.	Plate thickness incorrect		100%	3.2	Gage
105.	Material		-	3.1	Visual (6.4.3)
106.	Evidence of poor workmanship		100%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.11	Lower Clamp Assembly				9328304
					NEXT HIGHER ASSEMBLY 9328283
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Hinge Plate Bonding Assembly, Lower Clamp Bonding Assembly, Shaft or Swing Bolt Assembly missing or incorrectly assembled		100%	3.2	Visual/Manual
102.	Cap Screw (MS16997-60) missing or incorrectly torqued (4 places)		100%	3.2	Visual/Gage
103.	Cap Screw (MS16997-99) (Hole A) missing or incorrectly torqued (seven places)		100%	3.2	Visual/Gage
104.	Cap Screw (MS16997-101) (Hole B) missing or incorrectly torqued (3 places)		100%	3.2	Visual/Gage
105.	Height (max.) incorrect		100%	3.2	Gage
106.	Width (6.10 max.) incorrect		100%	3.2	Gage
107.	Mating surfaces do not make contact after assembly of cap screws (note 4)		100%	3.2	Visual
108.	Evidence of poor workmanship		100%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9328310
4.4.2.12	Upper Clamp Assembly				NEXT HIGHER ASSEMBLY 9328283
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Handle loose, damaged or missing		100%	3.2	Visual/Manual
102.	Clamp Pad Bonding Assembly missing or incorrectly torqued to Upper Clamp		100%	3.2	Visual/Gage
103.	Strike Plate missing, loose or incorrectly torqued to Upper Clamp		100%	3.2	Visual/Gage
104.	Strike missing, loose or incorrectly torqued		100%	3.2	Visual/Gage
105.	Overall length (10.87 Max.) incorrect		100%	3.2	Gage
106.	Width (5.70 Max.) incorrect		100%	3.2	Gage
107.	Cap screw (MS16997-61) missing or incorrectly torqued		100%	3.2	Visual/Gage
108.	Evidence of poor workmanship		100%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.13	Collar, Locking		9328312
			NEXT HIGHER ASSEMBLY 9328283

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Pitch diameter of 1.750-12UN-2B thread incorrect		100%	3.2	Gage
102.	Minor diameter of 1.750-12UN-2B thread incorrect		100%	3.2	Gage
103.	Pitch diameter of .250-20UNC-2B thread incorrect (2 holes)		100%	3.2	Gage
104.	Minor diameter of .250-20UNC-2B thread incorrect (2 holes)		100%	3.2	Gage
105.	Location of .250-20UNC-2B threaded holes incorrect (2 places)		100%	3.2	Gage
106.	Location of .406 dia holes incorrect (4 places)		100%	3.2	Gage
107.	Inside diameter of .406 $\frac{+.007}{-.002}$ holes incorrect (4 places)		100%	3.2	Gage
108.	Depth of .406 diameter hole incorrect (4 places)		100%	3.2	Gage
109.	Material		-	3.1	Visual (6.4.3)
110.	Protective finish incorrect or missing		100%	3.2	Visual
111.	Evidence of poor workmanship		100%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.14	Hinge Plate Bonding Assembly				9329695
					NEXT HIGHER ASSEMBLY 9328304
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Rubber cushion material damaged		100%	3.2	Visual
102.	Objective evidence for preparation of steel and rubber bonding surface per dwg. 9328287 prior to bonding		100%	3.2	Visual (6.4.1)
103.	Rubber cushion incorrectly or insecurely bonded		100%	3.2	Visual/Manual
104.	Overall height (7.70 Max.) incorrect		100%	3.2	Gage
105.	Overall width (6.10 Max.) incorrect		100%	3.2	Gage
106.	Bonding assembly incorrectly cured		100%	3.2	Record
107.	Adhesive not within shelf lifetime limit		100%	3.2	Visual
108.	Evidence of poor workmanship		100%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.15	Clamp Pad Bonding Assembly	1 OF 1	9340513
			NEXT HIGHER ASSEMBLY 9328310

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Rubber cushion material damaged		100%	3.2	Visual
102.	Objective evidence for preparation of steel and rubber bonding surface per dwg. 9328287 prior to bonding		100%	3.2	Visual (6.4.1)
103.	Grooves and threads not free of accumulated adhesive prior to application of rubber cushion		100%	3.2	Visual
104.	Rubber cushion incorrectly or insecurely bonded in place using adhesive		100%	3.2	Visual/Manual
105.	Bonding assembly incorrectly cured		100%	3.2	Record
106.	Evidence of poor workmanship		100%	3.6	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2018-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.16	Bracket	1 OF 1	9340515
			NEXT HIGHER ASSEMBLY: 9340556

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Location of holes incorrect (4 holes)		100%	3.2	Gage
102.	Diameter of holes incorrect (4 holes)		100%	3.2	Gage
103.	Location of 2 holes (in line) incorrect		100%	3.2	Gage
	Diameter of 2 holes (in line) incorrect		100%	3.2	Gage
104.	Hardness incorrect		100%	3.2	Gage
105.	Protective finish incorrect or missing		100%	3.2	Visual
106.	Evidence of poor workmanship		100%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.17	Bolt, Swing	1 OF 1	9340517
			NEXT HIGHER ASSEMBLY 9340556

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Pitch diameter of .437-20UNF-2A thread incorrect		100%	3.2	Gage
102.	Pitch diameter of .112-40UNC-2B thread incorrect		100%	3.2	Gage
103.	Overall length incorrect		100%	3.2	Gage
104.	Location of thru hole incorrect		100%	3.2	Gage
105.	Diameter of thru hole incorrect		100%	3.2	Gage
106.	Protective finish incorrect or missing		100%	3.2	Visual
107.	Evidence of poor workmanship		100%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.18	Pin Swing Bolt				9340518
					NEXT HIGHER ASSEMBLY 9340556
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Outside diameter of pin incorrect		100%	3.2	Gage
102.	Location of groove incorrect		100%	3.2	Gage
103.	Small diameter of groove incorrect		100%	3.2	Gage
104.	Protective finish incorrect or missing		100%	3.2	Visual
105.	Evidence of poor workmanship		100%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION MIL-S-63950(AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.18	Pin Swing Bolt		9340518
			NEXT HIGHER ASSEMBLY 9340556

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Outside diameter of pin incorrect		100%	3.2	Gage
102.	Location of groove incorrect		100%	3.2	Gage
103.	Small diameter of groove incorrect		100%	3.2	Gage
104.	Protective finish incorrect or missing		100%	3.2	Visual
105.	Evidence of poor workmanship		100%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.19	Pin, Hinge		9340519
			NEXT HIGHER ASSEMBLY 9328283

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Large diameter incorrect		100%	3.2	Gage
102.	Groove diameter incorrect		100%	3.2	Gage
103.	Width of groove incorrect		100%	3.2	Gage
104.	Location of groove incorrect		100%	3.2	Gage
105.	Overall length of pin incorrect		100%	3.2	Gage
106.	Hardness incorrect		100%	3.2	Gage
107.	Protective finish incorrect or missing		100%	3.2	Visual
108.	Material		-	3.1	Visual (6.5.3)
109.	Evidence of poor workmanship		100%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9340556
4.4.2.20	Swing Bolt Assembly				NEXT HIGHER ASSEMBLY 9329304
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Swing Bolt, Swing Bolt Pin or Bracket incorrectly assembled		100%	3.2	Visual/Manual
102.	Any part missing or damaged		100%	3.2	Visual
103.	Setscrew, Hex. Skt (MS51963-211) incorrectly torqued		100%	3.2	Visual/Gage
104.	Evidence of poor workmanship		100%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.21	Ring, Grounding	1 OF 1	9340652
			NEXT HIGHER ASSEMBLY: 9340655

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Inside diameter incorrect		100%	3.2	Gage
102.	Taper on inside dia incorrect		100%	3.2	Gage
103.	Location of holes (marked A) incorrect (3 places)		100%	3.2	Gage
104.	Pitch Dia. of .250-20UNC-2B threaded holes (marked A) incorrect (3 holes)		100%	3.2	Gage
105.	Location of holes (marked B) incorrect (4 holes)		100%	3.2	Gage
106.	Pitch diameter of .250-32-UNEF-2B threaded holes (marked B) incorrect (4 holes)		100%	3.2	Gage
107.	Stenciled characters missing		100%	3.2	Visual
108.	Inside diameter of .500 thru hole incorrect		100%	3.2	Gage
109.	Location of holes (marked C) incorrect (2 holes)		100%	3.2	Gage
110.	Pitch diameter of .250-20UNC-2B-2 threaded holes (marked C) incorrect		100%	3.2	Gage
111.	Surface finish incorrect		100%	3.2	Gage
112.	Protective finish incorrect or missing		100%	3.2	Visual
113.	Evidence of poor workmanship		100%	3.6	Visual

NOTES:

Source: https://assist.dla.mil Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.22	Grounding Ring Assembly		9340655
			NEXT HIGHER ASSEMBLY 9340714

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Knurled head screw does not turn freely thru entire threaded length (5 places)		100%	3.2	Visual/Manual
102.	Banana Jacks incorrectly installed (4 places)		100%	3.2	Visual/Manual
103.	Stencil "THIS SIDE UP" not readable		100%	3.2	Visual
104.	Evidence of poor workmanship		100%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.23	Stand, Nuclear Projectile: H4280 (Fit and Function)	1 OF 1	9340714, 9328283
			NEXT HIGHER ASSEMBLY: N.A.

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Outside diameter of steel cylinder (see note 1)		100%	3.2	Gage
102.	Length of steel cylinder (see note 1)		100%	3.2	Gage
103.	Finish of steel cylinder (see note 1)		100%	3.2	Gage
104.	The blank steel cylinder does not correctly fit into the Clamp Assembly		100%	3.4	4.5.2.1
105.	The angle of twist of the clamp assembly (with torque applied from 0 to 200 ±50 foot pounds) exceeds 5 degrees maximum		100%	3.4	4.5.2.2
106.	The Clamp Assembly does not rotate freely or the Latch does not engage and manually release in each of the eight Plate Index detents		100%	3.4	4.5.2.3

NOTES: 1. These dimensions apply to one blank steel cylinder per contract to be fabricated by the contractor as inspection equipment in accordance with note 10 of dwg. 9328283 for performance of the fit and function test.
2. These fit and function tests are considered non-destructive.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.24	Stand, Nuclear Projectile: H4280 (Assembly)				9340714
					NEXT HIGHER ASSEMBLY N.A.
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Assembly incomplete. Any part or subassembly missing or incorrectly prepared for shipment		100%	3.2	Visual
102.	Grounding Ring Assembly or Grounding Straps (4) missing, damaged or incorrectly assembled (see note)		100%	3.2	Visual
103.	Evidence of poor workmanship		100%	3.6	Visual

NOTES: This subassembly, consisting of items shown on dwgs. 9340655 and 9340533, shall be assembled as a unit and separately packaged in accordance with requirements of dwg. 9242973.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.25	Plate, Identification		9344102
			NEXT HIGHER ASSEMBLY 9328283

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Location of holes incorrect (4 holes)		100%	3.2	Gage
102.	Marking incorrect or missing		100%	3.2	Visual
103.	Material		-	3.1	Visual (6.4.3)
104.	Evidence of poor workmanship		100%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.26	Packaging				See 5.0
					NEXT HIGHER ASSEMBLY N.A.
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Major					
101.	Packing and packing materials not in accordance with applicable requirements		1 Complete Assembly	5.0	Visual
102.	Box assembly not dry, clean and free of dirt and other foreign material prior to packing		100%	5.0	Visual
103.	Fiberboard box missing		100%	5.0	Visual
104.	Fiberboard box not marked		100%	5.0	Visual
105.	Grounding Ring Assembly with Grounding Strap and specified hardware not separately packaged in accordance with requirements		100%	5.0	Visual
106.	Bagged items not properly sealed & marked before placing in fiberboard box		100%	5.0	Visual
107.	Stand assembly not properly positioned within cleated plywood box		100%	5.0	Visual/Manual
108.	Swing bolt not properly torqued (20 foot pounds)		100%	5.0	Gage
109.	Cover not properly placed on cleated plywood box or does not fit		100%	5.0	Visual/Manual
110.	Straps missing or not properly applied		100%	5.0	Visual
111.	Marking incorrect or missing		100%	5.0	Visual
112.	Evidence of poor workmanship		100%	5.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the tables starting with 4.4.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract (see MIL-A-48078 and 6.3).

4.5 Test Methods and Procedures.

4.5.1 Welding (see 3.3). Weld quality shall be inspected for the requirements of MIL-W-8611 & MIL-I-6866 with particular attention to the following details.

(a) All welds on the Pedestal Weldment (dwg. 9328291) shall be inspected using the liquid penetrant method to detect defects. The inspection shall be performed in accordance with the requirements of MIL-I-6866. Any Pedestal Weldment showing defective welds using this test method shall be rejected.

(b) Surfaces to be welded shall be free of dirt, grease, oil, paint or other foreign material prior to welding.

(c) When multiple welds are deposited, each layer shall be thoroughly clean and free of slag and gas pits before deposit of another layer.

(d) Tack welds, when used, shall be deposited in such a manner as to assure their incorporation into the final weld without causing discontinuity in the deposit.

(e) Final welds shall be of the fillet size specified on the dwg. and shall be free of discontinuities, overlaps, gas holes, slag, flux, or any other obvious defects representative of poor weld practice. There shall be no weld spatter on functional or machined mating surfaces. Weld spatter, when present on other surfaces, shall be removed by chipping, grinding or other commercial practice and the underlying surface refinished to the satisfaction of the Government QAR.

Removal of weld spatter shall not puncture, tear, distort or otherwise damage the underlying metal surface.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

(f) Dimensional characteristics on dwgs. shall apply after welding. The contractor shall provide all necessary shrinkage controls to assure the finished item complies with dwg. dimensional requirements.

4.5.2 Fit and Function (see 3.4).

4.5.2.1 Fit. A blank steel cylinder fabricated by the contractor in accordance with dwg. 9328283 and approved by the acquiring agency (see 4.4.4) shall fit snugly into the clamp assembly when assembled in accordance with the instructions therein. If the approved steel cylinder cannot be properly assembled in the clamp assembly in accordance with the applicable procedures, the stand shall be rejected.

4.5.2.2 Torque. The clamp assembly holding torque shall be verified by applying 200±50 foot pounds to the blank steel cylinder in accordance with the procedures outlined in dwg. 9328283 (note 7H). The angle of twist of the clamp assembly with this torque applied (no load to 200±50 foot pounds) shall not exceed five degrees maximum. Any angle of twist for the clamp assembly exceeding five degrees maximum shall be cause for rejection of the stand. In addition, following application of the specified torque, any physical failure (break, crack, etc.) of any part shall be cause for rejection of the stand.

4.5.2.3 Function.

(a) With the blank steel cylinder in the clamp assembly and the steel cylinder in a horizontal position, rotate (clockwise) the entire clamp assembly through one turn (360 degrees) stopping and setting the latch at each detent.

(b) Repeat this procedure for one turn (360 degrees) rotation counterclockwise.

(c) The assembly shall latch correctly in each detent position and rotate in both directions without undue effort. Any binding or sticking or failure to detent properly shall be cause for rejection.

5. PACKAGING

5.1 Packaging. Packaging shall be in accordance with dwg. 9342973.

5.2 Marking. Marking shall be in accordance with dwg. 9342973.

5.3 Loose Items. Loose items shall be packaged and marked in accordance with dwg. 9342973.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The item covered by this specification forms part of the ground handling equipment for the M753, 8-Inch Rocket-assisted Projectile.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification.

b. First article inspection, when required (see 3.5).

6.2.2 Data requirements. When this specification is used in an acquisition which incorporates a DD1423, Contract Data Requirements List (CDRL) the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL incorporated into the contract. When the provisions of DAR 7-104.9 (n) (2) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification is cited in the following paragraphs:

Paragraph no.	Data requirements	Applicable DID no.
4.4.4	Inspection equipment approval	DI-R-1714 (Tailored)

6.3 Equipment design approval. Submit equipment designs, as required, to Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAN-I, Dover, New Jersey 07801.

6.4 Objective evidence.

6.4.1 General. Records of contractor quality controls and inspections which can be verified.

6.4.2 MIL-SPEC and Commercial items. A certificate of conformance from the supplier certifying that the item complies with applicable dwg. or specification requirements.

6.4.3 Materials. A statement (certification) supported by test data that all materials produced or purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in contractual documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.

6.5 Supersession data. This specification includes the requirements of AR-PD-33 dated 15 December, 1980.

6.6 Drawings and specifications. Drawings and specifications listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings and specifications prepared and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings and specifications. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
Army-AR

Preparing activity:
Army-AR
(Project NUOR-A112)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:06Z
Check the source to verify that this is the current version before use.