NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.



(b) SIZE	O.D.	R ± .010 MOUNTING FLAT	S ACROSS FLATS	T NEF-2A MOUNTING THREAD
16	1 1/16	.375	1	7/8 - 20
19	1 1/4	.478	1 3/16	1 1/16 - 18
21	1 7/16	.578	1 3/8	1 1/4 - 18

(B)

(a) MATING DIMENSIONS, MALE THREAD, IN ACCORDANCE WITH MS24243M, PIN CONTACTS ONLY, "M" IN PART NUMBER.

(b) SHELL SIZE AS SPECIFIED IN CONNECTOR PART NUMBER

(c) INSERT ARRANGEMENT IN ACCORDANCE WITH MS24242. INSERT ARRANGEMENT NUMBER CORRESPONDING TO SHELL SIZE AND AS SPECIFIED IN CONNECTOR PART NUMBER. ALTERNATE INSERT POSITION, IF APPLICABLE, AS SPECIFIED IN CONNECTOR PART NUMBER. EXAMPLE OF CONNECTOR PART NUMBERS SEE MIL-C-25955

(B)

(d) SHOULDER DIAMETER EQUAL TO MAJOR DIAMETER OF MOUNTING THREAD "T"

DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED. TOLERANCES, DECIMALS ± .002, FRACTIONS ± 1/64, ANGLES ± 1/2°

APPROVED 9 JAN 58 REVISED (A) 27 MAY 58 (B) 18 OCT 60

CUSTODIANS	OTHER INT
Air Force	A N - AF

MILITARY STANDARD

CONNECTOR - RECEPTACLE, ELECTRICAL, HERMETIC, JAM NUT, FRONT MOUNTING

MS24241 (USAF)

SUPERSEDES

SHEET 1 OF 1

MIL-C-25955

DD FORM 572-1 OCT 52

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:50Z
Check the source to verify that this is the current version before use.