MIL–M–46323A(ORD)
17 OCTOBER 1962
SUPERSEDING
MIL–M–46323(ORD)
31 OCTOBER 1961

MILITARY SPECIFICATION

MOUNTS, TELESCOPE: M99 SERIES

1. SCOPE

1.1 This specification covers telescope mounts of the M99 series used to support Panoramic Telescopes of the M100 series (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL–P–12980—Packaging of Mounts, Telescopes T179, T179E2 (M99 Series)

MIL–F–13926—Fire Control Materiel: General Specification Governing the Manufacture and Inspection of

MIL–I–45208—Inspection Requirements, General Specification for

MIL–I–45607—Inspection Equipment, Supply and Maintenance or Ordnance

STANDARDS

MILITARY

MIL–STD–105—Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

ORDNANCE CORPS

F8237268—Fixture, Final Inspection

F8295051—Mount, Telescope: M99A1

F8295057—Mount, Telescope: M99A1C

LSQAP–8295051—Supplementary Quality Assurance Provisions for Mount Telescope M99A1

LSQAP–8295057—Supplementary Quality Assurance Provisions for Mount Telescope M99A1C

IEL–8295051—Inspection Equipment List for Mount Telescope M99A1

IEL–8295057—Inspection Equipment List for Mount Telescope M99A1C

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 **Initial production sample.** Unless otherwise directed by the contracting officer, an initial production sample shall be required. The sample shall be manufactured in the same manner, using the same materials, equipment,

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:33Z
Check the source to verify that this is the current version before use.

processes and procedures as will be used in regular production.

3.2 Materials. Materials shall be in accordance with drawings, material specifications, and general specifications forming a part of this specification.

3.3 Construction. The mount shall be manufactured in accordance with the drawings, applicable to the type mount specified in the contract or order and drawings pertaining thereto. The requirements of this specification are detailed only to the extent considered necessary to obtain the desired mechanical characteristics, performance and permanence to insure inherent quality and performance capabilities.

3.4 General specifications. The contractor shall be responsible for adherence to, and compliance with, the following requirements of Specification MIL–F–13926:

(a) Order of precedence
(b) Protective finished surfaces
(c) Special accuracy
(d) Finish, painting and protective
(e) Electrical
(f) Workmanship

3.5 Adjusting mount on Fixture 8237268 (see 6.5). The following adjustments shall be made on the fixture:

(a) A calibrated Panoramic Telescope of the M100 Series shall be installed in the mount. The azimuth unit shall be adjusted to a position where rotation of the unit shall result in the least movement of the line of sight of the telescope from a target point.

(b) The mount shall be adjusted in elevation, within the limits of the mounting bolts, in a plane parallel to the main mounting pads so that the bubbles of the four level vials are centered within the width of a graduation line.

(c) With the simulated gun of the inspection fixture set at zero elevation, the elevation counter shall read zero, the elevation indexes shall be in coincidence, and the angle of cant shall be zero.

3.6 Accuracy. With a mount adjusted in compliance with 3.5 the following requirements shall be met:

(a) The axis of the locating key for position of the telescope in the mount shall be parallel to the mounting surface within plus or minus 2.5 mils.

(b) Each of the four level vials shall show the bubble central with respect to the vial graduations within plus or minus the width of a graduation line, at any point of rotation of the azimuth unit.

(c) The line of sight of the telescope shall not deviate from a target point by more than plus or minus 0.5 mil when the simulated gun is activated from 0 to 1157 mils.

(d) When the index marks of the elevation scale and the vernier scale are in coincidence with the fixed index, the elevation of the simulated gun shall correspond to the reading indicated by the elevation counter within plus or minus 1.0 mil at any elevation setting between zero and 1157 mils.

(e) Backlash between the simulated gun trunnion and the elevation vernier scale shall not exceed 0.8 mil between 0 to 1157 mil elevation.

(f) Backlash at the pitch line between the Pinion Gear B8294984 and the Sector Gear D8294981 of the azimuth rotation unit shall not exceed 0.002 inch at any position.

3.7 Rigidity. With the simulated gun trunnion of the test fixture immobilized, the position of the line of sight of a M100 Series Panoramic Telescope shall not move in excess of the values of table I. A fifty pound tangential load shall be applied to the left of the eyeshield ring, the load released and a reading taken. The load shall then be applied to the right; then released and a reading taken.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:33Z
Check the source to verify that this is the current version before use.

The movement of the line of sight shall not have changed in each direction from its initial position by more than the values indicated in table I.

TABLE I. *Telescope movement*
(All readings in mils)

Movement	Elevation	Cant
0.25	0	0
2.0	1100	0
2.0	1100	124.4

3.8 Elevation.

3.8.1 *Mount Telescope M99A1.* The elevation limit stops shall be set to permit elevation of 65 degrees minus zero, plus 30 minutes (1157 mils minus zero, plus 9 mils) and depression of 10 degrees minus zero, plus 30 minutes (178 mils minus zero plus 9 mils) when the mount is set at zero Elevation and zero Cant.

3.8.2 *Mount Telescope M99A1C.* The elevation limit stops shall be set to permit elevation of 65 degrees, minus zero, plus 30 minutes (1157 mils minus zero, plus 9 mils) and depression of 7 degrees, minus zero, plus 30 minutes (125 mils minus zero, plus 9 mils) when the mount is set at zero Elevation and zero Cant.

3.8.3 *Interference.* At combinations of 15 degrees Cant and Elevation angles and 15 degrees Cant and depression angles, the cross levelling mechanism shall be adjusted to plumb the panoramic telescope. On 360 degrees rotation of the levelling mechanism, no interference between components or assemblies of the mount shall exist at these extreme positions or any other position to where it is possible to orient the mount with telescope installed. The over travel device in the elevation linkage system will operate to permit 360 degrees rotation and does not constitute an interference.

3.9 Azimuth correction. The mount shall give azimuth correction readings in accordance with table II.

TABLE II. *Azimuth corrections*
(All readings in mils)

Counter elevation	Cant	Azimuth corrections	Tolerance panoramic	Azimuth backlash*
300.0	124.4	37.9	0.4	0.2
700.0	124.4	102.8	0.7	0.3
1130.0	124.4	254.0	1.8	1.0

* Azimuth Backlash is defined as the difference between the actual measured azimuth correction angles read on elevation, and those read on depression.

3.10 Illumination.

3.10.1 *Fixed intensity lights.* With the circuit energized from a 24 volt source the index marking of the elevation index, the readings of elevation counter and the four level vials of the azimuth unit shall be adequately illuminated when observed in a darkened area.

3.10.2 *Variable intensity lights.* The actuation of the rheostat shall vary the voltage on contacts "D" and "G" of the receptacle assembly. The wire harness shall be checked to insure reticle light leads are in series with rheostats.

3.11 Insulation resistance. Insulation resistance shall be in accordance with requirements of Specification MIL–F–13926.

3.12 Vibration. With Travel Insert F8202252 installed in the mount, the mount shall be vibrated at a constant frequency of 30 cycles per second at an amplitude of $\frac{1}{16}$ inch ($\frac{1}{8}$ inch total excursion) for a period of 5 minutes plus or minus 15 seconds.

3.13 Post vibration. Subsequent to vibration the mount shall again be set up on the Ordnance inspection fixture to the requirements of 3.5. The mount shall not be damaged, there shall be no broken, missing or loose parts, and the mount shall be rechecked to the requirements of 3.6(b) to (e) inclusive, and 3.7.

3.14 Operability. The running torque required to rotate the operational adjustment shall not exceed the values specified in table III at the temperature indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:33Z
Check the source to verify that this is the current version before use.

TABLE III

Temperatures	+60°F to 90°F.	+150°F.	—40°F.
Cross Level Knob* 0° to 10° Cant	10 lb. in.	10 lb. in.	25 lb. in.
Cross Level Knob 10° to 15° Cant	15 lb. in.	15 lb. in.	25 lb. in.
Azimuth Rotation Knob	10 lb. in.	10 lb. in.	20 lb. in.
Counter Reset Knob	3.5 lb. in.	3.5 lb. in.	8 lb. in.
Counter Lock	Mechanically Operable & Lock.	Mechanically Operable & Lock.	Mechanically Operable & Lock.

* Cross level torque values are with boot installed.

3.15 Temperature requirements. The mount with Travel Insert F8202252 installed shall be exposed to an ambient temperature of minus 40° and plus 150° Fahrenheit for a period of at least 8 hours at each temperature. The mount shall meet the applicable requirements of 3.14 when exposed to these temperatures.

3.16 Post temperature check. Subsequent to being subjected to the temperature requirements of 3.14 the mount shall again be set up on the Ordnance inspection fixture to the requirements of 3.5. The mount shall not be damaged and shall meet the requirements of 3.6 (b) to (e) inclusive, and 3.7.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibilities. The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 General requirements. Inspection requirements and procedures shall be in accordance with Specification MIL–I–45208.

4.3 Initial production sample. Prior to production, the contractor shall submit the initial production sample in accordance with 3.1 for inspection by the contractor under the surveillance of the Government. This inspection shall be conducted at the contractor's facility, or Government approved laboratory, using test equipment authorized for use on the contract. The sample shall be inspected for all requirements of this specification by utilizing examination and testing methods prescribed herein.

4.3.1 *Initial production sample failure.* Should the production sample fail to pass the prescribed tests, the contractor shall cease those operations which are causing the rejection and shall make the necessary corrections. When corrections in the process have been made, a new production sample shall be examined and tested by the contractor under the surveillance of the Government. Acceptance of production lots will not commence until an acceptable production sample is submitted and corrective actions have been taken to eliminate deficiencies.

4.4 Lot formation. Inspection lot sizes and lot formation shall be in accordance with Standard MIL–STD–105.

4.4.1 *Defective units and lots.* Defective units and lots shall be processed as specified in Standard MIL–STD–105.

4.5 Material. Control of material shall be in accordance with test data requirements of Specification MIL–I–45208.

4.6 Inspection of components. Inspection requirements for component parts and subassemblies are contained herein and on Supplementary Quality Assurance Provisions (SQAP) listed in Supplementary Quality As-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:33Z
Check the source to verify that this is the current version before use.

surance Provisions List (LSQAP) 8295051 and 8295057.

4.6.1 *Contents of SQAP.* The contents of SQAP shall represent the minimum inspection requirements and shall be the basis for acceptance or rejection by lot of each component covered by a SQAP. The Government reserves the right, however, to inspect for the requirements of all drawings and specifications and to reject individual nonconforming items.

4.6.2 *Contractor's inspection for all components not covered by SQAP.* Inspection for these components shall be in accordance with the inspection procedures of the inspection system required by Specification MIL–I–45208. The system shall include procedures for checking all positional and functional characteristics shown on the drawings which indicate precision requirements and have a bearing on the functional accuracy and performance of the mount.

4.7 **Inspection equipment.** Inspection equipment shall conform to drawings listed in IEL 8295051 and 8295057, except as provided for under the alternative inspection procedures and inspection equipment requirements of Specification MIL–I–45208. Provisions of Specification MIL–I–45607 shall apply to test equipment provided by the Government or provided by the contractor and utilized in the Government approved inspection system. The Government reserves the right to use all approved test equipment, both Government furnished and contractor acquired, for verification inspection.

4.7.1 *Accuracy requirements.* Inspection equipment which incorporates features for measuring values or sizes established by product requirements shall be capable of measuring those values within an accuracy of ten percent of the specified tolerance except as specified in 4.7.2. In cases where the ten percent accuracy imposes impractical or very difficult design and fabrication problems, or results in a test equipment cost factor which is exorbitant in relation to the cost and application of the product to be inspected, the Government shall be expeditiously advised in order that necessary appropriate action can be taken.

4.7.2 *Inspection equipment design requirements.*

4.7.2.1 *Device to test temperature requirements.* Unless otherwise specified, the test equipment used when performing the temperature test shall be such that the equipment under test shall not exceed fifty percent of the internal volume of the test chamber and no portion shall be closer than six inches from any surface of the chamber. The temperature reading recorded shall be accurate within plus or minus 2° of the test temperature specified and shall maintain a relative humidity of plus or minus 2 percent of the testing humidity specified.

4.7.2.2 *Device to test vibration.* Unless otherwise specified, this device shall conform to the accuracy specified in Specification MIL–F–13926.

4.7.2.3 *Device to test accuracy.* The device used to test accuracy requirements specified in this specification shall conform to the accuracy requirements specified on Drawing F8237268.

4.8 **Acceptance inspection.**

4.8.1 *Classification of defects.* The classification of defects in Tables IV and V shall constitute the minimum inspection requirements to be performed prior to acceptance or rejection by lots. The AQL specified pertains to each individual characteristic.

4.8.1.1 Samples selected for acception inspection listed under Table V shall include those samples used for acceptance inspection specified in Table IV.

4.9 **Test methods and procedures.**

4.9.1 *Temperature.* The mount shall be placed in the chamber and the temperature shall be thermally stabilized at the temperatures specified in 3.15. When stability is reached at each temperature specified the operability checks shall be made. The results of these checks shall conform to the torque readings of Table III and shall be mechanical-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:33Z
Check the source to verify that this is the current version before use.

TABLE IV. *Classification of defects*

Use inspection level L8, in table III–B with sampling plan table IV–A of Standard MIL–STD–105.

Critical: None defined

Major:	*AQL 6.5% defective*	*Requirement paragraph*	*QA paragraph*	*Test method*
101.	Vibration	3.12	4.9.2	Special Testing Equipment (STE)
102.	Post vibration	3.13	4.9.2	Visual-Tactile
103.	Operability	3.14	4.9.3	Standard Meas. Equipment (SME)
104.	Temperature	3.15	4.9.1	SME
105.	Post temperature	3.16	4.9.1	SME-Visual

Minor: None defined

TABLE V. *Classification of defects*

Use inspection level II, in table III–A with sampling plan table IV–A of Standard MIL–STD–105.

Critical: None defined

Major:	*AQL 1.5% defective*	*Requirement paragraph*	*QA paragraph*	*Test method*
101.	Completeness of assy	3.3		Visual
102.	Key location	3.6(a)	4.10.2	STE
103.	Position of level bubble	3.6(b)	4.10.3	STE
104.	Plumb travel	3.6(c)	4.10.4	STE
105.	Coincidence between gun position and elevation counter.	3.6(d)	4.10.5	STE
106.	Backlash	3.6(e)	4.10.7	STE
107.	Backlash between pinion sector rack	3.6(f)	4.10.8	STE
108.	Rigidity	3.7	4.10.9	STE
109.	Elevation	3.8	4.10.6	STE
110.	Interference	3.8.3	4.10.10	STE
111.	Azimuth backlash	3.9	4.10.11	STE
112.	Insulation resistance	3.11	4.10.13	SME
Minor:	*AQL 4.0% defective*			
201.	Illumination	3.10.1	4.10.12.1	SME-Visual
202.	Variable light intensity	3.10.2	4.10.12.2	SME-Visual

ly operable as specified in 3.14. It shall not be damaged and shall meet the performance requirements of 3.6(b) to (e) and 3.7. Test procedures used to determine acceptability, operability, torque, performance and rigidity shall be as outlined herein.

4.9.2 *Vibration.* The mount shall be mounted to the vibration table by means of an adapter. The amplitude, duration, and frequency specified in 3.12 shall apply. Upon completion of vibration, the mount shall not be damaged and there shall be no broken, bent or missing parts when subjected to a visual inspection, and shall conform to the performance requirements of 3.6(b) to (e), and 3.7. The test procedures outlined herein shall be used to determine acceptable performance and rigidity.

4.9.3 *Operability.* The test for operability (torque readings) shall be performed using a standard torque wrench and appropriate adapters. The adapters shall be attached to the appropriate knob specified in table III and the reading shall be obtained when the mount has reached the stabilized temperature specified in table III. When performing these torque tests, the initial torque required to actuate the knobs shall be disregarded.

4.10 Examination.

4.10.1 *Fixture and associated equipment.* The following test procedures are to be performed using fixture 8237268 and associated equipment listed on Drawing F8237268.

4.10.2 *Determining the axis of the locating keys with respect to the mounting surface.*

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:33Z
Check the source to verify that this is the current version before use.

With the mount positioned on the fixture in accordance with the setup instructions, insert the Panoramic Telescope M100 Series into the mount and secure in position. Sight through the telescope and observe coincidence between the telescope's optical axis and a selected target point keeping the elevation knob of the telescope set to zero while simultaneously positioning the saddle assembly level in all planes. Coincidence is assured when the saddle assembly is rotated 360 degrees and the optical line of sight will not deviate from this selected target point. After this coincidence has been obtained, aline the centerline of the telescope's reticle to the plumb line by means of the telescope's azimuth knob. The plumb line and reticle centerlines shall be in coincidence within the tolerances specified in 3.6(a). Any misalinement will be measured by means of the azimuth knob of the telescope.

4.10.3 *Level vial position.* Each of the level vials shall indicate level within the limits specified in 3.6(b). This test can be determined during the previous test while rotating either the worm and support assembly between its limits by rotating the cant correction mechanism 360 degrees or by any combination of movements mentioned above.

4.10.4 *Plumb travel.* With the mount and telescope positioned as described in 4.10.2, plumb error can be determined by rotating the elevation handwheel of the fixture to simulate gun elevation while simultaneously observing coincidence between the telescope's intersecting reticle lines and the target line provided for this test. During the elevating operation, this intersecting reticle point must be in coincidence with target line within the limits of the tolerance lines provided on the target in order to conform with the requirement of 3.6(c).

4.10.5 *Elevation errors.* With the mount positioned as specified in 4.10.2, the elevation error will be measured by comparing the elevation reading produced by means of a gunner's quadrant of known error. The actual test is performed by inserting an angle of elevation into the mount by means of the fixture elevating mechanism and reading the angle of elevation on the counter and vernier scale. Set the gunner's quadrant to the identical angle of elevation and set the quadrant on the fixture surface provided for this purpose. The quadrant's level vial shall indicate level within the tolerance specified in 3.6(d). The number of readings to be taken shall total twelve readings including zero and 1170 mil settings. The remaining ten readings shall be made throughout the elevation movement; the actual selections shall be made by the Government.

4.10.6 *Elevation limit stops.* The check to determine where the elevation limit stops are located shall be determined during the elevation error test. With the mount positioned as outlined in 4.10.1, elevate the panoramic telescope's line of sight by means of the fixture elevating hand-wheel to maximum elevation; note the reading on the counter and vernier. Set the identical elevation reading into the gunner's quadrant and position the quadrant on the fixture by the means provided. The quadrant level vial bubble shall indicate level within the limit specified in 3.8. Repeat this operation in the opposite direction.

4.10.7 *Elevation backlash.* By means of the fixture elevating handwheel, elevate the telescope's line of sight to the maximum position. Set the counter to 1100 mils and depress the telescope's line of sight until the indices are alined. Set the gunner's quadrant to the identical elevation setting shown on the counter. Set the quadrant on the fixture by the means provided and observe the quadrant level vial. The vial should show level within the tolerance outlined in 3.6(e). Any movement necessary to level the quadrant's level vial will be made by rotating the quadrant's micrometer. The difference in elevation readings between the counter and vernier and the quadrant must conform to the limits outlined in 3.6(e). Backlash shall be checked at 12 positions including the 1170 and zero mil settings; the remaining ten readings shall be made throughout the elevation movement; the actual elevation selected shall be determined by the Government.

4.10.8 *Backlash between Pinion B8294984 and Sector D8294981.* Backlash shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:33Z
Check the source to verify that this is the current version before use.

checked by securing a dial indicator to the fixture by the means provided while the mount is positioned in the fixture. The actual check for backlash is made by preloading the dial indicator on the segments pitch diameter and attaching a calibrated spring scale to Sector D8294981 while the spline section of Pinion B8294984 is secured by the means provided. When performing this test, the indicator deflection shall conform to the limits specified in 3.6(f) when a force of ten pounds is applied, as measured by the calibrated scale, in either direction. Repeat this check at eight different positions of the pinion and sector.

4.10.9 *Rigidity.* Position the telescope mount as outlined in 4.10.2. Rigidity will be tested as follows: (a) Secure the simulated gun trunnions of the fixture by the means provided and coincide the panoramic telescope's intersecting reticle lines to the target point provided for this test. (b) Apply a force in the directions specified in 3.7 to the telescope eyepiece, release the force and observe the deflection of the telescope's line of sight. Deflection shall not exceed the limits of the tolerance line provided to facilitate this test. Repeat this procedure at the elevation and cant angles specified in table I. Movement at the various settings shall not exceed the limits of table I.

4.10.10 *Interference.* With the mount positioned to any combinations of cant and elevation angles, the cross leveling mechanism shall have sufficient adjustment to plumb the panoramic telescope. The leveling mechanism shall be capable of rotating 360 degrees without interference between components or subassemblies as specified in 3.8.3.

4.10.11 *Azimuth correction.* Insert a cant value specified in the setup and operating instructions and level the four bubbles of the saddle assembly. Set the elevation counter to zero and aline the intersecting point of the panoramic telescope's reticle lines with the target point provided and observe the reading on the panoramic telescope's azimuth counter and micrometer; both should indicate zero readings within the tolerance specified. Rotate the elevation handwheel of the fixture to indicate three hundred mils on the elevation counter. Rotate the telescope's azimuth knob to realine the intersecting point of the reticle to the target point provided. The amount of azimuth rotation required for this alinement as determined by the azimuth counter must coincide with the azimuth correction reading specified in the setup and operating instruction for the fixture. Record this reading.

4.10.11.1 Backlash measurements shall be checked after determining azimuth correction readings as follows: Continue to rotate the azimuth knob past the recorded setting of 4.10.11. Rotate this knob in the reverse direction to obtain the identical reticle target alinement of 4.10.11. Do not pass the previous point of coincidence. The difference between this reading and the recorded reading must coincide within the limits of 3.9.

4.10.11.1.1 Repeat this procedure at each of the elevation and cant settings specified on the setup and operating instruction supplied with the final test fixture. This procedure will be followed for both right angle cant and left angle cant when the mount provides such features.

4.10.12 *Illumination.*

4.10.12.1 *Fixed intensity.* Connect a 24-volt power source to the proper receptacle of the wiring harness to determine compliance with 3.10.1. Illumination of the index markings of the elevation index, elevation counter and the four leveling vials shall be observed when tested in a dark area.

4.10.12.2 *Variable intensity.* Variability of light intensity shall be observed by actuating the rheostat of the light control box while observing the illumination of the bulbs. By means of standard measuring equipment determine that contact D and G of the receptacle are in series with the rheostat in compliance with 3.10.2.

4.10.13 *Insulation resistance.* Insulation resistance as specified in 3.11 shall be tested in accordance with Specification MIL–F–13926.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:33Z
Check the source to verify that this is the current version before use.

4.11 Packaging, packing and marking. Quality assurance provisions specified in 5.1 shall apply.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking. Packaging, packing and marking shall be in accordance with Specification MIL–P–12980. The level of protection shall be as specified in the procurement document.

6. NOTES

6.1 Intended use. The Mount Telescopes of the M99 series are used in full tracked self-propelled artillery as follows:

(a) Mt. Telescope M99A1 with Panoramic Telescope M100 in Self-propelled Howitzer M52, 105mm.

(b) Mt. Telescope M99A1C and Panoramic Telescope M100 in Self-Propelled Howitzer M55–8 inch and Self-Propelled Gun M53, 155mm.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.

(b) Selection of applicable levels of preservation, packaging and packing.

(c) Applicable stock number.

(d) Availability of Ordnance Inspection Fixture Part No. 8237268 as Government furnished property.

(e) Provisions for initial production sample including date of delivery (see 3.1).

6.3 Definitions.

6.3.1 *Special test equipment (STE).* Special testing equipment is defined as special inspection fixtures, instruments, and modified standard measuring equipment.

6.3.2 *Standard measuring equipment (SME).* Standard measuring equipment is defined as the common hand type measuring devices which are usually stocked by commercial supply houses for ready supply (shelf items), and which are normally used by an inspector to perform dimensional inspection of items under procurement. This category also includes commercial testing equipment such as meters, optical comparators, etc.

6.3.3 *Tactile.* Skillful manipulation or sensing.

6.4 Design information. Information regarding specific design not covered or referenced in this specification may be obtained from the procuring activity upon the specific request of the contractor.

6.5 Inspection fixture. Due to the mass and complexity of these mounts, the only practical methods of mounting for inspection purposes is an Ordnance Inspection Fixture 8237268.

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any invention that may in any way be related thereto.

Custodian:
Army—Ord

Preparing activity:
Army—Ord

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:33Z
Check the source to verify that this is the current version before use.