MIL-M-46323A(MU)
AMENDMENT 2
21 September 1972
SUPERSEDING
AMENDMENT 1
21 March 1972

MILITARY SPECIFICATION

MOUNTS, TELESCOPE: M99 SERIES

This amendment forms a part of Military Specification MIL-M-46323A (ORD) dated 17 October 1962.

* Paragraph 3.7 Rigidity: Change "Fifty Pound Tangential Load" to "Twenty Pound Tangential Load".

Paragraph 3.7 Rigidity: In TABLE I under CANT delete: "124.4" and substitute "88.9".

Paragraph 3.9 Azimuth Correction: Delete and substitute the following: "The mount shall give azimuth correction reading in accordance with Table II for both right and left cant angles at the specified elevations.

TABLE II

AZIMUTH CORRECTIONS
(All readings in mils)

Counter Elevation	Cant	Azimuth Correction	Tolerance w/o Gimbal Boot Installed	Tolerance w/Gimbal Boot Installed	Azimuth Backlash*
300	88.9	27.0	0.5	0.5	0.5
700	88.9	73.2	1.0	1.5	0.5
1130	88.9	180.2	2.0	6.6	1.0
300	177.8	54.5	1.0	1.0	0.5
700	177.8	147.9	1.5	3.5	0.5
1000	177.8	272.0	3.0	6.6	1.0

*Azimuth Backlash is defined as the difference between the actual measured azimuth correction angles read on elevation, and those read on depression."

* The margin of this specification is marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army - MU

Preparing Activity:
Army - MU
Project No. 1240-A406

FSC 1240

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:33Z
Check the source to verify that this is the current version before use.