MIL-M-46325D(MU)
AMENDMENT 3
3 September 1968
SUPERSEDING
AMENDMENT 2
14 JUNE 1968

MILITARY SPECIFICATION

MOUNT, TELESCOPE: M128

This amendment forms a part of Military Specification MIL-M-46325D(MU), dated 25 May 1965.

Paragraph 2.1, Under Drawings - Delete" ''IEL 8245970 - List of Inspection Documents for Mount, Telescope: M128".

Paragraph 2.1, Under Packaging Data Sheet - Delete "MIL-p-14232/P8245970" and substitute " 8245970".

paragraph 3.10.1: Delete and substitute the following:

"3.10.1 Angle of site. - When the amount of backlash at each angle of site reading taken in accordance with 3.9.2 is added to the angle of site error at that setting the sum shall not exceed 1.2 mils."

Paragraph 3.11.1: Delete and substitite the following:

"3.11.1 Telescope clamping mechanism.- The telescope clamping mechanism shall be operable in the unlocked and locked positions when using a mandrel test piece having a diameter of .8427 - .0001 inches. These requirements shall be met at the standard ambient temperature of 3.3.2 and while the mount is subjected to the extreme operating temperatures of 3.3.1.

3.11.1.1 Unlocked position.- The mandrel test piece shall rotate freely and the clamping mechanism shall operate freely.

3.11.1.2 Locked position.- There shall be no movement of the mandrel test Piece when a 40 inch pound torque is applied to the mandrel."

Paragraph 3.11.5: Delete and substitute the following:

"3.11.5 Torque.- The running torque is inch ounces on all knobs shall be within the limits specified in Table I.

FSC 1240

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:34Z
Check the source to verify that this is the current version before use.

TABLE I

TORQUE VALUES (INCH OUNCES)

KNOB	+60° to 90°F (STANDARD TEMPERATURE) Min	Max	-40° and +150°F (EXTREME OPERATING TEMPERATURE) Min	Max
Angle of Site	10	20	10	40
Elevation	32	55	32	90
Azimuth	32	55	32	90

Paragraph 3.11.6: Add the following new paragraph:

paragraph 4.1.2, 4.2.3.2 and 4.1.2.2: Add the following new paragraphs:

"4.1.2 First Article (Initial Production) Approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of three (3) mounts plus three (3) each of all items covered by SQAP. The sample shall be manufactured in the same manner, using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.1.2.1 Government Testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.1.2.2 Contractor testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection."

Paragraph 4.2.2: Delete and substitute the following:

"4.2.2 Components and subassemblies.- All components and subassemblies shall be inspected in accordance with the inspection provisions contained in Supplementary Quality Assurance Provisions (SQAP) listed in the technical data package (TDP). In the absence of SQAP'S, the applicable Quality Assurance Provisions of MIL-F-13926 shall apply. Examination and tests related to Section 3 herein shall be performed on a single defect

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:34Z
Check the source to verify that this is the current version before use.

(individual characteristic) basis in accordance with MIL-STD-105 and the sampling plans specified in Tables II, III and IV herein. Examination and tests for packaging, packing and marking shall be in accordance with MIL-P-14232 and Section 5 herein. The tabulated classification of defects in Tables II, III and IV shall constitute the minimum inspection to be performed by the supplier after first article approval and prior to Government acceptance or rejection by item or lot."

* Paragraph 4.5.9: Delete "1100" and substitute "1600".

Paragraphs 4.5.16.1 and 4.5.16.2: Add the following new paragraphs:

"4.5.16.1 Unlocked Position.- When the specified test piece is positioned in the clamping mechanism, it shall rotate freely without drag or interference as specified in 3.11.1.1 It shall meet this requirement when subject to the temperatures specified in 3.3.1 and 3.3.2".

"4.5.16.2 Locked position.- With the specified test piece positioned in the clamping mechanism as in 4.5.16.1, the clamping mechanism shall be actuated to the locked position. The test piece shall have no movement when the specified torque (3.11.1.2) is applied. The clamping mechanism shall operate freely when subjected to temperatures specified in 3.3.1 and 3.3.2".

Paragraph 4.5.21: Add the following new paragraph:

Paragraph 5.1: Delete and substitute the following:

"5.1 Packing and marking.- Packaging, packing and marking shall be in accordance with Packaging Data Sheet 8245970. The level of protection shall be as specified in the procurement document (see 6.2)".

* The outside margins have been marked to indicate where additions to the previous amendment have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notation. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notation and relationship to the last previous amendment.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A094

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:34Z
Check the source to verify that this is the current version before use.