MILITARY SPECIFICATION

MODULES: REPRODUCER, SIGNAL DATA: AN/GSQ-64

This amendment forms a part of Military Specification MIL-M-46336C(MU), dated 10 March 1965.

Paragraph 3.8.5(a): Delete "-5.75 ± 0.4 volts" and substitute "5.42 ±0.4 volts".

Paragraph 3.8.11.3(a): Delete "-5.7 ± 0.5 volts" and substitute "-5.4 ± 0.5 volts".

Paragraph 3.9.1, Figure 2(B): Change "-11.5 ± 1.5 volts" to "-9.1 ±1.8 volts".

* Following paragraph 4.1.1, add paragraphs 4.1.2., 4.1.2.1 and 4.1.2.2.

"4.1.2 First Article (Initial Production) Approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of three (3) of each type module manufactured in the same manner using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.1.2.1 Government Testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.1.2.2 Contractor Testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection."

* Paragraph 4.3.2 Delete first sentence and substitute:

Modules shall be selected at random by a government representative as control samples from each three (3) months production or portion thereof as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:37Z
Check the source to verify that this is the current version before use.

3 units per first 100 of each type produced
5 units per 200 " " "
7 units per 300 " " "
9 units per 400 " " "
10 units per 500 " " "
12 units per 700 " " "
15 units per 1000 " " "
and 2 units per every 100 of each type produced in excess of 1000."

Paragraph 4.5.2.3.5.1: Delete "-5.75 ± 0.4 volts" and substitute "5.42 ± 0.4 volts".

Paragraph 4.5.2.3.11.3(a): Delete "-5.7 ± 0.5 volts: and substitute "-5.4 ± 0.5 volts".

* The outside margins have been marked to indicate where additions to the previous amendment have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notation. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A069

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:37Z
Check the source to verify that this is the current version before use.