MIL-M-46336C(MU)
AMENDMENT 4
2 August 1968
SUPERSEDING
AMENDMENT 3
8 May 1968

MILITARY SPECIFICATION

MODULES: REPRODUCER, SIGNAL DATA: AN/GSQ-64

This amendment forms a part of Military Specification MIL-M-46336C(MU), dated 10 March 1965.

* Paragraph 1.1, line 1: Change "five" to "six"; Add to list of modules: "Terminal Board TB-6: 10531591".

* Paragraph 2.1, under drawings: Add "D10531591 Terminal Board TB-6".

* Paragraph 3.5.2: Change "15g's" to "5g's".

* Figure 2(B): Delete "1.54 ± .1 msec" and substitute "1.54 $^{+.1}_{-.3}$msec"; delete "-11.5 ± 1.5v" and substitute "-9.1 ± 1.8v".

Paragraph 3.8.5(a): Delete "-5.75 ± 0.4 volts" and substitute "5.42 ± 0.4 volts".

Paragraph 3.8.11.3(a): Delete "-5.7 ± 0.5 volts" and substitute "-5.4 ± 0.5 volts".

Paragraph 3.9.1, Figure 2(B): Change "11.5 ± 1.5 volts" to "9.1 ± 1.8 volts".

* Paragraph 3.9.4: Change "480 ± 20 cps" to "488 ± 20 cps".

Add new paragraph "3.11":

"3.11 Terminal Board TB-6: 10531591.- The circuitry shall be in accordance with electrical schematic, Drawing D10531594. Unless otherwise specified, the following requirements apply at standard room temperature (60° to 90°F).

Diode.-

(a) Forward voltage drop.- When conducting 10ma, diodes CR1 through CR9 shall exhibit not more than 1.0 volt drop. At low temperature (-40°F), the drop shall be not more than 1.5 volts.

(b) Diode reverse current.- With 5 VDC applied in the reverse direction, not more than 5 μa shall flow through the diodes, CR1 through CR9. At high temperature (+125°F), the reverse current shall be not more than 35 μa."

FSC 1220

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:37Z
Check the source to verify that this is the current version before use.

Following paragraph 4.1.1, add paragraphs 4.1.2, 4.1.2.1 and 4.1.2.2.

"4.1.2 First article (initial production) approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of three (3) of each type module manufactured in the same manner using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.1.2.1 Government testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.1.2.2 Contractor testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for materials, shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection."

* Paragraph 4.2.3: Add the following sentence: "No lots shall be accepted until control samples have been completely tested."

Paragraph 4.3.2: Delete first sentence and substitute:

"Modules shall be selected at random by a Government representative as control samples from each three (3) months production or portion thereof as follows:

| | | | |
|---|---|---|---|
| 3 units per | first 100 | of each | type produced |
| 5 units per | 200 | " " | " |
| 7 units per | 300 | " " | " |
| 9 units per | 400 | " " | " |
| 10 units per | 500 | " " | " |
| 12 units per | 700 | " " | " |
| 15 units per | 1000 | " " | " |

and 2 units per every 100 of each type produced in excess of 1000."

* TABLE VII: Delete last column Test Procedures and substitute the following new column:

| "Test Procedures |
|---|
| 4.5.1.1 |
| 4.5.1.2 |
| 4.5.1.3.1 |
| 4.5.1.3.2" |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:37Z
Check the source to verify that this is the current version before use.

* Paragraph 4.4.1.1, Items 4, 5, 6, 7, 8, under Description: Delete "specified in 4.4.2.2" and substitute "specified in 4.4.1".

* Paragraph 4.5.2.1.4: Delete "4.5.1.5" and substitute "4.5.1.4".

* Table XVI, third column under (Min), lines 1 through 12: Delete "1,500" and substitute "1K".

* Table XVI, last column: Delete last eight (8) lines and substitute the following:

"3.7.1(d)
3.7.1(e)
3.7.1(f)
3.7.1(f)
3.7.1(f)
3.7.1(f)
3.7.1(f)
3.7.1(f)"

* Paragraph 4.5.2.2.3(a): Delete "+6 ± 0.5 volts" and substitute "+5.9 ± 0.6 volts".

* Paragraph 4.5.2.2.7(b): Delete "5.7 volts" and substitute "5.5 volts".

* Paragraph 4.5.2.2.8(a)(4): Delete "-7.1 ± 0.4 volts" and substitute "-7.1 ± 0.9 volts".

* Paragraph 4.5.2.2.8(b)(2): Delete "shall be -15 ± 1.5 volts" and substitute "with respect to -15 volts shall be less than 0.16 volt".

Paragraph 4.5.2.3.5.1: Delete "-5.75 ± 0.4 volts" and substitute "5.42 ± 0.4 volts".

Paragraph 4.5.2.3.11.3(a): Delete "-5.7 ± 0.5 volts" and substitute "-5.4 ± 0.5 volts".

* Add new paragraph "4.5.2.6":

"4.5.2.6 Terminal Board TB-6: 10531591.- Ground terminal 9 for the following tests.

(a) Apply -10 vdc through a 1K ohm resistor to each terminal (1 through 8) in consecutive order. The measured voltage at each terminal across the 1K ohm resistor shall be 1 vdc or less.

(b) Apply +5 vdc through 10K ohm ± 1% resistor to each terminal as specified in 4.5.2.6(a). The measured voltage across the 10K resistor shall not exceed .05 vdc.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:37Z
Check the source to verify that this is the current version before use.

(c) Apply +5 vdc through 10K ohm ± 1% resistor to junction of CR9 and R9. The measured voltage across the 10K resistor shall not exceed .05 vdc.

(d) Repeat the above tests at the low temperature conditions specified in 3.5.3 and 4.5.1.4. The measured voltage specified in 4.5.2.6(a) shall be 1.5 vdc.

(e) Repeat the above tests at the high temperature conditions specified in 3.5.3 and 4.5.1.4. The measured voltage specified in 4.5.2.6(b) shall not exceed .55 vdc. The measured voltage specified in 4.5.2.6(c) shall not exceed .35vdc."

*The outside margins have been marked to indicate where additions to the previous amendment have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notation. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A121



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:37Z
Check this source to verify that this is the current version before use.