MILITARY SPECIFICATION

POWER SUPPLY: 10516158
(TRANSISTORIZED)

This amendment forms a part of Military Specification MIL-P-46320C(MU) dated 1 April 1963.

Paragraph 2.1: Delete Federal Specification "QQ-N-290 - Nickel Plating (Electrodeposited)" and substitute Military Specification "MIL-T-10727 - Tin Plating, Electrodeposited or Hot-Dipped, for Ferrous and Nonferrous Metals".

Paragraph 3.2.1: Delete and substitute: "3.2.1 External surfaces.- The external metallic case of the power supply shall be tin plated in accordance with Type I of Specification MIL-T-10727, except that plating shall have a minimum thickness of 0.0004 inch".

Paragraph 3.9.1: Delete "1.52 volts" and substitute "1.53 volts".

* Tables I through IV: Delete and substitute:

TABLE I-ELECTRICAL CHARACTERISTICS (+125°F)

Minimum Output Current (Amperes)	Maximum Input Current (Ma)	Minimum Output Voltage Excluding DC Ripple (KV)
1×10^{-9}	24.0	15.2
1×10^{-7}	26.0	15.0
5×10^{-7}	30.0	14.5
1×10^{-6}	35.0	14.0

TABLE II-ELECTRICAL CHARACTERISTICS (+60° to +90°F)

Minimum Output Current (Amperes)	Maximum Input Current (Ma)	Minimum Output Voltage Excluding DC Ripple (KV)
1×10^{-9}	18.0	15.7
1×10^{-7}	20.0	15.4
5×10^{-7}	24.0	15.0
1×10^{-6}	30.0	14.0

FSC 1240

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:33Z
Check the source to verify that this is the current version before use.

TABLE III-ELECTRICAL CHARACTERISTICS (-40°F)

Minimum Output Current (Amperes)	Maximum Input Current (Ma)	Minimum Output Voltage Excluding DC Ripple (KV)
1×10^{-9}	24.0	15.2
1×10^{-7}	26.0	15.0
5×10^{-7}	30.0	14.5
1×10^{-6}	35.0	14.0

TABLE IV-OUTPUT VS. INPUT VOLTAGE (+60° to +90°F)

Maximum dc Input	Minimum Kilovolt Output at dc Load Currents Specified		
Volts	1×10^{-9} amperes	1×10^{-7} amperes	5×10^{-7} amperes
1.00	10.0	10.0	9.5
1.30	13.3	13.1	12.6
1.50	15.5	15.3	14.8
1.52	15.7	15.4	15.0
1.55	15.8	15.6	15.3

* Paragraph 3.9.3.3: Delete and substitute:

"3.9.3.3 Maximum output voltage.- The maximum output voltage including the peak ripple voltage shall not exceed 16.1 kilovolts (KV) under any condition of input voltage up to and including 1.53V."

* Paragraph 4.8.1.17: Delete "shall be 1.52 volts" and substitute "shall not exceed 1.53 volts".

* The outside margin has been marked to indicate where an addition to the previous amendment has been made. This has been done as a convenience only and the Government assumes no liability whatsoever for inaccuracies in this notation. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notation and relationship to the last previous amendment.

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1240-A424Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:33Z
Check the source to verify that this is the current version before use.