MILITARY SPECIFICATION

POWER SUPPLY: 10516158
(TRANSISTORIZED)

This amendment forms a part of Military Specification MIL-P-46320C(MU) dated 1 April 1963.

Paragraph 2.1, SPECIFICATIONS, Military: Add the following:

"MIL-T-10727 - Tin Plating, Electrodeposited or Hot-Dipped, for Ferrous and Nonferrous Metals."

Paragraph 3.2.1: Delete and substitute:

"3.2.1 External surfaces.- The external metallic case of the power supply shall be nickel plated .0003 thick minimum in accordance with Class I of QQ-N-290 or tin plated .0004 thick minimum in accordance with Type I of MIL-T-10727."

Paragraph 3.9.1: Delete "1.52 volts" and substitute "1.53 volts".

Tables I through IV: Delete and substitute:

TABLE I - ELECTRICAL CHARACTERISTICS (+125°F)

Minimum Output Current (Amperes)	Maximum Input Current (Ma)	Minimum Output Voltage Excluding DC Ripple (KV)
1×10^{-9}	24.0	15.2
1×10^{-7}	26.0	15.0
5×10^{-7}	30.0	14.5
1×10^{-6}	35.0	14.0

TABLE II - ELECTRICAL CHARACTERISTICS (+60° to +90°F)

Minimum Output Current (Amperes)	Maximum Input Current (Ma)	Minimum Output Voltage Excluding DC Ripple (KV)
1×10^{-9}	18.0	15.7
1×10^{-7}	20.0	15.4
5×10^{-7}	24.0	15.0
1×10^{-6}	30.0	14.0

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:33:55
Check the source to verify that this is the current version before use.

TABLE III - ELECTRICAL CHARACTERISTICS (-40°F)

Minimum Output Current (Amperes)	Maximum Input Current (Ma)	Minimum Output Voltage Excluding DC Ripple (KV)
1×10^{-9}	24.0	15.2
1×10^{-7}	26.0	15.0
5×10^{-7}	30.0	14.5
1×10^{-6}	35.0	14.0

TABLE IV - OUTPUT VS. INPUT VOLTAGE (+60° to +90°F)

Maximum dc Input	Minimum Kilovolt Output at dc Load Currents Specified		
Volts	1×10^{-9} amperes	1×10^{-7} amperes	5×10^{-7} amperes
1.00	10.0	10.0	9.5
1.30	13.3	13.1	12.6
1.50	15.5	15.3	14.8
1.52	15.7	15.4	15.0
1.55	15.8	15.6	15.3

Paragraph 3.9.3.3: Delete and substitute:

"3.9.3.3 Maximum output voltage.- The maximum output voltage including the peak ripple voltage shall not exceed 16.1 kilovolts (KV) under any condition of input voltage up to and including 1.53V."

Paragraph 4.8.1.17: Delete "shall be 1.52 volts" and substitute "shall not exceed 1.53 volts".

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A091

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:33Z
Check the source to verify that this is the current version before use.