MILITARY SPECIFICATION

PERISCOPE TANK: M35

This amendment forms a part of Military Specification MIL-P-46337B (MU) dated 31, January 1972.

Delete "MIL-B-14843" wherever it appears in the specification and substitute "MIL-B-50762".

Delete "10541950" wherever it appears in the specification and substitute "11743800".

Paragraph 2.1, Drawings:

Delete "F8575995" and F8575996" with their corresponding title.

Paragraph 4.6.1: Delete and substitute:

"4.6.1 Pre-vibration collimation, infrared reticle setting.- This test and the following tests of 4.6.1.1, 4.6.2.1.1 and 4.6.2.1.2 shall be performed with the periscope positioned and adjusted as in 4.6.4. Prior to performing these tests, disengage the index pin "D" from the index plate of the test fixture and place the 10 second level on surface "C" of the leveling base. The bubble of the level shall be centered within its graduation lines. If it is not, then adjustment is required in accordance with the procedures prescribed in paragraphs 7 and 8 of the set-up instructions contained on Drawing F8247391. With the index pin "D" disengage from the index plate and surface "C" of the leveling base level, view through the periscope eyepiece (infrared) and obtain coincidence of the periscope reticle boresight cross and the projected target image crosslines, by means of the infrared boresight knobs (do not slip knob scales). When coincidence has been obtained, record the boresight knob scale settings for use in the test in 4.6.2.1.1. Without distrubing the knob scale settings, the periscope shall be then subjected to the test in 4.6.1.1."

Paragraph 4.6.2.1: Delete "4.6.4" and substitute "4.6.1".

Paragraph 4.6.4: Delete and substitute:

"4.6.4 Performance.- To determine compliance with 3.6, the following tests shall be performed with the complete periscope positioned on the special test equipment specified in 4.5.2.3.1. Set-up of the test equipment and installation of the periscope under test shall be performed in accordance with the set-up and calibration instructions contained on Drawing F8247391. A target projector collimator having a clear aperture of at least 2.0 inches and containing an appropriate calibrated horizontal and

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:38Z
Check the source to verify that this is the current version before use.

verticle reticle crossline target test pattern shall be utilized with the specialized test equipment specified herein. The vertical reticle target line shall be aligned plumb when in the test position in a qualified level surface and the target projector collimator shall be adjusted for infinity. The target projector collimator shall be positioned at the rear of the daylight body of the periscope so that its optical axis is in alignment with the line of sight (geometric center) of Lens 8289292. The optical axis of the target projector collimator shall be aligned parallel with respect to Datum Plane "Y" and autocollimated within 10 seconds to Datum Plan "W". Unless otherwise specified during these tests, the Infrared Focusing Ring 8620059 shall be adjusted for best focus of the target image after the diopter adjustment knob of the infrared eyepiece is set for best focus of the phospher grain on the screen of the image tube; Eccentric 10516549 (for adjusting parallax) shall be adjusted for minimum parallax between the target image and reticle and then locked after the diopter adjustment knob of the daylight eyepiece is set for best focus of the projected infinity target; the clear filter shall be positioned in the field of view and the Collimator Projector 10547434 shall be adjusted for 1200 meters.

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 1240-A403

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:38Z
Check the source to verify that this is the current version before use.