MILITARY SPECIFICATION

QUADRANT, FIRE CONTROL: M15

This amendment forms a part of Military Specification MIL-Q-46315C(MU) dated 15 August 1972.

Paragraph 3.5.3: Delete paragraph and substitute:

"3.5.3 Vibration.- The quadrant shall show no evidence of physical failure or damage and shall meet the requirements of 3.5.1 to 3.9 inclusive after being vibrated under conditions specified in 3.5.3.1 and 3.5.3.2."

Paragraph 3.5.3.1: Delete paragraph and substitute:

"3.5.3.1 Vibration A.- Vibration shall be in accordance with MIL-F-13926, Procedure VI, Condition B, which involves a displacement of 1/8 inch at frequencies which vary logarithmically from 10 to 55 to 10 cycles per second."

Paragraph 3.5.3.2: Delete paragraph and substitute:

"3.5.3.2 Vibration B.- Vibration shall be in accordance with MIL-STD-810, Procedure VIII, using frequencies which vary logarithmically from 5 to 500 to 5 cycles per second with a maximum displacement of 0.5 inch."

Paragraph 4.3.2.1: Delete all after second sentence.

Paragraph 4.3.2.2: Renumber to 4.3.2.4.

Add paragraphs 4.3.2.2 and 4.3.2.3 as follows:

"4.3.2.2 First article test.- The mount shall successfully comply with the requirements outlined in Tables II and III and Vibration "B" and shock tests of 3.5. Additional first article testing will be required when the processes, material or changes in design occur subsequent to the original first article approval. All first articles so produced shall be submitted to the Government in accordance with 4.2 for approval."

"4.3.2.3 Final acceptance inspection.- Subsequent to first article approval, examination and tests related to Section 3 shall be performed on a single defect (individual characteristic) basis in accordance with MIL-STD-105 and the sampling plans specified in Tables II and III. Examination and tests for Packaging, Packing, and Marking

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:32Z
Check the source to verify that this is the current version before use.

shall be in accordance with MIL-P-14232 and Section 5 herein. The tabulated classification of defects in Tables II and III shall constitute the minimum inspection to be performed by the supplier after first article approval and prior to Government acceptance or rejection by item or lot."

Table III: Delete characteristics 305 and 306.

Paragraph 4.6.1.2: Change first sentence to read: "This test shall be performed as specified in MIL-F-13926, Procedure VI, Condition B, with the vibration input swept logarithmically from 10 to 55 to 10 cycles per second."

Paragraph 4.6.1.3: First sentence: Change Procedure I to Procedure VIII. Delete all after exceptions and substitute: "No resonance search or dwell shall be performed. Vibration input shall be at 0.5 inch DA from 5 cycles per second to the 1.5g curve, to 0.033 inch DA then to the 4g curve continuing to 500 cycles per second. Vibration input shall be swept logarithmically with the complete frequency exposure from 5 to 500 and return to 5 cycles per second completed in 15 minutes."

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1290-A318

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:32Z
Check the source to verify that this is the current version before use.