MILITARY SPECIFICATION

REPRODUCER, SIGNAL DATA: AN/GSQ-64
(READER, PUNCHED TAPE)

This amendment forms a part of Military Specification MIL-R-46332A(MU) dated 10 March 1965.

* Paragraph 2.1, under SPECIFICATIONS: Add

"MIL-M-46336	Modules, Reproducer, Signal Data: AN/GSQ-64
MIL-T-60177	Transistor Assembly"

* Paragraph 2.1, under DRAWINGS: Add

"B8623275	Tape, Test Set, Computer Logic Unit AN/GSM-70 (U) Self Test
D10531591	Terminal Board TB-6
F8213319	Amplifier Assembly, Photodiode
F10525770	Transistor Assembly
F10531686	Amplifier, Power Supply
F10531698	Signal Data Reproducer Subassembly"

* Following paragraph 3.1, add paragraph 3.1.1.

"3.1.1 List of assemblies.- The reproducer shall be comprised of the assemblies and modules listed herein. The assemblies and modules shall have been inspected and accepted in accordance with their respective drawings and specifications prior to incorporation in the reproducer.

Assembly	Drawing	Specification
Terminal Board TB-6	D10531591	MIL-M-46336
Amplifier Assembly, Photodiode	F8213319	MIL-M-46336
Transistor Assembly	F10525770	MIL-T-60177
Amplifier, Power Supply	F10531686	MIL-M-46336
Amplifier, Electronic Control	F10531690	MIL-M-46336
Signal Data Reproducer, Subassembly	F10531698	MIL-M-46336"

* Paragraph 3.3.1: Delete and substitute new paragraph as follows:

"3.3.1 Vibration.- The reproducer shall be subjected to a simple harmonic motion having an amplitude of 0.015 inch (0.030 inch maximum excursion). The frequency shall be varied continuously from 10 to 55

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:35Z
Check the source to verify that this is the current version before use.

cycles per second and return to 10 cycles and shall be transversed in approximately one minute ± 15 seconds. This motion shall be applied for a period of 10 minutes in each of the three mutually perpendicular direction (total of 30 minutes) at standard room ambient temperature (60°F to 90°F). Subsequent to vibration the reproducer shall not have been damaged or adversely affected and shall meet the electrical performance requirements of this specification."

Paragraph 3.3.2: Delete "15 gravity units" and substitute "5 gravity units".

Paragraph 3.4.3.1: Change "10.0 mv" to "20.0 mv".

Paragraph 3.5.1: Delete "52 inches" and substitute "44.5 inches". Delete "520 frames" and substitute "445 frames".

Paragraph 3.5.4: Delete in its entirety and substitute the following:

"3.5.4 Diameter and spacing of punched holes.- The diameter and spacing of punched holes shall be in accordance with Drawing B8623275."

Table I, Column 5 under (Max): Delete "15.6" and substitute "15.8". Column 9 under (Max): Delete "15.6" and substitute "15.85".

* Paragraph 3.6(a), delete first sentence and substitute the following:

"The bias voltage with respect to ground, measured at the terminal board connector pin listed in 3.6(c), shall have a minimum range of zero to minus 1.1 volts as the associated potentiometer is adjusted."

Paragraph 3.6.1: Delete the third sentence in its entirety and substitute the following:

"Pulse duration for t1 + t2 shall be 2.25 msec ± 10%. The normal pulse duration for t1 shall be 1.54 ± .05 msec. At temperature extremes the pulse duration for t1 shall be $1.54 \begin{smallmatrix}+.3\\-.1\end{smallmatrix}$ msec."

* Paragraph 3.6.2, delete paragraph 3.6.2 and substitute:

"3.6.2 Strobe pulses.- With the tape advance switch in OFF position, energizing the reproducer and electrically connecting Pin W of output connector PB to Pin 13 of J10 shall advance the tape. The reproducer shall simultaneously deliver an oscilloscope presentation of the strobe (clock) pulse shown in Figure 3. Nominal pulses duration (t_1 shall be $35 \begin{smallmatrix}+15\\-0\%\end{smallmatrix}$ of the entire 2.25 msec ±10% cycle ($t_1 + t_2$) shown in Figure 3. Under the above conditions the peak pulses amplitude shall be 5.06 to 5.7 volts. This pulse shall be obtained across a 5,600 ohm resistive load, existing between reproducer output connector Pin S and power supply ground, Pin N, and at a point within the range of rotation of potentiometer R9."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:35Z
Check the source to verify that this is the current version before use.

Table II: Delete the last line under the last six columns and substitute the following:

"5.06 5.7 5.06 5.7 5.06 5.7"

Paragraph 3.6.3, line 3: Delete "-0.5" and substitute "+0.5".

* Paragraph 3.7: Delete "3.6a and".

Following paragraph 4.1.1, add paragraphs 4.1.2, 4.1.2.1 and 4.1.2.2.

"4.1.2 First article (initial production) approval.- The requirement for first article approval and the responsibility (Government or contractor) for first article testing shall be as specified in the contract. The sample for first article approval tests shall consist of three (3) reproducers manufactured in the same manner using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as used in regular production.

4.1.2.1 Government testing.- When the Government is responsible for conducting first article approval tests, the contractor, prior to submitting the sample to the Government, shall inspect the sample to insure that it conforms to all the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials.

4.1.2.2 Contractor testing.- When the contractor is responsible for conducting first article approval tests, the sample shall be inspected and a record of this inspection, including certificates of conformance for materials shall be submitted to the Government for approval. The Government reserves the right to witness the contractor's inspection."

* Paragraph 4.5.1.1: Delete "inspected" and substitute "tested" in last sentence; delete "4.5.1.2" and substitute "4.5.2 to 4.5.4.14" in last sentence.

* Paragraph 4.5.1.2: Delete "inspected" and substitute "tested" in last sentence; delete "4.5.1.3" and substitute "4.5.2 to 4.5.4.14" in last sentence.

* Paragraph 4.5.1.3, in last sentence, delete "4.5.4.1.4" and substitute "4.5.4.14."

Paragraph 4.5.2.3, Table VI, delete "10.0 millivolts" and substitute "20.0 millivolts".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:35Z
Check the source to verify that this is the current version before use.

* Paragraph 4.5.2.4, delete paragraph 4.5.2.4 and substitute:

"4.5.2.4 Homing.- Set power and signal switches to the "OFF" position. Set FILL-VERIFY switch in FILL position. Load Tape II (Item 6 of 4.4.1.1) into the read head. Start the tape by placing the POWER and SIGNAL switches to "ON" position and by placing the tape ADVANCE switch from OFF position momentarily to the ON position and back to the OFF position. The tape advance shall be stopped when the homing slot is positioned in the photo diode read head. Set the FILL-VERIFY switch to the VERIFY position, restart the tape as noted above, observing that the tape advances continuously. After meeting this test at the standard ambient temperature (60°F to 90°F) in compliance with 3.4.4 the test shall be repeated at minus 40°F and plus 125°F."

* Paragraph 4.5.3, delete 4.4.2.3 and substitute 4.4.1.1.

Paragraph 4.5.3.1: Change "156 inches" to "133.5 inches".

* Paragraph 4.5.4.1, delete last sentence and substitute "This test is only to be performed during initial ajustment and when requirements of 4.5.4.2 and 4.5.4.3 are not met and readjustment is necessary."

* Paragraph 4.5.4.2, delete last sentence.

Paragraph 4.5.4.3, delete "80 ± 5% of the entire cycle" and substitute "1.54 ± 0.05 msec at ambient (60°F to 90°F) and 1.54 $^{+0.1}_{-0.3}$ msec at the extreme temperatures (-40°F and +125°F)."

* Paragraph 4.5.4.4: Delete "shall measure between minus 14.0 and minus 16.0 volts" and substitute "across the 5,600 ohm load at Pins S and N shall be 5.06 to 5.70 volts"; delete "and the values specified in Table II for these temperatures."

* Paragraph 4.5.5: Delete "4.5.4.1 and".

* The outside margins have been marked to indicate where additions to the previous amendment have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notation. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A201

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:35Z
Check the source to verify that this is the current version before use.