METRIC

MIL-L-46167B
AMENDMENT 1
12 June 1989

MILITARY SPECIFICATION

LUBRICATING OIL, INTERNAL COMBUSTION ENGINE, ARCTIC

This amendment forms a part of MIL-L-46167B, dated 29 July 1988, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

2.2, under AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM), D 2896, delete the word "Total" from the title and add:

"D 4624 - Measuring Apparent Viscosity by Capillary Viscometer at High Temperature and High-Shear Rates.
"D 4683 - Measuring Viscosity at High Temperature and High Shear rate by Tapered Bearing Simulator.
"D 4741 - Measuring Viscosity at High Temperature and High Shear Rate by Tapered-Plug Viscometer.
"D 4927 - Elemental Analysis of Lubricant and Additive Components - Barium, Calcium, Phosphorus, Sulfur, and Zinc by Wavelength Spectroscopy."

PAGE 8

Table II, add the following:

"Evaporation loss	X
.High temperature/high shear	X"

PAGE 12

4.5.2, add the following to the list:

"Evaporation loss
High temperature/high shear"

PAGE 13

Table III, under "test method", add a column "DIN" and add the following:

	ASTM	DIN
"Evaporation loss 10/	D 3887	51581
High temperature/high shear	D 4683, D 4624, D 4741	
Metallic components	D 4927"	

AMSC N/A FSC 9150

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:05Z
Check the source to verify that this is the current version before use.

Add the following footnote:

"10/ The DIN 51581 is the preferred method."

Custodians:
Army - ME
Navy - SH
Air Force - 68

Preparing activity:
Army - ME

Project 9150-1046

Review activities:
Army - AR, SM
Navy - AS, MC, SA, YD
Air Force - 11
DLA - GS

User activities:
Army - AT, MI
Navy - OS

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:05Z
Check the source to verify that this is the current version before use.