MIL-D-14820(MU)
22 July 1969
SUPERSEDING
FA-PD-MI-2568 Rev 0
5 September 1962

# MILITARY SPECIFICATION
# DELAY ELEMENT, CARTRIDGE: XM43 ASSEMBLY

## 1. SCOPE

1.1 This specification covers Delay Element, Cartridge: XM43, Assembly, for use in cartridges for propellant actuated devices in aircrew emergency escape systems.

## 2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

| | |
|---|---|
| MIL-B-550 | - Barium Chromate |
| MIL-A-2550 | - Ammunition and Special Weapons, General Specification for |
| MIL-E-5272 | - Environmental Testing, Aeronautical and Associated Equipment, General Specification for |
| MIL-P-46994 | - Pellet, Boron, Potassium Nitrate |
| MIL-B-51092 | - Boron, Amorphous Powder |
| MIL-C-60539 | - Coating, Anodic, Conventional for Aluminum and Aluminum Alloys |

STANDARDS

Military

| | |
|---|---|
| MIL-STD-105 | - Sampling Procedures and Tables for Inspection by Attributes |
| MIL-STD-109 | - Quality Assurance Terms and Definitions |
| MIL-STD-1167 | - Ammunition Data Card |

DRAWINGS

Munitions Command

| | |
|---|---|
| D10522704 | - Delay Element, Cartridge, XM43 Assembly |

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:50Z
Check the source to verify that this is the current version before use.

DRAWINGS (Cont'd)

| | |
|---|---|
| C8826729 | - Box, Packing, Ammunition for Delay Elements |
| C8864162 | - Ammunition Container, Metal, M21 for XM43 Delay Elements |
| IEL 10522704 | - Inspection Equipment List for Delay Element, Cartridge XM43 Assembly |

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.- The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

ASA B46.1 - Surface Texture

(Application for copies should be addressed to the American Standards Association, 10 East 40th Street, New York, N.Y. 10016)

3. REQUIREMENTS

3.1 General.- Materials, parts and assemblies shall conform to the applicable drawings and referenced specifications.

3.2 Protective finish.- Protective finish shall be in accordance with MIL-C-60539.

3.3 Vibration.- The delay element assembly shall withstand vibrations as prescribed in MIL-E-5272, Procedure XII, without evidence of any disintegration of the primer or delay charge or derangement of components.

3.4 Functional.

3.4.1 The delay element shall not fail to fire.

3.4.2 Ballistics.- The delay charge shall consist of pellets, boron, potassium nitrate as in MIL-P-46994, Barium chromate as specified in MIL-B-550 and Boron as specified in MIL-B-51092 in the proportion and quantity fixed by the contractor to produce the delay time as required in Table I (See 6.2 and 6.3).



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:50Z
Check the source to verify that this is the current version before use.

Table I

| Temperature | Delay Time, (Seconds) (See 6.4) |
|---|---|
| -65° to -70°F | 0.450 max. |
| 65° to 75°F | 0.30 ± 0.05 |
| 160° to 165°F | 0.150 min. |

3.5 Workmanship.- Workmanship shall be in accordance with the requirements of the applicable drawings, referenced specifications and the following:

3.5.1 Metal defects.- The metal part shall be free from cracks, splits, cold shuts, inclusions, porosity or other metal defects.

3.5.2 Burr.- The part shall not have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.5.3 Foreign matter.- The part or assembly shall not contain chips, dirt, grease, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 to define quality assurance terms used.

4.1.2 Inspection.- Inspection shall be in accordance with MIL-A-2550.

4.2 First article sample.

4.2.1 Initial production sample.- At the beginning of regular production, a sample shall be submitted in accordance with the contract requirements and shall consist of 23 delay bodies and 23 primer retainers for protective finish tests and 30 delay element assemblies for ballistic tests as indicated in Table II, and 10 sets of unassembled components (including explosive components) for dimensional and visual examination.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:50Z
Check the source to verify that this is the current version before use.

Table II

| Paragraph Requirement | Test | Test | Sample Size | Type of Test Dest. | Type of Test Non-Dest. |
|---|---|---|---|---|---|
| 3.2 | 4.4.1 | Protective Finish | 23 Delay Bodies | X | - |
| | | | 23 Primer Retainers | X | - |
| 3.3 | 4.4.2 | Vibration | 12 Cartridges from ballistic sample | - | X |
| 3.4.2 | 4.4.3.1 | Ballistics | 30 Delay Elements | X | - |

The sample shall be manufactured using the same materials, equipment, processes and procedures as used in regular production. All parts and materials, including packaging and packing shall be the same as used for regular production and shall be obtained from the same source of supply.

4.2.1.1 Examination and tests.- After examination and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility specified in the contract.

4.2.1.2 Ballistics.- The sample for ballistics tests shall be temperature conditioned and tested to determine compliance with Table I. The sample for firing shall consist of the following:

Table III

| Temperature | Vibrated | Not Vibrated |
|---|---|---|
| -65° to -70°F | 4 | 6 |
| 65° to 75°F | 4 | 6 |
| 160° to 165°F | 4 | 6 |

4.2.1.3 Initial production sample failure.- Failure of the sample to comply with the requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection provisions.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:50Z
Check the source to verify that this is the current version before use.

4.3.1 Lot.

4.3.1.1 Submission of product.- The product shall be submitted in accordance with MIL-STD-105.

4.3.1.2 Size of lot.- A lot shall consist of an identifiable group of metal parts assemblies produced by a homogeneous process and loaded with accepted delay charges.

4.3.2 Examination.- One hundred percent examination shall be performed for all critical defects. Examination for major or minor defects shall be performed on a defect basis in accordance with the classification of defects, using the sampling plan and associated criteria in Tables IV and V. For an individual defect (single characteristic) the criteria in Table IV shall be used. For total defects within a major or minor class, the criteria in Table V shall be used. All non-conforming material shall be rejected. Four power (4X) magnification may be used to perform visual examination for such defects as burr and foreign matter. The roughness comparison specimens prescribed in ASA-B46.1 shall be used as a basis of comparison for surface roughness determination.

Table IV

| Lot Size | Sample Size | Major | | Minor | |
|---|---|---|---|---|---|
| | | Accept | Reject | Accept | Reject |
| 1 - 300 | 100% Examination | | | | |
| 301 - 1300 | 110 | 1 | 2 | 2 | 3 |
| 1301 - 3200 | 150 | 2 | 3 | 3 | 4 |
| 3201 - 8000 | 225 | 3 | 4 | 4 | 5 |
| 8001 - 22000 | 300 | 4 | 5 | 5 | 6 |

Table V

| Sample Sizes for Major Defects Number of defects in class | Total Allowable Defects Per Sample Size | | | |
|---|---|---|---|---|
| | 110 | 150 | 225 | 300 |
| 2 - 3 | 1 | 2 | 3 | 4 |
| 4 - 7 | 2 | 3 | 4 | 5 |
| 8 - 19 | 3 | 4 | 5 | 7 |
| 20 - 43 | 4 | 5 | 8 | 10 |
| over 43 | 6 | 8 | 11 | 14 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:50Z
Check the source to verify that this is the current version before use.

Table V (Cont'd)

| Sample Sizes for Minor Defects Number of defects in class | Total Allowable Defects Per Sample Size 110 | 150 | 225 | 300 |
|---|---|---|---|---|
| 2 - 3 | 2 | 3 | 4 | 5 |
| 4 - 7 | 3 | 4 | 5 | 7 |
| 8 - 16 | 4 | 5 | 8 | 10 |
| 17 - 48 | 6 | 8 | 11 | 14 |
| over 48 | 8 | 11 | 17 | 20 |

4.3.2.1 Body, Delay C8594081, covering a detail of Dwg. D10522704.

| Defect | Method of Inspection |
|---|---|
| CRITICAL | |
| 1. Metal defective | Visual |
| MAJOR | |
| 101. Pitch diameter external thread, min. | Gage |
| 102. Major diameter external thread, min. | Gage |
| 103. Concentricity of head with pitch diameter of thread | Gage |
| 104. Diameter of cavity, max. | Gage |
| 105. Diameter of head, min. | Gage |
| 106. Diameter of flash hole | Gage |
| 107. Location of head | Gage |
| 108. Protective finish inadequate or defective | Visual |
| 109. Thread damaged or not full | Visual |
| 110. Burr | Visual |
| 111. Foreign matter | Visual |
| MINOR | |
| 201. Pitch diameter of external thread, max. | Gage |
| 202. Diameter of wrench holes | Gage |
| 203. Diameter of thread pilot | Gage |
| 204. Diameter of cavity, min. | Gage |
| 205. Diameter of head, max. | Gage |
| 206. Diameter of step rear of head | Gage |
| 207. Depth of wrench holes | Gage |



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:50Z
Check the source to verify that this is the current version before use.

4.3.2.1 (Cont'd)

| Defect | Method of Inspection |
|---|---|
| MINOR | |
| 208. Depth to base of cavity | Gage |
| 209. Total length | Gage |
| 210. Length of step rear of head | Gage |
| 211. Length of thread pilot | Gage |
| 212. Width of thread relief | Gage |
| 213. Location of wrench holes | Gage |
| 214. Radius or chamfer missing or incorrect | Visual |
| 215. Surface finish improper | Visual |

4.3.2.2 Gasket, Aluminum, Dwg. B8594082, covering a detail of Dwg. D10522704.

| | |
|---|---|
| CRITICAL | |
| None defined | |
| MAJOR | |
| 101. Diameter, outside, min. | Gage |
| 102. Diameter, inside, max. | Gage |
| 103. Metal defective | Visual |
| 104. Burr | Visual |
| 105. Foreign matter | Visual |
| MINOR | |
| 201. Diameter, outside, max. | Gage |
| 202. Diameter, inside, min. | Gage |
| 203. Thickness | Gage |
| 204. Surface finish improper | Visual |

4.3.2.3 Retaining Cup, Dwg. B8597232, covering a detail of Dwg. D10522704.

| | |
|---|---|
| CRITICAL | |
| 1. Metal defective | Visual |



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:50Z
Check the source to verify that this is the current version before use.

4.3.2.3 (Cont'd)

| Defect | Method of Inspection |
|---|---|
| **MAJOR** | |
| 101. Concentricity of large cavity with small cavity | Gage |
| 102. Concentricity of body with small cavity | Gage |
| 103. Diameter of large cavity, max. | Gage |
| 104. Diameter of small cavity, max. | Gage |
| 105. Diameter of body, min. | Gage |
| 106. Depth of large cavity | Gage |
| 107. Surface finish of small cavity and body, improper | Visual |
| 108. Burr or sharp corner | Visual |
| 109. Foreign matter | Visual |
| **MINOR** | |
| 201. Diameter of large cavity, min. | Gage |
| 202. Diameter of small cavity, min. | Gage |
| 203. Diameter of body, max. | Gage |
| 204. Total length | Gage |
| 205. Surface finish improper, except as otherwise classified | Visual |

4.3.2.4 Firing Plug, Dwg. B8597234, covering a detail of Dwg. D10522704.

| | |
|---|---|
| **CRITICAL** | |
| 1. Metal defective | Visual |
| **MAJOR** | |
| 101. Concentricity of flange with body | Gage |
| 102. Diameter of flange, min. | Gage |
| 103. Diameter of body, min. | Gage |
| 104. Height of boss, max. | Gage |
| 105. Surface finish of body improper | Visual |
| 106. Burr | Visual |
| 107. Foreign matter | Visual |
| **MINOR** | |
| 201. Diameter of flange, max. | Gage |
| 202. Diameter of body, max. | Gage |
| 203. Total length | Gage |
| 204. Length of body | Gage |



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:50Z
Check the source to verify that this is the current version before use.

4.3.2.4 (Cont'd)

| Defect | Method of Inspection |
|---|---|
| MINOR | |
| 205. Radius missing or incorrect | Visual |
| 206. Surface finish improper, except as otherwise classified | Visual |

4.3.2.5 Primer, Percussion, M42-Dwg. B8799925, covering a detail of Dwg. D10522704.

| | |
|---|---|
| CRITICAL | |
| 1. Improper assembly | Visual |
| 2. Any part missing | Visual |
| 3. Primer pellet broken, cracked or dislodged | Visual |
| 4. Metal defective | Visual |
| 5. Primer foil discolored | Visual |
| 6. Mixed primers | Visual |
| MAJOR | |
| 101. Burr | Visual |
| 102. Foreign matter | Visual |
| MINOR | |
| None defined | |

4.3.2.6 Primer, Retainer, Dwg. C10520003, covering a detail of Dwg. D10522704.

| | |
|---|---|
| CRITICAL | |
| 1. Depth of head counterbore | Gage |
| 2. Depth of primer pocket | Gage |
| 3. Depth of cup pocket | Gage |
| 4. Metal defective | Visual |
| MAJOR | |
| 101. Pitch diameter of internal thread, max. | Gage |
| 102. Minor diameter of internal thread, max. | Gage |
| 103. Concentricity of flange with primer pocket | Gage |



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:50Z
Check the source to verify that this is the current version before use.

4.3.2.6 (Cont'd)

| Defect | | Method of Inspection |
|---|---|---|
| MAJOR | | |
| 104. | Concentricity of flash hole with primer pocket | Gage |
| 105. | Concentricity of large end with primer pocket | Gage |
| 106. | Concentricity of head counterbore with primer pocket | Gage |
| 107. | Concentricity of cup pocket with primer pocket | Gage |
| 108. | Concentricity of shoulder at small end with primer pocket | Gage |
| 109. | Concentricity of pitch diameter of thread with shoulder at small end | Gage |
| 110. | Symmetry of wrench flats with pitch diameter of thread | Gage |
| 111. | Diameter of shoulder, small end, min. | Gage |
| 112. | Diameter of primer pocket, min. | Gage |
| 113. | Diameter of cup pocket, min. | Gage |
| 114. | Diameter of head counterbore | Gage |
| 115. | Depth of primer pocket | Gage |
| 116. | Depth of cup pocket | Gage |
| 117. | Length of effective thread, min. | Gage |
| 118. | Location of flange | Gage |
| 119. | Location of datum diameter | Gage |
| 120. | Thread damaged or not full | Visual |
| 121. | Protective finish inadequate or defective | Visual |
| 122. | Surface finish of primer pocket improper | Visual |
| 123. | Burr or sharp corner | Visual |
| 124. | Foreign matter | Visual |
| MINOR | | |
| 201. | Pitch diameter of internal thread, min. | Gage |
| 202. | Diameter of shoulder, small end, max. | Gage |
| 203. | Diameter of primer pocket, max. | Gage |
| 204. | Diameter of cup pocket, max. | Gage |
| 205. | Diameter of head | Gage |
| 206. | Depth or wrench flats | Gage |
| 207. | Depth to bottom of threaded cavity | Gage |
| 208. | Length of wrench flats | Gage |
| 209. | Length across wrench flats | Gage |
| 210. | Total length | Gage |
| 211. | Location of wrench flats | Gage |
| 212. | Radius or chamfer missing or incorrect | Visual |
| 213. | Surface finish improper, except as otherwise classified | Visual |



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:50Z
Check the source to verify that this is the current version before use.

4.3.2.7 Assembly, Dwg. D10522704.

| Defect | Method of Inspection |
|---|---|
| CRITICAL | |
| 1. Improper assembly | X-ray 1/ and Visual |
| 2. Any part missing | X-ray 1/ and Visual |
| 3. Retainer cup not seated to full depth of surface "S" | Visual |
| 4. Firing plug not flush or below with retaining cup | Visual |
| 5. Primer not seated to full depth of primer pocket | Visual |
| 6. Marking missing, incorrect or illegible | Visual |
| MAJOR | |
| 101. Concentricity of flange with body | Gage |
| 102. Junction of delay body, gasket and primer retainer not properly sealed | Visual |
| 103. Junction of top edge of primer pocket and crimp not properly sealed for 360° | Visual |
| 104. Burr | Visual |
| 105. Foreign matter | Visual |
| MINOR | |
| 201. Diameter of body, max. | Gage |
| 202. Total length, max. | Gage |

1/ The delay element shall be x-rayed with the element in a position horizontal to the rays. The x-rays properly identified shall be forwarded to the Procuring activity.

4.3.2.8 Ammunition Container, Metal, M21, Dwg. C8864162.

CRITICAL

None defined

MAJOR

None defined



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:50Z
Check the source to verify that this is the current version before use.

4.3.2.8 (Cont'd)

| Defect | Method of Inspection |
|---|---|
| MINOR | |
| 201. Contents loose | Manual & Visual |
| 202. Quantity of contents incorrect | Visual |
| 203. Separator or filler missing | Visual |
| 204. Heat seal incomplete, loose or distorted | Visual |
| 205. Cut or damaged through impregnated box | Visual |
| 206. Marking missing, incorrect or illegible | Visual |

4.3.2.9 Box, Packing Ammunition for Delay Element, M5 or M8, Drawing C8826729.

CRITICAL

None defined

MAJOR

None defined

MINOR

| | |
|---|---|
| 201. Contents loose | Manual & Visual |
| 202. Hardware missing, loose, broken or improperly engaged | Visual |
| 203. Strapping missing, loose, broken or improperly assembled | Visual |
| 204. Contents of box exposed | Visual |
| 205. Box damaged | Visual |
| 206. Marking missing, incorrect or illegible | Visual |
| 207. Number of cartons incorrect | Visual |
| 208. Car seal missing, unsealed or improperly positioned | Visual |

4.3.3 Inspection testing.- The following tests shall be performed in accordance with the provisions of 4.4.

4.3.3.1 Protective finish.- Twenty three delay bodies and twenty three primer retainers shall be selected for protective finish tests. Failure of any component to comply with the requirements of 3.2 shall be cause for rejection of the lot.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:50Z
Check the source to verify that this is the current version before use.

4.3.3.2 Vibration.- Twelve of the 30 assembled, x-rayed delay elements of the initial production sample shall be subjected to vibration in accordance with 3.3. After vibration, the 12 vibrated delay elements shall be x-rayed as directed in 1/ of 4.3.2.7. Failure of any delay element to comply with the requirements of 3.3 shall be cause for rejection of the lot. When there is a change in the method of charging the delay element, 12 additional delay elements shall be selected and tested as indicated herein.

4.3.3.3 Functional.- The following tests shall be performed by the Government.

4.3.3.3.1 Ballistics.- Thirty test delay elements shall be grouped and temperature conditioned in accordance with 4.4.3.1.1 and Table VI. Failure of any delay element to comply with the requirements of 3.4.2 shall be cause for rejection of the lot.

Table VI

| Temperature | Sample Size |
|---|---|
| -65° to -70°F | 10 |
| 65° to 75°F | 10 |
| 160° to 165°F | 10 |

4.3.4 Inspection equipment.- The examination and tests shall be made using equipment listed on IEL 10522704.

4.4 Test methods and procedures.

4.4.1 Protective finish.- Test procedures for protective finish tests shall be in accordance with MIL-C-60539. The cartridge and primer retainer shall be sectioned longitudinally to better expose the critical surfaces to the salt spray.

4.4.2 Vibration.- The method and procedure for performing the vibration test shall be in accordance with MIL-E-5272, Procedure XII.

4.4.3 Functional.

4.4.3.1 Ballistics.- Delay elements of the sample shall be grouped and temperature conditioned in accordance with 4.4.3.1.1 and rigidly supported in the test fixture. The sample shall be tested within 5 minutes after removal from the conditioning chamber. When this time limit is exceeded the sample shall be reconditioned in accordance with 4.4.3.1.1.



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:50Z
Check the source to verify that this is the current version before use.

4.4.3.1.1 Temperature conditioning.- A standard inert delay element containing a temperature sensitive device shall be placed in the conditioning chamber at the same time as the sample. The conditioning time shall be a minimum of one (1) hour longer than the time necessary to bring the device contained in the inert delay element to the required temperature. The vent holes of the delay elements shall be sealed against the environmental atmosphere of the conditioning chamber during the conditioning period. Upon completion of temperature conditioning, the vent hole seal shall be removed.

## 5. PREPARATION FOR DELIVERY

5.1 Packing and marking.- Packang and marking shall be in accordance with Dwgs. C8826729 and C8864162, except that the markings shall refer to Delay Element XM43, Assembly.

5.2 Data card.- Data card information shall be in accordance with MIL-STD-1167.

## 6. NOTES

6.1 Ordering data.- Procurement documents should specify the title, number and date of this specification.

6.2 Advisory output material (formation).- Approximately 23.7 percent Boron, 70.7 percent potassium nitrate and 5.6 percent binder. Advisory individual delay element output material weight - approximately 1.5 grains.

6.3 Advisory delay charge composition, (formulation) Approximately 90 percent barium chromate and 10 percent boron. Advisory individual delay element charge weight: approximately 17 grains.

6.4 Delay time is defined as the time lapse between the impact of the firing pin on the primer and evidence of gas flow from the vent hole of the delay element.

6.5 Supersession data.- This specification includes the requirements of Purchase Description FA-PD-MI-2568, Rev. 0 dated 5 September 1962.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1377-A289



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:50Z
Check the source to verify that this is the current version before use.

# SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:50Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
Department of the Army

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-N1100
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:50Z
Check the source to verify that this is the current version before use.