MIL-D-14826(MU)
30 December 1970
SUPERSEDING
FA-PD-M1-2421, Rev. 0
1 November 1960

MILITARY SPECIFICATION
DELAY ELEMENT, CARTRIDGE: M24 ASSEMBLY

1. SCOPE

1.1 This specification covers Delay Element, Cartridge: M24, Assembly, for use in cartridges for propellant actuated devices in aircrew emergency escape systems.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-A-2550	- Ammunition and Special Weapons, General Specification for
MIL-E-5272	- Environmental Testing, Aeronautical and Associated Equipment, General Specification for
MIL-C-13739	- Composition, Delay
MIL-C-60539	- Coating, Anodic, Conventional for Aluminum and Aluminum Alloys

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions

DRAWINGS

Munitions Command

D10519999	- Delay Element, Cartridge: M24 Assembly

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

DRAWINGS (Cont'd)

C8826729	- Box, Packing, Ammunition for Delay Element.
C8864162	- Ammunition, Container, Metal, M21 for M24, Delay Element
IEL 10519999	- Inspection Equipment List for Delay Element, Cartridge, M24, Assembly

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

2.2 Other publications - The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bid or request for proposal shall apply.

ASA B46.1 - Surface Texture

(Application for copies should be addressed to the American Standards Association, 10 East 40th Street, New York, N.Y. 10016)

3. REQUIREMENTS

3.1 General - Materials, parts and assemblies shall conform to the applicable drawings and referenced specifications.

3.2 Protective finish - Protective finish shall be in accordance with MIL-C-60539.

3.3 Vibration - The delay element assembly shall withstand vibrations as prescribed in MIL-E-5272, Procedure XII, without evidence of any disintegration of the primer or delay charge or derangement of components.

3.4 Functional

3.4.1 The delay element shall not fail to fire.

3.4.2 Delay charge - The delay charge shall comprise increments of type I and type II shown in MIL-C-13739, in the proportion and quantity fixed by the contractor to produce the delay time required in table I (see 6-2)

Source: https://assist.dla.mil -- Downloaded: 202610-18T04:51Z
Check the source to verify that this is the current version before use.

Table I

Temperature	Delay Time (seconds) (see 6.3)
-65° to -70°	2.40 max.
65° to 75°	1.80 min. to 2.20 max.
160° to 165°F	1.60 min.

3.5 Workmanship - Workmanship shall be in accordance with the requirements of the applicable drawings, referenced specifications and the following:

3.5.1 Metal defects - The metal parts shall be free from cracks, splits, cold shuts, inclusions, porosity or other metal defects.

3.5.2 Burr - The part shall not have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.5.3 Foreign matter - The part or assembly shall not contain chips, dirt, grease, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions - Reference shall be made to MIL-STD-109 to define quality assurance terms used.

4.1.2 Inspection - Inspection shall be in accordance with MIL-A-2550.

4.2 First article sample

4.2.1 Initial production sample - At the beginning of regular production, a sample shall be submitted in accordance with contract requirements and shall consist of 23 delay bodies and 23 primer retainers for protective finish tests and 30 delay element assemblies for ballistic tests as indicated in Table II and 10 sets of unassembled components (including explosive components) for visual and dimensional examination.

Source: https://assist.dla.mil -- Downloaded: 202640-18T04:51Z
Check the source to verify that this is the current version before use.

Table II

Paragraphs Requirements	Test	Test	Sample	Type of Test Destr.	Non-Destr.
3.2	4.4.1	Protective finish	23 Delay bodies	X	--
			23 Primer Retainers	X	--
3.3	4.4.2	Vibration	12 (from ballistics sample)	--	X
3.4.2	4.4.3.1	Ballistics	30 Delay elements	X	--

The sample shall be manufactured, using the same materials, equipment, processes and procedures as used in regular production. All parts and materials, including packaging and packing shall be the same as used for regular production and shall be obtained from the same source of supply.

4.2.1.1 Examination and tests - After examination and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility specified in the contract.

4.2.1.2 Ballistics - The sample for ballistic tests shall be temperature conditioned and tested to determine compliance with Table I. The sample for firing shall consist of the following:

Table III

Temperature	Vibrated	Not Vibrated
-65° to -70°F	4	6
65° to 75°F	4	6
160° to 165°F	4	6

4.2.1.3 Initial production sample failure - Failure of the sample to comply with the requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection provisions

4.3.1 Lot

4.3.1.1 Submission of product - The product shall be submitted in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 202610-18T04:51Z
Check the source to verify that this is the currentversion before use.

4.3.1.2 Size of lot - A lot shall consist of an identifiable group of metal parts assemblies produced by a homogeneous process and loaded with accepted delay charges.

4.3.2 Examination - One hundred percent examination shall be performed for all critical defects. Examination for major or minor defects shall be performed on a defect basis in accordance with the classification of defects, using the sampling plan and associated criteria in Tables IV and V. For an individual defect (single characteristic) the criteria in Table IV shall be used. For total defects within a major or minor class, the criteria in Table V shall be used. All non-conforming material shall be rejected. Four power (4X) magnification may be used to perform visual examination for such defects as burr and foreign matter. The roughness comparison specimens prescribed by ASA-B46.1 shall be used as a basis of comparison for surface roughness determination.

Table IV

Lot Size	Sample Size	Major		Minor	
		Accept	Reject	Accept	Reject
1 - 300	100% Examination	-	-	-	-
301 - 1300	110	1	2	2	3
1301 - 3200	150	2	3	3	4
3201 - 8000	225	3	4	4	5
8001 - 22000	300	4	5	5	6

Table V

Sample Sizes for Major Defects Number of defects in class	Total allowable defects per sample size			
	110	150	225	300
2 - 3	1	2	3	4
4 - 7	2	3	4	5
8 - 19	3	4	5	7
20 - 43	4	5	8	10
Over 43	6	8	11	14

Source: https://assist.dla.mil -- Downloaded: 20261O-18T04:51Z
Check the source to verify that this is the current version before use.

Table V (Cont'd)

Sample Sizes for Minor Defects Number of defects in class	Total allowable defects per sample size 110	150	225	300
2 - 3	2	3	4	5
4 - 7	3	4	5	7
8 - 16	4	5	8	10
17 - 48	6	8	11	14
Over 48	8	11	17	20

4.3.2.1 Body, Delay, Dwg. C8594081, covering a detail of Dwg. D10519999

Defect	Method of Inspection
CRITICAL	
1. Diameter of flash hole	Gage
2. Metal defective	Visual
MAJOR	
101. Pitch diameter of thread, min	Gage
102. Major diameter of thread, min	Gage
103. Concentricity of body with pitch dia of thread	Gage
104. Diameter of thread relief	Gage
105. Diameter of step at thread relief	Gage
106. Diameter of cavity, max	Gage
107. Diameter of body, min	Gage
108. Depth of cavity, max	Gage
109. Length from cavity face to body diameter	Gage
110. Thread damaged or not full	Visual
111. Protective finish inadequate or defective	Visual
112. Burr	Visual
113. Foreign matter	Visual
MINOR	
201. Pitch diameter of thread, max	Gage
202. Diameter of cavity, min	Gage
203. Diameter of body, max	Gage
204. Diameter of wrench holes	Gage
205. Diameter of thread pilot	Gage
206. Depth of cavity, min	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

4.3.2.1 Body, Delay, Dwg. C8594081, covering a detail of Dwg. D10519999-Cont'd

Defect	Method of Inspection
MINOR	
207. Depth of wrench holes	Gage
208. Total length	Gage
209. Length of thread pilot	Gage
210. Length of thread relief	Gage
211. Length of step at thread relief	Gage
212. Location of wrench holes	Gage
213. Radius or chamfer missing or incorrect	Visual
214. Surface finish improper	Visual

4.3.2.2 Gasket, Aluminum, Dwg. B8594082 covering a detail of Dwg. D10519999

CRITICAL	
None defined	
MAJOR	
101. Diameter outside, min.	Gage
102. Diameter inside, max.	Gage
103. Metal defective	Visual
104. Burr	Visual
105. Foreign matter	Visual
MINOR	
201. Diameter outside, max.	Gage
202. Diameter inside, min.	Gage
203. Thickness	Gage
204. Surface finish improper	Visual

4.3.2.3 Cup, Retaining, Dwg B8597232, covering a detail of Dwg D10519999

CRITICAL	
1. Metal defective	Visual
MAJOR	
101. Concentricity of counterbore with small hole	Gage
102. Concentricity of body with small hole	Gage
103. Diameter of counterbore, max	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

4.3.2.3 Cup, Retaining, Dwg B8597232, covering a detail of Dwg D10519999-Cont'd

Defect	Method of Inspection
MAJOR	
104. Diameter of small hole, max	Gage
105. Diameter of body, min	Gage
106. Depth of counterbore	Gage
107. Surface finish of small hole and body improper	Visual
108. Burr or sharp corner	Visual
109. Foreign matter	Visual
MINOR	
201. Diameter of counterbore, min	Gage
202. Diameter of small hole, min	Gage
203. Diameter of body, max	Gage
204. Total length	Gage
205. Surface finish improper except as otherwise classified	Visual

4.3.2.4 Firing Plug, Dwg B8597234, covering a detail of Dwg D10519999

CRITICAL	
1. Metal defective	Visual
MAJOR	
101. Concentricity of flange with body	Gage
102. Diameter of flange min	Gage
103. Diameter of body, min	Gage
104. Radius of striker incorrect	Gage
105. Length of striker	Gage
106. Surface finish on body improper	Visual
107. Burr or sharp corner	Visual
108. Foreign matter	Visual
MINOR	
201. Diameter of flange, max	Gage
202. Diameter of body, max	Gage
203. Total length	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

4.3.2.4 Firing Plug, Dwg B8597234, covering a detail of Dwg D10519999 - Cont'd

	Defect	Method of Inspection
MINOR		
204.	Length of body	Gage
205.	Radius missing or incorrect except as otherwise classified	Visual
206.	Surface finish improper except as otherwise classified	Visual

4.3.2.5 Primer, M42, Dwg. B8799925 covering a detail of Dwg. D10519999

CRITICAL		
1.	Improper assembly	Visual
2.	Any part missing	Visual
3.	Primer pellet broken, cracked or dislodged	Visual
4.	Metal defective	Visual
5.	Primer foil discolored	Visual
6.	Mixed primers	Visual
MAJOR		
101.	Burr	Visual
102.	Foreign matter	Visual
MINOR		
	None defined	

4.3.2.6 Primer Retainer, Dwg. C10520003, covering a detail of Dwg. D10519999

CRITICAL		
1.	Depth of large counterbore	Gage
2.	Depth of primer pocket	Gage
3.	Depth of small counterbore	Gage
4.	Metal defects	Visual
MAJOR		
101.	Pitch diameter of thread, max	Gage
102.	Minor diameter of thread, max	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

4.3.2.6 (Cont'd)

	Defect	Method of Inspection
MAJOR		
103.	Concentricity of flange with primer pocket	Gage
104.	Concentricity of flash hole with primer pocket	Gage
105.	Concentricity of large diameter with primer pocket	Gage
106.	Concentricity of large counterbore with primer pocket	Gage
107.	Concentricity of small counterbore with primer pocket	Gage
108.	Concentricity of body with primer pocket	Gage
109.	Concentricity of pitch diameter of thread with body	Gage
110.	Symmetry of wrench flats with pitch diameter of thread	Gage
111.	Diameter of body, min	Gage
112.	Diameter of primer pocket, min	Gage
113.	Diameter of small counterbore, min	Gage
114.	Diameter of large counterbore	Gage
115.	Depth of primer pocket	Gage
116.	Depth of small counterbore	Gage
117.	Length of effective thread, min	Gage
118.	Location of flange	Gage
119.	Location of datum diameter	Gage
120.	Thread damaged or not full	Visual
121.	Protective finish inadequate or defective	Visual
122.	Surface finish of primer pocket improper	Visual
123.	Burr or sharp corner	Visual
124.	Foreign matter	Visual
MINOR		
201.	Pitch diameter of thread, min	Gage
202.	Diameter of body, max	Gage
203.	Diameter of primer pocket, max	Gage
204.	Diameter of small counterbore, max	Gage
205.	Diameter of flange	Gage
206.	Depth of wrench flats	Gage
207.	Depth to bottom of threaded cavity	Gage
208.	Length of wrench flats	Gage
209.	Length across wrench flats	Gage
210.	Total length	Gage
211.	Location of wrench flats	Gage
212.	Radius or chamfer missing or incorrect	Visual
213.	Surface finish improper, except as otherwise classified	Visual

Source: https://assist.dla.mil -- Downloaded: 202610-18T04:51Z
Check the source to verify that this is the currentversion before use.

4.3.2.7 Delay Element, Cartridge, M24 Assembly, Dwg. D10519999

	Defect	Method of Inspection
CRITICAL		
1.	Primer not seated full depth primer pocket	X-ray[1]/ & Visual
2.	Firing plug not flush or below flush with retaining cup	X-ray[1]/ & Visual
3.	Retaining cup not flush or below with surface "s"	X-ray[1]/ & Visual
4.	Any part missing	X-ray[1]/ & Visual
5.	Improper assembly	X-ray[1]/ & Visual
6.	Marking missing, incorrect, or illegible	Visual
MAJOR		
101.	Concentricity of flange with body	Gage
102.	Seal between delay body, gasket and primer retainer incorrect	Visual
103.	Seal at junction of top edge of primer, primer pocket and crimp not complete for 360°	Visual
104.	Burr	Visual
105.	Foreign matter	Visual
MINOR		
201.	Diameter of body, max	Gage
202.	Total length, max	Gage

1/ The delay element shall be x-rayed with the element in a position horizontal to the rays. The x-ray properly identified shall be forwarded to the procuring activity.

4.3.2.8 Ammunition Container, Metal, M21 Dwg. C8864162

CRITICAL

None defined

MAJOR

None defined

MINOR

201.	Contents loose	Manual & Visual
202.	Quantity of contents incorrect	Visual

Source: https://assist.dla.mil -- Downloaded: 202610-18T04:51Z
Check the source to verify that this is the currentversion before use.

4.3.2.8 - Cont'd

Defect	Method of Inspection
MINOR	
203. Separator or filler missing	Visual
204. Heat seal incomplete, loose or distorted	Visual
205. Cut or damaged through impregnated box	Visual
206. Marking missing, incorrect or illegible	Visual

4.3.2.9 Box, Packing Ammunition for Delay Element M5 or M8, Dwg. C8826729

CRITICAL

None defined

MAJOR

None defined

MINOR

201. Contents loose	Manual & Visual
202. Hardware missing, loose, broken or improperly engaged	Visual
203. Strapping missing, loose, broken or improperly assembled	Visual
204. Contents of box exposed	Visual
205. Box damaged	Visual
206. Marking missing, incorrect or illegible	Visual
207. Number of cartons incorrect	Visual
208. Car seal missing, unsealed or improperly positioned	Visual

4.3.3 Inspection testing - The following tests shall be performed in accordance with the provisions of 4.4.

4.3.3.1 Protective finish - Twenty-three delay bodies and 23 primer retainers shall be selected for protective finish tests. Failure of any component to comply with the requirements of 3.2 shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

4.3.3.2 Vibration - Twelve of the 30 assembled x-rayed delay elements of the initial production sample shall be subjected to vibration in accordance with 3.3. After vibration, the 12 vibrated delay elements shall be x-rayed as directed in 1/ 4.3.2.7. Failure of any delay element to comply with the requirements of 3.3 shall be cause for rejection of the lot. When there is a change in the method of charging the delay element, 12 additional delay elements shall be selected and tested as indicated herein.

4.3.3.3 Functional

4.3.3.3.1 Ballistics - Thirty test delay elements shall be grouped and temperature conditioned in accordance with 4.4.3.1 and Table VI. Failure of any delay element to comply with the requirements of 3.4.2 shall be cause for rejection of the lot.

Table VI

Temperature	Sample Size
-65° to -70°F	10
65° to 75°F	10
160° to 165°F	10

4.3.4 Inspection equipment - The examination and tests shall be made using equipment listed on IEL 10519999.

4.4 Test methods and procedures

4.4.1 Protective finish - Test procedures for protective finish tests shall be in accordance with MIL-C-60539. The delay body and primer retainer shall be sectioned longitudinally to better expose the critical surfaces to the salt spray.

4.4.2 Vibration - The method and procedure for performing the vibration test shall be in accordance with MIL-E-5272, Procedure XII.

4.4.3 Functional

4.4.3.1 Ballistics - Delay elements of the sample shall be grouped and temperature conditioned in accordance with 4.4.3.1.1 and rigidly supported in the test fixture. The sample shall be tested within 5 minutes after removal from the conditioning chamber. When this time limit is exceeded, the sample shall be reconditioned in accordance with 4.4.3.1.1.

Source: https://assist.dla.mil -- Downloaded: 20261O-18T04:51Z
Check the source to verify that this is the current version before use.

4.4.3.1.1 Temperature conditioning - A standard inert delay element containing a temperature sensitive device shall be placed in the conditioning chamber at the same time as the sample. The conditioning time shall be a minimum of one (1) hour longer than the time necessary to bring the device contained in the inert delay element to the required temperature. The vent holes in the delay elements shall be sealed against the environmental atmosphere of the conditioning chamber during the conditioning period. Upon completion of the temperature conditioning, the vent seal shall be removed.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking - Packing and marking shall be in accordance with Dwgs. C8826729 and C8864162, except that the marking shall refer to Delay Element, Cartridge, M24 Assembly.

6. NOTES

6.1 Ordering data - Procurement documents should specify the title, number and date of this specification.

6.2 Advisory delay charge composition (formulation) - Consists of three increments of charge as follows: Approximately 5 grains, Type I, 10 grains Type II and 5 grains Type I, charged in that order.

6.3 Delay time is defined as the time lapse between the impact of the firing pin on the primer and evidence of gas flow from the vent hole of the delay element.

6.4 Supersession data - This specification includes the requirements of Purchase Description FA-PD-MI-2421, Rev. 0 dated 1 November 1960.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1377-A293

☆ U. S. GOVERNMENT PRINTING OFFICE: 1971-714-156/715

Source: https://assist.dla.mil -- Downloaded: 202610-18T04:51Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
Department of the Army

OFFICIAL BUSINESS

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-T1000
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

[ ] YES [ ] NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 68 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202610-18T04:51Z
Check the source to verify that this is the current version before use.