MILITARY SPECIFICATION

DELAY ELEMENT, CARTRIDGE: M60 ASSEMBLY

This amendment forms a part of Military Specification MIL-D-14842(MU), dated 25 September 1973, and is approved for use within the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1 Delete: "MIL-E-5272 . . ." and "MIL-P-46994 . . ." in their entirety.
Add: "MIL-STD-810 Environmental Test Methods and Engineering Guidelines"

PAGE 2

2.2 Delete "ASA B46.1 - Surface Texture" and
substitute "ANSI B46.1 Surface Texture (Surface Roughness, Waviness and Lay)"

3.3 Delete "as prescribed in MIL-E-5272, Procedures XII . . ."and substitute "as prescribed in MIL-STD-810, Method 514.3, Test Procedure I, Test Condition I-3.2.5 . . .".

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Ordnance Station, Standardization Branch (5241), Indian Head, MD 20640-5000.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:54Z
Check the source to verify that this is the current version before use.

PAGE 5

4.4.2, last sentence, change "ASA-B46.1" to "ANSI-B46.1".

Preparing Activity:
Navy - OS
Project No. 1377-N829

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:54Z
Check the source to verify that this is the current version before use.