MILITARY SPECIFICATION

HEAD ASSEMBLY: 8619900

This amendment forms a part of Military Specification MIL-H-14844B(MU) dated 31 December 1971 and is approved for use by all Departments and Agencies of the Department of Defense.

Paragraph 1.1.- Delete and substitute:

"1.1 This specification covers a modular unit of the Tank Commander's M34, M36 and M36E1 Periscope, herein referred to as "head assembly".

Paragraph 2.1.- Drawings, U.S. Army Frankford Arsenal

Delete "F8575658" together with its title.

Paragraph 3.7.1.2.2.- Delete "3.7.1.2.2 Torque.-" and substitute "3.7.1.2.2 Operability.-"

TABLE - I, Characteristic 111: Delete "Torque" and substitute"Operability"

TABLE - III, Characteristic 304: Delete "Torque, elevation input shaft" and substitute "Operability, elevation input shaft"

Paragraph 4.6.1: Delete and substitute:

"4.6.1 Storage temperature.- This test shall be performed on head assemblies procured as a repair part item. When the head assembly is provided with a complete periscope this temperature test will not be required when the complete periscope is subjected to temperature cycling. The testing equipment utilized in this test shall be in accordance with the "Test Facilities" requirements of MIL-F-13926 and the conditions of 3.4.1. The head assembly shall be placed in the test chamber and the temperature of the chamber reduced gradually (see NOTE below) to -80°F. The head assembly shall remain at this temperature for a minimum of five hours. At the completion of this five hour period, the temperature of the test chamber shall be gradually raised (see NOTE below) to +160°F. The head assembly shall remain at this temperature for a minimum of five hours. At the completion of this five hour period, the temperature of the test chamber shall be gradually reduced to room ambient temperature (+60° to +90°F), and the head assembly shall then be subjected to the visual, tactile and audible examination of 4.6.3. The head assembly shall conform to the requirements of 3.4.1.

NOTE: The rate of temperature change in the test chamber shall not exceed 20 degrees per hour throughout the temperature cycling tests of 4.6.1 and 4.6.2."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:54Z
Check the source to verify that this is the current version before use.

Paragraph 4.6.2: Delete and substitute:

"4.6.2 Operating temperatures.- This test shall be performed on head assemblies procured as a repair part item. When the head assembly is provided with a complete periscope this temperature test will not be required when the complete periscope is subjected to temperature cycling. The testing equipment utilized in this test shall be in accordance with the "Test Facilities" requirements of MIL-F-13926 and the conditions of 3.4.2. The head assembly shall be placed in the test chamber and the temperature of the chamber reduced gradually (see NOTE in 4.6.1) to -40°F. The head assembly shall remain at this temperature for a minimum of five hours. At the completion of this five hour period, and while at -40°F, the head assembly shall be subjected to the tests in 4.6.9 to determine compliance with the applicable requirements of 3.7.1.2.2 for this temperature (-40°F). Upon completion of this test, the temperature of the test chamber shall be gradually raised (see NOTE in 4.6.1) to +150°F. The head assembly shall remain at this temperature for a period of five hours. At the completion of this five hour period and while at +150°F, the head assembly shall again be subjected to the test in 4.6.9 to determine compliance with the applicable requirements of 3.7.1.2.2 for this temperature (+150°F). Upon completion of this test, the temperature of the test chamber shall be gradually reduced (see NOTE in 4.6.1) to room ambient temperature (+60° to +90°F) and the head assembly removed from the test chamber. Head assemblies which have passed the above tests shall be subjected to the test in 4.6.2.1."

Paragraph 4.6.3, 5th sentence: Delete and substitute:

"The head assembly shall be clamped on the vibrating equipment in its normal mounting or operating position (as depicted in the front view on Sheet 1 of Drawing F8619900) by means of an appropriate adapter having the same interface features as Mount Periscope: M119."

Paragraph 4.6.9: Delete "4.6.9 Torque, elevation input shaft.-" and substitute "4.6.9 Operability, elevation input shaft.-"

Paragraph 6.1: Delete and substitute:

"6.1 Intended use.- The Head Assembly, 8619900 is a modular unit of the Tank Commander's Periscopes: M34, M36 and M36E1, primarily used in the fire control system of the 105MM Gun Tank M60 Series."

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240 - A669

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:54Z
Check the source to verify that this is the current version before use.