MIL-P-14827A(MU)
6 July 1973
SUPERSEDING
MIL-P-14827(MU)
20 January 1969

MILITARY SPECIFICATION
PROJECTILE, 57MM: HE, M306A1, METAL PARTS ASSEMBLY

1. SCOPE

1.1 This specification covers Projectile, 57MM, HE, M306A1, Metal Parts Assembly.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification in the extent specified herein.

SPECIFICATION

Military

MIL-A-2550	- Ammunition and Special Weapons, General Specification For
MIL-I-6868	- Inspection Processes Magnetic Particle

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-410	- Qualification of Inspection Personnel (Magnetic Particle and Penetrant)
MIL-STD-1167	- Ammunition Data Card
MIL-STD-1168	- Lot Numbering of Ammunition

FSC 1310

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

2.1 (Cont'd)

MIL-STD-1169	- Packaging, Packing, and Marking for Shipment of Inert Ammunition Components
MIL-STD-1235	- Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

Munitions Command

D10535913	- Projectile, 57MM, H.E., M306A1, Metal Parts Assembly
IEL-10535913	- Inspection Equipment List for Projectile, 57MM, HE., M306A1, Metal Parts Assembly
F7548913	- Box, Fiberboard Ammunition

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

ASA-B46.1 - Surface Texture

(Application for copies should be addressed to the American National Standards Institute (ANSI), 1430 Broadway, New York, N.Y. 10018).

USAS Y32.3-1969 - Welding Symbols

(Application for copies should be addressed to the American Standards Institute, (ANSI), 1430 Broadway, New York, N.Y. 10018).

ASTM Method - American Society for Testing and Materials

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103).

3. REQUIREMENTS

3.1 General.-Materials, parts and assemblies shall comply with requirements specified on the applicable drawings, referenced specifications and the following:

3.2 Mechanical properties.-All components shall meet the mechanical properties requirements as specified on the applicable drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

3.2.1 Heat Treatment or Stress Relief.-Heat treatment or stress relief applied to any component part shall be uniform throughout and shall be so conducted as to produce the mechanical properties specified on the applicable drawing.

3.3 Metal Defects.

3.3.1 Body.-The body cavity shall be free of scale, fins, burrs, draw marks, laminations, imbedded foreign matter, pits and sharp edges.

3.3.2 Body cavity.-The body cavity shall be free of scale, fins, burrs, draw marks, laminations, imbedded foreign matter, pits and sharp edges.

3.3.3 Visual standards.-Visual standards for evaluation of metal defects will be established for each contract after the first months production. However, the establishment of visual standards will not waive the requirement for compliance, with 3.3.1 and 3.3.2. (see 6.2).

3.4 Protective coating.-Requirements relating to paint thickness are not specified, except as a guide for performance of the tests as indicated by the applicable drawing and specifications, Actual body assemblies must withstand the specified salt spray exposure with coating breakdown no greater than that described by the applicable specification.

3.5 Proving Ground functional tests.-The projectile assembly shall reveal no evidence of failure when tested at excess and service pressure. Metal parts failure shall be:

a. Permanent deformation greater than .010 inches on either body or bourrelet diameter.

b. Breakup or loss of metal parts components in flight or in the gun tube.

c. Complete shear of rotating band.

3.6 Workmanship.-The requirements for workmanship are as shown on the applicable drawings in the applicable specifications and the following:

3.6.1 Surface finish.-The requirements for workmanship are as shown on the applicable drawing.

3.6.2 Threads.-Threads shall be full and undamaged for the entire minimum length as required by the applicable drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

3.6.3 Burr.-No part shall have a burr which might interfere with the assembly or function of the round or which might be injurious to personnel handling the item.

3.6.4 Foreign matter.-No part or assembly shall contain dirt, grease, chips, rust, corrosion, or other foreign matter. Particular attention shall be given to the cavity of the body assembly, to insure that no grit, scale, or other foreign matter remains therein after final cleaning.

3.6.5 Base cover weld.-The weld shall be sound and the welding operation shall be so controlled that there will be adequate fusion between projectile body and base cover.

3.6.6 Rotating band.-After machining of the rotating band, care should be taken to protect it from being nicked, burred or otherwise damaged during subsequent handling and preparation for shipment.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- nless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.-Reference shall be made to MIL-STD-109 to define quality assurance terms used.

4.1.2 Inspection.-Inspection shall be in accordance with MIL-A-2550, except as specified herein.

4.1.3 Inspection criteria.

a. Successful passage of all inspections required by the drawings and specifications shall be considered as a condition precedent to performing the Proving Ground functional tests (see 3.5).

b. Acceptance or rejection of a lot by the Government shall be contingent on successful passage of the Proving Ground functional tests.

4.2 First article sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

4.2.1 Initial production sample.-At the beginning of regular production a sample shall be submitted in accordance with contract requirements and shall consist of 70 metal parts assemblies as follows:

55 projectile assemblies complete, painted
5 projectile assemblies complete, unpainted
10 sets of component parts, unassembled

Fifty of the above painted projectile assemblies shall be forwarded to a designated proving ground for ballistic testing. The sample shall be manufactured using the same materials, equipment, processes and procedures as used in regular production. All parts and material, including packaging and packing, shall be the same as used for the regular production and shall be obtained from the same source of supply. A first article sample or portion thereof as directed by the procuring agency shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacture processes, material used, drawing, specifications or source of supply, such as to significally affect product uniformity as determined by the responsible technical agency.

4.2.1.1 Examination and test.-After inspection and provisional acceptance at source, this shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility specified in the contract.

4.2.1.2 Initial production Sample Failure.-Failure of the sample to comply with the requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection Provisions.

4.3.1 Lot.

4.3.1.1 Submission of Product.- The product shall be submitted in accordance with MIL-STD-105.

4.3.1.2 Heat treatment lots.-Heat treatment lots shall contain heat treated bodies from not more than one heat of steel that have been heat treated in the same heat treating equipment at the same temperature in one unchanged process. The heat treated lot thus constituted shall form the basis for selecting sample bodies for the tension hereinafter prescribed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

4.3.1.3 Stress relief lots.-Stress relief lots shall contain cold worked bodies from not more than one heat of steel that have been cold worked by the same process utilizing the same tooling and equipment and stress relieved in the name furnace at the same temperature for the same length of time. The stress relief lot thus constituted shall be the basis for the selection of samples for the tension test hereinafter prescribed.

4.3.1.4 Bar stock lot.-Bodies machined from bar stock shall contain material from not more than one heat of steel and produced in one unchanged process. Wherever heat treatment is applicable, the heat treatment shall be performed in the same heat treating equipment at the same temperature in one unchanged process. The machining lot thus constituted shall be the basis for the selection of samples for the tension hereinafter prescribed.

4.3.1.5 Miscellaneous lots.-Small lots (such as bodies manufactured from abnormally small heats of steel or bodies that have become separated from previously delivered lots, etc.) may at the descretion of the supplier be grouped into miscellaneous heat treatment, stress relieved or machining lots as the case may be. Such lots shall be identified by a miscellaneous lot code number and processed in accordance with either 4.3.1.2, 4.3.1.3 or 4.3.1.4, as applicable. The miscellaneous lot thus constituted shall be the basis for the selection of samples for the tension test hereinafter prescribed.

4.3.1.6 Projectile lots.-All heat treatment or stress relief lots that have been determined to have complied with the mechanical properties requirements of the applicable component drawing, may be re-grouped for assembly into projectile lots. A projectile lot shall consist of projectile assemblies produced by one manufacturer, under one contract, in one unchanged process in accordance with the same drawing, same drawing revision, same specification and same specification revision.

4.3.2 Examination.-One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plans contained in MIL-STD-105. Continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the procuring activity. An AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect shall be used. All nonconforming material shall be rejected. Four power (4X) magnification may be used in performing visual examination. The roughness comparison specimens prescribed by ASA-B46.1 shall be used as a basis of comparison for surface roughness determination.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

4.3.2.1 Tool control dimensions.-Dimensions marked tool control shall be gaged during First Article testing and after each 250 items produced on each machine in operation,
Where destruction of components is necessary to inspect these dimensions, measurements of the tool may be substituted provided the contractor has established correlation between the tool dimensions and the component dimensions prior to the start of production. The contractor shall be responsible for maintaining adequate surveillance to assure that drawing requirements are being met throughout the life of the tool. Corrective action will be immediately instituted by the contractor.

4.3.2.2 Body, Drawing F10535914, covering a detail of Drawing D10535913.

Defect	Method of Inspection
CRITICAL	
1. Metal defective	Visual (Probe light)
MAJOR	
101. Thickness through base	Gage
102. Wall thickness	Gage
MINOR	
201. Length, total	Gage
202. Presence and location of identations rear of body (if applicable)	Visual (See 6.2)
203. Radii or chamfers missing or incorrect	Visual (See 6.2)
204. Surface finish improper	Visual (See 6.2)
205. Burr	Visual
206. Foreign matter	Visual

4.3.2.3 Metal Parts Assembly, Drawing D10535913 (before paint).

CRITICAL	
1. Metal defective (after phosphating)	Visual (Probe light)
MAJOR	
101. Runout of pitch diameter of threads with bourrelets, including front face	Gage
102. Runout of nose with bourrelets	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

4.3.2.3 (Cont'd)

Defect		Method of Inspection
MAJOR (Cont'd)		
103.	Runout of body with bourrelets	Gage
104.	Runout at rear with bourrelets	Gage
105.	Runout of inside taper with bourrelets	Gage
106.	Runout lands of rotating band with bourrelets	Gage
107.	True position of grooves with lands	Gage
108.	Diameter of bourrelets, min.	Gage
109.	Diameter of rotating bands	Gage
110.	Diameter of rotating band grooves	Gage
111.	Diameter of inside basic length	Gage
112.	Length from front face to forward outside basic diameter	Gage
113.	Length from front face to rear outside basic diameter	Gage
114.	Location of rotating band	Gage
115.	Length of rotating band	Gage
116.	Width of lands of rotating band	Gage
117.	Width of grooves of rotating band	Gage
118.	Angle rear of crimp relief groove	Gage
119.	Profile of radius rear of angle	Gage
120.	Foreign matter in cavity	Visual
MINOR		
201.	Diameter of body	Gage
202.	Diameter of rear	Gage
203.	Diameter of land undercut, min. (if applicable)	Gage
204.	Depth of crimp grooves	Gage
205.	Length from front face to rear of forward bourrelet	Gage
206.	Length from rear face to front of rear bourrelet	Gage
207.	Location of crimp groove rib	Gage
208.	Length from front face of rotating band to land undercut, min. (if applicable)	Gage
209.	Length, total max.	Gage
210.	Location of base cover, min.	Visual (see 6.2)
211.	Width of undercut front and rear of rotating band (if applicable)	Visual (see 6.2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

4.3.2.3 (Cont'd)

Defect	Method of Inspection
MINOR (Cont'd)	
212. Depth of undercut front and rear of rotating band (if applicable)	Visual (see 6.2)
213. Radii or chamfers missing or incorrect	Visual (see 6.2)
214. Surface finish improper	Visual (see 6.2)
215. Burr	Visual
216. Foreign matter (except as otherwise classified)	Visual

4.3.2.4 Metal Parts Assembly, Drawing D10535513 (after paint).

CRITICAL	
1. Metal defective	Visual (Probe light)
MAJOR	
101. Weight	Approved Scale
102. Pitch diameter of thread, max.	Gage
103. Pitch diameter of thread, min.	Gage
104. Minor diameter of thread, max.	Gage
105. Diameter of bourrelets, max.	Gage
106. Depth of thread cavity, max.	Gage
107. Length of effective thread, min.	Gage
108. Profile of rotating band, max. (functional)	Gage
109. Paint in cavity, inadequate or excessive	Visual
110. Foreign matter in cavity	Visual
MINOR	
201. Diameter of thread chamfer	Gage
202. Rotating band damaged	Visual
203. Paint not dry	Visual & Tactile
204. Paint on threads	Visual
205. Paint inadequate or damaged	Visual
206. Corrosion preventive compound missing	Visual
207. Marking missing, incorrect or illegible	Visual
208. Burr	Visual
209. Foreing matter (except as otherwise classified)	Visual
210. Protector cup missing	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

Defect	Method of Inspection

4.3.2.5 Base Cover, Drawing B10535915, covering a detail of Drawing D10535913

CRITICAL

None defined

MAJOR

None defined

MINOR

201.	Diameter	Gage
202.	Thickness	Gage

4.3.2.6 Packed Carton (prior to sealing).

CRITICAL

None defined

MAJOR

None defined

MINOR

201.	Support missing or damaged	Visual
202.	Separator missing or damaged	Visual
203.	Improper assembly	Visual
204.	Incorrect number in carton	Visual

4.3.2.7 Packed Carton (after sealing).

CRITICAL

None defined

MAJOR

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

4.3.2.7 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Carton damaged, cut or gouged through all layers	Visual
202. Carton not completely sealed	Visual
203. Contents loose	Visual/Manual
204. Marking missing, incorrect or illegible	Visual

4.3.3 Inspection Testing.-The following tests shall be performed in accordance with the provisions of 4.4:

4.3.3.1 Mechanical Properties

4.3.3.1.1 Hardness

4.3.3.1.1.1 Heat treatment lots.-In order to determine uniformity of heat treatment, each body in the heat treatment lot (as defined by 4.3.1.2) shall be subjected to a hardness test with a Rockwell Hardness Tester or by any other method of hardness testing approved by the procuring activity.

4.3.3.1.1.3 Bar stock lot.-When mechanical properties of the bar stock are altered by heat treatment during the manufacture of bodies, each body in the bar stock lot (as defined by 4.3.1.4) shall be subjected to a hardness test with a Rockwell Hardness Tester or by any other method approved by the procuring activity in order to determine uniformity of heat treatment.

4.3.3.1.1.4 Miscellaneous lots.-Miscellaneous heat treatment lots shall be subjected to a hardness test in accordance with 4.3.3.1.1.1. Miscellaneous stress relieved lots shall be subject to a hardness test in accordance with 4.3.3.1.1.3.

4.3.3.1.2 Tension test.

4.3.3.1.2.1 Heat treatment lots.-Two bodies, one of the hardest and one of the softest as determined by the hardness test in accordance with 4.3.3.1.1.1 or 4.3.3.1.1.3 shall be subjected to this test. Failure of any tension test specimen to comply with the mechanical properties requirements of the applicable drawing shall be cause for rejection of the lot. At the option of the supplier, a production control sample may be utilized to establish the hardness range. When a production control sample is used the hardness range thus established shall be maintained throughout the lot. The size of the sample shall be determined by the supplier. Projectile bodies which fall outside of the established range may be re-heat treated to fall within the range or new mechanical properties may be determined from newly selected projectile bodies which will represent the true extremes of hardness in the heat treatment lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

4.3.3.1.2.2 Stress relieved lots.-Two bodies, one of the hardest and one of the softest as determined by the hardness test from the first twenty-five bodies selected in accordance with 4.3.3.1.1.2 shall be subject to this test. Failure of any tension test specimen to comply with the mechanical properties requirements of the applicable drawing shall be cause for rejection of the lot. When it has been determined that the mechanical properties comply and furnace temperature and time have been established, the furnace temperature and time shall be maintained throughout the stress relieved lot. The furnace temperature may vary within twenty-five degrees F, but not below the minimum temperature of 700 degrees F. and the soak time of 30 minutes minimum. Furnace temperature and time will be recorded every hour to assess adequate control of stress relief equipment. The furnace temperature will be calibrated every eight hours by an independent method.

4.3.3.1.2.3 Bar stock lots.-When heat treatment is not required during manufacture of bodies from bar stock; two projectiles from each lot of 5000 projectiles or fraction thereof shall be subjected to this test. Failure of any tension test specimen to comply with the yield strength or elongation requirements of the applicable drawing shall be cause for rejection of the production represented by the sample.

4.3.3.1.2.4 Miscellaneous lots.-Samples for the tension test of miscellaneous heat treatment or stress relieved lots shall be selected in accordance with 4.3.3.1.2.1, or 4.3.3.1.2.2 as applicable. Failure of any tension test specimen to comply with the mechanical properties requirements of the applicable drawing, shall be cause for rejection of the lot. Tension tests shall be performed on each miscellaneous heat of steel before being grouped into a miscellaneous lot.

4.3.3.2 Cleaning and application of protective coating.-The sample size and acceptance criteria for the inspection of cleaning the item and application of the protective coating shall be as specified in the applicable specification, except body assemblies will be used instead of panels. Failure to comply with the requirements of the applicable drawings and specification shall be cause for taking the corrective action recommended therein.

4.3.3.3 Base cover weld.-Two body assemblies from each hour of production or fraction thereof per welding machine in operation, shall be subjected to this test. Failure of the weld to meet the requirement of 3.6.5 shall be cause for rejection of the assemblies represented by the sample.

4.3.4 Functional proving ground test.-The following Proving Ground tests will be performed by the Government.

4.3.4.1 First Article Sample

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

4.3.4.1.1 Initial Production Sample.-The quantities listed in Table I shall be ballistically tested in the phases indicated.

TABLE I

Phase	Quantity
Excess pressure	25
Service pressure	25

4.3.4.2 Production lot sample.-The quantities listed in Table II shall be ballistically tested in the phases indicated.

TABLE II

Phase	Quantity
Excess pressure	10 each lot
Service pressure	10 each lot

4.3.4.3 Excess pressure.-Samples provided in accordance with Table I and II will be subjected to this test. Failure of any projectile assembly to comply with 3.5 shall be cause for rejection of the initial production sample or the production lot represented by the sample.

4.3.4.4 Service pressure.-Samples provided in accordance with Tables I and II will be subjected to this test. Failure of any projectile assembly to comply with 3.5 shall be cause for rejection of the initial production sample or the production lot represented by the sample.

4.3.5 Inspection Equipment.-Index of Inspection Equipment List Number IEL-10535913 identifies the inspection equipment required to perform the examination and tests prescribed herein. Equipment design shall be in accordance with the code designation on the applicable IEL.

4.4 Test Methods and Procedures

4.4.1 Mechanical Properties

4.4.1.1 Hardness

4.4.1.1.1 Body.-After final heat treatment or stress relief and prior to final machining, the hardness test shall be performed on the sidewall of the body in the area of the rotating band. The test shall be performed using the equipment and procedures for performing this test as prescribed by ASTM Method E-10.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

4.4.1.1.2 Bar stock.-After final machining, the hardness test shall be performed on the sidewall of the body in an area approximately one-half inch rear of the rotating band. The test shall be performed using the equipment and procedures for performing this test as prescribed by ASTM Method E-10.

4.4.1.2 Tension test

4.4.1.2.1 Yield strength and elongation.-From the samples selected in accordance with 4.3.3.1.2.1, 4.3.3.1.2.2 or 4.3.3.1.2.3, tension test specimens conforming to the largest obtainable standard "R" type specimen as prescribed by ASTM Method E-8 shall be taken as follows: Two tension test specimens shall be taken longitudinally from opposite sides of the body 180 degrees apart and one transverse tension test specimen through the base area of the body. (centerline of the specimen shall be between .25 and .35 inches from the centerline of the base. The number of specimens and their location is to determine the acceptability of the mechanical properties requirements and the Government shall not be restricted from testing.additional specimens at other locations to determine that the meghanical properties of the projectile meet the drawing requirements. The criteria for performing this test shall be prescribed by ASTM Method E-8, except that elongation shall be measured to the nearest thousanth(0.000) prior to conversion into percent elongation. Percent elongation shall be recorded to the nearest tenth (0.0).

4.4.2 Protective coating.-The procedure for testing the cleaning and surface treatment methods for the components and assemblies shall be in accordance with the methods and criteria for testing as specified in the applicable specification. The salt spray prescribed shall be performed in compliance with ASTM Method B-117.

4.4.3 Base cover weld.-The test of the base cover weld shall be performed as follows: visually inspect the base cover and select the area that appears to have the weakest weld; insert a 1/2 to 5/8" cold chisel with a 75 degrees point. held at a 15 degree angle with the base of the projectile and apply force by use of a one pound steel hammer with approximately a one foot stroke. If the weld breaks loose after 2 strokes, the metal parts assembly will be classed defective. If the weld is found to be secure, the burr made by the chisel may be knocked back into position and accepted.

4.4.4 Proving Ground Functional tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

4.4.4.1 Excess pressure.-The projectiles supplied in accordance with Tables I and II, inert loaded dummy fuzed and assembled into complete rounds will be fired for recovery in a gun for which the round is standard, the tube of which shall have a minimum of 25 percent life remaining, based on current gun tube condemnation criteria. A propellant charge adjusted to produce 109 to 117 percent of the upper pressure limit of the propellent used with the applicable projectile. Photographic equipment will be set-up near the gun muzzle to record the flight of the projectile to determine compliance with 3.5.

4.4.4.2 Service pressure.-The projectiles supplied in accordance with Tables I and II, inert loaded, dummy fuzed and assembled into complete rounds, will be fired alternately with projectiles from a reference lot for comparison. The projectile shall be fired in a gun for which the round is standard, the tube of which the round is standard, the tube of which shall have a minimum of 25 percent life remaining based on current gun tube condemnation criteria. All rounds will be fired to impact on a verticle target at a range selected by the Proof Director. Accuracy in terms of maximum spread both horizontal and verticle will be recorded for evaluation by the technical agency. Photographic equipment will be set up near the gun muzzle to record the flight of the projectile and to determine compliance with 3.5. Velocity and chamber pressures will be recorded for each round fired, for informational purposes only. (see 6.1).

5. PREPARATION FOR DELIVERY

5.1 Packing and marking. - Level C.-Packing and marking shall be in accordance with Drawing F7548913.

5.2 Packing

5.2.1 Body assembly.-Body assemblies shall be packed in accordance with Drawing F7548913.

5.3 Marking.-Packaged body assemblies shall be marked in accordance with MIL-STD-1169.

5.4 Shipping.-When component parts from more than one lot are shipped as a carload, each lot must be kept separate and division between lots clearly indicated to prevent mixing in transit.

5.5 Data cards.-The contractor shall prepare and furnish data cards in the number to be determined by the contracting officer in accordance with MIL-STD-1167.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ballistic test.-Rounds fired for velocity-accuracy are not acceptance tests, but the results will be carefully analyzed by the Munitions Command to determine quality of ammunition produced. Evidence of excessive variation in either plase of the Proving Ground tests will result in immediate investigation by the Munitions Command.

6.2 Visual examination qualification.-When compliance with the applicable requirement is in doubt as a result of visual examination, the characteristic may be measured or gaged to determine acceptability.

6.3 Visual standards.-Visual standards to be established at contractors plant in compliance with 3.6.3.

6.4 Alternative mechanical properties testing.-Alternative procedures for mechanical properties testing may be used by the contractor when such testing and procedures provide as a minimum the quality assurance specified herein. Prior to applying the alternative procedures, the contractor shall describe them in a written proposal and shall demonstrate for the approval of the responsible technical agency that their effectiveness is equal to or better than the quality assurance provisions specified herein.

6.5 Ordering data.-Procurement documents should specify the title, number and date of this specification.

Custodian:

Army - MU

Preparing activity:

Army - MU(FA)

Project No. 1310 -A218

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-P-14827A(MU) Projectile, 57MM: HE, M306A1, Metal Parts Assembly

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:51Z
Check the source to verify that this is the current version before use.