MILITARY SPECIFICATION

PROJECTILE, 4.2 INCH TACTICAL CS, XM633 METAL PARTS ASSEMBLY

1. SCOPE

1.1 This specification covers Projectile, 4.2 Inch, Tactical CS, XM633 Metal Parts Assembly.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-A-2550 - Ammunition and Special Weapons, General Specification for

STANDARDS

Federal

Federal Test Method Standard No. 141 - Paint, Varnish, Lacquer, and Related Materials; Methods of Inspection, Sampling and Testing.

Federal Test Method Standard No. 151 - Metals; Test Methods

FSC 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:52Z
Check the source to verify that this is the current version before use.

2.1 (Cont'd)

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-1167	- Ammunition Data Card
MIL-STD-1168	- Lot Numbering of Ammunition
MIL-STD-1169	- Packaging, Packing and Marking for Shipment of Inert Ammunition Components
MIL-STD-1235	- Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

Munitions Command

F10543050	- Projectile, 4.2 Inch, Tactical CS, XM633 Metal Parts
F8848553	- Pallet
IEL10543050	- Inspection Equipment List for Projectile, 4.2 Inch, Tactical CS, XM633

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other Publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

ASA-B46.1 - Surface Texture

(Application for copies should be addressed to the American Standards Association, 10 East 40th Street, New York, N.Y.)

3. REQUIREMENTS

3.1 General.-Materials, parts and assemblies shall comply with the requirements specified on the applicable drawings and referenced specifications, and the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:52Z
Check the source to verify that this is the current version before use.

3.2 Heat treatment or stress relief.-Heat treatment or stress relief applied shall be uniform throughout each lot of components and shall be so conducted as to produce in each component the mechanical properties specified on the applicable drawing.

3.2.1 Cold shaping.-Cold shaping shall be so accomplished as to produce in each component the mechanical properties specified by the applicable drawing. The components shall be stress relieved at a temperature of 700 degrees Fahrenheit (°F) minimum, following the final operation during which plastic flow takes place.

3.2.1.1 Bases.-Bases may be heat treated by normalizing in lieu of quenching and tempering to obtain specified mechanical properties. The bases shall be heated to a temperature of 1600° F. minimum, held at temperature for a minimum, of 30 minutes and cooled in such a manner as to produce uniform mechanical properties throughout each base.

3.2.2 Tubing.-Bodies manufactured from tubing shall be stress relieved after cold forming of the nose.

3.3 Mechanical properties.-Mechanical properties as specified on the applicable component drawing shall apply throughout the component.

3.4 Quality of joint.-The total area of inclusions, lack of adhesion, solder grooves or other defects shall not exceed 25 percent of the total faying surfaces of the joint.

3.5 Functional

3.5.1 Excess pressure.-There shall be no separation or loss of components in flight, nor shall there be evidence of failure of components due to firing stresses.

3.6 Workmanship.-The requirements for workmanship are as shown on the applicable drawing, in the applicable specifications and the following:

3.6.1 Metal defects.-All components shall be free from cracks, splits, cold shuts, pipe, porosity, inclusions or any similar defect.

3.6.2 Surface finish.-The requirements for surface finish are as detailed on the applicable drawings. The components shall be free of scale, fins, seams, die scratches, pits or other discontinuities.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:52Z
Check the source to verify that this is the current version before use.

3.6.3 Protective coating.-The protective coating shall be in accordance with the assembly drawing and the specifications listed thereon.

3.6.4 Threads.-Threads shall be full and undamaged for the entire minimum length or depth as required by the applicable drawing and shall be in accordance with the provisions of MIL-A-2550.

3.6.5 Burr.-No part shall have a burr which might interfere with the assembly or function of the round or might be injurious to personnel handling the item.

3.6.6 Foreign matter.-No part or assembly shall contain dirt, grease, chips, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.-Reference shall be made to MIL-STD-109 to define quality assurance terms used.

4.1.2 Inspection.-Inspection shall be in accordance with MIL-A-2550, except as specified herein.

4.2 First article sample

4.2.1 Initial production sample.-At the beginning or regular production, a sample shall be submitted in accordance with contract requirements and shall consist of thirty-five projectile metal parts as follows:

25 Projectile metal parts complete (painted)
5 Projectile metal parts complete (unpainted)
5 Sets of components parts unassembled and unpainted

Twenty of the above complete and painted metal parts assemblies shall be forwarded to a designated proving ground for functional testing. The sample shall be manufactured using the same materials, equipment, processes and procedures as will be used in regular production. All parts and materials including packaging and packing shall be the same as used in regular productions and shall be obtained from the same source of supply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:52Z
Check the source to verify that this is the current version before use.

4.2.1.1 Examination and test.-After inspection and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility specified in the contract.

4.2.1.2 Initial production sample failure.-Failure of the sample to comply with the requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection provisions

4.3.1 Lot

4.3.1.1 Submission of product.-The product shall be submitted in accordance with MIL-STD-105.

4.3.1.2 Heat treatment lots.-Heat treatment lots shall contain base forgings from not more than one heat of steel that have been heat treated in the same heat treating equipment, at the same temperature, in one unchanged process. The heat treatment lot thus constituted shall be the basis for the selection of samples for the tension test hereinafter prescribed.

4.3.1.3 Stress relieved lots.-Stress relieved lots shall contain cold worked bases from not more than one heat of steel that have been cold worked by the same process, utilizing the same tooling and equipment and stress relieved in the same furnace at the same temperature for the same length of time. The stress relieved lot thus constituted shall be the basis for the selection of samples for the tension test hereinafter prescribed.

4.3.1.4 Tubing lots.-Bodies manufactured from tubing shall be fabricated from tubing lots containing not more than one heat of steel. The bodies shall be cold nosed and stress relieved using the same equipment and procedures. Lots of bodies thus constituted shall be the basis for the selection of samples for the tension test hereinafter prescribed.

4.3.1.4.1 Adapters.-Adapters manufactured from tubing shall be fabricated from tubing lots containing not more than one heat of steel. Tubing lots thus constituted shall be the basis for the selection of samples for the tension test hereinafter prescribed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:52Z
Check the source to verify that this is the current version before use.

4.3.1.5 Bar stock lots.-Bar stock lots shall contain not more than one heat of steel. Bar stock lots thus constituted shall be the basis for the selection of samples for the tension test hereinafter prescribed.

4.3.1.6 Miscellaneous lots.-Small lots (such as bodies manufactured from abnormally small heats of steel or bodies and bases that have become separated from previously delivered lots, etc.) may at the discretion of the supplier be grouped into miscellaneous heat treatment, stress relieved or tubing lots as the case may be. Such lots shall be identified by a miscellaneous lot code number and processed in accordance with 4.3.1.2, 4.3.1.3 or 4.3.1.4 as applicable. The miscellaneous lot thus constituted shall be the basis for the selection of samples for the tension test hereinafter prescribed.

4.3.1.7 Projectile lots.-When it has been determined that a heat treated, stress relieved, tubing, bar stock or miscellaneous lots of bodies, bases or adapters have complied with the mechanical properties requirement of the applicable drawing, they may be regrouped for assembly into projectile lots, to which will be assigned a projectile lot number in accordance with MIL-STD-1168. The projectile lot shall consist of projectile assemblies produced by one supplier under one contract in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision, under conditions of continuous production free from interruptions other than those due to the end of a shift, day or workweek. The projectile lot thus constituted shall be the basis for the selection of samples for the functional test hereinafter prescribed.

4.3.2 Examination.-One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plans contained in MIL-STD-105. Continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the procuring activity. An AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect shall be used. All nonconforming material shall be rejected. Four power (4X) magnification may be used in performing visual examination for such defects as cracks, burr and foreign matter. The roughness comparison specimens prescribed by ASA-B46.1 shall be used as a basis for surface roughness determination.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:52Z
Check the source to verify that this is the current version before use.

4.3.2.1 Spacer, Drawing C10534156, covering a detail of Drawing F10543050

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR	
101. Diameter outside, small	Gage
102. Diameter of holes	Gage
103. Length of small diameter, min	Gage
104. Surface finish on small diameter	Visual (see 6.1)
105. Metal defective	Visual
MINOR	
201. Length, total	Gage
202. Thickness of wall	Gage
203. Radii or chamfers missing or incorrect	Visual (see 6.1)
204. Surface finish improper (except as otherwise classified)	Visual
205. Burr	Visual

4.3.2.2 Adapter, Nose, Drawing D10534158, covering a detail of Drawing F1053050

CRITICAL	
None defined	
MAJOR	
101. Concentricity of spacer cavity with brazing area, including perpendicularity of front shoulder	Gage
102. Concentricity of small inside diameter with spacer cavity	Gage
103. Diameter, inside, small	Gage
104. Diameter of brazing surface	Gage
105. Diameter of spacer cavity	Gage
106. Surface finish of brazing surface	Visual (see 6.1)
107. Metal defective	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:52Z
Check the source to verify that this is the current version before use.

4.3.2.2 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Diameter of large shoulder	Gage
202. Length from front face to front shoulder	Gage
203. Length, total	Gage
204. Radii or chamfer missing or incorrect	Visual (see 6.1)
205. Surface finish improper (except as otherwise classified)	Visual (see 6.1)
206. Burr	Visual

4.3.2.3 Adapter Assembly, Drawing C10543051, covering a detail of Drawing F10543050

CRITICAL	
None defined	
MAJOR	
101. Length, total, max.	Gage
102. Gap between spacer and adapter shoulder	Visual (see 6.1)
MINOR	
None defined	

4.3.2.4 Plug, Base, Drawing D10534160, covering a detail of Drawing F10543050 (before paint)

CRITICAL	
1. Metal defective	Visual
MAJOR	
101. Concentricity of large outside diameter with press fit diameter, including perpendicularity of front face of flange	Gage
102. Concentricity of pitch diameter of thread with press fit surface, including perpendicularity of front and rear face(s) of flange	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:52Z
Check the source to verify that this is the current version before use.

4.3.2.4 (Cont'd)

	Defect	Method of Inspection
103.	Symmetry of rotating disc seat with major diameter of thread	Gage
104.	Diameter of force fit surface at rear of taper	Gage
105.	Diameter of flange	Gage
106.	Height of rotating disc seat	Gage
107.	Thickness through flange and disc seat	Gage
108.	Width of rotating disc seat	Gage

MINOR

201.	Depth of cavity	Gage
202.	Height of thread boss	Gage
203.	Length of taper	Gage
204.	Length, total	Gage
205.	Radii or chamfers, missing or incorrect	Visual (see 6.1)
206.	Surface finish improper	Visual (see 6.1)
207.	Burr	Visual
208.	Foreign matter	Visual

4.3.2.5 Plug, Base, Drawing C10534160, covering a detail of Drawing F10543050 (after paint)

CRITICAL

None defined

MAJOR

101.	Pitch diameter of thread, min	Gage
102.	Major diameter of thread, min.	Gage
103.	Surface finish on press fit diameter improper or damaged	Visual (see 6.1)

MINOR

201.	Pitch diameter of thread, max.	Gage
202.	Protective coating inadequate or damaged	Visual
203.	Wax emulsion inadequate or damaged	Visual
204.	Corrosion preventive compound missing from thread	Visual
205.	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:52Z
Check the source to verify that this is the current version before use.

4.3.2.6 Body, Drawing D10534159, covering a detail of Drawing F10543050

Defect	Method of Inspection
CRITICAL	
1. Metal defective	Visual
MAJOR	
101. Diameter of brazing surface	Gage
102. Length to datum diameter	Gage
103. Length to rear of forward bourrelet	Gage
104. Thickness of wall at ogive	Gage
105. Variation in wall thickness	Gage
MINOR	
201. Diameter at front, outside	Gage
202. Length, total	Gage
203. Surface finish improper	Visual (see 6.1)
204. Burr	Visual
205. Foreign matter	Visual

4.3.2.7 Metal parts, Drawing F10543050 (before paint)

CRITICAL	
None defined	
MAJOR	
101. Concentricity of pitch diameter of nose thread with bourrelets, including perpendicularity of front face of nose	Gage
102. Concentricity of nose adapter with bourrelets	Gage
103. Concentricity of ogive with bourrelets	Gage
104. Concentricity of body with bourrelets	Gage
105. Concentricity of illuminant charge cavity with bourrelets	Gage
106. Concentricity of base plug cavity with bourrelets	Gage
107. Perpendicularity of rear face with bourrelets	Gage
108. Diameter of bourrelets, min.	Gage
109. Diameter of body	Gage
110. Diameter of illuminant charge cavity	Gage
111. Depth of thread cavity	Gage
112. Mating surfaces at body, adapter joint improper	Visual (see 6.1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:52Z
Check the source to verify that this is the current version before use.

4.3.2.7 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Diameter of nose outside	Gage

4.3.2.8 Metal parts, Drawing F10543050 (after paint)

CRITICAL	
None defined	
MAJOR	
101. Absence of pressure stamp (indication failure to pass pressure test)	Visual
102. Pitch diameter of nose thread, max.	Gage
103. Minor diameter of nose thread, max.	Gage
104. Diameter of bourrelets, max.	Gage
105. Diameter of base plug cavity	Gage
106. Depth of base plug cavity	Gage
107. Length of effective nose thread, min. (if applicable)	Gage
108. Surface finish of base plug cavity improper or damaged	Visual
MINOR	
201. Pitch diameter of nose thread, min.	Gage
202. Protective coating inadequate or damaged	Visual
203. Thread(s) damaged or not full	Visual
204. Marking missing incorrect or illegible	Visual
205. Foreign matter	Visual

4.3.2.9 Pallet, Drawing F8848553

CRITICAL	
None defined	
MAJOR	
None defined	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:52Z
Check the source to verify that this is the current version before use.

4.3.2.9 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Pallet damaged	Visual
202. Sleeve missing	Visual
203. Improperly packed	Visual
204. Strapping missing, loose or broken	Visual/Manual

4.3.3 Inspection testing.-The following tests shall be performed in accordance with the provisions of 4.4

4.3.3.1 Mechanical properties

4.3.3.1.1 Tension test

4.3.3.1.1.1 Body.-Two bodies from each tubing lot, after final heat treatment or stress relief, shall be subjected to this test to determine compliance with the yield strength and elongation requirements of the applicable drawing. Failure of any tension test specimen to comply shall be cause for rejection of the lot.

4.3.3.1.1.2 Base plugs.-Two base plugs from each heat treatment or cold shaping lot shall be subjected to this test to determine compliance with the yield strength and elongation requirements of the applicable drawing. Failure of any tension test specimen to comply shall be cause for rejection of the lot.

4.3.3.1.1.3 Adapter.-Two adapters shall be selected from each lot and subjected to this test to determine compliance with the applicable component drawing. Failure to comply shall be cause for rejection of the lot.

4.3.3.1.1.3.1 Machined from tubing.-With the approval of the procuring activity when the adapter is machined from tubing in such a manner that the mechanical properties are not altered, test coupons approximately 6 inches in length may be removed from one end of each of 3 tubes for each heat of steel and tested in lieu of testing the component. Failure of any tension test specimen to comply with the yield strength and elongation requirements of the applicable component drawing shall be cause for rejection of the tubing lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:52Z
Check the source to verify that this is the current version before use.

4.3.3.1.1.4 Machined from bar stock.-With the approval of the procuring activity when base plugs or adapters are machined from bar stock in such a manner that the mechanical properties are not altered, test coupons approximately 6 inches in length may be removed from one end of each of 3 bars for each heat of steel in the lot and tested in lieu of the component. Failure of any tension test specimens to comply with yield strength and elongation requirements of the applicable component drawing shall be cause for rejection of the bar stock lot.

4.3.3.2 Brazed joint

4.3.3.2.1 Strength of brazed joint.-(Major Defect) Each body assembly shall be subject to a mechanical load test to determine compliance with requirements of the applicable drawing. Failure of any assembly to comply shall be cause for rejection of the assembly. Body assemblies which comply with drawing requirements shall be stamped with letter "P" as indicated on the assembly drawing.

4.3.3.2.2 Quality of joint.-Two body assemblies prior to painting shall be selected from each lot and subjected to this test to determine compliance with 3.5.1. Failure of any segment of either joint to comply shall be cause for rejection of the lot.

4.3.3.3 Cleaning and application of protective coating.-The sample size and acceptance criteria for inspection of the cleaning of the item and the application of protective coating shall be as specified in the applicable specification. Failure to comply with the requirements shall be cause for taking the corrective action prescribed therein.

4.3.4 Functional.-The following proving ground tests will be performed by the Government.

4.3.4.1 First article sample

4.3.4.1.1 Initial production sample.-The quantity listed in Table I shall be ballistically tested in the phase indicated.

TABLE I

Test Phase	Quantity
Excess pressure	20

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:52Z
Check the source to verify that this is the current version before use.

4.3.4.1.2 Excess pressure.-Samples provided in accordance with Table I will be subjected to this test. Failure of any projectile metal parts to comply with 3.5.1 shall be cause for rejection of the initial production sample.

4.3.5 Inspection equipment.-Index of inspection equipment lists IEL-10543050 identifies the inspection equipment required to perform the examinations and tests prescribed herein.

4.4 Test methods and procedures

4.4.1 Mechanical properties

4.4.1.1 Body.-From each body selected in accordance with 4.3.3.1.1.1 for the convenience of the Government two tension test specimens conforming to the largest obtainable standard "T" type specimen as prescribed by Federal Test Method Standard No. 151 shall be taken longitudinally from each side of the body 180 degrees apart or from any other location deemed necessary by the Government. The criteria for determining yield strength by the offset method shall be as prescribed by Federal Test Method Standard No. 151. The limiting set shall be 0.1 percent (0.001 inch per inch of gage length).

4.4.1.2 Base plug.-From each base plug selected in accordance with 4.3.3.1.1.2 one tension test specimen conforming to the largest obtainable standard "R" type specimen as prescribed by Federal Test Method Standard No. 151 shall be taken from the center of the base plug in a transverse direction normal to the centerline of the part. The criteria for performing this test shall be as prescribed by Federal Test Method Standard No. 151. The limiting set shall be 0.1 percent (0.001 inch per inch of gage length).

4.4.1.3 Adapter.-From each adapter selected in accordance with 4.3.3.1.1.3, one tension test specimen conforming to the largest obtainable "R" type specimen as prescribed by Federal Test Method Standard No. 151 shall be taken longitudinally from the adapter and tested in accordance with the criteria for determining yield strength by the offset method as specified in Federal Test Method Standard No. 151. The limiting set shall be 0.1 percent (0.001 inch per inch of gage length).

4.4.1.3.1 Machined from tubing.-From the test coupons supplied in accordance with 4.3.3.1.1.3.1, one tension test specimen conforming to the largest obtainable standard "R" type tension test specimen as prescribed by Federal Test Method Standard No. 151 shall be taken longitudinally from each test coupon and tested in accordance with the criteria for determining yield strength by the offset method as specified in Federal Test Method Standard No. 151. The limiting set shall be 0.1 percent (0.001 inch per inch of gage length).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:52Z
Check the source to verify that this is the current version before use.

4.4.1.4 Machined from bar stock.-From the samples by 4.3.3.1.1.4 one type "R" tension test specimen shall be taken longitudinally at mid radius from one end of each coupon. The criteria for determining yield strength and elongation as prescribed by Federal Test Method Standard No. 151. Yield strength shall be determined by the offset method, the limiting set shall be 0.1 percent (0.001 per inch per inch of gage length).

4.4.2 Strength of brazed joint.-The projectile shall be placed over the holding fixture and the pressure applied to the ogive at the rear of the brazed joint. Care shall be exercised in applying the pressure to assure that the fixture contacts the ogive below the brazed joint.

4.4.3 Sectionalized specimens.-The projectile assemblies selected in accordance with 4.3.3.2.2 shall be sectionalized by cutting through the body at least two inches to the rear of the brazed joint. Each of the sections containing the braze joint shall be cut into two 180 degree segments.

4.4.3.1 Quality of joint.-The sidewall shall be peeled or stripped from each segment by applying continuous pressure. The braze surface of each segment of the adapter and each segment of the sidewall shall be visually examined to determine compliance with the requirements of 3.4.

4.4.4 Protective coating.-The procedures for testing the cleaning of components and assemblies and the application of protective coatings shall be in accordance with the applicable drawings and the applicable specification listed thereon. The salt spray test shall be performed utilizing the equipment and procedures prescribed by Federal Test Method Standard No. 141.

4.4.5 Proving ground functional tests

4.4.5.1 Excess pressure.-The metal parts assemblies provided in accordance with Table I for this phase, inert loaded to the service weight will be assembled into complete rounds and fired in a mortar for which the round is standard. The propellant charge will be adjusted to obtain 112 percent of the standard service pressure of the round in a new mortar. Photographic equipment will be set up near the gun muzzle to record the flight of the projectile. An attempt will be made to recover at least 60 percent of the projectiles fired in this phase. The recovered projectile will be examined to determine if:

Deformation occurred in the gun tube as evidenced by the presence of rifling marks extending more than 180 degrees around the circumference, increase or decrease in the diameter of body (beyond drawing tolerances) in vicinity of bourrelet, dishing of the base, or other evidence of component failure due to firing stresses.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:52Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging

5.1.1 Level C.-Base Plugs - Part No. 10534160 shall be packed in accordance with the requirements of MIL-STD-1169.

5.2 Packing

5.2.1 Lever C.-Metal parts assemblies shall be palletized in accordance with Drawing F8848553.

5.3 Data card information shall be as specified in MIL-STD-1167.

6. NOTES

6.1 Visual examination qualification.-When compliance with the applicable requirements is in doubt as a result of visual examination, this characteristic may be measured or gaged to determine acceptability.

6.2 Ordering data.-Procurement documents should specify the title, number, and date of this specification.

Custodian

Army - MU

Preparing Activity

Army - MU

Project No. 1315 - A646

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:52Z
Check the source to verify that this is the current version before use.