MIL-S-14823
AMENDMENT 2
25 October 1968

MILITARY SPECIFICATION

STOP WATCH, MILITARY

This amendment forms a part of Military Specification MIL-S-14823, 11 July 1968 and is mandatory for use by all Departments and Agencies of the Department of Defense.

Page 3: Add "3.7.3 Crown.- The crown shall be located at the 60 second position of the dial."

Page 3: Add "3.7.4 Push button.- The push button shall be located between the 5 and 10 seconds or the 50 and 55 seconds position of the dial. The position as illustrated in Figure 2 is for reference only."

Page 4, paragraph 3.8.6: Delete and substitute "3.8.6 Magnetism.- The three (3) minute rate (3.8.8.1b) shall not change by more than ± 0.2 second when the watch is subjected to a magnetic field of 60 Gauss (+5 Gauss, -0 Gauss) for a minimum of five (5) seconds in each of the following positions:

a. Vertical (with crown in any position).
b. Horizontal (with dial up or down)."

Page 9, paragraph 4.4.8.6: Delete "0.4 second" and substitute "+0.4 second, -0.2 second."

Custodians:
Army - MU
Navy - SH
Air Force - 82

Review activities:
Army - WC
Navy - OS

User activities:
Army - EL
Navy - AS, MC

Preparing activity:
Army - MU

Project No. 6645-0248

FSC 6645

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:50Z
Check the source to verify that this is the current version before use.