MILITARY SPECIFICATION SHEET
CABLES FOR ATOMIC DEMOLITION CHARGES

W3-AP-1 CABLE ASSEMBLY

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-14982(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for W-3-AP1 Cable Assembly Training for use with Training Atomic Demoltion Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-14982(MU) - Cables for Training Atomic Demolition Charge, General Specification for

STANDARDS

MILITARY

MS15795 - Washer
MS20470 - Rivet
MS25281 - Clamp

DRAWINGS

ORDNANCE CORPS

8850958 - Connector

FSC 1195

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

8851157 - Test Clip
8851159 - Insulator, Black
8851852 - Molding Compound Polyurethane, Black
8851861 - Cap and Chain Assembly
8851876 - Cable, Black 5 Conductor
8851879 - W3-AP-1 Cable Assembly
8851893 - Box Set-up, Paperboard for Cable Assembly W3-AP-1 (TNG)
8851901 - Primer Metal to Polyurethane
8851902 - Primer Polyurethane to B.Y.C.
EL8851879 - Equipment List

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-C-14982(MU) and as specified herein.

3.2 Circuit resistance. The cable assembly circuit shall be in accordance with Table I.

Table I

Circuit resistance (see dwg 8851879)

From wire	To P5-1 Connector Pin	Ohms max
white	4	0.2
white	5	0.2
black	all pins	infinite
grey-orange	all pins	infinite
brown	all pins	infinite
orange	2	0.2

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection sh ll be in accordance with MIL-C-14982(MU) and as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

4.1.1 Sampling and inspection not applicable. The following classification of defects in MIL-C-14982(MU) is not applicable:

a. 4.3.2.1.4 Bag, packing, ammunition for cable assembly.

4.2 First article inspection.

4.2.1 Quantity to be submitted. In addition to quantities specified in 4.2.1 MIL-C-14982(MU), 3 sub-assemblies shall be submitted (see dwg. 8851879) W3-AP-1 Cable Assembly Training before potting and molding.

4.3 Classification of characteristics.

4.3.1 Connector,(see dwg. 8850958); test clip (see dwg. 8851157); Insulator black (see dwg. 8851159); Molding compound polyurethane black (see dwg. 8851852); cap and chain assembly (see dwg. 8851861); cable, black 5 conductor (see dwg. 8851876); Brimer metal to polyurethane (see dwg. 8851901); primer polyurethane to B.Y.C. (see dwg. 8851902); Washer (see MS 15795-204); Rivet (see MS 20470-B4-7); and clamp (see MS 25281-W) covering details of dwg. 8851879).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see 6.3 MIL-C-14982(MU) available for parts in accordance with applicable standard or drawing	Visual
Minor:		
201.	Workmanship (see 3.12 MIL-C-14982(MU)	Visual-Manual

4.3.2 W3-AP-1 Cable assembly training (see dwg. 8851879) before potting and molding.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Primer applied to connectors	Visual
102.	Primer applied to cable	Visual
103.	Length of wires	*measure

*Measure with suitable scale.

Minor: None defined.

4.3.3 W3-AP-1 cable assembly training (see dwg. 8851879).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of inspection
Critical:	None defined.	
Major:		
101.	Length	*measure
102.	Small diameter of tapered mold	gage
103.	Large diameter of tapered mold	gage
104.	All components present	Visual
105.	Materials (see 3.2 MIL-C-14982(MU)	Visual
106.	Marking	Visual
107.	Clamp tight on cable	Manual

*Measure with suitable scale.

Minor:		
201.	Serialization (see 3.5 MIL-C-14982(MU)	Visual

4.4 Insulation resistance. The cable assembly insulation resistance shall be tested in accordance with Table II.

Table II

Insulation resistance (see dwg 8851879)

Positive Potential to wire	Negative potential to shell all other pins, wires and clip except; P5-1 Connector pins
white clip	4 and 5
black	
grey-orange	
brown	
orange	2

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies. Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-14982(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. Preservation and packaging shall be as specified in MIL-C-14982(MU).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

5.2.1.1 Level A. The cable assembly shall be packaged in accordance with dwgs. 8851893 and 8808362 and as specified in MIL-C-14982(MU).

5.2.1.2 Level C. The cable assembly shall be packaged in accordance with dwgs. 8851893 and 8808362 and MIL-C-14982(MU).

5.2.2 Packing.

5.2.2.1 Level A and C. The cable assembly shall be packed in accordance with dwgs. 8851893 and 8808362 and MIL-C-14982(MU).

5.2.3 Marking. Marking shall be as specified in dwgs. 8851843 and 8808362 and MIL-C-14982(MU).

6.0 NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-14982(MU).

Custodian
Army - MU

Preparing activity
Army - MU

Project No. 1195-A036

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.