MILITARY SPECIFICATION SHEET
CABLES FOR ATOMIC DEMOLITION CHARGES

W4-AP-1 CABLE ASSEMBLY

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-15982(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for W4-AP-1 Cable Assembly Training for use with Training Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-14982(MU) - Cables for Training Atomic Demolition Charge, General Specification for

DRAWINGS

ORDNANCE

8850972 - Connector, Plug, Electrical
8851880 - W4-AP-1 Cable Assembly Training
8851926 - Box set-up, Paperboard for W4-AP-1(TNG) Cable Assembly
8881768 - Polyurethane Molding Compound
8881769 - Primer, Polyurethane Molding Compound
9207508 - Primer, Polyurethane Molding Compound
EL8851880 - Equipment List

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-C-14982(MU) and as specified herein.

3.2 Circuit resistance. The cable assembly circuit resistance shall be in accordance with Table I.

Table I

Circuit resistance (see dwg. 8851880)

From P4-1 Connector Pin	To	Ohms Max.
F	Field wire	0.2
A	other field wire	0.2
D	Red Clip	0.2
C	Black Clip	0.2

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-C-14982(MU) and as specified herein.

4.1.1 Sampling and inspection not applicable. The following classification of defects in MIL-C-14982(MU) is not applicable:

a. 4.3.2.1.4 Bag, packing, ammunition for cable assembly.

4.2 First article inspection.

4.2.1 Quantity to be submitted. In addition to quantities specified in 4.2.1 MIL-C-14982(MU), 3 sub-assemblies shall be submitted (see dwg. 8851880) W4-AP-1 Cable Assembly Training before potting and molding.

4.3 Classification of characteristics.

4.3.1 Connector, plug, electrical (see dwg. 8850972); polyurethane molding compound (see dwg. 8881768); Primer, polyurethane molding compound (see dwgs 8881769 and 9207508); covering details of dwg 8851880.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Objective evidence (see 6.3 MIL-C-14982(MU) available for parts in accordance with applicable drawing.....Visual

Minor:
201. Workmanship (see 3.12 MIL-C-14982(MU).....Visual-Manual

4.3.2 W4-AP-1 Cable assembly training (see dwg. 8851880) before potting and molding.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Primer applied to connectors.....Visual
102. Primer applied to cable.....Visual

Minor: None defined.

4.3.3 W4-AP-1 cable assembly training (see dwg. 8851880).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Length of field wire.....*measure
102. Length of vinyl tubing.....*measure
103. Length of red and black wires.....*measure
104. Cable tied at intervals before applying vinyl tubing and molding.....*measure
105. Field wire molds removable.....Visual-Manual
106. Marking.....Visual
107. Materials (see 3.2 MIL-C-14982(MU).....Visual

*Measure with suitable scale.

Minor:
201. Serialization (see 3.5 MIL-C-14982(MU).....Visual

4.4 Insulation resistance. The cable assembly insulation resistance shall be tested in accordance with table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

Table II

Insulation resistance (see dwg 8851880)

Positive Potential P4-1 Connector Pin	Negative potential to shell, all other pins wires and clips except:
F	Field wire
A	other field wire
D	Red clip
C	Black clip

5.0 PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies. Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-14982(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. Preservation and packaging shall be as specified in MIL-C-14982(MU).

5.2.1.1 Level A. The cable assembly shall be packaged in accordance with dwgs. 8851926 and 8808362 and as specified in MIL-C-14982(MU).

5.2.1.2 Level C. The cable assembly shall be packaged in accordance with dwgs. 8851926 and 8808362 and MIL-C-14982(MU).

5.2.2 Packing.

5.2.2.1 Level A and C. The cable assembly shall be packed in accordance with dwgs. 8851926 and 8808362 and MIL-C-14982(MU).

5.2.3 Marking. Marking shall be as specified in dwgs. 8851926 and 8808362 and MIL-C-14982(MU).

6.0 NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-14982(MU).

Custodian
Army - MU

Preparing activity
Army - MU

Project No. 1195-A037

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.