MILITARY SPECIFICATION SHEET
CABLES FOR ATOMIC DEMOLITION CHARGES

W143-11 CABLE ASSEMBLY

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-14982(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for Cable Assembly Training W143-11 for use with Training Atomic Demoltion Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-14982(MU) - Cables for Training Atomic Demolition Charge, General Specification for

STANDARDS

MILITARY

MS 15795 - Washer
MS 16535 - Rivet
MS 25281 - Clamp

DRAWINGS

ORDNANCE CORPS

FSC 1195

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

8850958 - Connector
8850963 - Connector
8851852 - Molding Compound Polyurethane, Black
8851861 - Cap and Chain Assembly
8851862 - Cap and Chain Assembly
8851901 - Primer Metal to Polyurethane
8851903 - Primer Polyurethane to B.Y.C.
8851981 - Molding Shell
8852184 - Cable Assembly Training W143-11
8852275 - Box Set-up, Paperboard for W143-11 (TNG) and W143-12 (TNG) Cable Assembly
EL-8852184 - Equipment List

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-C-14982(MU) and as specified herein.

3.2 Circuit resistance. The cable assembly circuit resistance shall be in accordance with Table I.

Table I

Circuit resistance (see dwg 8852184)

From Connector	To Connector	Ohms Max
P601	P143-8	
Pin	Pin	
2	C	0.5
4	B	0.5

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-C-14982(MU) and as specified herein.

4.1.1 Sampling and inspection not applicable. The following classification of defects in MIL-C-14982(MU) is not applicable.

a. 4.3.2.1.4 Bag, packing, ammunition for cable assembly.

4.2 First article inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

4.2.1 Quantity to be submitted. In addition to quantities specified in 4.2.1 MIL-C-14982(MU), 3 sub-assemblies shall be submitted (see dwg. 8852184) Cable Assembly Training before potting and molding.

4.3 Classification of characteristics.

4.3.1 Connector (see dwgs. 8850958 and 8850963); molding compound polyurethane black (see dwg. 8851852); cap and chain assembly (see dwgs 8851861 and 8851862); primer metal to polyurethane (see dwg. 8851901); primer polyurethane to B.Y.C. (see dwg. 8851903); molding shell (see dwg. 8851981); Washer (see MS 15795-204); Rivet (see MS 16535-160); clamp (see MS 25281-4W) covering details of dwg. 8852184.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see 6.3 MIL-C-14982(MU) available for parts in accordance with applicable standard or drawing	Visual
Minor:		
201.	Workmanship (see 3.12 MIL-C-14982(MU)	Visual-Manual

4.3.2 Cable assembly training (see dwg. 8852184) before potting and molding.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Primer applied to connectors	Visual
102.	Primer applied to cable	Visual
Minor: None defined.		

4.3.3 Cable assembly training W143-11 (see dwg. 8852184).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Length	*measure
102.	Length of large diameter of mold	*measure
103.	Length of tapered diameter of mold	*measure
104.	Diameter of cable	gage
105.	Marking	Visual
106.	Materials (see 3.2 MIL-C-14982(MU)	Visual
107.	Clamp tight	Manual

*Measure with suitable scale.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

Minor:
201. Serialization (see 3.5 MIL-C-14982(MU).....Visual

4.4 Insulation resistance. The cable assembly insulation resistance shall be tested in accordance with table II.

Table II

Insulation resistance (see dwg 8852184)

Positive Potential Connector P60-1 Pin	Negative potential, shells, and other pins except Connector P143-8 Pin
2	C
4	B

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies. Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-14982(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. Preservation and packaging shall be as specified in MIL-C-14982(MU).

5.2.1.1 Level A. The cable assembly shall be packaged in accordance with dwgs. 8852275 and 8808362 and as specified in MIL-C-14982(MU).

5.2.1.2 Level C. The cable assembly shall be packaged in accordance with dwgs. 8852275 and 8808362 and MIL-C-14982(MU).

5.2.2 Packing.

5.2.2.1 Level A and C. The cable assembly shall be packed in accordance with dwgs. 8852275 and 8808362 and MIL-C-14982(MU).

5.2.3 Marking. Marking shall be as specified in dwgs. 8852275 and 8808362 and MIL-C-14982(MU).

6.0 NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-14982(MU).

Custodian
Army - MU

Preparing activity
Army - MU
Project No. 1195-A038

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.