MILITARY SPECIFICATION SHEET

CABLES FOR ATOMIC DEMOLITION CHARGES

CABLE ASSEMBLY

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-14982(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for Cable Assembly for use with Training Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-14982(MU) - Cables for Training Atomic Demolition Charge, General Specification for

STANDARDS

MILITARY

MS3181 - Cap Protective
MS25036 - Terminal

DRAWINGS

ORDNANCE CORPS

8800546 - Bag Packing Ammunition for Cable Assembly
8850975 - Connector, Plug, Electrical
8852203 - Cable Assembly
8881768 - Polyurethane Molding Compound
8881769 - Primer Polyurethane Molding Compound
9207508 - Primer Polyurethane Molding Compound
EL-8852203 - Equipment List

FSC 1195

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-C-14982(MU) and as specified herein.

3.2 Circuit resistance. The cable assembly circuit resistance shall be in accordance with table I.

Table I

Circuit resistance (see dwg 8852203)

From Connector Pin	To Wire Terminal	Ohms Max
A	Orange	0.2
B	Black	0.2
C	Red	0.2

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-C-14982(MU) and as specified herein.

4.1.1 Sampling and inspection not applicable. The following classification of defects in MIL-C-14982(MU) are not applicable:

a. 4.3.2.1.5 Box, set-up paperboard for applicable cable assembly.

4.2 First article inspection.

4.2.1 Quantity to be submitted. In addition to quantities specified in 4.2.1 MIL-C-14982(MU), 3 sub-assemblies shall be submitted (see dwg 8852203) Cable Assembly before potting and molding.

4.3 Classification of characteristics.

4.3.1 Connector, plug, electrical (see dwg 8850975); polyurethane molding compound (see dwg 8881768); primer polyurethane molding compound (see dwg 8881769); primer polyurethane molding compound (see dwg 9207508); cap, protective (see MS3181-10); terminal (see MS25036-2) covering details of dwg 8852203.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Objective evidence (see 6.3 MIL-C-14982(MU)) available for parts in accordance with applicable standard or drawing.....Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

Minor:
201. Workmanship (see 3.12 MIL-C-14982(MU))..... Visual/Manual

4.3.2 Cable assembly (see dwg 8852203) before potting and molding.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Primer applied to connectors	Visual
102.	Primer applied to cable	Visual
Minor: None defined.		

4.3.3 Cable assembly (see dwg 8852203).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Length of sleeve	* Measure
102.	Length of wires	* Measure
103.	Diameter of sleeve portion	Gage
104.	Material (see 3.2 MIL-C-14982(MU))	Visual
105.	Sleeving tied	Visual
106.	Extension of sleeving in mold	* Measure

* Measure with suitable scale

Minor: None defined.

4.4 Insulation resistance. The cable assembly insulation resistance shall be tested in accordance with table II.

Table II

Insulation resistance (see dwg 8852203)

Positive Potential Connector Pin	Negative potential to shell and all other pins and terminals except Terminal
A	Orange
B	Black
C	Red

5.0 PREPARATION FOR DELIVERY

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

5.1 Preparation for delivery for production cable assemblies. Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-14982(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. Preservation and packaging shall be as specified in MIL-C-14982(MU).

5.2.1.1 Level A. The cable assembly shall be packaged in accordance with dwgs 8800546 and 8808362 and as specified in MIL-C-14982(MU).

5.2.1.2 Level C. The cable assembly shall be packaged in accordance with dwg 8808362 and MIL-C-14982(MU).

5.2.2 Packing.

5.2.2.1 Levels A and C. The cable assembly shall be packed in accordance with dwgs 8800546 and 8808362 and MIL-C-14982(MU).

5.2.3 Marking. Marking shall be as specified in dwgs 8800546 and 8808362 and MIL-C-14982(MU).

6.0 NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-14982(MU).

Custodian:
Army - MU

Preparing agency:
Army - MU

Project No. - 1195-A039

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.