MILITARY SPECIFICATION SHEET
CABLES FOR ATOMIC DEMOLITION CHARGES

CABLE ASSEMBLY CONTROL RECEIVER

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-14982(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for Cable Assembly Control Receiver for use with Training Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-14982(MU) - Cables for Training Atomic Demolition Charge, General Specification for
MIL-S-60902(MU) - Soldering, Electrical Connections for Nuclear Weapon Systems, Procedure for

DRAWINGS

ORDNANCE CORPS

8800546 - Bag Packing Ammunition for Cable Assembly
8851187 - Connector
8852509 - Cable Assembly Control Receiver
EL-8852509 - Equipment List

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

FSC 1195

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

3.1 Requirements. Requirements shall be in accordance with MIL-C-14982(MU) and as specified herein.

3.1.1 Requirements not applicable. The humidity requirement in MIL-C-14982 is not applicable.

3.2 Circuit resistance. The cable assembly circuit resistance shall be in accordance with table I.

Table I

Circuit resistance (see dwg 8852509)

From J14-6 Connector Pin	To Wire	Ohms Max.
A	Red	0.2
B	Black	0.2
C	Orange	0.2
D	Yellow	0.2

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-C-14982(MU) and as specified herein.

4.1.1 Sampling and inspection not applicable. The following inspections in MIL-C-14982(MU) are not applicable:

a. Quantity to be submitted (see 4.2.1). No sub-assemblies are required.

b. Inspection and testing to be performed (see 4.2.2). Table I delete Humidity test only.

c. All cables before potting or molding (see 4.3.2.1.1).

d. All cables after potting and molding when potting or molding is required (see 4.3.2.1.2).

e. Box, set-up paperboard for applicable cable assembly (see 4.3.2.1.5).

f. Humidity (see 4.4.6).

4.2 Classification of characteristics.

4.2.1 Cable assembly control receiver (see dwg 8852509).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Length of red, orange and yellow wires	*Measure
102.	Length of black wire	*Measure
103.	Soldering in accordance with MIL-S-60902(MU)	Visual
104.	Material (see 3.2 MIL-C-14982(MU))	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

105. Length of vinyl tubing.....*Measure
106. Objective evidence (see 6.3 MIL-C-14982(MU)) available for connector in accordance with dwg 8851187.....Visual

*Measure with suitable scale

Minor:
201. Workmanship (see 3.12 MIL-C-14982(MU)).....Visual/Manual

4.3 Insulation resistance. The cable assembly insulation resistance shall be tested in accordance with table II.

Table II

Insulation resistance (see dwg 8852509)

Positive Potential J14-6 Connector Pin	Negative potential to shell, all other pins and wires except wire
A	Red
B	Black
C	Orange
D	Yellow

5.0 PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies. Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-14982(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. Preservation and packaging shall be as specified in MIL-C-14982(MU).

5.2.1.1 Level A. The cable assembly shall be packaged in accordance with dwgs 8800546 and 8808362 and as specified in MIL-C-14982(MU).

5.2.1.2 Level C. The cable assembly shall be packaged in accordance with dwg 8808362 and MIL-C-14982(MU).

5.2.2 Packing.

5.2.2.1 Levels A and C. The cable assembly shall be packed in accordance with dwg 8800546 and 8808362 and MIL-C-14982(MU).

5.2.3 Marking. Marking shall be as specified in dwg 8800546 and 8808362 and MIL-C-14982(MU).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

6.0 NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-14982(MU).

Custodian:
Army - MU

Preparing agency:
Army - MU

Project No. - 1195-A040

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.