MILITARY SPECIFICATION SHEET
CABLES FOR ATOMIC DEMOLITION CHARGES

W143-12 CABLE ASSEMBLY

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-14982(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for W143-12 Cable Assembly Training for use with Training Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-14982(MU) - Cables for Training Atomic Demolition Charge, General Specification for

STANDARDS

MILITARY

MS15795 - Washer
MS16535 - Rivet
MS25281 - Clamp

DRAWINGS

ORDNANCE CORPS

8850958 - Connector
8850960 - Connector
8851852 - Molding Compound Polyurethane, Black

FSC 1195

Source: https://assist.dla.mil,-- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

8851861 - Cap and Chain Assembly
8851901 - Primer Metal to Polyurethane
8851903 - Primer Polyurethane to B.Y.C.
8852275 - Box Set-up, Paperboard for W143-11(TNG) Cable Assembly
8852528 - W143-12 Cable Assembly Training
9229202 - Cover Protective
EL-8852528 - Equipment List

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-C-14982(MU) and as specified herein.

3.2 Circuit resistance. The cable assembly circuit resistance shall be in accordance with table I.

Table I

Circuit resistance (see dwg 8852528)

From P-601 Connector Pin	To P5-1 Connector Pin	Ohms Max.
2	4	0.2
4	5	0.2

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-C-14982(MU) and as specified herein.

4.1.1 Sampling and inspection not applicable. The following classification of defects in MIL-C-14982(MU) is not applicable:

a. 4.3.2.1.4 Bag, packing, ammunition for cable assembly.

4.2 First article inspection.

4.2.1 Quantity to be submitted. In addition to quantities specified in 4.2.1 MIL-C-14982(MU), 3 sub-assemblies shall be submitted (see dwg 8852528) W143-12 Cable Assembly Training before potting and molding.

4.3 Classification of characteristics.

4.3.1 Connector (see dwgs 8850958 and 8850960); molding compound polyurethane, black (see dwg 8851852); cap and chain assembly (see dwg 8851861); primer metal to polyurethane (see dwg 8851901); primer

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

polyurethane to B.Y.C. (see dwg 8851903); cover, protective (see dwg 9229202); washer (see MS15795-204); rivet (see MS16535-160); clamp (see MS25281-4W) covering details of dwg 8852528.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Objective evidence (see 6.3 MIL-C-14982(MU) available for part in accordance with applicable standard or drawing.....Visual

Minor:
201. Workmanship (see 3.12 MIL-C-14982(MU))).....Visual/Manual

4.3.2 W143-12 Cable assembly training (see dwg 8852528) before potting and molding.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Primer applied to connectors.....Visual
102. Primer applied to cable.....Visual
103. Rubber insert, plastic sleeve and retaining nut removed from connector.....Visual

Minor: None defined.

4.3.3 W143-12 cable assembly training (see dwg 8852528).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Length.....*Measure
102. Length of mold right connector.....*Measure
103. Material (see 3.2 MIL-C-14982(MU)).....Visual
104. Marking.....Visual

* Measure with suitable scale

Minor:
201. Serialization (see 3.5 MIL-C-14982(MU)).....Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

4.4 Insulation resistance. The cable assembly insulation resistance shall be tested in accordance with table II.

Table II

Insulation resistance (see dwg 8852528)

Positive Potential P601 Connector Pin	Negative potential to shells, and all other pins except Connector P5-1 Pin
2	4
4	5

5.0 PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies. Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-14982(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. Preservation and packaging shall be as specified in MIL-C-14982(MU).

5.2.1.1 Level A. The cable assembly shall be packaged in accordance with dwg 8852275 and 8808362 and as specified in MIL-C-14982(MU).

5.2.1.2 Level C. The cable assembly shall be packaged in accordance with dwgs 8852275 and 8808362 and MIL-C-14982(MU).

5.2.2 Packing.

5.2.2.1 Level A and C. The cable assembly shall be packed in accordance with dwgs 8852275 and 8808362 and MIL-C-14982(MU).

5.2.3 Marking. Marking shall be as specified in dwgs 8852275 and 8808362 and MIL-C-14982(MU).

6.0 NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-14982(MU).

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1195-A041

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.