MILITARY SPECIFICATION SHEET
CABLES FOR ATOMIC DEMOLITION CHARGES

W143-14 CABLE ASSEMBLY

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-14982(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for Cable Assembly W143-14 Training for use with Training Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-14982(MU) - Cables for Training Atomic Demolition Charge, General Specification for

STANDARDS

MILITARY

MS15795 - Washer
MS20470 - Rivet
MS25281 - Clamp

DRAWINGS

ORDNANCE CORPS

8881768 - Polyurethane Molding Compound
8881769 - Primer Polyurethane Molding Compound
9203770 - Cable Assembly W143-14 Training
9206885 - Box, Set-up, for Cable Assembly W143-14 Training
9207508 - Primer Polyurethane Molding Compound

FSC 1195

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

9210991 - Boot
9210992 - Boot
9211192 - Connector
9211816 - Tubing, Heat Shrinkable, Neoprene
9211817 - Connector, Plug, Electrical
9211840 - Cap, Protective
9212203 - Cap, Protective
EL-9203770 - Equipment List

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-C-14982(MU) and as specified herein.

3.2 Circuit resistance. The cable assembly circuit resistance shall be in accordance with table I.

Table I

Circuit resistance (see dwg 9203770)

From P-143-14 Connector Pin	To J-143-8 Connector Pin	Ohms Max.
A	A	1.0
B	B	1.0
C	C	1.0

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with MIL-C-14982(MU) and as specified herein.

4.1.1 Sampling and inspection not applicable. The following classification of defects in MIL-C-14982(MU) is not applicable:

a. 4.3.2.1.4 Bag, packing, ammunition for cable assembly.

4.2 First article inspection.

4.2.1 Quantity to be submitted. In addition to quantities specified in 4.2.1 MIL-C-14982(MU), 3 sub-assemblies shall be submitted (see dwg 9203770) Cable Assembly W143-14 Training before potting and molding.

4.3 Classification of characteristics.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

4.3.1 Polyurethane molding compound (see dwg 8881768); primer polyurethane molding compound (see dwgs 8881769 and 9207508); boot (see dwgs 9210991 and 9210992); connector (see dwg 9211192); tubing heat shrinkable, neoprene (see dwg 9211816); connector, plug, electrical (see dwg 9211817); cap, protective (see dwgs 9211840 and 9212203); washer (see MS15795-204); rivet (see MS20470D4-8); clamp (see MS25281-R6) covering details of dwg 9203770.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see 6.3 MIL-C-14982(MU)) available for parts in accordance with applicable drawing or standard	Visual
Minor:		
201.	Workmanship (see 3.12 MIL-C-14982(MU))	Visual/Manual

4.3.2 Cable assembly W143-14 training (see dwg 9203770) before potting and molding.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Primer applied to connectors	Visual
102.	Primer applied to cable	Visual
103.	Sleeving tied both ends	Visual
Minor: None defined.		

4.3.3 Cable assembly W143-14 training (see dwg 9203770).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Length	* Measure
102.	Material (see 3.2 MIL-C-14982(MU))	Visual
103.	Length of sleeve (cable identification)	* Measure
104.	Length of sleeve (serial No.)	* Measure
105.	Marking	Visual

* Measure with suitable scale

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

Minor:
201. Serialization (see 3.5 MIL-C-14982(MU))..... Visual

4.4 Insulation resistance. The cable assembly insulation resistance shall be tested in accordance with table II.

Table II

Insulation resistance (see dwg 9203770)

Positive Potential P-143-14 Connector Pin	Negative potential to shells, and all other pins except J-143-8 Connector Pin
A	A
B	B
C	C

5.0 PREPARATION FOR DELIVERY

5.1 Preparation for delivery for repair cable assemblies.

5.2 Preservation and packaging. Preservation and packaging shall be as specified in MIL-C-14982(MU).

5.2.1.1 Level A. The cable assembly shall be packaged in accordance with dwgs 9206885 and 8808362 and as specified in MIL-C-14982(MU).

5.2.1.2 Level C. The cable assembly shall be packaged in accordance with dwgs 9206885 and 8808362 and MIL-C-14982(MU).

5.2.2 Packing.

5.2.2.1 Level A and C. The cable assembly shall be packed in accordance with dwgs 9206885 and 8808362 and MIL-C-14982(MU).

5.2.3 Marking. Marking shall be as specified in dwgs 9206885 and 8808362 and MIL-C-14982(MU).

6.0 NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-14982(MU).

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1195-A042

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.