MILITARY SPECIFICATION SHEET
CABLES FOR ATOMIC DEMOLITION CHARGES

143-13 CABLE ASSEMBLY

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-14982(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for Cable Assembly W143-13 Training for use with Training Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-14982(MU) - Cables for Training Atomic Demolition Charge General Specification for.

STANDARDS

MILITARY

MS 3116 - Connector
MS 3180 - Cap, Protective
MS 3181 - Cap and Chain Assembly
MS 87006 - "S" Hook

DRAWINGS

ORDNANCE CORPS

8881768 - Polyurethane Molding Compound
8881769 - Primer, Polyurethane Molding Compound

FSC 1195

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

9206886 - Bag, for Cable Assembly W143-13 Training
9207508 - Primer, Polyurethane Molding Compound
9207511 - Gasket, Mounting Flange, Receptacle, Connector, Miniature Electrical
9207512 - Connector, Receptacle, Wall Mounting, Miniature Electrical
9207513 - Cable Assembly W143-13 Training
9211816 - Tubing, Heat Shrinkable, Neoprene
EL-9207513 - Equipment List

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. - Requirements shall be in accordance with MIL-C-14982(MU) and as specified herein.

3.2 Circuit resistance. - The cable assembly circuit resistance shall be in accordance with Table I.

Table I

Circuit Resistance (see dwg 9207513)

From J-143-14 Connector Pin	To other Connector Pin	Ohms Max
A	A	0.2
B	B	0.2
C	C	0.2

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. - Sampling and inspection shall be in accordance with MIL-C-14982(MU) and as specified herein.

4.1.1 Sampling and inspection not applicable . - The following classification of defects in MIL-C-14982(MU) are not applicable:

a. 4.3.2.1.5 Box, set-up paperboard for applicable cable assembly.

4.2 First article inspection.

4.2.1 Quantity to be submitted. - In addition to quantities specified in 4.2.1 of MIL-C-14982(MU), 3 sub-assemblies shall be submitted (see dwg 9207513) Cable Assembly W143-13 Training before potting and molding.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

4.3 Classification of characteristics.

4.3.1 Polyurethane molding compound (see dwg 8881768); primer, polyurethane molding compound (see dwgs 8881769 and 9207508); gasket, mounting flange (see dwg 9207511); connector, receptacle, wall mounting (see dwg 9207512); tubing, heat shrinkable, neoprene (see dwg 9211816); connector (see MS 3116P-10-6S); cap, protective (see MS 3180-10); cap and chain assembly (see MS 3181-14C); "S" hook (see MS 87006-3) covering details of dwg 9207513.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Objective evidence (see 6.3 MIL-C-14982(MU) available for parts in accordance with applicable standard or drawing.....Visual

Minor:

201. Workmanship (see 3.12 MIL-C-14982(MU).....Visual/Manual

4.3.2 Cable assembly W143-13 training (see dwg 9207513) before molding and potting.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Primer applied to connectors.....Visual
102. Primer applied to cable.....Visual
103. Ends of sleeving tied.....Visual
104. Wires twisted.....Visual

Minor: None defined.

4.3.3 Cable assembly W143-13 training (see dwg 9207513).

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Length.....*Measure
102. Material (see 3.2 MIL-C-14982(MU).....Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

103. Minimum extension of jacket into molding.....*Measure
104. Marking.....Visual

*Measure with suitable scale.

Minor:

201. Serialization (see 3.5 MIL-C-14982(MU).....Visual

4.4 Insulation resistance. - The cable assembly insulation resistance shall be tested in accordance with table II.

Table II

Insulation Resistance (see dwg 9207513)

Positive Potential J-143-14 Connector Pin	Negative potential to shells and all other pins except other connector pin
A	A
B	B
C	C

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies. - Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-14982(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. - Preservation and packaging shall be as specified in MIL-C-14982(MU).

5.2.1.1 Level A. - The cable assembly shall be packaged in accordance with dwgs 9206886 and 8808362 and as specified in MIL-C-14982(MU).

5.2.1.2 Level C. - The cable assembly shall be packaged in accordance with dwg 8808362 and MIL-C-14982(MU).

5.2.2 Packing.

5.2.2.1 Level A and C. - The cable assembly shall be packed in accordance with dwgs 9206886 and 8808362 and MIL-C-14982(MU).

5.2.3 Marking. - Marking shall be as specified in dwgs 9206886 and 8808362 and MIL-C-14982(MU).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Notes. - Notes shall be in accordance with MIL-C-14982(MU).

Custodian
Army MU

Preparing activity
Army-MU
Project No. 1195-A043

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:17Z
Check the source to verify that this is the current version before use.